INCH-POUND

GGG-D-751D
19 January 1989
SUPERSEDING
GGG-D-751C
October 27, 1967

FEDERAL SPECIFICATION

DRILLS, TWIST (TAPER-SQUARE, STRAIGHT AND TAPER-ROUND SHANKS)

This Specification was approved by the Assistant Administrator, Office of Federal Supply and Services, General Services Administration, for the use of all Federal Agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers metal-cutting twist drills with straight, taper, and taper-square shanks and sets of these twist drills.

1.1.1 Federal specification coverage. Federal specifications do not include all types and classes of the commodities indicated by the titles of the specifications, but include only those most commonly used by the Federal Government. The tolerances in this specification do not apply to tools other than those specifically endorsed by this specification.

1.2 Classification.

1.2.1 Types and classes. Individual twist drills and twist drills in sets shall be of the following types and classes, as specified (see 6.2):

Type A - Bitstock, carbon steel.
  Class 1 - Taper-square shank 3/16 by 3/8 by 1-1/4 inches.

Type B - Straight shank, fractional sizes, high-speed steel.
  Class 1 - Jobbers length (short length).
  Class 2 - Taper length (long length).

Type C - Straight shank, wire-gage sizes, jobbers length, high-speed steel.
Type D - Straight shank, letter sizes, jobbers length, high-speed steel.
Type E - American Standard taper (Morse) shank, high-speed steel.

Beneficial comments, recommendations, additions, deletions, clarifications, and any data which may improve this document should be sent to: USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 5133

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:42Z
Check the source to verify that this is the current version before use.

1.2.2 Sizes. The sizes of the twist drills shall be in accordance with ANSI/ASME B94.11M for the respective types and classes, as specified (see 6.2).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications, and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

Federal Specifications

GGG-C-116[1]/	- Case, Twist Drill; and Stand, Twist Drill.
PPP-P-40	- Preservation and Packing of Hand Tools; Tools and Tool Accessories for Power Driven, Metal and Woodworking Machinery.

Federal Standard

FED-STD-123	- Marking for Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification, other Federal specifications and commercial item descriptions required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TXk; Hourston, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Auburn, WA.

(Federal Government activities may obtain copies of Federal standardization documents and the Index of Federal Specifications, Standards and Commercial Item Descriptions from established distribution points in their agencies.)

Military Standards

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

1/ The "Used-in-lieu of" revision of GGG-C-116 shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:42Z
Check the source to verify that this is the current version before use.

Federal Regulations

Code of Federal Regulations

48 CFR 23.4 - Use of Recovered Materials.

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on the date of invitation for bids or request for proposal shall apply.

American National Standards Institute, Inc. (ANSI).

ANSI/ASME B5.10 - Machine Tapers.
ANSI/ASME B94.11M - Twist Drills.

(Application for copies should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.) or (The American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017).

American Society for Testing and Materials (ASTM) Standards.

ASTM A 600 - Tool Steel High Speed, Standard Specification for.
ASTM E 18 - Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials, Standard Method of Tests for.
ASTM E 384 - Microhardness of Materials, Standard Method of Tests for.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Society of Automotive Engineers (SAE)

SAE J1249 - Former SAE Standard and Former SAE Ex-Steels.
(Application for copies should be addressed to the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15086.)

(Non-Government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

3. REQUIREMENTS

3.1 First article. Unless otherwise specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:42Z
Check the source to verify that this is the current version before use.

3.2 Illustrations. The illustrations shown herein are descriptive and not restrictive and are not intended to preclude the purchase of twist drills which are otherwise in accordance with the requirements of this specification.

3.3 Materials. Type A drills shall be made of carbon or high-speed steel (HS) conforming to ASTM A 600. Types B, C, D and E drills shall be made of either M-1, M-2, M-7 or M-10 high-speed steel except when M-42 cobalt high-speed steel is specified (see 6.2).

3.3.2 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 (48 CFR 23.4) to the maximum extent practical.

3.4 Hardness. At least 75 percent of the drill flute length, from the point to the shank, shall have a hardness value of Rockwell C 58-64 for type A drills. Types B, C, D, and E drills shall have at least 75 percent of the drill flute length hardened to Rockwell C 63-66 or a Knoop microhardness not less than 799 nor more than 870 for sizes 5/64-inch, and smaller. The hardness at the shank end for all drills shall be a minimum of Rockwell C 50 or Knoop 542.

3.5 Concentricity. The run-out of the axis of all drills between the shank and point (except type A) shall not exceed the following tolerances when tested in accordance with 4.5.3:

Type B, Class 1, Type C (jobbers length), and Type D:

Diameter Range	Maximum Total Indicator Runout (TIR)
1/32 to 1/8 inch	0.008 inch
1/8 to 1/4 inch	0.007 inch
1/4 to 3/8 inch	0.006 inch
3/8 inch and larger	0.005 inch

Type B, Class 2 and Type C (taper length):

Diameter Range	Maximum Total Indicator Runout (TIR)
1/32 to 1/16 inch	0.020 inch
1/16 to 1/8 inch	0.018 inch
1/8 to 1/4 inch	0.012 inch
1/4 to 1/2 inch	0.009 inch
1/2 to 3/4 inch	0.008 inch
3/4 to 1 inch	0.007 inch
1 inch and larger	0.006 inch

Type E:

Diameter Range	Maximum Total Indicator Runout (TIR)
1/8 to 3/8 inch	0.015 inch
3/8 to 1-1/2 inches	0.010 inch
1-1/2 inches and larger	0.007 inch

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:42Z
Check the source to verify that this is the current version before use.

3.6 Design and dimensions. Type A drills shall be of the design for use in a carpenter's brace, and shall conform to the requirements in 3.7. Types B, C, and D shall be of the two flute, straight shank, drills of the sizes and dimensions show in ANSI/ASME B94.11M. Type E drills shall conform to the design and dimensions for the two flute drills with Morse (ANSI/ASME B5.10) tapered shanks as shown in table 5 of ANSI/ASME B94.11M. Unless otherwise specified (see 6.2), all drills shall be for right-hand rotation with drill points ground ready for general purpose drilling.

3.7 Type A, bitstock drills.

3.7.1 Class 1, square shank 3/16 by 3/8 by 1-1/4 inches. Class 1 drills shall be suitable primarily for use with ratchet braces in drilling either metal or wood. The drills shall have a steel taper-square shank 3/16 by 3/8 by 1-1/4 inches long, except that die-cast, taper-square shanks of the same dimensions may be used provided the portion of the drill inserted in the die-cast shank is knurled, serrated, or otherwise conditioned to prevent the turning of the drill in the shank. The drills shall conform to table I for the size specified (see 1.2) and shall be similar to figure 1.

TABLE I. Type A, class 1, bitstock, drills, square shank, 3/16 by 3/8 by 1-1/4 inches.

Drill diameter	Overall length	Flute length
Inch	Inches	Inches
1/16	3	7/8
3/32	3-3/8	1-1/4
1/8	3-5/8	1-1/2
5/32	4	1-7/8
3/16	4-3/8	2-1/4
7/32	4-3/4	2-1/2
1/4	5-1/8	2-7/8
9/32	5-1/4	3
5/16	5-1/2	3-1/4
11/32	5-3/4	3-1/2
3/8	5-7/8	3-5/8
7/16	6-1/4	4
1/2	6-3/4	4-1/2

3.8 Type B. Type B straight shank drills shall have cylindrical shanks suitable for use in conventional three-jaw drill chucks. Type B drills shall be furnished in class 1 jobbers length (short length) series and class 2 taper length (long length) series. They shall conform to the requirements of ANSI/ASME B94.11M for the size specified (see 6.2).

3.9 Type C, straight shank. Type C straight shank drills shall have cylindrical shanks suitable for use in conventional three-jaw drill chucks. Type C drills shall be furnished in jobbers lengths (short length) series, or when specified (see 6.2) in taper length series. They shall conform to the requirements of ANSI/ASME B94.11M for the size specified (see 1.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:42Z
Check the source to verify that this is the current version before use.

3.10 Type D, straight shank. Type D straight shank drills shall have cylindrical shanks suitable for use in conventional three-jaw chucks. Type D drills shall be furnished in jobbers lengths (short length) series. They shall conform to the requirements of ANSI/ASME B94.11M for the size specified (see 1.2).

3.11 Type E. Type E drills shall be furnished with Morse tapered shanks conforming to ANSI/ASME B5.10. Type E drills shall conform to ANSI/ASME B94.11M for the size specified (see 1.2). Unless otherwise specified (see 6.2), type E drills shall be furnished with regular shanks.

3.12 Drill sets. Drills in sets shall be furnished in the respective quantities, types, classes, and sizes specified in 3.12.1 through 3.12.9. The set number shall be specified (see 6.2). Drills in individual sets shall be of the same type, class, and make. When specified (see 6.2), drill sets shall be furnished in cases, stands, or rolls. The cases and stands shall conform to GGG-C-00116D. Drill sets furnished in cases shall be placed in the applicable hole size in the case drill holder. Rolls shall be heavy canvas, fire-resistant plastic, or imitation leather with a separate pocket for each drill. Each pocket shall be stamped or marked with the applicable drill size. The roll shall be provided with a flap and tie tape or buckle so arranged that the set may be easily rolled up and fastened in a secure and dustproof manner.

3.12.1 Set No. 1. Bitstock, class 1, drills. Set 1: Nine type A drills: one each of the 1/16, 3/32, 1/8, 5/32, 3/16, 7/32, 1/4, 5/16, and 3/8 inch sizes.

3.12.2 Set No. 2. Straight shank, fractional sizes, high-speed steel, jobbers length drills. Set 2: type B, class 1, 1/16 to 1/2 inch sizes inclusive, by 64ths.

3.12.2.1 Set No. 2-A. Straight shank, fractional sizes, high-speed steel, jobbers length drills. Set 2-A: type B, class 1, 1/16 to 1/2 inch sizes inclusive, by 16ths.

3.12.2.2 Set No. 2-B. Straight shank, fractional sizes, high-speed steel, jobbers length drills. Set 2-B: type B, class 1, 1/16 to 9/32 inch sizes inclusive, by 32nds.

3.12.2.3 Set No. 2-C. Straight shank, fractional sizes, high-speed steel, jobbers length drills. Set 2-C: type B, class 1, 1/16 to 3/8 inch sizes inclusive, by 64ths.

3.12.3 Set No. 3. Straight shank, wire-gage sizes, high-speed steel, jobbers length drills. Set 3: type C, no. 1, to no. 60 sizes inclusive.

3.12.4 Set No. 4. Straight shank, wire-gage sizes, high-speed steel, jobbers length drills. Set 4: type C, no. 61 to no. 80 sizes inclusive.

3.12.5 Set No. 5. Straight shank, letter sizes, high-speed steel, jobbers length drills. Set 5: type D, sizes A to Z inclusive.

3.12.6 Set No. 6. No. 2 American Standard taper (Morse) shank, high-speed steel drills. Set 6: type E, 33/64 to 3/4 inch sizes inclusive, by 64ths.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:42Z
Check the source to verify that this is the current version before use.

SEAMLESS AND WELDED

3.12.7 Set No. 7. Nos. 2 and 3 American Standard taper (Morse) shank, high-speed steel drills. Set 7: type E, 49/64 to 1 inch sizes inclusive, by 64ths.

3.12.8 Set No. 8. Straight and taper shank, fractional sizes, high-speed steel, jobbers length and taper length drills. Set 8: type B, class 1, 1/8 to 1/2-inch sizes inclusive, by 16ths; type B, class 2, 9/16 to 3/4-inch sizes inclusive, by 16ths.

3.12.9 Set No. 9. American Standard taper (Morse) shank, high-speed steel drills. Set 9: type E, 1-1/64 to 1-1/16-inch sizes inclusive, by 64ths, and type E, 1-5/64 to 1-1/2-inch sizes inclusive, by 64ths.

3.13 Identification marking. Drills 0.125-inch and larger shall be marked in a plain and permanent manner with the size and the manufacturer's name or with a trademark of such known character that the source of manufacture may be readily determined. High-speed steel drills 3/32-inch diameter and larger shall have the words "High-Speed" or "HS" clearly stamped or engraved upon them.

3.14 Workmanship. Workmanship shall be equal to the quality generally accepted as good commercial practice in industry. The drills shall be free of all burrs, fins, sharp projections (except the cutting lip), surface roughness, or any other imperfection that may impair their durability and serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. Inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of preparation for delivery (see 4.6).

4.3 First article inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:42Z
Check the source to verify that this is the current version before use.

4.3.1 Examination. A sample of two drills shall be examined as specified in 4.4.3.

4.3.2 Tests. A sample of two drills shall be tested as specified in 4.5 through 4.5.4.

4.4 Quality conformance inspection.

4.4.1 Lot. A lot shall consist of all drills of the same type, class, and size in a heat treatment batch, or all drills of the same type, class, and size offered for delivery at one time, whichever is less.

4.4.2 Sample. A random sample of drills shall be selected from each lot in accordance with MIL-STD-105. The inspection level for examination shall be S-4, and the inspection level for quality conformance tests shall be S-1.

4.4.3 Examination. Each of the sample drills selected in accordance with 4.4.2 shall be dimensionally and visually examined for compliance with the requirements specified herein for design, finish, marking, and workmanship. All dimensions shall be within the tolerances specified. Acceptable quality level (AQL) shall be 1.0 percent defective. Any drill containing one or more defects shall not be offered for delivery and if the number of nonconforming drills exceeds the acceptance number for the sample, the lot represented by the sample shall be rejected.

4.5 Quality conformance tests. Each sample unit selected in accordance with 4.4.2 shall be tested in accordance with the tests in 4.5.1. AQL shall be 1.0 percent defective.

4.5.1 Hardness testing. The sample units shall be tested for compliance with 3.4 using the procedures outlined in ASTM E18 or ASTM E384, as applicable.

4.5.2 Shank and drill body slippage. Type A, class 1, bitstock drills, carbon steel with die-cast square-taper shanks shall be tested by having the shank secured in the chuck of a carpenter's brace, with the point end of the drill held in a vise. The brace shall be rotated until the drill fractures in the flute. None of the drills tested in this manner shall show evidence of the drill turning in the shank.

4.5.3 Concentricity test. All drills except type A shall be tested for concentricity as follows: Rotate the full length of drill shank in a vee block, or mount in an index head so that it can be rotated 360 degrees. The full indicator variations shall be taken and recorded at the point diameter and one-fourth turn of the helix back from the point diameter. The AQL for this test shall be 1.0 percent defective. If the number of drills not conforming to the limits specified in 3.5 exceed the acceptance number for the sample, the lot represented by the sample shall be rejected.

4.5.4 Drilling test. Each sample unit shall be tested for performance by drilling twenty holes through the test plate. The steel test plate shall be in accordance with SAE J1249, table 1, SAE No. 3245. The test plate shall have a Brinell hardness within the range of 302 to 321, except when testing drills number 30 and smaller, the test plate shall have Brinell hardness of 286 to 302. Thickness of the plate for the size of drill being tested shall be as specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:42Z
Check the source to verify that this is the current version before use.

in table II. A coolant consisting of soluble oil with 20 to 25 parts of water shall be used for all drill sizes. The drills shall be tested as furnished by the manufacturer from his normal production run for general purpose drills. Machinery used in conducting the test must have prior approval by the contracting officer or his representative.

TABLE II. Test plate thicknesses.

Drill Size	Plate Thickness
0 to 1/8 inch	3/16 inch
1/8 to 1/4 inch	3/8 inch
1/4 to 7/16 inch	1 inch
7/16 to 9/16 inch	1-1/4 inches
9/16 inch and larger	2-3/8 inches

The first and last test holes drilled shall be compared for size and finish. Both holes shall have diameters within minus 0.005 inch to plus 0.010 inch of the nominal drill size, and the surface finish of the holes shall have a maximum surface roughness of 125 microinches. The holes on the breakout side of the plate shall be free of excessive burrs after the test holes have been drilled. A drill shall be considered to have failed the drill test when the drill breaks, chatters, squeals, labors, or dulls to a degree that the drill no longer cuts. The AQL for the drill test shall be 1.0 percent defective.

4.6 Inspection of preparation for delivery. Sample twist drills and packages shall be selected and inspected to verify conformance to the requirements of section 5, and PPP-P-40.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, and packing. Unless otherwise specified (see 6.2), the drills shall be preserved, packaged, and packed in accordance with PPP-P-40. The level of preservation and packaging shall be level A or C and the level of packing A, B, or C, as specified (see 6.2).

5.2 Marking.

5.2.1 Civil agencies. In addition to any markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with FED-STD-123.

5.2.2 Military agencies. In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The twist drills, taper-square, straight, and taper-round shanks covered by this specification are for use with drilling machines and hand, pneumatic, or electric portable drills for drilling ferrous and nonferrous materials.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:42Z
Check the source to verify that this is the current version before use.

UNIFORM CLASSIFICATION COMMITTEE

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Type and class and size required (see 1.2.1 and 1.2.2).
c. Size of drills or number of the drill set required (see table I or ANSI/ASME B94.11M).
d. When first article inspection is not required (see 3.1).
e. When M-42 cobalt high-speed steel is required (see 3.3).
f. When left-hand rotation drill is required (see 3.6).
g. When taper length drills are to be supplied (see 3.9).
h. Shank for type E drills if other than regular (see 3.11).
i. When drills are to be furnished in sets, specify the set No. required (see 3.12).
j. When drills are to be furnished in cases, rolls, or stands, specify type of case, stand, or rolls required (see 3.12).
k. Selection of applicable level of preservation, packaging, and packing required (see 5.1). When level B packaging is required for civil agency procurements, the level A requirements in 5.1 shall apply.

6.3 First article. When a first article inspection is required, the drills should be a preproduction model. The first article should consist of two drills (see 4.4.2). The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of the first article test results and disposition of the first articles. Invitation for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Subject term (key word) listing.

Drills, twist
Shank, straight
Shank, taper-round
Shank, taper-square

6.5 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

6.6 Changes from previous issue. Asterisks or vertical lines are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:42Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:
COORDINATING ACTIVITIES

Custodians:

Army - ME
Air Force - 99

Review Activities:

Army - GL
Air Force - 84

User Activities:

Army - AR
Navy - AS, OS, MC, YD

CIVIL AGENCY

GSA - FSS

PREPARING ACTIVITY:

Army - ME
Project 5133-0047

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:42Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
GGG-D-751D	Drills, Twise (Taper-Square, Straight and Taper-Round Shanks)

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

(T) DETACH THIS FORM ALONG THIS LINE.

c. Recommended Wording

d. Reason/Rationale for Recommendation

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:42Z
Check the source to verify that this is the current version before use.

during the second step, which is a test for soundness. The flattening shall be continued

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provid suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, an mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE. This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
Belvoir RDE Center
ATTN: STRBE-TSE
Fort Belvoir, VA 22060-5606

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:42Z
Check the source to verify that this is the current version before use.