The documentation and process conversion measures necessary to comply with this revision shall be completed by 20 November 2024.

INCH-POUND

MIL-PRF-19500/746D
w/AMENDMENT 3
20 June 2024
SUPERSEDING
MIL-PRF-19500/746D
w/AMENDMENT 2
24 April 2023

PERFORMANCE SPECIFICATION SHEET

TRANSISTOR, FIELD EFFECT, RADIATION HARDENED, N-CHANNEL, SILICON,
SURFACE MOUNT AND UN-ENCAPSULATED, TYPES 2N7587, 2N7589, 2N7591, AND 2N7593,
QUALITY LEVELS JANTXV, JANS, JANHC, AND JANKC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for a N-channel, enhancement-mode, MOSFET, radiation hardened (total dose and single event effects (SEE)), power transistor. Two levels of product assurance (JANTXV and JANS) are provided for each encapsulated device. Two levels of product assurance (JANHC and JANKC) are provided for each unencapsulated device. Three levels (R, F and G) of radiation hardness assurance (RHA) are provided for product assurance levels JANTXV, JANS, JANHC, and JANKC.

1.2 Physical dimensions.

1.2.1 Package outlines. The device package outline is a TO-276AA in accordance with figure 1 for all encapsulated device types.

1.2.2 Die dimensions and topography. The dimensions and topography for JANHC and JANKC unencapsulated die are in accordance with figure 2 and figure 3.

1.3 Maximum ratings. Unless otherwise specified, T_A = +25°C.

Type (1)	P_T (2) T_C = +25°C	P_T T_A = +25°C	$R_{\theta JC}$ (3)	V_{DS}	V_{DG}	V_{GS}	I_{D1} (4) (5) T_C = +25°C	I_{D2} T_C = +100°C	I_S	I_{DM} (6)	T_J and T_{STG}	V_{ISO} 70,000 ft. altitude
	W	W	°C/W	V dc	V dc	V dc	A dc	A dc	A dc	A (pk)	°C	V dc
2N7587	75	1.56	1.67	100	100	±20	22	19	22	88	-55	
2N7589	75	1.56	1.67	150	150	±20	19	12	19	76	to	
2N7591	75	1.56	1.67	200	200	±20	16	10	16	64	+150	
2N7593	75	1.56	1.67	250	250	±20	12.4	7.8	12.4	49.6		250

(1) Also applies to U3 and U3C suffix versions.
(2) Derate linearly by 0.6 W/°C for T_C > +25°C.
(3) See figure 4, thermal impedance curves.

Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime, ATTN: VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

FSC 5961

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

1.3 Maximum ratings − continued.

(4) The following formula derives the maximum theoretical I_D limit. I_D is limited by package and internal wires and may be limited by pin diameter: $I_D = \sqrt{\frac{T_{JM} - T_C}{(R_{\theta JC}) \times (R_{DS}(on) \text{ at } T_{JM})}}$

(5) See figure 5, maximum drain current graph.
(6) I_{DM} = 4 X I_{D1}; I_{D1} as calculated by footnote (4).

1.4 Primary electrical characteristics. Unless otherwise specified at T_C = +25°C.

Types (1)	Min $V_{(BR)DSS}$ V_{GS} = 0 I_D = 1.0mA dc	$V_{GS(TH)1}$ $V_{DS} \geq V_{GS}$ I_D = 1.0 mA dc	Max I_{DSS1} V_{GS} = 0 V_{DS} = 80% of rated V_{DS}	Max $r_{DS(on)}$ (2) V_{GS} = 12V, $I_D = I_{D2}$	Max $r_{DS(on)}$ (2) V_{GS} = 12V, $I_D = I_{D2}$	E_{AS}
				T_J = +25°C	T_J = +150°C	
	V dc	V dc Min	Max	µA dc	Ω	Ω	mJ
2N7587	100	2.0	4.0	10	0.042	0.084	73
2N7589	150	2.0	4.0	10	0.088	0.207	60
2N7591	200	2.0	4.0	10	0.130	0.300	60
2N7593	250	2.0	4.0	10	0.210	0.494	56

(1) Also applies to U3 and U3C suffix versions.
(2) Pulsed (see 4.5.1).

1.5 Part or Identifying Number (PIN). The PIN is in accordance with MIL-PRF-19500, and as specified herein. See 6.4 for PIN construction example and 6.5 for a list of available PINs.

1.5.1 JAN certification mark and quality level.

1.5.1.1 Quality level designators for encapsulated devices. The quality level designators for encapsulated devices that are applicable for this specification sheet are as follows: "JANTXV" and "JANS".

1.5.1.2 Quality level designators for un-encapsulated devices (die). The quality level designators for un-encapsulated devices that are applicable for this specification sheet are as follows: "JANHC" and "JANKC".

1.5.2 Radiation hardness assurance (RHA) designator. The RHA levels that are applicable for this specification sheet for product assurance levels JANTXV, JANS, JANHC, and JANKC from lowest to highest are as follows: "R", "F" and "G". See 1.6 for RHA details.

1.5.3 Device type. The designation system for the device types of transistors covered by this specification sheet are as follows.

1.5.3.1 First number and first letter symbols. The transistors of this specification sheet use the first number and letter symbols "2N".

1.5.3.2 Second number symbols. The second number symbols for the transistors covered by this specification sheet are as follows: "7587", "7589", "7591", and "7593".

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

1.5.4 Suffix letters. The following suffix letters are incorporated in the PIN for this specification sheet:

U3	Indicates a metal lidded 3 pad surface mount package similar to a TO-276AA (SMD-0.5) (see figure 1).
U3C	Indicates a ceramic lidded 3 pad surface mount package similar to a TO-276AA (SMD-0.5) (see figure 1).

1.5.5 Lead finish. The lead finishes applicable to this specification sheet are listed on QPDSIS-19500.

1.5.6 Die identifiers for un-encapsulated devices (manufacturers and critical interface identifiers). The manufacturer die identifier that is applicable for this specification sheet is "A", and “B” (see figure 2, figure 3, and 6.5).

1.6 Radiation features. The following radiation features are applicable for RHA devices supplied to this specification sheet.

1.6.1 Maximum total ionizing dose (TID). The maximum TID that RHA devices were tested to in accordance with condition A (dose rate = 50 to 300 rad(Si)/s) of method 1019 of MIL-STD-750 are as follows:

For device types 2N7587U3, 2N7589U3, 2N7591U3: ..... 300 krads(Si) 1/
For device types 2N7587U3C, 2N7589U3C, 2N7591U3C: ..... 300 krads(Si) 1/

For device type 2N7593U3: ..... 500 krads(Si) 1/

1.6.2 Heavy ion irradiation SEE. SEE testing includes Single-Event Burnout (SEB) and Single-Event Gate Rupture (SEGR) tests at the specified linear energy transfer (LET) units. See 6.7 for the specific RHA SEE characterization testing details. The following characterization conditions were used for the testing to the requirements herein:

For device type 2N7587:
No SEB and SEGR were observed at surface LET (see table IV) ..... ≤ 90 MeV·cm^2/mg 2/
(In-situ Bias V_{DS} = 100 V and V_{GS} = -5 V)


For device type 2N7589:
No SEB and SEGR were observed at surface LET (see table IV) ..... ≤ 90 MeV·cm^2/mg 2/
(In-situ Bias V_{DS} = 50 V and V_{GS} = -5 V)
(In-situ Bias V_{DS} = 30 V and V_{GS} = -10 V)

For device type 2N7591:
No SEB and SEGR were observed at surface LET (see table IV) ..... ≤ 90 MeV·cm^2/mg 2/
(In-situ Bias V_{DS} = 150 V and V_{GS} = -4 V)
(In-situ Bias V_{DS} = 110 V and V_{GS} = -5 V)

For device type 2N7593:
No SEB and SEGR were observed at surface LET (see table IV) ..... ≤ 90 MeV·cm^2/mg 2/
(In-situ Bias V_{DS} = 250 V and V_{GS} = -5 V)

1/ The manufacturers supplying these device types have performed characterization testing in accordance with condition A (dose rate = 50 to 300 rad(Si)/s) of method 1019 of MIL-STD-750. The radiation end point limits are guaranteed only to a maximum TID level of and 300 krads(Si) and 500 krads(Si).
2/ The manufacturers have performed SEE tests at Texas A&M University (TAMU) Radiation Effects Facility in accordance with method1080 of MIL-STD-750. For more information on SEE testing and results, customers should contact the qualified manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.




Symbol	Dimensions				Symbol	Dimensions			
	Inches	Inches	mm	mm		Inches	Inches	mm	mm
	Min	Max	Min	Max		Min	Max	Min	Max
BL	.395	.405	10.03	10.29	LS1	.150 BSC		3.81 BSC	
BW	.291	.301	7.39	7.65	LS2	.075 BSC		1.91 BSC	
CH (for U3)	.108	.124	2.74	3.15	LW1	.281	.291	7.14	7.39
CH (for U3C)		.1335		3.39	LW2	.090	.100	2.29	2.54
LH	.010	.020	0.25	0.51	Q1	.030		0.76	
LL1	.220	.230	5.59	5.84	Q2	.030		0.76	
LL2	.115	.125	2.92	3.18					

NOTES:
1. Dimensions are in inches. Millimeters are given for information only.
2. Terminal 1 is the drain, terminal 2 is the gate, and terminal 3 is the source.
3. The following suffixes apply to this package configuration: Metal lid: U3 suffix; Ceramic lid: U3C suffix.
4. The lid shall be electrically isolated from the drain, gate, and source.

* FIGURE 1. Dimensions and configuration of surface mount (TO-276AA, SMD-0.5) package.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.




Key	Dimensions					
	Inches	Inches	Micrometers	Micrometers	Tolerance	Tolerance
	X	Y	X	Y	Inches	μmeter
1	0	0	0	0	±.0002	±5
2	.02129	0	541	0	±.0002	±5
3	0	.02119	0	538.3	±.0002	±5
4	.02129	.02119	541	538.3	±.0002	±5
5	.00303	.03570	77	906.8	±.0002	±5
6	.04606	.03570	1169.9	906.8	±.0002	±5
7	.00303	.15726	77	3994.5	±.0002	±5
8	.04606	.15726	1169.9	3994.5	±.0002	±5
A	.1815		4611		±.0079	±200
B	.1160		2946		±.0079	±200
C	.0074		187.9		N/A	N/A

NOTES:
1. Dimensions are in inches. Micrometers are given for general information only.
2. All dimensions are valid for all radiation hardness levels specified.
3. For sawn die, outline dimensions (A and B) will be reduced by .00098 inches (25 μm), due to saw kerf.
4. Die bond pad coordinates are provided for use in automated bonding equipment. Key locations 1 through 4 refer to adjacent gate (G) pad corners. Key locations 5 through 8 refer to adjacent source (S) pad corners.
5. Key 2 through 8 are relative to Key 1.
6. Top metal: Aluminum, 56,000 Å thick.
7. Back metal: Aluminum, Titanium, nickel, silver 1000 Å, 1000 Å, 4000 Å, 6000 Å thick, respectively.
8. Backside metal is the drain connection.

FIGURE 2. JANHC and JANKC (A-version) die dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.



Key	Dimensions					
	Inches	Inches	Micrometers	Micrometers	Tolerance	Tolerance
	X	Y	X	Y	Inches	μmeter
1	0	0	0	0	± 0.0002	± 5
2	0.01504	0	382	0	± 0.0002	± 5
3	0	0.01657	0	421	± 0.0002	± 5
4	0.01504	0.01657	382	421	± 0.0002	± 5
5	0.02055	0.06040	522	1534.2	± 0.0002	± 5
6	0.03559	0.06040	904	1534.2	± 0.0002	± 5
7	0.02055	0.10631	522	2700.2	± 0.0002	± 5
8	0.03559	0.10631	904	2700.2	± 0.0002	± 5
A	0.1843		4682		± 0.0079	± 200
B	0.1543		3920		± 0.0079	± 200
C	0.0150		381		± 0.0010	± 25

NOTES:
1. Dimensions are in inches. Micrometers are given for general information only.
2. All dimensions are valid for all radiation hardness levels specified.
3. For sawn die, outline dimensions (A and B) will be reduced by 0.001 inches (25 μm), due to saw kerf.
4. Die bond pad coordinates are provided for use in automated bonding equipment. Key locations 1 through 4 refer to adjacent gate (G) pad corners. Key locations 5 through 8 refer to adjacent source (S) pad corners.
5. Key 2 through 8 are relative to Key 1.
6. Top metal: 150V and 250V - Aluminum Copper (0.5%) Silicon (1%), 55,000 Å
7. Back metal: Titanium, Nickel, Silver 700 Å, 3200 Å, 7500 Å thick, respectively
8. Backside metal is the drain connection.

FIGURE 3. JANHC and JANKC (B-version) die dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 – Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 – Test Methods For Semiconductor Devices.
MIL-STD-883 – Test Method Standard for Microcircuits.

(Copies of these documents are available online at https://quicksearch.dla.mil).

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturer's list (QML) before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

3.4 Interface requirements and physical dimensions. The interface requirements and physical dimensions shall be as specified in MIL-PRF-19500 and herein. The device package style is either a metal lidded or ceramic lidded TO-276AA in accordance with figure 1 for all encapsulated devices. See figure 2 and figure 3 for un-encapsulated JANHC and JANKC die.

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.4.2 Multiple chip construction. Multiple chip construction shall not be permitted in order to meet the requirements of this specification.

3.4.3 Pin-out. The pin-out of the device shall be as shown on figure 1.

3.4.4 Silicone die coating. The use of a silicone die coat requires a successful completion of method 5011 of MIL-STD-883, on each lot of silicone die coating for its intended applications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

3.5 Marking. Marking shall be in accordance with MIL-PRF-19500.

3.6 Electrostatic discharge sensitive (ESDS). The devices covered by this specification sheet have been classified as ESDS. The devices shall be handled in accordance with the ESD program established to comply with the requirements of MIL-PRF-19500 to avoid damage due to the accumulation of static charge. The following handling practices shall be followed:

a. Devices should be handled on benches with conductive handling devices.

b. Ground test equipment, tools, and personnel handling devices.

c. Do not handle devices by the leads.

d. Store devices in conductive foam or carriers.

e. Avoid use of plastic, rubber or silk in MOS areas.

f. Maintain relative humidity above 50 percent if practical.

g. Care should be exercised during test and troubleshooting to apply not more than maximum rated voltage to any lead.

* h. Gate must be terminated to source, R ≤ 100 kΩ, whenever bias voltage is applied drain to source.

3.7 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I.

3.8 RHA. RHA requirements and test levels shall be as defined in MIL-PRF-19500 and herein. RHA characterization data shall be made available upon request of the acquiring or qualifying activity.

3.8.1 SEE. After being tested for SEE as specified in 4.5.2 at the identified test location (see 6.7) using the exposure, beam and bias conditions listed in table IV, the device testing conditions shall be listed in table IV.

3.9 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4 and tables I, and II).

d. Element evaluation of un-encapsulated die (see 4.6).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table III tests, the tests specified in table III herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

4.2.2 SEE. SEE (SEB/SEGR) shall be performed at initial qualification and thereafter whenever a process or a major die design change which may affect radiation hardness is introduced. Upon qualification, manufacturers shall provide the SEE verification test conditions from section 5 of method 1080 of MIL-STD-750 that were used to qualify the device for inclusion into section 6 herein.

4.2.3 Silicone die coating. The successful completion of method 5011 of MIL-STD-883 on silicone die coating shall be part of the full MIL-PRF-19500 qualification process.

4.3 Screening of encapsulated devices. Screening of packaged devices shall be in accordance with table E-IV of MIL-PRF-19500, and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (1) (2)	Measurements for JANS	Measurements for JANTXV
(3)	Gate stress test (see 4.3.1)	Gate stress test (see 4.3.1)
(3)	Method 3470 of MIL-STD-750, E_{AS} (see 4.3.2)	Method 3470 of MIL-STD-750, E_{AS} (see 4.3.2)
(3) 3c	Method 3161 of MIL-STD-750, thermal impedance, (see 4.3.3)	Method 3161 of MIL-STD-750, thermal impedance, (see 4.3.3)
5	Method 2052 of MIL-STD-750, PIND (see 4.3.4)	Not applicable
9	Subgroup 2 of table I herein	Not applicable
10	Method 1042 of MIL-STD-750, test condition B	Method 1042 of MIL-STD-750, test condition B
11	Subgroup 2 of table I herein. ΔI_{GSSF1} = ±20 nA dc or ±100 percent of initial value, whichever is greater. ΔI_{GSSR1} = ±20 nA dc or ±100 percent of initial value, whichever is greater. ΔI_{DSS1} = ±10 µA dc or ±100 percent of initial value, whichever is greater.	Subgroup 2 of table I herein.
12	Method 1042 of MIL-STD-750, test condition A	Method 1042 of MIL-STD-750, test condition A
13	Subgroups 2 and 3 of table I herein ΔI_{GSSF1} = ±20 nA dc or ±100 percent of initial value, whichever is greater. ΔI_{GSSR1} = ±20 nA dc or ±100 percent of initial value, whichever is greater. ΔI_{DSS1} = ±10 µA dc or ±100 percent of initial value, whichever is greater. $\Delta r_{DS(ON)1}$ = ±20 percent of initial value. $\Delta V_{GS(TH)1}$ = ±20 percent of initial value.	Subgroup 2 of table I herein ΔI_{GSSF1} = ±20 nA dc or ±100 percent of initial value, whichever is greater. ΔI_{GSSR1} = ±20 nA dc or ±100 percent of initial value, whichever is greater. ΔI_{DSS1} = ±10 µA dc or ±100 percent of initial value, whichever is greater. $\Delta r_{DS(ON)1}$ = ±20 percent of initial value. $\Delta V_{GS(TH)1}$ = ±20 percent of initial value.
17	For TO-276AA packages: Method 1081 of MIL-STD-750, DWV (see 4.3.5), Endpoints: Subgroup 2 of table I herein.	For TO-276AA packages: Method 1081 of MIL-STD-750, DWV (see 4.3.5), Endpoints: Subgroup 2 of table I herein.

(1) At the end of the test program, I_{GSSF1}, I_{GSSR1}, and I_{DSS1} are measured.
(2) An out-of-family program to characterize I_{GSSF1}, I_{GSSR1}, I_{DSS1} and $V_{GS(th)1}$ shall be invoked.
(3) Shall be performed anytime after temperature cycling, screen 3a; JANTXV does not need to be repeated in screening requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

4.3.1 Gate stress test. Apply V_{GS} = 24 V minimum for t = 250 µs minimum.

4.3.2 Single pulse avalanche energy (E_{AS}). The test for single pulse avalanche energy shall be performed in accordance with method 3470 of MIL-STD-750. The following details shall apply:

a. Peak current (I_{AS}) ..... $I_{AS} = I_{D1}$.

b. Inductance (L) ..... $L = \left[\frac{2E_{AS}}{(I_{D1})^2}\right]\left[\frac{V_{BR} - V_{DD}}{V_{BR}}\right]$ mH minimum.

c. Gate to source resistor (R_{GS}) ..... $25 \leq R_{GS} \leq 200\ \Omega$.

d. Supply voltage (V_{DD}) ..... V_{DD} = 25 V dc, except V_{DD} = 50 V dc (2N7593), up to rated V_{DS}.

e. Peak gate voltage (V_{GS}) ..... 12 V, up to maximum rated V_{GS}.

f. Initial case temperature (T_C) ..... T_C = +25°C +10°C, -5°C.

g. Number of pulses to be applied ..... 1 pulse minimum.

4.3.3 Thermal impedance. The thermal impedance measurements shall be performed in accordance with method 3161 of MIL-STD-750 using the guidelines in that method for determining I_M, I_H, t_H, t_{SW}, t_{MD} (and V_H where appropriate). See table III, group E, subgroup 4 herein.

4.3.4 PIND. Not applicable in screening when devices are processed using alternative method and flow requirements approved by the qualifying activity, that includes incorporating the use of certified clean processing and silicone die coat. Instead, the PIND test performance shall be performed in group B3 and group C3, on a lot sample basis. PIND failures detected in group B or C will represent lot jeopardy and be evaluated for root cause and lot integrity.

4.3.5 Dielectric withstanding voltage (DWV). The test for DWV shall be performed in accordance with test method 1081 of MIL-STD-750. The following details shall apply:

a. Magnitude of test voltage.....600V dc.

b. Duration of application of test voltage.....15 seconds (min).

c. Points of application of test voltage .....All leads to case (bunch connection).

d. Method of connection.....Mechanical.

e. Kilovolt-ampere rating of high voltage source .....1,200 V, 1.0 mA (min).

f. Maximum leakage current.....1.0 mA.

g. Voltage ramp up time.....500 V/second.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with table E-V of MIL-PRF-19500 and table I herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VIA (JANS) and table E-VIB (JANTXV) of MIL-PRF-19500, and as follows.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

4.4.2.1 Quality level JANS (table E-VIA of MIL-PRF-19500).

Subgroup	Method	Condition
B3	1051	Test condition G, 100 cycles.
B3	2077	Scanning electron microscope (SEM).
B3	2052	PIND, required if not performed in screening. Sampling plan 22 devices, c = 0 for large lots, 12 devices, c = 0 for small lots.
B4	1042	Intermittent operation life, condition D, t_{on} shall be 30 seconds minimum.
B5	1042	Accelerated steady-state gate bias, condition B, V_{GS} = rated V_{GS}; T_A = +175 °C, t = 24 hours minimum; or T_A = +150 °C, t = 48 hours minimum.
B5	1042	Accelerated steady-state reverse bias, condition A, V_{DS} = rated V_{DS}; T_A = +175 °C, t = 120 hours minimum; or T_A = +150 °C, t = 240 hours minimum.
B5	2037	Test condition D.

4.4.2.2 Quality level JANTXV (table E-VIB of MIL-PRF-19500).

Subgroup	Method	Condition
B2	1051	Test condition G, 25 cycles.
B3	1042	Intermittent operation life, condition D, t_{on} shall be 30 seconds minimum.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of MIL-PRF-19500 and as follows.

Subgroup	Method	Condition
C2	2036	Terminal strength is not applicable.
C3	2052	PIND, required if not performed in screening. Sampling plan 22 devices, c = 0 for large lots, 12 devices, c = 0 for small lots.
C5	3161	See 4.3.3, $R_{\theta JC}$ = 1.67 °C/W.
C6	1042	Intermittent operation life, condition D, t_{on} shall be 30 seconds minimum.

4.4.4 Group D inspection. Group D inspection shall be conducted in accordance with table E-VIII of MIL-PRF-19500 and table II herein.

4.4.5 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-IX of MIL-PRF-19500 and as specified in table III herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

4.5.2 SEE. The heavy ion SEE (SEB/SEGR) characterization testing shall be performed in accordance with method 1080 of MIL-STD-750. Electrical measurements (end-points) shall be in accordance with table III herein.

4.6 Element evaluation of un-encapsulated die. The element evaluation of un-encapsulated die shall be in accordance with appendix G of MIL-PRF-19500.

TABLE I. Group A inspection.

Inspection 1/, 2/	MIL-STD-750		Symbol	Limits	Limits	Unit
	Method	Condition		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Thermal impedance 3/	3161	See 4.3.3	$Z_{\theta JC}$			°C/W
Breakdown voltage drain to source	3407	Bias condition C, V_{GS} = 0 V, I_D = 1 mA dc	$V_{(BR)DSS}$			
2N7587				100		V dc
2N7589				150		V dc
2N7591				200		V dc
2N7593				250		V dc
Gate to source voltage (threshold)	3403	$V_{DS} \geq V_{GS}$, I_D = 1 mA dc	$V_{GS(TH)1}$	2.0	4.0	V dc
Gate current	3411	Bias condition C, V_{GS} = +20 V dc, V_{DS} = 0 V	I_{GSSF1}		+100	nA dc
Gate current	3411	Bias condition C, V_{GS} = -20 V dc, V_{DS} = 0 V	I_{GSSR1}		-100	nA dc
Drain current	3413	Bias condition C, V_{GS} = 0 V dc, V_{DS} = 80 percent of rated V_{DS}	I_{DSS1}		10	µA dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/, 2/	MIL-STD-750		Symbol	Limits	Limits	Unit
	Method	Condition		Min	Max	
Subgroup 2 - continued.						
Static drain to source on-state resistance	3421	Condition A, V_{GS} = 12 V dc, pulsed (see 4.5.1), $I_D = I_{D2}$	$r_{DS(ON)1}$			
2N7587					0.042	Ω
2N7589					0.088	Ω
2N7591					0.130	Ω
2N7593					0.210	Ω
Forward voltage	4011	Condition A, V_{GS} = 0 V dc, $I_D = I_{D1}$	V_{SD}		1.2	V dc
Subgroup 3						
High temperature operation		$T_C = T_J$ = +125°C				
Gate current	3411	Bias condition C, V_{GS} = ±20 V dc, V_{DS} = 0 V	I_{GSS2}		±200	nA dc
Drain current	3413	Bias condition C, V_{GS} = 0 V dc, V_{DS} = 80 percent of rated V_{DS}	I_{DSS2}		25	μA dc
Static drain to source on-state resistance	3421	Condition A, V_{GS} = 12 V dc, pulsed (see 4.5.1), $I_D = I_{D2}$	$r_{DS(ON)3}$			
2N7587					0.080	Ω
2N7589					0.176	Ω
2N7591					0.273	Ω
2N7593					0.441	Ω
Gate to source voltage (threshold)	3403	$V_{DS} \geq V_{GS}$, I_D = 1 mA dc	$V_{GS(TH)2}$	1.0		V dc
Low temperature operation		$T_C = T_J$ = -55°C				
Gate to source voltage (threshold)	3403	$V_{DS} \geq V_{GS(TH)3}$, I_D = 1 mA dc	$V_{GS(TH)3}$		5.0	V dc
Subgroup 4						
Forward transconductance	3475	$I_D = I_{D2}$, V_{DD} = 15 V dc (see 4.5.1)	g_{FS}			
2N7587				14		S
2N7589				13		S
2N7591				10		S
2N7593				8.8		S

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/, 2/	MIL-STD-750		Symbol	Limits	Limits	Unit
	Method	Condition		Min	Max	
Subgroup 4 - continued.						
Switching time test	3472	I_D = rated I_{D1}, V_{GS} = 12 V dc, R_G = 7.5 Ω, V_{DD} = 50 percent of rated V_{DS}				
Turn-on delay time			$t_{d(on)}$		25	ns
Rise-time			t_r		30	ns
Turn-off delay time			$t_{d(off)}$		60	ns
Fall time			t_f		30	ns
Subgroup 5						
Safe operating area	3474	See figure 6; tp = 10 ms min. V_{DS} = 80 percent of max. rated V_{DS}				
Electrical measurements		See table I, subgroup 2				
Subgroup 6						
Not applicable						
Subgroup 7						
Gate charge	3471	Condition B, I_D = I_{D1}, V_{GS} = 12 V dc V_{DD} = 50 percent of rated V_{DS}				
On-state gate charge			$Q_{G(ON)}$		50	nC
and turn-off gate charge			$Q_{G(OFF)}$		50	nC
Gate to source charge			Q_{GS1}		15	nC
(turn-on and turn-off)			Q_{GS2}		15	nC
Gate to drain charge			Q_{GD1}		20	nC
(turn-on and turn-off)			Q_{GD2}		20	nC
Reverse recovery time	3473	Condition A, di/dt = -100 A/µs, V_{DD} ≤ 50 V, I_D = I_{D1}	t_{rr}			
2N7587					350	ns
2N7589					350	ns
2N7591					350	ns
2N7593					450	ns

1/ Also applies to U3 and U3C suffix versions.
2/ For sampling plan, see MIL-PRF-19500.
3/ For end-point measurements, this test is required for the following subgroups:
Group B, subgroups 2 and 3 (JANTXV).
Group B, subgroups 3 and 4 (JANS).
Group C, subgroup 2 and 6.
Group E, subgroup 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

TABLE II. Group D inspection.

Inspection 1/ 2/ 3/	MIL-STD-750		Symbol	Pre-irradiation limits		Post-irradiation limits		Unit
	Method	Conditions		R, F, G	R, F, G	R, F, G	R, F, G	
				Min	Max	Min	Max	
Subgroup 1								
Not applicable								
Subgroup 2		T_C = + 25 °C						
Steady-state total dose irradiation (V_{GS} bias) 4/	1019	Condition A, V_{GS} = 12 V; V_{DS} = 0						
Steady-state total dose irradiation (V_{DS} bias) 4/	1019	Condition A, V_{GS} = 0; V_{DS} = 80 percent of rated V_{DS} (pre-irradiation)						
End-point electricals								
Breakdown voltage, drain to source	3407	Bias condition C, V_{GS} = 0; I_D = 1 mA	$V_{(BR)DSS}$					
2N7587				100		100		V dc
2N7589				150		150		V dc
2N7591				200		200		V dc
2N7593				250		250		V dc
Gate to source voltage (threshold)	3403	$V_{DS} \geq V_{GS}$, I_D = 1 mA	$V_{GS(th)1}$	2.0	4.0	2.0	4.0	V dc
Gate current	3411	Bias condition C, V_{GS} = +20 V; V_{DS} = 0	I_{GSSF1}		100		100	nA dc
Gate current	3411	Bias condition C, V_{GS} = -20 V; V_{DS} = 0	I_{GSSR1}		-100		-100	nA dc
Drain current	3413	Bias condition C, V_{GS} = 0, V_{DS} = 80 percent of rated V_{DS} (pre-irradiation)	I_{DSS}		10		10	µA dc
Static drain to source on-state voltage	3405	V_{GS} = 12 V; I_D = I_{D2} condition A, pulsed (see 4.5.1)	$V_{DS(on)}$					
2N7587					0.855		0.855	V dc
2N7589					1.104		1.104	V dc
2N7591					1.340		1.340	V dc
2N7593					1.638		1.638	V dc
Forward voltage source drain diode	4011	Bias condition A, V_{GS} = 0; I_D = I_{D1}	V_{SD}		1.2		1.2	V dc

1/ For sampling plan, see MIL-PRF-19500. Characteristics also apply to U3 and U3C suffix versions.
2/ Group D qualification may be performed prior to lot formation. Wafers qualified to these group D QCI requirements may be used for any other specification sheets utilizing the same die design.
3/ At the manufacturer's option, group D samples need not be subjected to the screening tests and may be assembled in its qualified package or in any qualified package that the manufacturer has data to correlate the performance to the designated package.
4/ Separate samples shall be selected for each bias. Devices supplied to this specification sheet have been characterized through RHA levels R and F of irradiation. Pre and Post irradiation values are identical unless otherwise specified in table II. When performing post irradiation electrical measurements for any RHA level, T_A = +25°C (see 1.6 herein).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

TABLE III. Group E inspection (all quality levels) for qualification or re-qualification only.

Inspection	MIL-STD-750		Sample plan
	Method	Conditions	
Subgroup 1			45 devices, c = 0
Temperature cycling	1051	Test condition G, 500 cycles.	
Hermetic seal	1071	Fine and gross leak, as applicable.	
Electrical measurements		See table I, subgroup 2 herein.	
Subgroup 2 1/			45 devices, c = 0
Steady-state gate bias	1042	Condition B, 1,000 hours.	
Electrical measurements		See table I, subgroup 2 herein.	
Steady-state reverse bias	1042	Condition A, 1,000 hours.	
Electrical measurements		See table I, subgroup 2 herein.	
Subgroup 4			Sample size, N/A
Thermal impedance curves		See MIL-PRF-19500.	
Subgroup 5			
Barometric pressure	1001	Condition C (to 70,000 feet).	3 devices, c = 0
Subgroup 10			22 devices, c = 0
Commutating diode for safe operating area	3476	Test conditions shall be derived by the manufacturer.	
Subgroup 11			3 devices
SEE 2/ 3/	1080	See 1.6, 6.2, 6.7, and table IV.	

1/ A separate sample for each test shall be selected.
2/ Group E qualification of SEE testing may be performed prior to lot formation. Qualification may be extended to other specification sheets utilizing the same structurally identical die design.
3/ Device qualification to a higher level LET is sufficient to qualify all lower level LETs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.






FIGURE 4. Thermal response curve.


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.




2N7587U3 and 2N7587U3C



2N7589U3 and 2N7589U3C



2N7591U3 and 2N7591U3C




2N7593U3 and 2N7593U3C

FIGURE 5. Maximum drain current versus case temperature graphs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

2N7587U3 and 2N7587U3C



2N7589U3 and 2N7589U3C





FIGURE 6. Safe operating area graph.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

2N7591U3 and 2N7591U3C



2N7593U3 and 2N7593U3C




FIGURE 6. Safe operating area graph − Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).

c. Lead finish (see 3.4.1).

d. The complete PIN, see 1.5 and 6.4.

e. For acquisition of JANHC or JANKC die, the die identifier letter version should be specified (see 1.5.6, 6.4.2, figure 2 and figure 3).

f. For acquisition of RHA designated devices, table II, subgroup 1 testing of group D herein is optional. If subgroup 1 is desired, it should be specified in the contract.

g. If specific SEE characterization conditions are desired (see section 6.7 and table IV), manufacturer's CAGE code should be specified in the contract or order.


h. If SEE testing data is desired, it should be specified in the contract or order.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML 19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Land and Maritime, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://qpldocs.dla.mil.


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

6.4 PIN construction examples.

6.4.1 Encapsulated devices. The PINs for encapsulated devices are constructed using the following form.



6.4.2 Un-encapsulated devices. The PINs for un-encapsulated devices are constructed using the following form.



6.5 List of PINs.

6.5.1 List of PINs for encapsulated devices. The following is a list of possible PINs for encapsulated devices available on this specification sheet.

Quality level "TXV" 1/		Quality level "S" 1/		
JANTXVF2N7587U3	JANTXVR2N7587U3	JANSF2N7587U3	JANSR2N7587U3	
JANTXVF2N7587U3C	JANTXVR2N7587U3C	JANSF2N7587U3C	JANSR2N7587U3C	
JANTXVF2N7589U3	JANTXVR2N7589U3	JANSF2N7589U3	JANSR2N7589U3	
JANTXVF2N7589U3C	JANTXVR2N7589U3C	JANSF2N7589U3C	JANSR2N7589U3C	
JANTXVF2N7591U3	JANTXVR2N7591U3	JANSF2N7591U3	JANSR2N7591U3	
JANTXVF2N7591U3C	JANTXVR2N7591U3C	JANSF2N7591U3C	JANSR2N7591U3C	
JANTXVF2N7593U3	JANTXVR2N7593U3	JANSF2N7593U3	JANSR2N7593U3	JANSG2N7593U3
JANTXVF2N7593U3C	JANTXVR2N7593U3C	JANSF2N7593U3C	JANSR2N7593U3C	

These PIN are also available without a RHA designator.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

* 6.5.2 List of PINs for un-encapsulated devices. The following is a list of possible PINs available on this specification sheet. The qualified die suppliers with the applicable letter version (e.g., JANHCAR2N7587) will be identified on the QML.

Die ordering information		
Type	Manufacturer 1/	Manufacturer 1/
	69210	43611
2N7587	JANHCA#2N7587 JANKCA#2N7587	JANHCB#2N7587 JANKCB#2N7587
2N7589	JANHCA#2N7589 JANKCA#2N7589	JANHCB#2N7589 JANKCB#2N7589
2N7591	JANHCA#2N7591 JANKCA#2N7591	
2N7593	JANHCA#2N7593 JANKCA#2N7593	JANHCB#2N7593 JANKCB#2N7593

1/ The number sign (#) represent one of three RHA designators available (R, F, or G). The PIN is also available without a RHA designator.

6.6 Substitution information. Devices covered by this specification are substitutable for the manufacturer's and user's PIN (without JAN and RHA prefix). This information in no way implies that manufacturer's PINs are substitutable for the military PIN.

Preferred military types	Commercial PIN	Commercial PIN
2N7587U3 2N7589U3 2N7591U3 2N7593U3	IRHNJ67130 IRHNJ67134 IRHNJ67230 IRHNJ67234	MRH15N19U3 MRH25N12U3
2N7587U3C 2N7589U3C 2N7591U3C 2N7593U3C	IRHNJC67130 IRHNJC67134 IRHNJC67230 IRHNJC67234	

6.7 Manufacturer specific SEE irradiation characterization conditions. The manufacturer's SEE irradiation characterization conditions listed in table IV is for information only. Each qualified manufacturer identified in table IV has characterized its devices to the requirements of method 1080 of MIL-STD-750 using the testing conditions specified herein (see 1.6 and table IV). Since each manufacturer's characterization testing conditions can be different and may vary by the revision of method 1080 of MIL-STD-750 that was used during qualification testing, the revision and conditions used by each manufacturer for characterization have been listed in table IV for information only.

The SEE (SEB and SEGR) conditions and figures listed herein are current of the date of this specification sheet. For irradiation testing results data, please contact the qualified manufacturer for the most recent conditions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

TABLE IV. SEE characterization conditions for method 1080 of MIL-STD-750. 1/

Inspection	Type	Irradiation conditions
		Applicable to manufacturer CAGE code 69210 only. 2/ Sample size of 3 devices. Applicable to devices with a date code of September 2009 and newer.
Pre SEE electrical measurements	All devices in sample	I_{GSSF1}, I_{GSSR1}, and I_{DSS1} in accordance with table I, subgroup 2
SEE 3/		Fluence = $3x10^5$ ±20 percent ions/cm^2 Flux = $2x10^3$ to $2x10^4$ ions/cm^2/sec, temperature = 25 ±5°C
	2N7587	Surface LET = 39 MeV-cm^2/mg, range = 40 µm, Kr ion energy = 315 MeV In-situ bias conditions: V_{DS} = 100 V and V_{GS} = -19 V; V_{DS} = 40 V and V_{GS} = -20 V (Typical 3.80 MeV/Nucleon at Texas A & M Cyclotron)
	2N7589	Surface LET = 39 MeV-cm^2/mg, range = 50 µm, Kr ion energy = 410 MeV In-situ bias conditions: V_{DS} = 150 V and V_{GS} = -20 V (Typical 4.90 MeV/Nucleon at Texas A & M Cyclotron)
	2N7591	Surface LET = 42 MeV-cm^2/mg, range = 205 µm, Kr ion energy = 2450 MeV In-situ bias conditions: V_{DS} = 200 V and V_{GS} = -10 V; V_{DS} = 190 V and V_{GS} = -15 V (Typical 18.93 MeV/Nucleon at Texas A & M Cyclotron)
	2N7593	Surface LET = 44 MeV-cm^2/mg, range = 125 µm, Ag ion energy = 1350 MeV In-situ bias conditions: V_{DS} = 250 V and V_{GS} = -15 V, V_{DS} = 40 V and V_{GS} = -20 V (Typical 10.05 MeV/Nucleon at Texas A & M Cyclotron)
Post SEE electrical measurements	All devices in sample	I_{GSSF1}, I_{GSSR1}, and I_{DSS1} in accordance with table I, subgroup 2

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

TABLE IV. SEE characterization conditions for method 1080 of MIL-STD-750 − Continued. 1/

Inspection	Type	Irradiation conditions
		Applicable to manufacturer CAGE code 69210 only − continued. 2/
		Sample size of 3 devices. Applicable to devices with a date code of September 2009 and newer.
Pre SEE electrical measurements	All devices in sample	I_{GSSF1}, I_{GSSR1}, and I_{DSS1} in accordance with table I, subgroup 2
SEE 3/		Fluence = $3x10^5$ ±20 percent ions/cm^2 Flux = $2x10^3$ to $2x10^4$ ions/cm^2/sec, temperature = 25 ±5°C
	2N7587	Surface LET = 61 MeV-cm^2/mg, range = 32 µm, Xe ion energy = 345 MeV
		In-situ bias conditions: V_{DS} = 100 V and V_{GS} = -10 V; V_{DS} = 30 V and V_{GS} = -15 V
		(Typical 2.70 MeV/Nucleon at TAMU Cyclotron)
	2N7589	Surface LET = 61 MeV-cm^2/mg, range = 66 µm, Xe ion energy = 825 MeV
		In-situ bias conditions: V_{DS} = 150 V and V_{GS} = -10 V V_{DS} = 40 V and V_{GS} = -15 V
		(Typical 6.40 MeV/Nucleon at TAMU Cyclotron)
	2N7591	Surface LET = 61 MeV-cm^2/mg, range = 66 µm, Xe ion energy = 825 MeV
		In-situ bias conditions: V_{DS} = 200 V and V_{GS} = -10 V, V_{DS} = 190 V and V_{GS} = -15 V
		(Typical 6.41 MeV/Nucleon at TAMU Cyclotron)
	2N7593	Surface LET = 61 MeV-cm^2/mg, range = 66 µm, Xe ion energy = 825 MeV
		In-situ bias conditions: V_{DS} = 250 V and V_{GS} = -10 V, V_{DS} = 50 V and V_{GS} = -15 V
		(Typical 6.41 MeV/Nucleon at TAMU Cyclotron)
Post SEE electrical measurements	All devices in sample	I_{GSSF1}, I_{GSSR1}, and I_{DSS1} in accordance with table I, subgroup 2

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

TABLE IV. SEE characterization conditions for method 1080 of MIL-STD-750 − Continued. 1/

Inspection	Type	Irradiation conditions
		Applicable to manufacturer CAGE 69210 only − continued. 2/ Sample size of 3 devices. Applicable to devices with a date code of September 2009 and newer.
Pre SEE electrical measurements	All devices in sample	I_{GSSF1}, I_{GSSR1}, and I_{DSS1} in accordance with table I, subgroup 2
SEE 3/		Fluence = $3x10^5$ ±20 percent ions/cm^2 Flux = $2x10^3$ to $2x10^4$ ions/cm^2/sec, temperature = 25 ±5°C
	2N7587	Surface LET = 90 MeV-cm^2/mg, range = 29 µm, Au ion energy = 375 MeV In-situ bias conditions: V_{DS} = 100 V and V_{GS} = -5 V, (Typical 1.88 MeV/Nucleon at TAMU Cyclotron)
	2N7589	Surface LET = 90 MeV-cm^2/mg, range = 80 µm, Au ion energy = 1472 MeV In-situ bias conditions: V_{DS} = 50 V and V_{GS} = -5 V, V_{DS} = 30 V and V_{GS} = -10 V (Typical 7.47 MeV/Nucleon at TAMU Cyclotron)
	2N7591	Surface LET = 90 MeV-cm^2/mg, range = 80 µm, Au ion energy = 1470MeV In-situ bias conditions: V_{DS} = 150 V and V_{GS} = -4 V, V_{DS} = 110 V and V_{GS} = -5 V; (Typical 11.40 MeV/Nucleon at TAMU Cyclotron)
	2N7593	Surface LET = 90 MeV-cm^2/mg, range = 80 µm, Au ion energy = 1470 MeV In-situ bias conditions: V_{DS} = 75 V and V_{GS} = -5 V (Typical 6.40 MeV/Nucleon at TAMU Cyclotron)
Post SEE electrical measurements	All devices in sample	I_{GSSF1}, I_{GSSR1}, and I_{DSS1} in accordance with table I, subgroup 2

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

TABLE IV. SEE characterization conditions for method 1080 of MIL-STD-750 − Continued. 1/

	Inspection	Type	Irradiation conditions
			Applicable to manufacturer CAGE 43611 only. Sample size of 3 devices. 2/
	Pre SEE electrical measurements	All devices in sample	I_{GSSF1}, I_{GSSR1}, and I_{DSS1} in accordance with table I, subgroup 2
	SEE 3/		Fluence = $3x10^5$ ±20 percent ions/cm^2 Flux = $2x10^3$ to $2x10^4$ ions/cm^2/sec, temperature = 25 ±5°C
*		2N7587	Surface LET = 43.9 MeV-cm^2/mg, range = 50 µm, Ag ion energy = 1330 MeV In-situ bias conditions: V_{DS} = 100 V and V_{GS} = -19 V; V_{DS} = 40 V and V_{GS} = -20 V (Typical 3.80 MeV/Nucleon at Texas A & M Cyclotron)
		2N7589	Surface LET = 38.6 MeV-cm^2/mg, range = 50.8 µm, Kr ion energy = 410 MeV In-situ bias conditions: V_{DS} = 150 V and V_{GS} = -20 V, (Typical 4.89 MeV/Nucleon at TAMU Cyclotron)
		2N7593	Surface LET = 44 MeV-cm^2/mg, range = 125 µm, Ag ion energy = 1350 MeV In-situ bias conditions: V_{DS} = 250 V and V_{GS} = -15 V, V_{DS} = 40 V and V_{GS} = -20 V (Typical 10.05 MeV/Nucleon at TAMU Cyclotron)
*		2N7587	Surface LET = 61 MeV-cm^2/mg, range = 66 µm, Xe ion energy = 825 MeV In-situ bias conditions: V_{DS} = 100 V and V_{GS} = -10 V; V_{DS} = 30 V and V_{GS} = -15 V (Typical 2.70 MeV/Nucleon at TAMU Cyclotron)
		2N7589	Surface LET = 64 MeV-cm^2/mg, range = 69.9 µm, Xe ion energy = 942 MeV In-situ bias conditions: V_{DS} = 150 V and V_{GS} = -10 V, V_{DS} = 40 V and V_{GS} = -15 V (Typical 7.31 MeV/Nucleon at TAMU Cyclotron)
		2N7593	Surface LET = 61 MeV-cm^2/mg, range = 66 µm, Xe ion energy = 825 MeV In-situ bias conditions: V_{DS} = 250 V and V_{GS} = -10 V, V_{DS} = 50 V and V_{GS} = -15 V (Typical 6.41 MeV/Nucleon at TAMU Cyclotron)

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

TABLE IV. SEE characterization conditions for method 1080 of MIL-STD-750 − Continued. 1/

Inspection	Type	Irradiation conditions
		Applicable to manufacturer CAGE 43611 only. Sample size of 3 devices. 2/
Pre SEE electrical measurements	All devices in sample	I_{GSSF1}, I_{GSSR1}, and I_{DSS1} in accordance with table I, subgroup 2
*	2N7587	Surface LET = 90 MeV-cm^2/mg, range = 80 µm, Au ion energy = 1470 MeV In-situ bias conditions: V_{DS} = 100 V and V_{GS} = -4 V, (Typical 1.88 MeV/Nucleon at TAMU Cyclotron)
	2N7589	Surface LET = 90 MeV-cm^2/mg, range = 83.2 µm, Au ion energy = 1489 MeV In-situ bias conditions: V_{DS} = 50 V and V_{GS} = -5 V, V_{DS} = 30 V and V_{GS} = -10 V (Typical 7.56 MeV/Nucleon at TAMU Cyclotron)
	2N7593	Surface LET = 90 MeV-cm^2/mg, range = 80 µm, Au ion energy = 1470 MeV In-situ bias conditions: V_{DS} = 250 V and V_{GS} = -5 V (Typical 6.40 MeV/Nucleon at TAMU Cyclotron)
Post SEE electrical measurements	All devices in sample	I_{GSSF1}, I_{GSSR1}, and I_{DSS1} in accordance with table I, subgroup 2


1/ Devices were tested in a TO-257 (T3) package for manufacturer 69210 or in a TO-204AA (TO-3) package for manufacturer 43611 in lieu of the TO-276AA (U3 or U3C) packages described by this specification sheet.

2/ Electrical measurements (I_{GSSF1}, I_{GSSR1}, and I_{DSS}) were taken before and following SEE irradiation to determine acceptability for each bias condition. Other test conditions in accordance with table I, subgroup 2 may be taken at the manufacturer's option.


*3/ Manufacturer performed heavy ion SEE (SEB/SEGR) test at TAMU Radiation Effects Facility for the MOSFET technology devices in accordance with method 1080.0 of MIL-STD-750. No single event burnout (SEB) and Single event gate rupture (SEGR) were observed to surface LET as stated above table IV and safe operating area (see figures 7, 8, 9, and 10). Limits are characterized at initial qualification and after any design or process changes which may affect the SEE (SEB/SEGR) characteristics. For more information on SEE (SEB/SEGR) test results, customers are requested to contact the qualified manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.


2N7587



2N7589



2N7591



2N7593





FIGURE 7. Typical SEE safe operating area graphs (CAGE 69210).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.


2N7587



NOTES:
1. LET for Ag is 43.9 ±5 percent, 50 µm ±5 percent, 1330 MeV ±5 percent.
2. LET for Xe is 61 ±5 percent, 66 µm ±7.5 percent, 825 MeV ±5 percent.
3. LET for Au is 90 ±5 percent, 80 µm ±5 percent, 1470 MeV ±5 percent.

* FIGURE 8. Typical SEE safe operating area response (CAGE 43611).


2N7589



NOTES:
1. LET for Kr is 38.6 ±5 percent, 50.8 µm ±10 percent, 410 MeV ±5 percent.
2. LET for Xe is 64 ±5 percent, 69.9 µm ±7.5 percent, 942 MeV ±5 percent.
3. LET for Au is 90 ±5 percent, 83.2 µm ±5 percent, 1489 MeV ±5 percent.

FIGURE 9. Typical SEE safe operating area response (CAGE 43611).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.



NOTES:
1. LET for Ag is 44 ±5 percent, 125 µm ±10 percent, 1350 MeV ±5 percent.
2. LET for Xe is 61 ±5 percent, 66 µm ±7.5 percent, 825 MeV ±5 percent.
3. LET for Au is 90 ±5 percent, 80 µm ±5 percent, 1470 MeV ±5 percent.

FIGURE 10. Typical SEE safe operating area response (CAGE 43611).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.

6.8 Request for new types and configurations. Requests for new device types or configurations for inclusions in this specification sheet should be submitted to: DLA Land and Maritime, ATTN: VAC, Post Office Box 3990, Columbus, OH 43218-3990 or by electronic mail at Semiconductor@dla.mil or by facsimile (614) 692-6939 or DSN 850-6939.

6.9 Amendment notations. The margins of this specification are marked with asterisks to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army − CR
Navy − SH
Air Force − 85
NASA − NA
DLA − CC

Review activities:
Army − MI
Air Force − 19

Preparing activity:
DLA − CC

(Project 5961-2024-053)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:27Z
Check the source to verify that this is the current version before use.