NOT MEASUREMENT SENSITIVE


MIL-B-3628/14J
30 July 1993
SUPERSEDING
MIL-B-3628/14H
8 July 1991

MILITARY SPECIFICATION SHEET


BADGE, QUALIFICATION, BASIC, EXPERT, SHARPSHOOTER AND MARKSMAN, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense


The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3628.



EXPERT



SHARPSHOOTER



MARKSMAN

MATERIAL: Red Brass, Nickel Silver or Zinc Aluminum

DASH NO:
-1: Expert
-2: Sharpshooter
-3: Marksman

FINISH:

Red Brass or Nickel Silver: Nickel Plated (Red Brass only), Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.

Zinc Aluminum: Copper Plated, Nickel Plated, Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:50Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

HEIGHT (Overall):
-1: 1-11/32 inches (3.41 cm) (REF)
-2: 1 inch (2.54 cm) (REF)
-3: 1 inch (2.54 cm) (REF)

WIDTH (Overall):
-1: 1-5/32 inches (2.94 cm) (REF)
-2: 1 inch (2.54 cm) (REF)
-3: 1 inch (2.54 cm) (REF)

THICKNESS (At rim of cross): 0.070 inch ± 0.005 inch (0.177 cm ± 0.012 cm)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Piercing shall be as indicated.

3. The attaching device shall be prong and clutch type. The prongs shall be located on the horizontal centerline, equidistant from each side and 1 inch ± 1/32 inch (2.54 ± 0.08 cm) apart for Dash No 1 and 3/4 inch ± 1/32 inch (1.91 cm ± 0.08 cm) apart for Dash No 2 and 3.

4. Lugs shall be equidistant from each side and 0.675 inch + 0.015 inch - 0 inch (1.71 cm + 0.038 cm - 0 cm) on centers.

5. Badges covered by this specification sheet shall be used in conjunction with badge clasps covered in specification sheet MIL-B-3628/15.

6. Badge may be nickel or rhodium plated with a mirror-like polished finish which shall match the TIOH Metal Finish Chip Number 16 for commercial sale only. For nickel plated or rhodium plated items, the silver plating requirement shall not apply.

Custodian:
Army - IH

Preparing Activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0693)

Source: https://assist.dla.mil - Downloaded: 2026-10-16T18:50Z
Check the source to verify that this is the current version before use.