NOT MEASUREMENT SENSITIVE

MIL-B-3628/15F
26 April 1991
SUPERSEDING
MIL-B-3628/15E
10 February 1988

MILITARY SPECIFICATION SHEET

Badge Clasps, Badge, Qualification, Basic, Sharpshooter and Marksman, Army

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3628.



PEBBLED BACKGROUND

DASH NO:	Badge Clasp Title
-1:	Rifle
-2:	Recoilless Rifle
-3:	Auto-Rifle
-4:	Small Bore Rifle
-5:	Bayonet
-6:	Pistol
-7:	Flame Thrower
-8:	Small Bore Pistol
-9:	Tank Weapons
-10:	Carbine
-11:	Machine Gun
-12:	Rocket Launcher
-13:	Submachine Gun
-14:	Grenade
-15:	Field Artillery
-16:	A.A. Artillery
-17:	Mortar
-18:	Missile
-19:	Aeroweapons

MATERIAL: Red brass or nickel silver
Jump Rings: Nickel silver

DIMENSIONS:
HEIGHT (Including Lugs): .410 inch (1.04 cm) (REF)
HEIGHT (Excluding Lugs): .200 inch (0.508 cm) (REF)
WIDTH (Overall): 1 inch (2.54 cm) (REF)
THICKNESS (At rim): .060 inch ± .005 inch (0.152 ± 0.012 cm)

FINISH:
Nickel plated (red brass only), silver plated, oxidized, highlights satin finish with reverse and edges clean

Jump Rings: Satin finished, lacquered

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:51Z
Check the source to verify that this is the current version before use.

NOTES:

1. All lugs are integral.
2. Two jump ring shall be positioned on the top lugs.
3. All badge clasps are of identical design except for lettering therefore only one sample is shown.
4. The badge clasps covered by this specification sheet shall be used in conjunction with the basic qualification badges on specification sheet MIL-3628/14.
5. Lugs shall be located equidistant from each end and .675 inch ± .015 inch - 000 inch (1.71 cm ± 0.038 cm - 0 cm) on centers.
6. Badge may be nickel or rhoduim plated with a mirror-like polished finish for commercial sale except the silver plating requirement shall not apply.

Custodian:
Army - IH

Preparing Activity:
Army - IH

Review Activity:
DLA - CT

(Projected No. 8455-0586)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:51Z
Check the source to verify that this is the current version before use.