NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/15J
23 September 1997
SUPERSEDING
MIL-DTL-3628/15H
15 November 1996

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, CLASPS, BASIC, EXPERT, SHARPSHOOTER AND MARKSMAN, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.



DASH NO.	BADGE CLASP TITLES
-1:	Rifle
-2:	Recoilless Rifle
-3:	Auto-Rifle
-4:	Small Bore Rifle
-5:	Bayonet
-6:	Pistol
-7:	Flame Thrower
-8:	Small Bore Pistol
-9:	Tank Weapons
-10:	Carbine
-11:	Machine Gun
-12:	Rocket Launcher
-13:	Submachine Gun
-14:	Grenade
-15:	Field Artillery
-16:	A.A. Artillery
-17:	Mortar
-18:	Missile
-19:	Aeroweapons

MATERIAL:
BADGE CLASP: Red Brass or Nickel Silver
JUMP RINGS: Nickel Silver

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:51Z
Check the source to verify that this is the current version before use.

FINISH: Nickel Plated (Red Brass only), Silver Plated, Oxidized, Relieved, Matte Finish with reverse and edges clean and shall match TIOH Metal Finish Chip Number 14.

DIMENSIONS:
HEIGHT (Including Lugs): 0.410 inch (1.04 cm) (REF)
HEIGHT (Excluding Lugs): 0.200 inch (1.51 cm) (REF)
WIDTH (Overall): 1 inch (2.54 cm) (REF)
THICKNESS (At Rim): 0.060 inch ± .005 inch (0.152 cm ± 0.012 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Lugs shall be located equidistant from each end and 0.0675 inch ± 0.015 inch (1.71 cm ± 0.038 cm) on centers.

3. Two jump ring links shall be positioned on top lugs and shall use the same finish as the badge clasp. Links shall be 13/64 inch ± 1/64 inch (0.52 cm ± 0.04 cm) in width and 1/4 inch ± 1/64 inch (0.64 cm ± 0.04 cm) in length and shall be fabricated from 0.044 inch ± 0.005 inch (0.114 cm ± 0.012 cm) diameter wire.

4. All badge clasps are of identical design except for lettering.

5. Badge clasps covered by this specification sheet shall be used in conjunction with the basic qualification badges on specification sheet MIL-DTL-3628/14.

6. At the option of the manufacturer, badge may be nickel or rhodium plated with a mirror-like polished finish which shall match the TIOH Metal Finish Chip Number 16. For nickel plated or rhodium plated items, the silver plating requirement shall not apply.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0907)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:51Z
Check the source to verify that this is the current version before use.