NOT MEASUREMENT SENSITIVE


MIL-B-3628/9E
30 July 1993
SUPERSEDING
MIL-B-3628/9D
9 August 1991

MILITARY SPECIFICATION SHEET

BADGE, QUALIFICATION, RIFLEMAN, NAVY; PENDANT AND SUSPENSION BAR

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3628.



MATERIAL:
PENDANT: Gilding Metal
SUSPENSION BAR:
-1, -2: Red Brass
-3: Gilding Metal

DASH NO.
-1: Gold
-2: Silver
-3: Bronze

FINISH:
PENDANT:
OBVERSE:
-1: Hard Enamel, Gold Plated, Matte Finish, Highlights and Rim Polished and shall match TIOH Metal Finish Number 8.
-2: Hard Enamel, Nickel Plated, Silver Plated, Matte Finish, Highlights and Rim Polished and shall match TIOH Metal Finish Number 13.
-3: Highlights and Rim Polished.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:47Z
Check the source to verify that this is the current version before use.

REVERSE:
-1: Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Number 6.
-2: Nickel Plated, Silver Plated, Mirror-like Polished and shall match TIOH Metal Finish Number 16.
-3: Mirror-like Polished.

SUSPENSION BAR:
OBVERSE:
-1: Gold Plated, Matte Finish, Highlights and Rim Polished and shall match TIOH Metal Finish Number 8.
-2: Nickel Plated, Silver Plated, Matte Finish, Highlights and Rim Polished and shall match TIOH Metal Finish Number 13.
-3: Highlights and Rim Polished.
REVERSE:
-1: Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Number 6.
-2: Nickel Plated, Silver Plated, Mirror-like Polished and shall match TIOH Metal Finish Number 16.
-3: Mirror-like Polished.

DIMENSIONS:
PENDANT:
DIAMETER: 1-5/16 inch (3.33 cm) (REF)
THICKNESS (At Edge): 0.085 inch + 0.010 inch - 0 (0.215 cm + 0.025 cm - 0)

SUSPENSION BAR:
HEIGHT (Including Lugs): 3/8 inch (0.05 cm) (REF)
WIDTH (Overall): 1-7/16 inch (3.65 cm) (REF)
THICKNESS (At Edge): 0.080 inch + 0.010 inch (0.215 cm + 0.025 cm - 0)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Enameled areas shall be as indicated. The color shall conform to the TIOH chip numbers listed below or the standard sample.

COLOR	CHIP NUMBER
Black	26
White	28

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of manufacturer. Epoxy resin shall be smooth and flush with the dikes.

4. The lug (suspension ring) for the pendant shall have a minimum outside diameter of 5/32 inch (0.40 cm) and wire thickness shall be 0.050 inch (0.127 cm). The lug shall be soldered at the top of the pendant vertical center line.

5. Suspension links shall be 5/32 inch (0.40 cm) in width by 3/16 inch (0.48 cm) in length and fabricated from 0.050 inch (0.127 cm) nominal diameter wire with the same material and finish as the pendant and suspension bar.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:47Z
Check the source to verify that this is the current version before use.

6. Jump rings shall be fabricated from 0.050 inch (0.127 cm) nominal diameter wire with the same material and finish as the suspension bar. The rings shall have an outside diameter of 3/16 ± 1/32 inch (0.48 cm ± 0.08 cm).

7. The attaching device shall be prong and flat ball clutch type. Nickel plated flat ball clutches shall be used for Dash No. -2 and brass flat ball clutches shall be used for Dash No. -1 and -3. The prongs shall be located on the horizontal center line of the suspension bar, equidistant from each end and 1-11/32 inches ± 1/32 inch (3.41 cm ± 0.08 cm) apart.

8. The suspension bar shall have two integral lugs. The lugs shall be equidistant from each ends and 13/16 inch (2.06 cm) on centers.

9. The use of any type of plastic packaging material is prohibited.

Custodian:
Army - IH
Navy - NU

Preparing activities:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0693)

Source: https://assist.dla.mil - Downloaded: 2026-10-16T18:47Z
Check the source to verify that this is the current version before use.