INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

LABEL: FOR CLOTHING, EQUIPAGE, AND TENTAGE, (GENERAL USE)

This Interim Amendment was developed by the U.S. Army Natick Research and Development Laboratories (GL), Natick, MA 01760, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this interim amendment as a valid exception to Federal Specification DDD-L-20E.

PAGE 5

3.2.4.2, line 4, after "resin": Add "when tested as specified in 4.2.4".

PAGE 6

Table I: Delete and substitute:

"TABLE I. Physical requirements for type VI finished label

Weight oz. per sq. yd. (g/m^2) minimum	Breaking strength lbs. (newton) minimum		Tearing strength g (newton) minimum		Bursting strength psi (kPa) minimum
	Machine direction	Transverse direction	Machine direction	Transverse direction	
3.2 (108)	15 (67)	10 (45)	300 (2.9) .656	250 (2.5) .562 lb	50 (345)"

3.3.2, line 1: Delete "(see 6.20)" and substitute "(see 6.2)".

PAGE 11

3.5.5, line 4, after "4.2.4": Add "(see 6.2)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T18:51Z
Check the source to verify that this is the current version before use.

PAGE 15

TABLE III, in "Requirement paragraph" column, opposite "Yarns per inch - Filling": Delete "---" and substitute "3.2.3.1".

In "Charactersitic" column, under "Writing test": Delete "(classes 1 and 10)" and substitute "(class 10 and combination classes 1 and 10)".

PAGE 17

TABLE III, in "Requirement paragraph" column, opposite "Bond strength (type V)": Delete "3.2.5.2" and substitute "3.2.3.2".

Custodian:

Army - GL

Review activity:

DLA - CT

Preparing activity:

Army - GL

Project No. 8315-A295

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:31Z
Check the source to verify that this is the current version before use.