DDD-T-00101a (GSA-FSS)
March 6, 1968
INTERIM REVISION OF
Fed. Spec. DDD-T-101
May 31, 1932

INTERIM FEDERAL SPECIFICATION

TAPE, TEXTILE, COTTON, TYING

This Interim Federal Specification was developed by the General Services Administration, Federal Supply Service, Washington, D. C., 20405, based on currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 This specification covers the requirements for one type of tying tape primarily intended for use in tying documents, books, and publications for storage, shipment or sale.

2. APPLICABLE DOCUMENTS

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:
CCC-T-191—Textile Test Methods.
PPP-B-566—Boxes, Folding, Paperboard.
PPP-B-636—Box, Fiberboard.
PPP-B-665—Boxes, Paperboard, Metal Stayed (including stay material).
PPP-B-676—Boxes, Setup.

Federal Standards:
Fed. Std. No. 4—Glossary of Fabric Imperfections.
Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C., 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:
MIL-W-43334—Webbing and Tape, Textile, Packaging and Packing of.

Military Standard:
MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

Rules and Regulations Under the Textile Fiber Products Identification Act.

(Copies may be obtained without charge from the Federal Trade Commission, Washington, D. C., 20580.)

FSC 8315

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:32Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Standard sample. When a standard sample is established, the tape shall match the standard sample for shade and shall be equal to or better than the standard sample with respect to all characteristics for which the standard sample is referenced (see 6.2).

3.2 Materials.

3.2.1 Yarn. Yarn used in the manufacture of tape shall be of cotton which has been cleaned, carded, drawn, spun, and twisted into not less than 2 plies for the warp and singles for the filling.

3.3 Color. Unless otherwise specified, the tape shall be unbleached.

3.3.1 Dyeing. When a color is specified the tape shall be either stock, yarn or piece dyed.

3.3.1.1 Matching. The color of the tape shall match the standard sample or color index number, as applicable, under natural (north sky) daylight, or artificial daylight having a color temperature of 7500° Kelvin and shall be a good approximation to the standard sample or color index number under incandescent lamplight at 2800° Kelvin.

3.3.1.2 Colorfastness. Dyed tape shall show colorfastness to light, crocking, and accelerated weathering equal to, or better than the standard sample. When no standard sample is established the tape shall show "good" colorfastness to light, crocking, and accelerated weathering when tested in accordance 4.3.

3.4 Physical requirements.

3.4.1 Weave. The weave of the tape shall be plain, with both edges being woven.

3.4.2 Yarns (per width-per inch).

3.4.2.1 Warp. The total number of warp yarns per width of tape shall be not less than 19 when tested in accordance with 4.3.

3.4.2.2 Filling. There shall be not less than 12 filling yarns per inch when tested in accordance with 4.3.

3.4.3 Breaking strength. The breaking strength in the warp direction of the tape shall be not less than 25 pounds when tested in accordance with 4.3.

3.4.4 Width. The finished width of the tape shall be 5/16 inch with a plus or minus tolerance of 1/16 inch.

3.5 Nonfibrous material. The starch and protein content including chloroform-soluble and water-soluble material of the tape shall not exceed 10 percent when tested in accordance with 4.3.

3.6 Put-up. Unless otherwise specified tape shall be wound on standard commercial spools. Each spool shall contain 72 yards plus or minus 2 percent, of tape with not more than three pieces on each spool and no piece shall be less than 10 yards in length.

3.7 Fiber identification. Each spool or holder shall be lableled or ticketed for fiber content in accordance with the Textile Fiber Products Identification Act.

3.8 Identification label. Each spool or holder of tape shall have an identification gummed label attached to the head end of the spool or to the outside end of the holder as applicable. The color of the lablel shall be light in intensity to permit easy reading of printed, stamped or typed markings. The use of handwritten entries is prohibited. The label shall be legibly printed with water insoluble ink with the following information, unless otherwise specified:

Stock number.
Nomenclature.
Yardage.
Contract number and date.
Purchase order.

3.9 Workmanship. The tape shall conform to the quality and grade of product established by this specification. Occurrence of defects shall not exceed the applicable acceptance quality levels (AQLs).

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:32Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements, as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Inspection. Sampling and inspection shall be in accordance with the provisions of MIL-STD-105, except where otherwise indicated.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase documents. In addition the end item shall be tested for the characteristics specified in accordance with the referenced test method of CCC-T-191.

4.2.2 End item examination. Defects found during the examination shall be classified in accordance with 4.2.2.1, 4.2.2.2, and 4.2.2.3.

4.2.2.1 Yard-by-yard examination for visual defects. The required yardage of each spool or other holder shall be inspected on both sides and visual defects classified as listed in table I. All defects found shall be counted regardless of their proximity one to another, except where two or more defects represent a single local condition of the tape, in which case only the more serious defect shall be counted as one defect for each warpwise yard or fraction thereof in which it occurs. The sample unit for this examination shall be 1 linear yard. The sample size shall be in accordance with level I of MIL-STD-105. The AQL shall be 4.0 (major and minor combined) defects per 100 units (yards). The lot size shall be expressed in units of 1 yard each. An approximate equal number of yards shall be examined from each spool or holder selected.

TABLE I. Classification of defects

Glossary No. (Fed. Std. No. 4, sec. 1)	Defects	Classification	
		Major	Minor
79	Abrasion marks—resulting in a weak place.....	X	
33	Broken or missing ends—two or more within a linear inch, regardless of size of missing portion.....	X	
	Single, 1/2 inch or more in length.....		X
90, 91, 92	Cut, hole, or tear—any.....	X	
13, 34	Float or skips: Multiple, more than 1/4 inch in combined warp and filling directions.....	X	
	Multiple, 1/4 inch or less in combined warp and filling directions.....		X
	Single, floating over 1 inch or more in length.....		X
	Single, over more than 1/2 the width of the tape.....		X

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:32Z
Check the source to verify that this is the currentversion before use.

TABLE I. (continued)

Glossary No. (Fed. Std. No. 4, sec. 1)	Defects	Classification	
		Major	Minor
3, 5, 27	Jerked-in or sloughed-off filling, slub or slug—clearly visible[1] ...		X
6, 28	Kink or loop on surface of tape.....		X
7, 29	Knots—large, improperly pieced knots, clearly visible,[1] protruding from surface or with tails extending from surface of tape		X
10	Mispick—any		X
49, 54	Edges frayed, slack, rolled, wavy, or otherwise poorly constructed, 4-1/2 inches or more	X	
	Less than 4-1/2 inches, but more than 1/2 inch		X
78	Smash—any	X	
40	Wrong draw—9 inches or more in length		X

[1] Clearly visible at normal inspection distance (approximately 3 feet).

4.2.2.2 Overall examination for visual defects. Each defect listed below, when applicable, shall be counted no more than once in each spool or other holder examined. The sample unit for this examination shall be one spool or holder. The sample size and acceptance number shall be as shown in table II.

Defects

Off shade, not within established tolerances.
Uneven dyeing.
Poor dye penetration.
Shaded throughout.
Objectionable odor.
Overall uncleaness.
Not labeled in accordance with Textile Fiber Products Identification Act.

TABLE II. Sample size

Lot size in spools or other holders	Sample size in spools or other holders	Maximum number of defects acceptable in sample (see 4.2.2.2 and 4.2.2.3.1)
5 or less	1	0
6 up to and including 15	2	0
16 up to and including 40	3	0
41 up to and including 110	5	0
111 up to and including 300	7	0
301 and over	10	1

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:32Z
Check the source to verify that this is the currentversion before use.

4.2.2.3 Length and width examination.

4.2.2.3.1 Examination for length and width of tape on individual spools or other holders. Each defect listed below shall be counted no more than once in each spool or other holder examined. The sample unit for this examination shall be one spool or holder. The sample size and acceptance number shall be as shown in table II.

Defects

Total yardage on spool or holder less than the applicable minimum or more than the applicable maximum length:
Width not within specified tolerance.
Any piece less than minimum specified.
More than the number of pieces specified.
Actual gross length more than 2 yards less than gross length marked on spool ticket.

4.2.2.3.2 Examination for total yardage in sample. The lot shall be unacceptable if the total of the actual gross lengths of spools or other holders in the sample is more than 5 yards less than total of the gross lengths marked on holder or package tickets.

4.2.3 Examination of preparation for delivery requirements. An examination shall be made in accordance with the provisions of MIL-W-43334 to determine that packaging, packing, and marking requirements of section 5 of this specification are complied with.

4.3 Testing of the end item. The method of testing specified in CCC-T-191, wherever applicable, and as listed in table III shall be followed. The physical and chemical values specified in section 3 apply to the results of the determinations made on a sample unit for test purposes as specified in the applicable test methods. All test reports shall contain the individual values utilized in expressing the final result. The sample size shall be as follows:

Lot size (yards)	Sample size
800 or less	2
801 up to and including 22,000	3
22,001 and over	5

The lot shall be unacceptable if one or more units fail to meet any requirement specified. The lot size shall be expressed in units of 1 linear yard. The sample unit for testing shall be 10 linear yards.

TABLE III. Test methods

Characteristic	Reference requirement	Test method	No. of determinations per unit of product
Identification of cotton	3.2.1	1200	———
Colorfastness to:			
Light	3.3.1.2	5660	———
Crocking	3.3.1.2	5651	———
Accelerated weathering	3.3.1.2	5671	———
Weave	3.4.1	Visual	1
Yarns (number of):			
Warp (total)	3.4.2	5050	———
Filling (per inch)	3.4.2	5050	———
Breaking strength	3.4.3	5100 1/	———
Nonfibrous material	3.5	2611	———

1/ Breaking strength shall be determined on the full width of the tape and the jaw dimensions shall be greater than the width of the tape.

NOTE: When the data in "No of determinations per unit of product" column are not specified in table III, they shall be required by the referenced test method.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.1).

5.1.1 Level A. Tape shall be packaged in accordance with the level A requirements of MIL-W-43334.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:32Z
Check the source to verify that this is the current version before use.

5.1.2 Level B. (civil agencies). Six spools of tape shall be packaged in a close-fitting box conforming to PPP-B-566, PPP-B-665, or PPP-B-676. Each box shall be secured to prevent accidental opening.

5.1.2.1 Intermediate packaging. Twelve unit packages shall be intermediate packaged in a box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to the box specification.

5.1.3 Level C. Spools of tape shall be packaged in accordance with the requirements of MIL-W-43334.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.1).

5.2.1 Level A and B. Packing shall be in accordance with the level A and B requirements of MIL-W-43334.

5.2.2 Level B (civil agencies). Four intermediate packages shall be packed in a box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to the box specification.

5.2.3 Level C. Tape shall be packed in accordance with the requirements of MIL-W-43334.

5.3 Marking.

5.3.1 Civil agencies. In addition to markings required by the contract or order, the interior and shipping container shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. In addition to markings required by the contract or order, markings shall be in accordance with the requirements of MIL-W-43334.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.2 For access to the standard sample, address procuring office issuing the invitation for bids.

CIVIL AGENCIES INTEREST:
GSA-FSS
GAO
INT-BIA
COM

GSA OC 68-14030

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:32Z
Check the source to verify that this is the currentversion before use.