MIL-C-3653A
18 June 1975
SUPERSEDING
MIL-C-3653
29 December 1951

MILITARY SPECIFICATION

CASE, VETERINARY EGG INSPECTION SET

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers an empty egg inspection case designed to provide the necessary assembly of equipment to facilitate the inspection of shell eggs.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

QQ-A-250/2	Aluminum Alloy 3003, Plate and Sheet.
QQ-A-250/8	Aluminum Alloy 5052, Plate and Sheet.
QQ-W-423	Wire, Steel, Corrosion-Resisting.
TT-E-527	Enamel, Alkyd, Lustreless.
TT-P-1757	Primer Coating, Zinc Chromate, Low Moisture Sensitivity.
PPP-B-585	Boxes, Wood, Wirebound.
PPP-B-601	Boxes, Wood, Cleated Plywood.
PPP-B-621	Boxes, Wood, Nailed and Lock Corner.
PPP-B-636	Boxes, Shipping, Fiberboard.

Military

MIL-C-5541	Chemical Conversion, Coatings, on Aluminum and Aluminum Alloys.
MIL-A-8625	Anodic Coatings, for Aluminum and Aluminum Alloys.
MIL-L-10547	Liner, Case and Sheet, Overwrap, Water Vaporproof or Waterproof, Flexible.

FSC 6545

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:39Z
Check the source to verify that this is the current version before use.

MIL-M-10578	Corrosion Removing and Metal Conditioning Compound (Phosphoric Acid Base)

STANDARDS

Federal

FED-STD-151	Metal, Test Methods
FED-STD-595	Color

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection By Attributes
MIL-STD-129	Marking for Shipment and Storage

DRAWINGS

Defense Personnel Support Center (DPSC)

1732	Egg Inspection Set, Veterinary
1783	Egg Inspection Set, Veterinary

3. REQUIREMENTS

3.1 Material. Except as specified herein, materials shall conform to the applicable portions of the specifications, standards, and drawings specified herein, and shall be capable of meeting the requirements specified therein. In addition, the metals shall conform to the chemical requirements of their applicable specifications when tested as specified in Section 4. When materials to be used are not specifically designated, those used shall be of the highest commercial quality, and entirely suitable for the purpose intended.

3.1.1 Aluminum alloy. Aluminum alloy sheets shall conform to Specification QQ-A-250/2 and shall be H14 or H24 tempers.

3.1.2 Plastic. Handles shall be molded of a high-impact type phenolic plastic. Color shall be black or green.

3.1.3 Primer. Primer shall conform to color Y of TT-P-1757.

3.1.4 Enamel. Enamel shall conform to TT-E-527. Color of the enamel shall approximate 34037 (lusterless olive drab) as specified in FED-STD-595 except that for marking as specified in 3.4, color shall approximate 37038 (lusterless black) of the same standard.

Source: https://assist.dla.mil -- Downloaded: 202610-16T20:39Z
Check the source to verify that this is the currentversion before use.

3.1.5 Clips. The steel clips shall be formed of annealed spring steel containing 0.65 to 0.75 percent carbon or 0.96 to 1.00 percent carbon. After forming, the clips shall be tempered to a hardness of 46 to 48 on the Rockwell C scale.

3.1.6 Hinge, piano. The piano hinge flange halves shall be fabricated of aluminum conforming to QQ-A-250/8, H24 or H34.

3.1.7 Hinge pin. Hinge pins shall be corrosion resisting steel conforming to QQ-W-423, form I, condition B, composition 302, 304 or 316.

3.1.8 Drawbolts. The drawbolts shall be constructed of steel.

3.1.9 Handle fasteners. The handle fasteners shall be steel.

3.1.10 Hasp and staple. The hasps and staples shall be made of steel, zinc or cadmium plated, and held in place by aluminum rivets.

3.1.11 Glides. The case shall be provided with eight (8) steel glides, zinc or cadmium plated, fastened to the case with either solid or tubular aluminum rivets.

3.1.12 Mounting rod. A square steel mounting rod of the size and design shown on Drawing 1783 shall be furnished with each case. A steel pin shall also be provided, to be used as a stop in raising or lowering the mounting rod when the mounting rod is used as a stand for the egg candler. The mounting rod shall be capable of easy movement when tested as specified in 4.3.2.

3.1.13 Mounting rod holder. The mounting rod holder shall be constructed of 0.0375 aluminum and spot welded as shown on Drawing 1783.

3.2 Design and construction. The case shall be of the design and construction as shown on Drawing 1783. The outer case shall be constructed of aluminum sheet, 0.064 inch thick; the inner portion and dividers shall be made of 0.064 inch aluminum sheet. The above dimensions shall apply prior to applying the protective coating. The various parts used to hold the components in place, except steel spring clips and turnbutton fasteners. Shall be spot-welded. The spacing of the spot welds shall be as shown on the drawing. All components contained in the borrowed Veterinary Egg Inspection Set (see 6.4) shall fit when the case is tested as specified in 4.3.3.

3.2.1 Clips. The clips are to be used to hold the component parts of the set in position, and shall be placed in various positions as shown on Drawing 1783.

3.2.2 Hinges. The case shall be provided with two (2) hinges. The hinges shall be fabricated of material specified in 3.1.6 and shall be constructed, and spot welded in place in accordance with Drawing 1783.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:39Z
Check the source to verify that this is the current version before use.

3.2.3 Hinge pins. The hinge pins shall be fabricated of material specified in 3.1.7. Pins shall be of suitable size and length to accommodate the specified hinges, and shall be secured in place.

3.2.4 Drawbolts. The case shall be provided with two (2) drawbolts. The drawbolts shall be of the size and design as shown on Drawing 1783. They shall be held in place by five flatheaded aluminum rivets.

3.2.5 Handle. The case shall be provided with a plastic handle of the size and design as shown on Drawing 1783. The handle shall be made of plastic specified in 3.1.2, and held in place by four (4) flatheaded aluminum rivets.

3.2.6 Hasp and staple. The case shall be provided with a good grade commercial hasp and staple (see 3.1.10), conforming to the size and design as shown on Drawing 1783.

3.2.7 Glides. The glides (see 3.1.11) shall be of the size, and shall be spaced, as shown on Drawing 1783.

3.2.8 Mounting rod holder. The mounting rod (see 3.1.12) shall be contained in an aluminum sheet bent to shape in accordance with Drawing 1783. This mounting rod holder shall be welded to the underside of the lid in accordance with the Drawing. The mounting rod in its holder is intended to be used as an adjustable stand for the candler.

3.2.9 Welding. Welding shall be durable, sound in every detail and in accordance with latest practices recommended by the American Welding Society. All welds shall be produced by qualified welding operators with satisfactory welding equipment using satisfactory filler metal or electrode where applicable to provide the best possible weld. Surfaces to be welded shall be free from grease, oil, oxides or any other foreign matter; any cleaning method which will remove these substances and leave the surface clean is satisfactory. All weld joints shall blend into the adjacent metal in gradual, smooth curves. These welds shall be continuous with no visible voids, pin holes, or cracks. All exposed spot welds shall be smoothed sufficiently so as to match adjacent area. Welds shall not be oxidized.

3.2.10 Diagram. An illustrated diagram of the contents, as indicated on Drawing 1732, showing the position of each component in the case, shall be provided and firmly affixed to the inside of the top lid of the case with transparent tape or other suitable method.

3.3 Finish.

3.3.1 Aluminum alloy. After welding has been completed, but before attachment of all component parts, all accessible aluminum alloy surfaces shall be thoroughly cleaned free from dirt, oil, grease, welding flux and loose scale with solvents, detergents, or other processes which have no deleterious effect on the surfaces. After thorough cleaning and degreasing, surfaces to be enameled shall be prepared for topcoating by one of the following methods:

Source: https://assist.dla.mil -- Downloaded: 202640-16T20:39Z
Check the source to verify that this is the currentversion before use.

3.3.1 Aluminum alloy (cont'd)

1. Chemical treatment in accordance with MIL-C-5541, class 1A.
2. Anodic treatment in accordance with MIL-A-8625.
3. Priming treatment, using primer specified in 3.1.3, thinned and applied by spray in accordance with the directions specified under "Preparation for Delivery" of TT-P-1757, and air dried for not less than 30 minutes before topcoating.

3.3.2 Steel. Before attachment of steel parts, all steel parts, except hinge pins (3.1.7) shall be treated with a metal conditioner conforming to Military Specification MIL-M-10578 for type I or II. Treated steel parts shall then be primed as specified in method 3 of 3.3.1.

3.3.3 Topcoating. After complete assembly of the case, except for the mounting rod and pin, the completed case shall be topcoated with one coat of enamel as specified in 3.1.4, reduced as specified in the paragraph titled "Spraying properties" in the requirement section of TT-E-527, applied by spraying and cured by a heat treatment equivalent to baking at 250 F., for not less than 45 minutes. The resultant finish shall be hard, smooth, and highly resistant to abrasion, chipping, cracking, acid, alkali, and solvents.

3.4 Identification marking. The case shall be permanently and legibly marked with black enamel (3.1.4) in accordance with the drawing.

3.5 Workmanship. Workmanship shall be first class throughout. The veterinary egg inspection set case shall be free from defects which detract from its appearance or may impair its serviceability.

4 QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the suppler may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specificiation where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of three (3) years after delivery of the supplies to which such records relate.

Source: https://assist.dla.mil -- Downloaded: 202610-16T20:39Z
Check the source to verify that this is the current version before use.

4.1.2 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.1.3 Certificates of quality. Certificates of quality, supplied by the manufacturer of the aluminum, steel, and corrosion resisting steel components, may be furnished in lieu of actual performance of such testing by the contractor, provided lot identity has been maintained and can be demonstrated to the Government. The certificate shall include the name of the contractor, the contract number, the name of the manufacturer or supplier, the NSN, the item identification, the name of the component/material, the lot number, the lot size, the sample size, the date of testing, the test method, individual test results, and the specification requirements.

4.2 Quality conformance inspection. The examinations and tests required to assure conformance of those items or lots of items to be offered for acceptance are classified as specified in tables I and II (see 4.2.1 and 4.2.2) and 4.2.3.

4.2.1 Sampling for examination. Sampling for examination shall be conducted in accordance with MIL-STD-105. The inspection levels and acceptable quality levels shall be as indicated in table I. Unit of product for examination purposes shall be one case.

Table I Sampling for examination

Visual Examination	Inspection level	AQL (percent defective)
Major	S-4	1.0
Minor	S-4	4.0

4.2.2 Examination.

4.2.2.1 Case. The case shall be examined for defects including, but not limited to, those listed in Table II.

Table II Classification of defects

Major	
101	Any component missing.
102	Any component cracked, broken, dented, or otherwise damaged.
103	Welds not clean, nonporous, and free from pitmarks and imperfections.
104	Drawbolts do not function.
105	Hinge and hasp do not line up.
106	Identification markings omitted, incorrect, or illegible.

Source: https://assist.dla.mil -- Downloaded: 202640-16T20:39Z
Check the source to verify that this is the current version before use.

Table II Classification of defects (cont'd)

Minor	
201	Hinged components operate stiffly.
202	Clipboard holder difficult to rotate.
203	Identification markings less than size specified.
204	Identification markings not located as specified.
205	Enamel finish not free of scratches.

4.2.2.2 Preparation for delivery. An examination shall be made to determine whether the packaging, packing, and marking comply with the requirements of Section 5. Defects shall be scored as specified in Table III. Sampling shall be in accordance with MIL-STD-105. The sample unit shall be one container fully prepared for delivery. The lot shall be the number of containers offered for inspection at one time. The inspection level shall be S-2 and the acceptable quality level shall be 4.0 (defects per hundred units).

Table III Examination for preparation for delivery

Examination	Defect
Containers	Not as specified.
Quantity	Quantity in interior packages and shipping containers not as specified.
Packaging and packing materials	Any component missing or damaged.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, tape improperly applied, or containers distorted.
Markings	Omitted, incorrect, illegible, improper size, location, sequence, or method of application.

4.2.3 Sampling for tests. Sampling for tests shall be conducted in accordance with MIL-STD-105, Inspection Level S-1, except that the acceptance number shall be zero for all sample sizes. Unit of product for test purposes shall be one case.

4.2.3.1 Chemical analysis of metals. A sufficient amount of each lot of each metal used in the construction of the case shall be selected for chemical analysis as specified in 4.3.1.

4.2.4 Sample unit usage. Where possible, the same sample unit shall be used for the determination of two or more test characteristics.

Source: https://assist.dla.mil -- Downloaded: 20260-16T20:39Z
Check the source to verify that this is the current version before use.

4.3 Tests. Tests shall be conducted to determine compliance with specification requirements.

4.3.1 Chemical analysis of the metals. The samples selected in accordance with 4.2.3.1 shall be analyzed in conformance with methods 111 or 112 of Federal Test Method Standard No. 151. In case of dispute, method 111 shall be used for referee analysis.

4.3.2 Mounting rod fit test. The mounting rod shall be extended vertically through the cover of the case approximately 8 inches and secured. The cover shall be closed and both latches locked. The mounting rod shall be released and returned to within 2 inches of its full depth, and then completely withdrawn.

4.3.3 Assembly test. Each of the components in the borrowed Veterinary Egg Inspection Set (see 6.4) shall be removed, and assembled in the sample case under test in accordance with Drawing 1732.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Unit package. Each case shall be packaged in a snug fitting box of appropriate size constructed in accordance with PPP-B-636, type CF, class domestic. Closure shall be adequate to prevent accidental opening.

5.1.2 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Level A. Size (6) cases shall be packed in a box designed for a type 2 load and constructed in accordance with PPP-B-585, class 3, style 3; PPP-B-601, overseas type; PPP-B-621, class 2; or PPP-B-636, class weather-resistant. Closure and strapping shall be in accordance with appendix of applicable box specification.

5.2.1.2 Case liner. Each level A wood box shall be lined with a waterproof case liner conforming to MIL-L-10547. Closure and sealing shall conform to applicable paragraphs of appendix thereto. Case liner shall not be required for fiberboard boxes. Fiberboard box shall be waterproof as specified in the appendix of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:39Z
Check the source to verify that this is the current version before use.

5.2.2 Level B. Six (6) cases shall be packed in a box designed for a type 2 load and constructed in accordance with PPP-B-585, class 1, style 3; PPP-B-601, domestic type; PPP-B-621, class 1; or PPP-B-636, class domestic. Closure of boxes shall be as specified in the appendix of the applicable box specification.

5.2.3 Level C. The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.3 Marking.

5.3.1 Interior packages. Each unit package shall be marked in accordance with MIL-STD-129. When labels are utilized, waterproofing shall be required only when applicable carton is fabricated of water-resistant material. Contract or purchase order number and name of contractor shall be shown.

5.3.2 Exterior container. Exterior container shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The case is intended to accommodate the components of NSN 6545-00-805-8700 Egg Inspection Set, Veterinary.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. NSN and item identification of the case.
c. Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.3 Availability of color chips. The individual 3 by 5 inch chips of the colors referenced in 3.1.4 are available from Commissioner, Federal Supply Service, General Services Administration, Standardization Division, Paints Branch, Washington, DC 20406.

6.4 Veterinary egg inspection set. A veterinary Egg Inspection Set for use in checking the fit of specific individual set components in sample contracted cases (4.3.3), will be loaned to the successful bidder. A deposit will be required. Although the case containing the components does not meet the requirements of this specification, it is loaned for the purpose of conveying the components and illustrating their placement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:39Z
Check the source to verify that this is the current version before use.

6.5 The case covered by this specification is listed in the Federal Supply Catalog as follows:

National Stock Number	Item Identification
6545-00-802-2050	CASE, VETERINARY EGG INSPECTION SET

Custodians
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DM

Project No. 6545-0020
is

Source: https://assist.dla.mil -- Downloaded: 20260-16T20:39Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-C-3653A CASE, VETERINARY EGG INSPECTION SET

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:39Z
Check the source to verify that this is the current version before use.

FOLD

DEFENSE PERSONNEL SUPPORT CENTER
2800 South 20th Street
Philadelphia, Pa. 19101

POSTAGE AND FEES PAID
DEFENSE SUPPLY AGENCY
DoD - 304

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

HEADQUARTERS, DEFENSE PERSONNEL SUPPORT CENTER
ATTN: DIRECTORATE OF MEDICAL MATERIEL, CODE ATT
2800 SOUTH 20TH STREET
PHILADELPHIA, PA. 19101

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-16T20:39Z
Check the source to verify that this is the current version before use.