MILITARY SPECIFICATION

CONNECTORS, COAXIAL, RADIOFREQUENCY, SERIES LC

This amendment forms a part of Military Specification MIL-C-3650A, 2 December 1960, and has been approved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy, and the Air Force.

Page 1, paragraph 2.1: Under SPECIFICATIONS, MILITARY Add:

"MIL-G-45204 - Gold Plating (Electrodeposited)."

Page 2, paragraph 3.3.1: Delete and substitute:

"3.3.1 Metal parts. - Unless otherwise specified (see 3.1) all contacts shall be gold plated in accordance with type II class 2 of MIL-G-45204. A nickel strike shall be used under the gold plate. All other metal parts shall have a silver plating of not less than 0.0002 inch thick. Silver plating shall be in accordance with QQ-S-365. Plating shall be of sufficient smoothness and density to withstand the salt spray (corrosion) test specified in 4.6.4. Dimensions of metal parts shall include the plating.

Page 9, paragraph 6.3: Delete and substitute:

"6.3 Engineering information. - Illustrations and additional engineering data on the connectors and fittings covered by this specification (see 3.1) are available in MIL-HDBK-216, RF Transmission Lines and Fittings, copies of which are available upon request from the Naval Supply Depot, CODE DCI, 5801 Tabor Avenue, Philadelphia 20, Pa.

Custodians
Army - EL
Navy - Ships
Air Force - ASD

Preparing Activity:
Navy - Ships
(Project 5935-1083)

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:39Z
Check the source to verify that this is the current version before use.