INCH POUND

MIL-DTL-3655/2C
18 March 2008
SUPERSEDING
MIL-C-3655/2B
11 April 1980

DETAIL SPECIFICATION SHEET

CONNECTOR, RECEPTACLE, ELECTRICAL, CLASS I (COAXIAL, SERIES TWIN) TYPE UG-422/U

Inactive for new design after 11 April 1980

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-3655.





FIGURE 1. Type UG-422/U, connector, electrical, receptacle.

AMSC N/A

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:40Z
Check the source to verify that this is the current version before use.







FIGURE 1. Type UG-422/U, connector, electrical, receptacle – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:40Z
Check the source to verify that this is the current version before use.






FIGURE 1. Type UG-422/U, connector, electrical, receptacle – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:40Z
Check the source to verify that this is the current version before use.






FIGURE 1. Type UG-422/U, connector, electrical, receptacle – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:40Z
Check the source to verify that this is the current version before use.





NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, the tolerance is ± 005 (0.13 mm).
4. Silver solder all around.
5. Either item 7 or 8 may be used in the alternate construction of item 5.
6. All undimensioned pictorial configurations are for reference purposes only.


FIGURE 1. Type UG-422/U, connector, electrical, receptacle - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:40Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm	Inches	mm
.001	0.03	.030	0.76	.095	2.41	.535	13.59
.002	0.05	.031	0.79	.105	2.67	.562	14.27
.003	0.08	.045	1.14	.112	2.84	.565	14.35
.004	0.10	.050	1.27	.125	3.18	.590	14.99
.005	0.13	.055	1.40	.186	4.72	.620	15.75
.0075	0.190	.059	1.50	.187	4.75	.625	15.88
.008	0.20	.060	1.52	.217	5.51	.628	15.95
.0095	0.241	.061	1.55	.218	5.54	.648	16.46
.010	0.25	.062	1.57	.250	6.35	.650	16.51
.012	0.30	.063	1.60	.280	7.11	.671	17.04
.015	0.38	.070	1.78	.369	9.37	.687	17.45
.018	0.46	.080	2.03	.388	9.86	.718	18.24
.020	0.51	.090	2.29	.475	12.0	.750	19.05
.022	0.56	.092	2.34	.500	12.70	.960	24.38
.025	0.64	.093	2.36	.533	13.54	1.000	25.40

FIGURE 1. Type UG-422/U, connector, electrical, receptacle - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:40Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm
.001	0.03	.062	1.57
.002	0.05	.250	6.35
.003	0.08	.533	13.54
.005	0.13	.590	14.99
.015	0.38	.620	15.75

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for information only.

FIGURE 2. Interface mating requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:40Z
Check the source to verify that this is the current version before use.

ENGINEERING DATA

Nominal impedance: 95 ohms (balanced line not matched).

Frequency range: DC to 500 MHz, maximum.

Voltage rating: 500 V peak, maximum at sea level.

Mating connector: M3655/1-0421.

Intended use: Type M3655/2-0422 electrical connector is designed for use with receptacle shield M3655/11-0106.

REQUIREMENTS:

Design and construction: See figures 1 and 2.
Center contact shall be plated in accordance with MIL-DTL-3655. All other metal parts shall be silver plated to a minimum thickness of .0002 inch in accordance with ASTM-B700.

Force to engage/disengage:
Torque: Not applicable.
Longitudinal force: Not applicable.

Coupling proof torque: Not applicable.

Mating characteristics (see figures 1 and 2 for dimensions):

Center contact:
Oversize test pin: .062 inch diameter, minimum (non-closed entry contact only).
Test pin finish: 16 microinches.
Insertion depth: .093 inch, minimum.
Number of insertions: One.
Insertion force test:
Steel test pin diameter: .062 inch, minimum.
Test pin finish: 16 microinches.
Insertion depth: .125 inch, minimum.
Insertion force: 2 pounds, maximum.
Withdrawal force test:
Steel test pin diameter: .052 inch, maximum.
Test pin finish: 16 microinches.
Insertion depth: .125 inch, minimum.
Withdrawal force: 2 ounces, minimum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:40Z
Check the source to verify that this is the current version before use.

Permeability: Applicable.

Hermetic seal: Not applicable.

Leakage: Not applicable.

Insulation resistance: 5×10^9 ohms, minimum.

Contact insulator captivation: Not applicable.

Salt spray (corrosion): Applicable.

Connector durability: Applicable.

Contact resistance (milliohms, maximum):

	Initial	After environment
Inner conductor contacts:	2.67	3.50
Outer conductor contacts:	.38	Not applicable
Braid to body	.20	Not applicable

Dielectric withstanding voltage: 1,500 V rms, minimum, at sea level.

Vibration, high frequency: Applicable.

Shock (specified pulse): Not applicable.

Temperature cycling: Applicable.

Humidity: Applicable, but no measurement shall be made at high humidity. Insulation resistance shall be at least 2×10^8 ohms within 5 minutes after removal from the humidity chamber.

Cable retention force: Not applicable.

Coupling nut retention: Not applicable.

Part or Identifying Number (PIN): M3655/2-0422.

First article shall apply as follows: First article test inspection shall be performed in accordance with the requirements outlined in the latest revision of MIL-DTL-3655.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:40Z
Check the source to verify that this is the current version before use.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-3655, this document references the following:

ASTM-B700

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force – 11
DLA – CC

Preparing activity:
DLA - CC

(Project 5935-2007-015)

Review activities:
Army – AT, AV, MI
Navy – AS, MC, OS, SH
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:40Z
Check the source to verify that this is the current version before use.