MILITARY SPECIFICATION

CONTAINER, SHIPPING AND STORAGE

MK 311 MOD 1

This specification has been approved by the
Bureau of Naval Weapons, Department of the Navy

1. SCOPE

1.1 Scope - This specification establishes the requirements for the procurement of one type of reusable shipping and storage container for the AQM-37A Target Body. Containers for other Target components are procured under separate specifications,

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

MIL-P-116	Preservation, Methods of
MIL-D-3464	Desiccants, Activated, Bagged
MIL-B-81205(WP)	Band, Handling, Mk 84 Mod 0

STANDARDS

MIL-STD-105	Sampling Procedure and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage

FSC 1450

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:05Z
Check the source to verify that this is the current version before use.

DRAWINGS AND LISTS

BUREAU OF NAVAL WEAPONS

DL 1453999 Container, Shipping and Storage Mk 311 Mod 1

(And all drawings referenced thereon)

(Copies of specifications, standards and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General Requirements

3.1.1 Construction - The Mk 311 Mod 1 Container shall be manufactured in strict accordance with Bureau of Naval Weapons Data List, DL 1453999, and all documents referenced thereon.

3.1.2 Precedence - In the event of any conflict between applicable documents, the following order of precedence shall be observed:

(a) Contract or Purchase Order

(b) This specification

(c) Applicable drawings of DL 1453999

(d) Referenced documents of DL 1453999

(3) Other applicable documents as referenced in 2.1.

3.1.3 Preproduction samples - Unless otherwise specified in the contract or order (see 6.2), preproduction samples of the Container shall be manufactured using the methods and procedures proposed for production. The samples will be tested as specified in Section 4 herein for the purpose of determining that, prior to starting production, the contractors production methods are capable of yielding items that comply with the technical requirements of the documents noted in 3.1.2.

3.2 Performance requirements and product characteristics Containers covered by this specification shall be capable of meeting the following performance requirements and product characteristics.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:05Z
Check the source to verify that this is the current version before use.

3.2.1 Rough handling requirements

3.2.1.1 Rotational drop - There shall be no evidence of structural failure, visible damage, or permanent deformation when each corner of the loaded Container base is allowed to fall freely onto a rigid steel or concrete surface from a height of 18 inches as described in 4.4.1.

3.2.2 Leakage - The container, when closed and sealed with all latches properly secured, shall show an average leakage rate not to exceed an amount equivalent to a pressure drop of 13.5 inches of water in 30 minutes when pressurized and tested as described in 4.5.3.

3.3 Government-loaned property - The Government will furnish the contractor, on a loan basis, with a dynamically simulated Target Body and two (2) Mk 84 Mod 0 Handling Bands. This equipment will be utilized in testing Containers supplied under this specification (see 6.2).

3.4 No data is required by this specification, or by documents referenced in 2.1, unless specified in the contract or order (see 6.2),

3.5 Workmanship - Workmanship in the fabrication and assembly of Containers shall be of sufficiently high quality to assure that completed equipment will comply with all requirements of this specification. Particular attention shall be paid to plating, bonding, painting, welding, riveting, marking, and freedom of parts from burrs and sharp edges. The assembled Containers shall be thoroughly clean of all dirt, chips, and other foreign matter. The standards of workmanship exhibited in any approved preproduction sample, subject to any qualification stated in the Government's notice of approval, shall be determinative of the requirements of the contract relative to workmanship insofar as not specifically covered by applicable specifications.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:05Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections - Inspection of the Container shall be classified as follows:

(a) Preproduction inspection (see 4.4)

(b) Quality conformance inspection (see 4.5)

4.3 Sampling

4.3.1 Preproduction sample - A preproduction sample of one (1) Container, manufactured in accordance with 3.1.1 and 3.1.3, shall be subjected to the preproduction tests specified in 4,4. Acceptance of the preproduction sample shall be based on no defects in the sample. Further production of the Container by the supplier, prior to the approval of the preproduction sample, shall be at the supplier's risk.

4.3.2 Quality conformance inspection sampling - The sampling plans and procedures set forth in MIL-STD-105 shall be used in the determination of acceptability of the Containers inspected as specified in 4.5.

4.3.3 Inspection lot - The number of units in an inspection lot shall-be, where practicable, 30 Containers. In no event will an inspection lot exceed 30 units.

4.4 Preproduction inspection - The preproduction samples, after satisfactorily passing the examinations of 4.5.2, shall be subjected to the Rotational Drop Test of 4.4.1. Upon conclusion of the Rotational Drop Test, each preproduction sample shall be subjected to the Leakage Test of 4.5.3. Certified inspection data covering the results of preproduction inspections shall be forwarded to the Bureau of Naval Weapons, if required (see 6.2).

4.4.1 Rotational drop test - Each preproduction sample shall be subjected to the following test. The Container, loaded with a simulated Target Body held in place with Mk 84 Mod 0 Handling Bands, shall be supported at one corner of its base on a block 6 inches in height. A 12-inch high block shall be placed under the other corner of the same end of the Container, The lowest point of the opposite end of the Container shall then be raised to a height of 18 inches and allowed to fall freely onto a steel or concrete surface of sufficient mass to absorb the shock without deflection. This test shall be applied to all four corners of the Container base. Any evidence of structural failure, visible damage, or permanent deformation to the Container shall be cause for rejection of the preproduction samples. Minor dents, scratches, or paint flaking are not cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:05Z
Check the source to verify that this is the current version before use.

4.5 Quality conformance inspection

4.5.1 Samples shall be selected using the plans and procedures set forth in Standard MIL-STD-105, Inspection Level II. Each Container in the sample shall be examined as required by 4.5.2. An AQL of 2.5 per cent for MAJOR Defects and 6,5 per cent for MINOR Defects shall be used. Each Container manufactured shall be subjected to the leakage test of 4.5.3.

4.5.2 Examination - The supplier is responsible for assuring that all requirements of applicable drawings are met.

4.5.3 Leakage test - With the outlet relief valve removed and the hole plugged, the Container shall be pressurized with air to 1.0 ± 0.25 PSIG (equals 27.7 ± 7.0 inches of water) with measurements beginning at a pressure not less than 20.7 inches of water, the average leakage rate shall not exceed an amount equivalent to a pressure drop of 13.5 inches of water in 30 minutes. Correction shall be made as required for the effect of change in temperature of the air in the Container. Care should be taken not to pressurize the Container above 1.25 PSIG, nor to apply pressure with the Container lid or other removable covers partially secured. To locate leaks, brush all seams, joints, rivets, and gasketed areas with a soap solution. Any evidence of leakage beyond the above stated limits shall be cause for rejection of the Container. Replace outlet relief valve after test.

5. PREPARATION FOR DELIVERY

5.1 Preservation - Preservation shall be Level A or C as specified (see 6.2).

5.1.1 Level A

5.1.1.1 Cleaning - Containers shall be cleaned in accordance with Specification MIL-P-116, Process C-1.

5.1.1.2 Drying - After cleaning, the Containers shall be dried in accordance with Specification MIL-P-116, Procedure D-1 or D-4 or a combination of both.

5.1.1.3 Preservative application

5.1.1.3.1 Insert 120 units of dessicant, conforming to Specification MIL-D-3464, and secure Container cover.

5.1.2 Level C - Cleaning, drying and preservation shall be in accordance with the manufacturer’s commercial practice.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:05Z
Check the source to verify that this is the current version before use.

5.2 Packing

5.2.1 Level A and C - The Container requires no packing for delivery. However, all loose interior pieces and all latches shall be tightly secured.

5.3 Marking - In addition to any special marking required by the contract or order, Containers shall be marked in accordance with Standard MIL-STD-129,

6. NOTES

6.1 Intended use - A Container supplied under this specification is intended for use in the shipment, storage and stowage of an AQM-37A Target Body (less Wings, Fins and Canards). To utilize the Container for shipment, storage, or stowage of the AQM-37A Target Body, two (2) Mk 84 Mod 0 Handling Bands (LD477247) are required (see 6.3).

6.2 Ordering data - Procurement documents shall specify:

(a) Title, number, and date of this specification.

(b) Preproduction sample size, if different (see 4,3.1).

(c) Activity designated to perform preproduction testing (see 4.1).

(d) Name and address of activity which will furnish Government-loaned property (see 3.3).

(e) Desired level of preservation and packaging (see 5 and 6.4).

(f) duction inspection data, if required (see 3.4 and 4.4).

6.3 The two (2) Handling Bands required to secure the AQM-37A Target Body in the Container may be procured under Specification MIL-B-81205(WP).

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:05Z
Check the source to verify that this is the current version before use.

6.4 The attention of the contracting officer is invited to the following criteria for selection of the proper level of preservation, packaging and packing:

For Level A - This level shall be used for those items which are to be shipped to indeterminate destinations or stored under indeterminate conditions for worldwide redistribution.

For Level C - This level shall be used only when it is definitely known that the packaged item is to be shipped to domestic installations for immediate use at the first receiving activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:05Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

MIL-C-81204A(WP) Container, Shipping and Storage Mk 311 Mod 1

ORGANIZATION *(Of submitter)*	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 APR 63 1426

C-8278

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:05Z
Check the source to verify that this is the current version before use.