MILITARY SPECIFICATION
NAVIGATION SET, TACAN AN/ARN-84(V)

This amendment forms a part of Military Specification MIL-N-81207A(AS) dated 8 Jauary 1973 and has been approved by theNaval Air Systems Command, Department of the Navy.

Page 8, paragraph 3.3.2.2: Change first sentence to read:

"The equipment shall have a total operating life of 10,000 hours with reasonable servicing and replacement of parts."

Page 11, paragraph 3.3.12.1(1) Add:

"26 volts 60 volt amps"

Page 12, paragraph 3.3.13: Change to road:

"The equipment shall *operate* satisfactorily when supplid with ambient *cooling air from* the internal blower and with aircraft supplied conditioned air in accordance with figure 1."

Page 31, paragraph 3.5.1.14(c): Add:

"The North Reference Trigger is a shunt to ground of 6 ± 1.0 volts (input impedance *of* 1.0K ohms or greater). The shunt shall be applied for a period *of* 70 ± 10 microseconds at a repetition rate of 15 hz ± 0.2%

Page 48, paragraph 3.5.7.15.4: In second sentence delate:

"When loaded with 91 ohms and 500 pf to ground".

Page 49, paragraph 3.5.7.19, Change *to* read:

"A discrete output signal of + 25 ± 5 volts dc shall be provided, in the Receive, Transmit-Receive, and Air to Air modes, to associated equipment for the purpose *of* external power control."

Page 11, Add new paragraph:

"3.3.10.2: Temperature Altitude - The equipment shall operate satisfactorily when subjected to the temperature-altitude requirement *of* MIL-E-5400 *Figure* 3. The navigation set control shall *conform* to MIL-E-5400 Figure 3 except that the temperature shall not axceed + 70°C."

Page 9, Add new paragraph:

"3.3.5.3 Automatic Support Equipment - The equipment shall be capable of being tested to the WRA, SRA and sub SRA levels on the AAI5510 test set.

Preparing Activity:
NAVY-AS
Project No. 5326-N138

NSC-5826

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:05Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:05Z
Check the source to verify that this is the current version before use.