INCH-POUND

MIL-P-71089 (AR)
AMENDMENT 2
29 September 1994
SUPERSEDING
AMENDMENT 1
28 April 1992

MILITARY SPECIFICATION

PROJECTILE, PRACTICE, 155MM, M804E1
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-P-71089(AR), dated 15 November 1991, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Title: Change "M804E1" to "M804A1"

* 1.1 Line 2: Change "M804E1" to "M804A1"

2.1.1 Standard Military add "MIL-STD-1168 - Lot numbering of Ammunition

PAGE 2

* 2.1.2 Drawings, 12913926: Change "M804E1" to "M804A1"

PAGE 4

3.8 Delete in its entirety.

* Add "3.10.6.1 Rust on cup. At the time of receipt inspection and at assembly, the cup surface may exhibit surface rust, absent pitting and exfoliation. Loose rust shall be removed from the threads prior to assembly.

PAGE 6

4.3.1 Line 6, Under "Quantity" delete "25" and substitute "5".

* 4.3.1 Line 7: Change "M804E1" to "M804A1"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:20Z
Check the source to verify that this is the current version before use.

PAGE 7

* Table I, Examination or Test: Change "M804E1" to "M804A1"

Table I, Delete the following:

"(Except Proving Ground Test)" and
"Proving Ground Test 20, Level I, 3.8, 4.5.7"

PAGE 12

* 4.4.2.1 Major 104 Delete "20, 0-1" and substitute "4.4.3.2.2".

PAGE 22 and 23

* 4.4.2.10 Title block: Change "M804E1" to M804A1"

PAGE 25

* 4.4.3.2.1.1 Add the following new sentence: "If the hardness of any cup is over the maximum requirement, that cup shall be rejected and removed from the lot."

* 4.4.3.2.1.2 Add the following new sentence: "If the hardness of any sample cup is over the maximum requirement, all parts in that stress relief lot shall be tested for hardness, and all cups over the maximum requirement shall be rejected and removed from the lot."

* Add "4.4.3.2.2 Tensile force. Five sample cups shall be selected from each heat treatment or stress relief lot and subjected to the tensile force test. The sample cups shall be those with the lowest hardness, considered to represent acceptable process, as measured in 4.4.3.2.1.1 or 4.4.3.2.1.2 above. If any sample cup fails to meet the applicable requirement, the heat treatment or stress relief lot represented by this sample, shall be rejected. Procedures for reheat or stress relief, or for screening of rejected lots shall be submitted to the Government procurement agency for approval. The tensile force test shall be conducted prior to magnetic particle inspection. All cups with hardness below the lowest tested and accepted shall be rejected and removed from the lot."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

PAGE 28

4.5.7 Delete in its entirety.

PAGE 29

6.6, Line 4, Delete the following: "ballistic test data and"
Line 6, Delete: "SMCAR-CCH-P" and substitute: "SMCAR-FSA-MS".

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1320-AD17)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.