MILITARY SPECIFICATION

RECORDER-REPRODUCER SET, SOUND AN/TNH-23( )

This amendment forms a part of Military Specification MIL-R-49203(CR), dated 4 March 1980, and is approved for use within the Communications-Electronics Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

First Paragraph: Delete "the Communications Research and Development Command". and substitute "Communications Electronics Command".

Block on bottom: line 3; Delete "U.S. Army Communications Research and Development Command, ATTN: DRDCO-CM-DM" and substitute "U.S. Army Communications-Electronics Command, ATTN: AMSEL-ED-TO".

PAGE 2

2.1, Under Standards, Military, delete the following:

"MIL-STD-461 Electromagnetic Interference Characteristics Requirements for Equipment Subsystems and Systems

MIL-STD-462 Electromagnetic Interference Characteristics, Measurement of."

3.1, delete last sentence and substitute "The system shall consist of an assembly of items all interfaced to provide the working system described in detail herein."

PAGE 3

3.2, line 1, after "order" add "(see 6.2c)".

3.3.1, line 3, delete "height shall not be greater than one third the width".

3.4.1, delete paragraph.

3.4.n, delete paragraph and substitute:
"n 115 ± 5 volt/220 ± 10 volt plug adapter, three each."

AMSC N/A FSC 5835

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:55Z
Check the source to verify that this is the current version before use.

3.4.1, line 5, delete "117 volt" and substitute "115 ± 5 volt" and delete "220 volt" and substitute "220 ± 10 volt".

3.4.1, line 8, delete "117/220V" and substitute "115 ± 5V/220 ± 10V."

PAGE 4

3.4.2, delete third and fourth sentences and substitute "This unit shall contain batteries which shall be capable of operating the recorder for at least two hours in the record mode. The unit shall be capable of using zinc alkaline batteries BA-3058/U."

4.4, delete "4.4" and substitute "3.4.4.".

3.4.7, delete "such as the "Stenomask" as manufactured by Talk Inc., 455 Union Ave., Westbury, Long Island, N.Y., or equal.".

PAGE 5

3.4.9, delete paragraph and substitute:

"3.4.9 Shipping/Carrying/Storage Case(s). Two ruggedized cases with removable top covers shall be furnished. No tools shall be required to remove/install the covers. The equipment inside the case(s) shall be protected from moisture, dirt and shock.".

3.4.10, delete line 2 and 3 and substitute "The adapter shall operate from 115 ± 5 Vac, 60 Hz and 220 ± 10 Vac, 50 Hz power lines. The output of the adapter shall plug directly into the battery powered recorder/reproducer unit and shall automatically disconnect the internal batteries."

3.4.12, line 1, in heading delete "(Open-Room" Type)" and substitute "(Omnidirectional" Type), and in first sentence delete "open-room" and substitute "omnidirectional".

3.4.12, line 5, delete "Stenomask" and substitute "privacy".

PAGE 6

3.8.5, delete and substitute:

"3.8.5 Recording Head. The heads of the recorder/reproducer units shall meet the requirements of 4.9.5."

3.8.6, delete and substitute:

"3.8.6 Rewind Time. Rewind time of a 45 minute side of a cassette shall not exceed 240 seconds for both AC powered and battery powered recorder/playback units."

3.8.8, delete paragraph.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:55Z
Check the source to verify that this is the current version before use.

PAGE 7

3.9.3, delete paragraph.

3.9.4, delete and substitute:

"3.9.4 Frequency Response. The frequency response of the AC powered and the battery powered recorder/playback units (through the record/playback cycle) shall be within ± 5 dB from 250 to 5000Hz."

3.9.5, delete paragraph.

3.11, delete paragraph.

PAGE 11

TABLE I, under Functional, change "Recording Head Position" to read "Recording Head".

TABLE I, under Electrical, delete "Signal-to-Noise Ratio 3.9.5 4.10.5".

TABLE II, under Functional, delete "WOW and Flutter 3.8.8 4.9.8".

TABLE II, under Electrical, delete "Bias Frequencies 3.9.3 4.10.3".

PAGE 13

TABLE III, subgroup II, delete entire subgroup.

PAGE 14

4.9.5, lines 1 and 2. In heading delete "Position" and delete first sentence.

4.9.5, line 4, delete "vertically".

PAGE 15

4.9.6 c, delete third section and substitute "Stop tape movement when stop watch indicates 240 seconds for both AC powered and battery powered recorder/player units".

4.9.7, lines 3 and 4, delete second sentence.

4.9.7 d, line 4, delete " ± 25% and substitute " ± 15%".

4.9.8, delete, including subparagraphs.

PAGE 16

4.10.1.1, line 4, delete "333 Hz" and substitute "1000 Hz".

4.10.1.1, line 8, after "(VTVM)" add "or equal".

4.10.1.1 c, line 1, delete "333 Hz" and substitute "1000 Hz".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:55Z
Check the source to verify that this is the current version before use.

PAGE 17

4.10.1.2c, line 1, delete "333 Hz" and substitute "1000 Hz".

4.10.2a, line 1, after "VTVM" add ", or equal,".

4.10.2c and 4.10.2d, line 1, delete "333 Hz" and substitute "1000 Hz".

4.10.3, delete, including subparagraphs.

PAGE 18

4.10.4a, line 2, after "VTVM" add "or equal".

4.10.4d, line 1, delete "333 Hz" and substitute "1000 Hz".

4.10.4e, lines 1 and 2, change to read "Record a 250, 1000 (repeat of reference), 2000, 3000 and a 5000 Hz tone" and in line 4 delete "7000 and".

4.10.4f, line 2, delete "333 Hz" and substitute "1000 Hz".

4.10.4h, delete and substitute:

"h. The response through the recorder/playback cycle for both AC powered and battery powered units shall be within ± 5 dB of that of the reference tone between 250 and 5000 Hz."

4.10.5, delete, including subparagraphs.

PAGE 19

4.10.6b and 4.10.6c, line 1, delete "333 Hz" and substitute "1000 Hz".

4.11.1, delete and substitute:

"4.11.1 Humidity. The equipment in its transit case shall be tested in accordance with Method 507.2, Procedure II of MIL-STD-810."

PAGE 20

4.11.2, delete and substitute:

"4.11.2 Bounce, Loose Cargo. The equipment in its transit case shall be tested in accordance with Method 514.3, Procedure II of MIL-STD-810."

4.11.3, line 2, delete "516.2, Procedure II" and substitute "Method 516.3, Procedure IV."

4.11.4, line 2, delete "506.1" and substitute "506.2".

4.12, delete paragraph

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:55Z
Check the source to verify that this is the current version before use.

PAGE 22

4.13 c. line 2, delete "220 volt" and substitute "220 ± 10 volt".

PAGE 23

6.1. line 6, delete "117/220 volt" and substitute "117 ± 5 volt/220 ± 10 volt".

Custodian:
Army - CR

Preparing Activity:
Army - CR
Project No. 5835-A091

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:55Z
Check the source to verify that this is the current version before use.