MILITARY SPECIFICATION

Rocket, 2.75 Inch, Complete Round:
Assembling, Packing and Testing

This Amendment forms a part of Military Specification MIL-R-50263A(PA) dated 23 June 1976.

Change "XM255" to "M255" wherever it occurs.

PAGE 1

Paragraph 1.1.2
Add under Fuze, Rocket "M433 (Loading)"

PAGE 5

Paragraph 2.1
Add under drawings "9260701 - Fuze, Rocket: M433 (Loading)"
"9260925 - Umbilical Test Set"
"9260926 - RC Fuze Setting and Rocket Firing Subsystem"

PAGE 8

Paragraph 3.4.10
Delete lines 3 and 4, and substitute "mated with an M429 fuze or an M433 fuze in the bunker or canopy mode, or upon ground impact when mated with an M423 or M427 fuze or an M433 fuze in the SQ mode. Also, M247 HE Warhead shall".

Paragraph 3.7
Delete in its entirety and substitute: "3.7 Charge Circuit Continuity (Fuze Unarmed)-The continuity of the charge circuit through the umbilical, shall be 220 ohms minimum and 3.3K ohms maximum.

PAGE 15

Paragraph 4.4.2.2
Add to title: ",M433". Also, add Major 105:

Category	Examination or test	AQL	Requirement Paragraph	Paragraph Reference
105	Charge Circuit Resistance Test (M433 only)	100%	3.7	4.5.3

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:18Z
Check the source to verify that this is the current version before use.

Paragraph 4.4.3.1
Delete line 6 and substitute: "with 4.4.4 and 4.5.4. The sample"
Delete line 8 and substitute: "temperatures prescribed in 4.5.5.1 or Table II."

Paragraph 4.5.3
Delete "XM255" from the title

Paragraph 4.5.3.1
Delete in its entirety and substitute: "4.5.3.1 Umbilical Continuity Test-Each umbilical shall be connected to an Umbilical Test Set (9260925). Each umbilical must meet the acceptance requirements. Any umbilical that does not meet the acceptance requirements shall be classed as defective. If one or more defective samples are found, the fuze or fuze/warhead lost shall be rejected."

Paragraph 4.5.3.2
Delete line 2 in its entirety and substitute: "be subjected to the Umbilical Continuity Test in paragraph 4.5.3.1 both before"

Paragraph 4.5.4
Delete in its entirety and substitute:
"4.5.4 Warhead Function Time
"4.5.4.1 XM255 Warhead. Each warhead to be ballistically tested will have its fuze set for one thousand (1000) meters using an RC Fuze Setting and Rocket Firing Subsystem (9260926). A hard copy of the fuze charge signature shall be made at this time. The function time is the time from first motion of the round to first motion of the ogive from the warhead. The function time as indicated on the test equipment shall be correlated between the calibrated nominal time value of the RC Fuze Setting and Rocket Firing Subsystem and the nominal time value of 2.165 seconds. The times recorded for this test are for for information only.
"4.5.4.2 M433 Fuzed Round. Each warhead to be ballistically tested will have its fuze set in accordance with Table II using and RC Fuze Setting and Rocket Firing Subsystem (9260926). A hard copy of the fuze charge signature shall be made at this time. The accept criteria shall be the time measurements and function distances behind target as specified in Table II. The rounds will be tested against a 3-foot bunker made of one inch thick plywood and a 40-foot by 40-foot canopy wall of 3/4 inch thick plywood. Standard television with stop action recorders will be used to record airburst behind the bunker/wall."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:18Z
Check the source to verify that this is the current version before use.

PAGE 31

Paragraph 4.5.5.9
Delete "Picatinny Arsenal, SARPA-QA-A-R" and substitute" ARRADCOM, DRDAR-QAF-T".

PAGE 35

Paragraph 6.3
Delete "Picatinny Arsenal, ATTN: SARPA-QA-T-T" and substitute "ARRADCOM, ATTN: DRDAR-QAF-I".

PAGE 36 TO 40

APPENDIX
Delete in its entirety and substitute Table II, attached.

Custodian:
ARMY - AR

Project Number: 1340-A555

Preparing Activity
ARMY-AR

PROJECT NUMBER: 1320-A555

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:18Z
Check the source to verify that this is the current version before use.

TABLE II

RC Fuze Setting and Rocket Firing Subsystem Settings for M433 Fuzed Rounds

Nominal Time Setting (MILLISEC)	Acceptance Limits (Complete Round) Time (MILLISEC)	Function Behind Target (FEET)
20	0 to 38	0 to 82
200	182 to 218	358 to 471
600	564 to 636	1110 to 1374

The above time settings apply to each temperature test phase (i.e. 24 round sample, 8 fired at each of three temperatures, of these 8, two shall be fired at 200 MS and three each at 20 MS and 600 MS). The Fuze/Warhead Test temperatures shall be -65°F + 4°F/-0°F, + 70°F + 4°F and + 160° ± 4°F. All motors shall be conditioned at + 155°F ± 4°F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:18Z
Check the source to verify that this is the current version before use.