MIL-S-53046
INTERIM AMENDMENT 2(ME)
6 December 1988
USED IN LIEU OF
AMENDMENT 1
27 January 1986

MILITARY SPECIFICATION

SURVEYING EQUIPMENT, ELECTRONIC

DISTANCE MEASURING, MEDIUM-RANGE

(SEDME-MR)

This interim amendment is approved for use within the US Army Belvoir Research, Development and Engineering Center, Department of the Army, with MIL-S-53046, dated 15 August 1984.

PAGE 5

* 3.5, delete in its entirety and substitute:

"3.5 Reliability. The specified Mean-Time Between-Failure (MTBF) of the SEDME shall be 20 missions when tested as specified in 4.5.2.15 for the system and 300 hours for the continuous electronic cycling."

PAGE 6

3.10 and 3.10.1, delete in their entirety and substitute:

"3.10 Treatment and painting. The portions of SEDME painted shall be cleaned, treated, and painted in accordance with MIL-T-704, type F or G, as applicable. Unless otherwise specified (see 6.2), the color shall be green 383."

* 3.11.2, line 4, delete "50 pounds" and substitute "75 pounds".

PAGE 7

3.11.7.3, line 2, add "All external lighting shall be blue-green color between 400-700 nanometer wave lengths with no light visibility beyond a 50 meter circle with the instrument as center point under moonless and starless night conditions. All external visible light produced shall be intensity adjustable."

PAGE 9

3.16, add "The cases shall be the same color as specified for the instrument (see 3.10)."

AMSC N/A FSC 6675
DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:54Z
Check the source to verify that this is the current version before use.

PAGE 10

* 3.18, after last item, add "Tribrach 2 ea".

PAGE 12

Table 1, add:

| | | | | |
|---|---|---|---|---|
| "X | - | Secure Lighting | 4.5.2.18 | 3.11.7.3" |

PAGE 19

* 4.5.2.15, delete the second sentence and substitute:

"The reliability test mission shall consist of 10 cycles of the following profile for a total of 200 missions."

PAGE 20

After 4.5.2.17, add:

"4.5.2.18 Secure lighting. The SEDME-MR will be tested to insure that all external lighting conforms to 3.11.7.3."

PAGE 22

6.2, delete "d" and "e" in their entirety and substitute:

"d. Color when other than as specified (see 3.10)."

* Add at the end:

"k. When tribrachs are required (see 3.18)."

The margins of the amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletion) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - ME

User activity:
Navy - YD

Review activity:
DLA - GS

Preparing activity:
Army - ME

Project 6675-A854



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:54Z
Check the source to verify that this is the current version before use.