# MILITARY SPECIFICATION

## WATER QUALITY ANALYSIS SET: ENGINEER

This amendment forms a part of MIL-W-52874B(ME), dated 7 March 1983 and is approved for use within the USA Belvoir Research, Development, and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1, under SPECIFICATIONS, MILITARY, delete, "MIL-E-52798 and MIL-E-52929" in their entirety.

2.1, under STANDARDS, add:

"FEDERAL

FED-STD-595 - Colors."

2.1, under STANDARDS, MILITARY, change "MIL-STD-810" to read "MIL-STD-810 1/" and at bottom of page add:

"1/ The "C" revision of MIL-STD-810 (dated 10 March 1975) shall be used".

2.1, under STANDARDS, MILITARY, delete, "MIL-STD-1188" in its entirety.

PAGE 3

2.2, under Other publications, add:

"AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103)."

AMSC N/A FSC 6630

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:37Z
Check the source to verify that this is the current version before use.

PAGE 4

3.5.1, line 6 and 7 delete, "One from 5 to 100 units in increments of 5 units and the other from 10 to 200 units in increments of 10 units" and substitute, "The first range of 5 to 100 units, in increments of 5 units from 5 to 50, and increments of 25 units from 50 to 100. The second range of 10 to 200 units, in increments of 10 units from 10 to 100 and increments of 50 units from 100 to 200."

PAGE 6

3.6.1.1, delete and substitute:

"3.6.1.1 Set case finish. Unless otherwise specified (see 6.2), the portion of the case normally painted internally and externally shall be cleaned, treated and painted in accordance with MIL-T-704, type F or G as applicable. Unless otherwise specified (see 6.2), top coat shall be camouflage green 383 conforming to MIL-C-46168. Unless otherwise specified (see 6.2), non-metallic cases having the color pigmentation compounded in the material shall be color matched to color 34094 of FED-STD-595 and shall not require painting."

PAGE 7

3.6.1.2, delete and substitute:

"3.6.1.2 Catch assemblies. Unless otherwise specified (see 6.2), the exterior catch assemblies per drawing 13222E777, after treatement, shall be painted per 3.6.1.1. The internal fasteners shall be painted at the option of the contractor."

PAGE 8

3.7.2, TABLE II, under "induced air" column, delete "70 to 145" and substitute "70 to 120".

3.8.1.1, delete second sentence and substitute:

"Stenciling will be applied on the case top siding above the case pressure relief valve with .75 inch high block letters."

PAGE 9

3.10, delete items "2, 3, and 4" and related data, and substitute:



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:37Z
Check the source to verify that this is the current version before use.

"2. Water Testing Kit Chemical Agents, M272" NSN 6665-01-134-0885 1

Change item "5" to "3".

3.11, delete and substitute:

"3.11 Transportability. The set shall be capable of withstanding the stress and shock encountered in transporting as loose cargo, transit dropping and airdrop delivery."

PAGE 14

4.7.2.1, TABLE IV under column 3: delete, "X" for "Environmental" and "Transportability".

4.7.2.2.2, delete and substitute:

"4.7.2.2.2 Storage. Each sample set shall be tested in accordance with MIL-STD-810C, method 501.1, procedure II, and method 502.1, procedure I, with the following exceptions.

Method 501.1, procedure II

Step 4 - Change 71 °C (160 °F) to 52 °C (125 °F).
Step 6 - Repeat steps 3, 4, and 5 one additional time (making a total of two 12 hour cycles).
Step 7 - Delete.
Step 8 - Delete.

Method 502.1, procedure I

Step 2 - Lower the internal chamber temperature -35 °C (-30 °F) for six continuous hours with no wind or solar radiation and with humidity tending toward saturation.
Step 3 - Delete.
Step 4 - Raise the internal chamber temperature to -23 °F) and maintain for 6 hours.
Step 5 - Repeat steps 2 and 4 one additional time (making a total of two 12 hour cycles).

The test sets will be transferred directly from the conditions of step 6, procedure II, method 501.1 to step 1, procedure I, method 502.1. Upon completion of this test, each sample will be inspected for damage to case and contents. Any evidence of permanent deformation, cracks, or broken items shall constitute failure of this test."



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:37Z
Check the source to verify that this is the current version before use.

PAGE 15

4.7.2.3.1, delete title and first sentence and substitute:

"4.7.2.3.1 Transit drop. When speified (see 6.2), each sample set shall be tested in accordance with MIL-STD-810C, method 516.2, procedure II (transit drop test) except that the test shall be performed on an 8-inch thick bed of dry sand."

PAGE 17

5.2.3, line 2, delete "MIL-STD-1188" and substitute "ASTM D 3951"

5.4, line 2, delete "MIL-STD=1188" and substitute "ASTM D 3951".

6.2, (f) Delete "color and"

(g) Change to "(i)"

Add new (g):

"(g). When color is other than as specified (see 3.6.1.1)."

(h) Change to "(j)".

Add new (h):

"(h). When color pigmentation compounded is other than as specified (see 3.6.1.1)."

(i) Change to "(k)".

(j) Change to "(m)".

(k) Change to "(n)".

(l) Change to "(o)".

Add new (l).

"(l) When transit dop test is required (see 4,7.2.3.1)."

(m) Change to "(p)".

(n) Change to "(q)".

Custodian:
Army - ME

Preparing activity:
Army - ME



Project 6630-A444

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:37Z
Check the source to verify that this is the current version before use.