[Metric]
A-A-209B
October 12 1995
Superseding
A-A-209A
November 6th, 1989

COMMERCIAL ITEM DESCRIPTION
INK, STAMP PAD

This Commercial Item Description is approved by the Commissioner, Federal Supply Service, General Services Administration for use by all federal agencies

1. Scope: This Commercial Item Description covers quick-drying ink for use with rubber-stamp inking pads

2. Classification:

Type	I	For Fabric, Foam Latex Rubber, and Foam Plastic Pads
	II	For Wooden Pads

3. Salient Characteristics:

3 1 Type I Quick drying ink for fabric, foam latex rubber and or foam plastic pads shall meet the requirements of the drying time, and stability tests.

3 2 Type II Quick drying ink for wooden pads shall dry promptly by absorption without spreading and shall meet the requirements of the drying time, stability, and effect on rubber stamp tests

3.3 The ink shall be furnished in the following colors Black, Blue, Green, Red, and Purple also in containers of the following proportions 29 6 cm3 (1 fl oz), 59.1 cm3 (2 fl oz), 118.3 cm3 (4 fl oz) or 236 6 cm3 (8 fl oz) and cans containing four or eight fluid ounces

3 4 The inks used shall be specifically used on stamp pads manufactured in accordance with commercial item descriptions A-A-207 and A-A-1383

3 5 Applicators. The applicator, if required, shall be capable of mechanically distributing ink to the appropriate pads without damaging the pad, applicator, or soiling the user according to normal commercial practice. Inks furnished in 118.3 cm3 (4 fl oz) or 236 6 cm3 (8 fl oz) containers shall be fitted with applicators designed to distribute both limited and a directed flow of ink to the pad

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to General Services Administration, Federal Supply Service, Engineering Branch, 26 Federal Plaza, New York, NY 10278.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:05Z
Check the source to verify that this is the current version before use.

3.6 Effect On Applicator The applicator shall not be adversely affected by the contents The brush type applicator shall be securely attached to the cap of the bottle The other types shall be securely attached to the bottle

3 7 Workmanship The bottles, cans, caps and brushes shall be in accordance with the manufacturers best commercial practice and shall have no defects that affect serviceability or appearance The bottles, caps, and brushes shall not be damaged (cracked, bent, defective brushes etc) nor have stripped screw threads The caps shall fit snugly when tightened with moderate hand applied force, and shall not be damaged by such action The ink containers shall not show any signs of leakage or free homogeneous liquids, lumps, strings and objectionable odors

3 8 Shelf Life The ink shall meet all the requirements of this specification from the time of delivery to a minimum of 24 months in storage under normal conditions and shall replace any item not meeting this requirement

4. Regulatory Requirements:

The offerer/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23 403 of the Federal Acquisition Regulation (FAR)

4 1 Toxicity The use of benzene or carbon tetrachloride solvents and any known carcinogens as ingredients are prohibited Trace amounts of benzene derivatives present in commercial grades of acceptable aromatics are permissible Inks shall contain no chlorinated compounds or other toxic hydrolyzable chlorine derivatives Use of any toxic substance must be in accordance with all applicable federal statutes

4.2 Labeling Stamp pad ink containers shall be labeled to comply with the "Federal Hazardous Substances Act Regulations", 16 Code of Federal Regulations Part 1500

4 3 Material Safety Data Sheets Safety data sheets shall be furnished in accordance with Fed-Std-313. The pertinent government mailing addresses for submission of data are listed in appendix B of Fed Std 313

5. Quality Assurance Requirements:

5 1 Contractor Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this commercial item description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices The government reserves the right to require proof of such conformance prior to first delivery and therefore as may be otherwise provided for under the provisions of the contract

Source: https://assist.dla.mil -2Downloaded: 2026-10-26T08:05Z
Check the source to verify that this is the current version before use.

5 2 Examination and Testing

5.2 1 Suppliers are encouraged to use quality control (QC) techniques that exhibit control over their processes (e.g (Statistical Process Control) SPC Techniques) as defined in American National Standards Institute (ANSI) Z1.1, Z1.2 and Z1.3 / American Society for Quality Control (ASQC) B.1, B.2 and B.3 that systematically reduce excess variations If used, objective evidence shall be available that demonstrates overall measurement adequacy techniques and controls These techniques shall ensure quality levels equal to, or greater than, those cited in applicable technical document or, herein

5.2 2 End item inspection / testing may be used by the offeror or the Government representative, as a means to determine the effectiveness of the in process quality controls In process controls shall not be substituted for end item performance testing

5.2 3 For those characteristics for which there are no such controls, or for end item performance test, lot by lot sampling for inspection / test shall be required The sample unit shall be either one bottle or container Sampling shall be in accordance with the American National Standards Institute (ANSI) / American Society for Quality Control (ASQC) Z1 4, Sampling Procedures and Tables for Inspection by Attributes

5.2 4 An inspection lot shall consist of all like items submitted for inspection at one time The inspection level for visual and dimensional testing shall be S-4 with an AQL of 4 0 percent defective. The inspection level for performance testing shall be S-1 with an AQL of 4.0 percent defective. The supplier must provide objective evidence (tests and inspection records) that the presented material meets the requirements of the sampling plan as indicated above

6. Performance Tests:

6.1 Drying Time Type I & Type II Impressions shall be made from fabric pads, foam latex rubber pads, or foam plastic pads (Type I) or wooden pads (Type II) with clean rubber stamps on test paper in accordance with A-A-2804A, type III white bond paper having a pH of 5.0 with a basis weight of 60 grams per square meter (16 pound, 17 x 22 - 500). A tolerance of 5% is allowable. Test paper shall have an additional requirement of 160 - 140 seconds maximum smoothness on both sides using the Sheffield method per the most current TAPPI T538 test method. Alternately, paper conforming to JCP-O-60 can be used as an alternate source. After 30 seconds the impressions shall be sufficiently dry not to smear when rubbed lightly with index finger, or when ink is transferred to another sheet of test paper when ten (10) sheets are laid on top of the impression

6 2 Stability The fabric, foam latex rubber, foam plastics or wooden pads used in testing drying time shall be exposed, uncovered, in a atmosphere of 73 4° F ± 3 6° for 3 days and 50 ± 5% relative humidity (the use of a desiccator or chamber which does not allow for the even exchange of air shall be prohibited) The impressions made from the exposed pad shall dry as quickly and be at least as sharp and intensely colored as the impressions made before exposure There shall be no swelling of the foam latex rubber pad

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:05Z
Check the source to verify that this is the current version before use.

THE FOLLOWING TEST IS FOR TYPE II ONLY

6.3 Effect On Rubber Stamp. The type face of a clean rubber stamp shall be immersed for 10 days in a sample of Type II ink. Surplus ink shall then be removed from the stamp and impressions shall be made with the stamp on test paper in accordance with A-A-2804A, type III white bond paper having a pH of 5.0 with a basis weight of 60 grams per square meter (16 pound, 17 x 22 - 500). A tolerance of 5% is allowable Paper for this test shall have an additional requirement of 160 - 140 seconds maximum smoothness on both sides using the Sheffield method per the most current TAPPI T538 test method Alternately, paper conforming to JCP-O-60 can be used as an alternate source The impressions shall be sharp and regular in outline

7. Packaging:

7 1 Preservation, packing, and marking shall be specified in the contract or order

8. Notes:

8 1 Applicable Documents Issues of the following documents, in effect on the date of invitation for bids or request for proposal form a part of this document to the extent specified herein

8 1.1 Federal Acquisition Regulation (FAR) may be obtained from the Superintendent of Documents, Government Printing Office, Washington DC 20402

8.1.2 ANSI / ASQC Z1.4 may be obtained from the American Society for Quality Control, PO Box 3005, 611 E Wisconsin Avenue, Milwaukee, Wisconsin 53201-4606.

8 1.3 Federal Standards and Specifications may be obtained from the General Services Administration Specifications Section (3FBO-W) in Suite 8100 at 490 L'Enfant Plaza, SW Washington DC 20407.

8.1.4 Technical Association of the Pulp and Paper Industry (TAPPI) T479 method may be obtained from TAPPI, Technology Park, PO Box 105113, Atlanta, Georgia, 30348-5113

8.1 5 JCP-O-60 specifications may be obtained from Chief Paper Procurement Section, MMPP, US Government Printing Office, North Capital and H Street, NW, Washington DC 20401

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:05Z
Check the source to verify that this is the current version before use.

8 2 Ordering Information Purchaser should select the required options permitted herein, and include the following information in procurement documents

A. Title, number, and date of this commercial item description
B Purchasers shall specify the color of ink required
C Purchasers shall specify size of container
D Purchasers shall specify arrangement for inspection and inspection facilities, if other than specified (see tests and quality assurance requirements)
E Purchasers shall specify packaging, packing and special marking
F Purchasers shall specify if bar code marking is not required
G Purchasers may specify alternative applicator style, if required
H. MSD's required, in addition to those required by FED-STD-313
I Purchasers shall specify palletization, if required

8 3 National Stock Number Listing

7510-00-057-9305
7510-00-161-4236
7510-00-161-4237
7510-00-161-4238
7510-00-161-4240
7510-00-161-4241
7510-00-254-2953
7510-00-285-2557
7510-00-782-6257

MILITARY INTERESTS.
NONE· DoD has determined that no military activity has an interest in this commercial item description

PREPARING ACTIVITY
GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:05Z
Check the source to verify that this is the current version before use.