A-A-2238
October 8, 1985

COMMERCIAL ITEM DESCRIPTION
Stand, Office Machine (EDP TERMINAL, Dual Surface)

The General Services Administration has authorized the use of this commercial item description

Salient Characteristics

These characteristics concisely describe the essential physical and functional/performance features of the items covered herein.

Design. The dual surfaces terminal stand shall be designed for heavy duty use and to be compatible with other components of the modular line.

Ordering options. Tilting keyboard surface; tilting machine surface; color and grain of plastic laminate; color of finish; left and right side extensions; accessories.

Tops. Tops shall be covered with HP plastic laminate with backing sheet on bottom (steel cores excepted), walnut grain per GSA Standard Sample No. FSS-L-01002, light oak grain per GSA Standard No. FSS-L-01015 or matte parchment laminate within the limits of the parchment enamel. Alternatively, the manufacturer may provide his equivalent walnut or light oak grain HP plastic laminate subject to the contracting officer approval. Molding, if used, shall have radius corners and shall match the baked enamel finish within the limits of the material used. Self edge not allowed on front or rear edges of tops. Overall thickness shall be 1" minimum. The rear surface (machine) shall be 27"W by 17"D, minimum and shall have a range of infinite adjustability from 26-1/2" high to 32" high (glides fully retracted). Greater ranges are acceptable. The adjusting mechanism shall be located for operation from the sitting position and shall not interfere with the work tasks of the operator. The front surface (keyboard) shall be 27"W by 12"D minimum and shall have a range of infinite adjustability from 24" high to 28" high (glides fully retracted). Greater ranges are acceptable. Additionally, the surface shall slide forward a minimum of 3". Mechanical stops shall limit the range of travel to all adjustments. Disassembly of the top from the base by removal of screws directly screwed into composite tops is unacceptable.

FSC 7110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:20Z
Check the source to verify that this is the current version before use.

Base. The base shall have 4 corrosion resistant adjustable glides. Conventional table legs not acceptable. Wire management which controls wires between top surface and the floor shall be provided. The metal finish shall be semi- gloss baked enamel with colors Fed. Std. No. 595 black (27040) or parchment within the range delimited by (26586) and (26405). Alternatively, the manufacturer may provide his commercial black baked enamel finish subject to the contracting officer approval.

Tilting machine surface. In addition to the height adjustment, when specified the rear surface (machine) shall tilt 3 degrees forward and 12 degrees backward (15 degrees overall) minimum.

Side extensions. The left and right side extensions for the dual-surface stand shall be constructed and laminated the same as the top and shall be 13"W by 30"D, minimum. They shall have a minimum range of adjustability in increments of 1" maximum from 24" high to 28" high. Infinite adjustability is acceptable.

Accessories.
a. Padded palm rest
b. Copy holder
c. Foot rest

Identification label. The label shall nave the contractor's name or trademark, contract or order number, National Stock Number (if specified) and month and year of manufacture legibly marked in permanent dark ink. The label shall be affixed under the top of the stand and on the bottom of all other items and shall not be removable by hand without defacement after being affixed for 4 hours.

Workmanship. The workmanship shall be of the quality to produce finished items acceptable in appearance, function and serviceability and to prevent potential hazard to personnel or their clothing.

Performance. Each unit shall comply with the following requirements. Failure of any unit to comply with these requirements shall be cause for rejection.

ANSI/BIFMA. American National Standard for Desk Products X5.5-1983. Perform following tests: 4, 5, 10, 11, 12, and 14.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:20Z
Check the source to verify that this is the current version before use.

Regulatory requirement. In accordance with the section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials.

Packaging, packing and marking. Packaging, packing and marking shall be as specified in the contract or order.

Plastic laminate sample. A sample panel of the decorative plastic laminate is obtainable from the Engineering Division, Furniture Commodity Center, Federal Supply Services, General Services Administration, Washington, DC 20406.

Color sample. A sample panel of the enamel finish is obtainable from the Business Service Center, Federal Supply and Services, General Services Administration, Washington, DC 20405 or the Business Service Center in the nearest General Services Administration Regional Office.

ANSI/BIFMA Standards are available from the American National Standards Institute Inc., 1430 Broadway, New York, NY 10018.

Note. The Commercial Certification Clause is not required when this Commercial Item Description is used for procruement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:20Z
Check the source to verify that this is the current version before use.