[METRIC]
A-A-82B
January 16, 1996
SUPERSEDING
A-A-82A
FEBRUARY 25, 1992

COMMERCIAL ITEM DESCRIPTION

DISPENSER, PRESSURE-SENSITIVE ADHESIVE TAPE (COUNTER TYPE FOR 7.62 cm(3-INCH TAPE))

1. SCOPE: This description covers counter top, manually operated tape dispensers which are used to dispense pressure-sensitive adhesive tape.

2. SALIENT CHARACTERISTICS:

2.1 Tape dispensers shall be capable of dispensing single or multiple rolls of tape with the following dimensions:

Maximum Tape Width	Maximum Outer Tape Diameter	Inner Core Tape Diameter
7.7 cm (3-1/32 inches)	12.7 cm (5 inches)	7.62, +.16 ,-0 cm (3, + 1/16,-0 inches).

Dispensers that can accommodate tape roll widths of up to, and including 10.2 cm (4-1/32 inches) shall also be acceptable.

2.2 Have a firmly attached, serrated or corrugated metal blade suitable for manually cutting pressure-sensitive tape.

2.3 Have a space of at least 1.6 cm (5/8 inch) diameter between a full roll of tape, the dispenser body, and the tape holding platform to allow the extended tape to be easily grasped and detached.

2.4 Have either a revolving reel of sufficient diameter to hold the tape roll securely during operation, or a nonrevolving drum which permits the unhindered revolution of the tape roll around it.

2.5 Have a body constructed of a commercially appropriate metal, no less than .8 mm (1/32 inch) thick, or a commercial appropriate plastic capable of meeting the performance requirements of this document.

2.6 Have feet or a rubberized base permanently attached to the bottom of the body to prevent any damage and marring of work surfaces (e.g. wood, glass or metal). Feet/base shall provide lateral stability.

Beneficial comments, recommendations, additions, deletions, clarifications etc. Any data which may improve this document should be sent to:
General Services Administration
Federal Supply Service,
Engineering Branch (2FYEE)
26 Federal Plaza, New York, NY 10278

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:04Z
Check the source to verify that this is the current version before use.

2.7 Dispense tape freely without binding against any part of the dispenser body and shall cut without wrinkling and tearing unevenly.

2.8 Be marked in a legible and permanent manner with the manufacturer's name and/or trademark.

2.9 Workmanship: Except for the cutting edge of the blade, the tape dispenser shall be free of sharp edges. Any fasteners or pins shall be set in accordance with normal commercial practice, including, but not limited to, exhibiting a firmly tightened, flush seating. The tape dispenser body (whether metal or plastic) shall be free of any defects which will impair serviceability and adversely affect the appearance or which might constitute a personal hazard to the user. The tape dispensers shall not exhibit evidence of deformity, including, but not limited to cracking, bending, loosened parts, warping, or visible stress marks.

2.10 Corrosion Resistance: Except for the actual cutting edge of the blade, all metal parts shall be resistant to corrosion. Individual parts shall be either corrosion resistant stainless steel or steel that is anodized,plated,finished with baked enamel, subjected to a bluing process, or whatever is commercially appropriate for the specific function of the part. The contractor shall provide a manufacturer's chemical certification of corrosion resistance upon request by the Government.

3. REGULATORY REQUIREMENTS: The offeror/contractor is encouraged to use recovered materials in accordance with paragraph 23-403 of the Federal Acquisition Regulation (FAR).

4. QUALITY ASSURANCE PROVISIONS:

4.1 Contractor Certification: The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards,and quality assurance practices. The government reserves the right to require proof of such conformance prior to the first delivery and thereafter as maybe otherwise provided for under the provisions of the contract.

4.2 Inspection & Sampling: Suppliers are encouraged to use quality control (QC) techniques that exhibit control over their processes (e.g. (Statistical Process Control) SPC techniques) as defined in American National Standards Institute (ANSI)Z1.1, Z1.2 and Z1.3/ American Society for Quality Control(ASQC) B.1, B.2 and B.3 that systematically reduce excess variations. Objective evidence shall be available that demonstrates overall measurement adequacy techniques and controls. These techniques shall ensure quality levels equal to, or greater than, those cited in applicable technical document or,herein.

End item inspection/testing may be used by the offeror or the Government representative, as a means to determine the effectiveness of the in process quality controls. In process controls shall not be substituted for end item performance testing.

For those characteristics for which there are no such controls, or for end item performance test, lot by lot sampling for inspection/test shall be required. Sampling shall be in accordance with (ANSI)/(ASQC)Z1.4. An inspection lot shall consist of all like items submitted for inspection at one time. The sample unit shall be one tape dispenser The inspection level shall be S-3 with an AQL of 4% defective for visual,dimensional and workmanship.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:04Z
Check the source to verify that this is the currentversion before use.

The supplier must provide objective evidence (tests and inspection records) that the presented material meets the requirements of the sampling plan as indicated above.

5. PACKAGING, PACKING, LABELING, MARKING, AND PALLETIZATION:

Packaging, packing, labeling, marking and, palletization shall be as specified in the contract or order.

6. NOTES

6.1 Referenced Documents: The following documents form a part of this Commercial Item Description to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply:

6.1.1 **ANSI/ASQC Z1.4** is available from:
American Society for Quality Control
P.O. Box 3005
611 E. Wisconsin Avenue
Milwaukee, WI 53201-4606.

6.1.2 **Federal Acquisition Regulation(FAR)** is available from:
The Superintendent of Documents
Government Printing Office
Washington DC 20402

6.2 Ordering Data: Purchasers should select the preferred options permitted herein,and include the following information in procurement documents:

(1) Title, number,and date of this Commercial Item Description.
(2) Arrangement for inspections and inspection facilities, if different than provisions under Quality Assurance.
(3) Special packaging and packing, if different than provisions in Packaging and Packing.
(4) Special marking, if different than provisions in Marking.
(5) Specify, only if Bar Code marking is not required.

6.3 List Of NSN'S

7520-00-634-6724

MILITARY INTEREST:

NONE: DoD has no registered interest in revisions and amendments to this Commercial Item Description until further notice.

PREPARING ACTIVITY:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:04Z
Check the source to verify that this is the currentversion before use.