MILITARY SPECIFICATION SHEET

ADAPTERS, CONNECTOR, COAXIAL, RADIO FREQUENCY, (SERIES SMA), CLASS 2, RIGHT ANGLE, MALE TO FEMALE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

This amendment forms a part of Military Specification Sheet MIL-A-55339/2A, dated 4 August 1975, and is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

PERFORMANCE, delete and substitute:

"PERFORMANCE (for each test of a threaded coupling connector where the test is performed on mated pairs, the pairs shall be torqued 7 to 10 inch pounds (.791 to 1.13 Nm))".

Coupling proof torque: Delete "max" and substitute "min".

PAGE 3

FIGURE 2. Mating dimensions: At arrow beneath the word "PROJECTION", add ".010 MAX RECESSION"; in dimension columns, after .003 inch, .08 mm, add ".010 inch, .25 mm".

PAGE 4

VSWR, delete and substitute:

"VSWR: 1.05 +.010 F (F in GHz) max at .5 to 12.4 GHz".

Custodian:
Air Force - 85

Review activities:
Air Force - 11, 99
DLA - ES

User activity:
Air Force - 19

Preparing activity:
Air Force - 85

(Project 5935-3193-2)

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:04Z
Check the source to verify that this is the current version before use.