MIL-T-52953/5(ME)
8 December 1986

MILITARY SPECIFICATION SHEET

TRUCK, LIFT, FORK, ELECTRIC, SOLID TIRES,

3,000-POUND CAPACITY, 130-INCH LIFT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the truck described herein shall consist of this document and the issue in effect of MIL-T-52953.

REQUIREMENTS

1. Capacity: 3000 pounds at 24 inch load center.
2. Collapsed mast height: 72 inches maximum.
3. Maximum fork height: 130 inches minimum.
4. Free lift height: 48 inches minimum.
5. Fork size: 1-11/16 inches maximum thickness X 4 inches maximum width X 48 inches long, plus 0 inches, minus 1/2 inch.
6. Fork spacing: 10 inches minimum to 32 inches maximum.
7. Overhead guard height: 83 inches maximum.
8. Right angle turn dimension: 142 inches maximum. (Add 4 inches when side shift is used.)
9. Travel speed: 6 mph minimum.
10. Upright tilt: 5 degrees, plus or minus 1 degree forward; 5 degrees minimum rearward.
11. Lifting speed (loaded): 48 feet per minute (minimum).
12. Battery: 850 A @ 6 hr. rate (minimum).

Custodian:
Army - ME
Navy - SA
Air Force - 99

Preparing activity:
Army - ME

Project 3930-A605

Review activities:
Army - AT, SM
Navy - MC
DLA - CS

AMSC N/A

FSC 3930

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.