MILITARY SPECIFICATION

VOLTAGE REGULATOR SUBASSEMBLY: 10525750

This amendment forms a part of Military Specification MIL-V-60216(MU), dated 3 March 1965.

Table II, Variable inputs: Delete all of the column under Variable inputs and substitute:

"NAME	LOW LINE (volts)	NOMINAL LINE (volts)	HIGH LINE (volts)
+6V main DC	+13.5 ± 1.4	+17.1	+20.0
-10V main DC	-14.5 ± 1.2	-17.9	-21.5
+20V	+17.0 ± 1.5	+21.0	+25.0
-32V	-26.0	-32.0	-37.5
-12V	-11.0 ± 0.2	-12.0 ± 0.2	-13.0 ± 0.2"

Table II, under Trip load: Delete "1.5 ± 0.2" and "2.4 ± 0.2" and substitute "1.5 + 0.30 and "2.4 + 0.30".
- 0.0 - 0.0

Table II, under Loads: Add new column:

"Extreme Temperature Trip Loads

-10V Load	1.5 +0.40 amperes
+6V Load	2.4 +0.40 amperes"

Table II, Tripped output: Delete "(+10 percent)" and substitute "(±10 percent)".

Table III, Characteristic 107, Requirement Column: Delete "3.4.7" and substitute "3.5".

Paragraph 4.5.1.3.2: Delete in its entirety and substitute:

"4.5.1.3.2 Operating.- This test shall be conducted in accordance with the humidity test defined in Procedure III of MIL-F-13926, except that the humidity shall be maintained at 92 to 97 percent for the 24-hour period, and the test shall cease at the end of that period (Method 106 of MIL-STD-202 shall be excluded). Throughout the test period, the board shall be capable of performing the tests of 4.5.4. In order to demonstrate this capability, the tests of 4.5.4 shall be performed a minimum of once each 6 hours of the 24-hour period. The final test shall be conducted during the final portion of the 24-hour period. Between tests, the board shall be electrically energized as described in 4.5.4.1."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:19Z
Check the source to verify that this is the current version before use.

Paragraph 4.5.1.4: Delete in its entirety and substitute:

"4.5.1.4 Salt spray.- This test shall be conducted in accordance with the salt spray test defined in Method 101, Condition B of MIL-STD-202 using a 5 percent salt solution. At the end of the exposure period, salt deposits shall be removed from the board by a gentle wash, not exceeding 30 minutes, in running water not warmer than 100°F, using a soft-hair brush or plastic-bristle brush. The board shall then be air dried in a controlled environment at 72°F ± 5°F and a relative humidity of 30 to 50 percent for a period of 24 hours. The board shall be inspected visually for any physical damage, then tested in accordance with 4.5.4 to 4.5.9 inclusive."

Paragraph 4.5.2: Delete in its entirety and substitute:

"4.5.2 Performance.- To determine compliance with 3.4.1, the voltage regulator shall be visually inspected to insure that all components are physically present and conform to ordnance drawing No. 10525753. If resistors R8, R9, R21, R23, R25, R26, R43, R52, R58, R66, R69 and R74 are missing, they shall be selected and installed using procedure indicated in 4.5.3.1 to 4.5.3.5 inclusive. If the voltage regulator conforms to ordnance drawing No. 10525753, it shall be electrically tested as indicated in 4.5.4.1 to 4.5.8 inclusive."

Paragraph 4.5.3.2: Delete "Table V" and substitute "Table II".

Paragraph 4.5.3.3: Delete "Table V" and substitute "Table II".

Paragraph 4.5.3.5: Add to last sentence: "except that the trip current resistors shall be values that give the next higher bias ratio (R8 to R9 for -10V and R52 to R43 for +6V) than the potentiometer settings."

Paragraph 4.5.4.3: Delete "1.75" and substitute "1.79".

Paragraph 4.5.4.4: Delete "2.65" and substitute "2.8".

Figure 5, line 8: Delete "R4: 10526600" and substitute "R4: 10526660".

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A024

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:19Z
Check the source to verify that this is the current version before use.