# MILITARY SPECIFICATION

## INDICATOR, SAFETY LEVEL, RF

1. SCOPE

1.1 This specification covers one type of portable, battery operated radio frequency energy indicator.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

Federal

| | |
|---|---|
| NN-P-530 | Plywood, Flat-Panel |
| QQ-P-416 | Plating, Cadmium (Electrodeposited) |
| QQ-Z-325 | Zinc Coating, Electrodeposited, Requirements For |
| PPP-B-601 | Boxes, Wood, Cleated-Plywood |
| PPP-B-636 | Box, Fiberboard |

Military

| | |
|---|---|
| MIL-B-18 | Batteries, Dry |
| MIL-P-116 | Preservation, Methods Of |
| MIL-D-1000 | Drawings, Engineering And Associated Lists |
| MIL-M-3171 | Magnesium Alloy, Processes For Pre-treatment And Prevention Of Corrosion On |
| MIL-C-5541 | Chemical Films And Chemical Film Materials For Aluminum And Aluminum Alloys |
| MIL-C-6021 | Castings, Classification And Inspection Of |
| MIL-I-6869 | Impregnants For Aluminum Alloy And Magnesium Alloy Castings |
| MIL-S-7742 | Screw Threads, Standard, Optimum Selected Series: General Specification For |
| MIL-A-8625 | Anodic Coatings, For Aluminum And Aluminum Alloys |



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:47Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

| | |
|---|---|
| MIL-STD-129 | Marking For Shipment And Storage |
| MIL-STD-130 | Identification Marking Of US Military Property |
| MIL-STD-143 | Specifications And Standards Order Of Precedence For The Selection Of |
| MIL-STD-147 | Palletized And Containerized Unit Loads 40" X 48" 4-Way (Partial) Pallet Skids, Runners, Or Pallet-Type Base |
| MIL-STD-810 | Environmental Test Methods For Aerospace And Ground Equipment |
| MIL-STD-1186 | Cushioning, Anchoring, Bracing, Blocking, And Waterproofing; With Appropriate Test Methods |

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Preproduction testing. This specification makes provision for preproduction testing.

3.2 Components. The indicator shall consist of a control/indicator unit and antenna(s).

3.3 Selection of specifications and standards. Specifications and standards for all materials, parts, and Government certification and approval of processes and equipment which are not specifically designated herein and which are necessary for the execution of this specification, shall be selected in accordance with MIL-STD-143, except as provided in the following paragraph:

3.3.1 Standard parts. AN Standard and MIL Standard parts shall be utilized whenever suitable. They shall be identified by applicable part number. Commercial parts such as screws, bolts, nuts, and cotter pins may be used if replaceable by AN Standard and MIL Standard parts without alteration. The corresponding AN Standard or MIL Standard part numbers shall be on applicable drawings and parts lists. In applications for which no suitable AN Standard or MIL Standard is in effect on date of invitation for bids, commercial parts may be used provided requirements of this specification are adhered to.

3.4 Materials.

3.4.1 Metals. Metals shall be of the corrosion-resistant type or be suitably treated to resist corrosion during normal service life. Materials contained within hermetically sealed inclosures are considered to be suitably protected



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:47Z
Check the source to verify that this is the current version before use.

from corrosion. Requirements specified for fungicidal and corrosion protective treatment, anodizing of aluminum alloy parts, and cadmium plating of steel parts are not applicable for parts within hermetically sealed instruments. Steel parts that have been cadmium plated and aluminum alloy parts that have been anodized shall be further protected against corrosion if necessary.

3.4.1.1 Anodic treatment. Aluminum alloy parts shall be anodically treated in accordance with MIL-A-8625, when practicable. As an alternate, chemical treatment in accordance with MIL-C-5541 may be used.

3.4.1.2 Plating. Cadmium plating shall be in accordance with QQ-P-416, Type II. In cases where cadmium plating is considered impractical or undesirable the parts shall be given a "Parkerizing," "Bonderizing," "Granadizing," or equivalent treatment. Zinc plating shall be in accordance with QQ-Z-325.

3.4.1.3 Magnesium alloy. Magnesium alloy parts shall be surface treated in accordance with MIL-M-3171, where practicable.

3.4.1.4 Electrolytic corrosion. All parts of the indicator shall be designed to provide protection against electrolytic corrosion through contact of dissimilar metals, for all operational and climatic conditions specified herein. Dissimilar metals shall not only be insulated from each other, but where contact of dissimilar metals is required, the possibility of a conductive moisture film carrying an electrical potential between two dissimilar metals shall be eliminated by either interposing a neutral material or by coating or painting the exposed surfaces of the contact area.

3.4.1.5 Casting. Castings shall be of high quality, clean, sound and free from holes, porosity, cracks, and other defects, and shall conform to MIL-C-6021 Inspection procedures. All Class A castings shall have a type test. Imperfections not materially affecting the suitability of the castings may be repaired in accordance with MIL-I-6869.

3.4.2 Nonmagnetic materials. Nonmagnetic materials shall be used for all parts of the indicator, except where magnetic materials are essential.

3.4.3 Fungus-proof materials. Materials which are not nutrients for fungi shall be used to the greatest extent practicable. In cases where materials that are nutrients for fungi must be used, such materials shall be treated with a fungicidal agent as approved by the procuring agency.

3.4.4 Protective treatment. When materials are used in the construction of the indicator that are subject to deterioration when exposed to climatic and environmental conditions likely to occur during service usage, they shall be protected against such deterioration in a manner that will in no way prevent compliance with the performance requirements of this specification. The usage of any protective coating that will crack, chip, or scale with age or extremes of climatic and environmental conditions shall be avoided.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:47Z
Check the source to verify that this is the current version before use.

from corrosion. Requirements specified for fungicidal and corrosion protective treatment, anodizing of aluminum alloy parts, and cadmium plating of steel parts are not applicable for parts within hermetically sealed instruments. Steel parts that have been cadmium plated and aluminum alloy parts that have been anodized shall be further protected against corrosion if necessary.

3.4.1.1 Anodic treatment. Aluminum alloy parts shall be anodically treated in accordance with MIL-A-8625, when practicable. As an alternate, chemical treatment in accordance with MIL-C-5541 may be used.

3.4.1.2 Plating. Cadmium plating shall be in accordance with QQ-P-416, Type II. In cases where cadmium plating is considered impractical or undesirable the parts shall be given a "Parkerizing," "Bonderizing," "Granadizing," or equivalent treatment. Zinc plating shall be in accordance with QQ-Z-325.

3.4.1.3 Magnesium alloy. Magnesium alloy parts shall be surface treated in accordance with MIL-M-3171, where practicable.

3.4.1.4 Electrolytic corrosion. All parts of the indicator shall be designed to provide protection against electrolytic corrosion through contact of dissimilar metals, for all operational and climatic conditions specified herein. Dissimilar metals shall not only be insulated from each other, but where contact of dissimilar metals is required, the possibility of a conductive moisture film carrying an electrical potential between two dissimilar metals shall be eliminated by either interposing a neutral material or by coating or painting the exposed surfaces of the contact area.

3.4.1.5 Casting. Castings shall be of high quality, clean, sound and free from holes, porosity, cracks, and other defects, and shall conform to MIL-C-6021 Inspection procedures. All Class A castings shall have a type test. Imperfections not materially affecting the suitability of the castings may be repaired in accordance with MIL-I-6869.

3.4.2 Nonmagnetic materials. Nonmagnetic materials shall be used for all parts of the indicator, except where magnetic materials are essential.

3.4.3 Fungus-proof materials. Materials which are not nutrients for fungi shall be used to the greatest extent practicable. In cases where materials that are nutrients for fungi must be used, such materials shall be treated with a fungicidal agent as approved by the procuring agency.

3.4.4 Protective treatment. When materials are used in the construction of the indicator that are subject to deterioration when exposed to climatic and environmental conditions likely to occur during service usage, they shall be protected against such deterioration in a manner that will in no way prevent compliance with the performance requirements of this specification. The usage of any protective coating that will crack, chip, or scale with age or extremes of climatic and environmental conditions shall be avoided.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:47Z
Check the source to verify that this is the current version before use.

3.5 Design and construction. The indicator shall be designed and constructed so that no parts will work loose in service and shall be built to withstand the strains, jars, vibration, and other conditions incident to shipping, storage, assembly and service without failure.

3.5.1 The construction of the indicator shall be reasonably simple to permit repair without requiring special tools or fixtures and without disassembly of the electrical circuits.

3.5.2 The indicator shall be so designed as to show the numerical value of the received signal as well as a color coded indication as to safe and dangerous readings. The numerical value of the meter scale shall be decibel (db) referred to 10 milliwatt (mw) per square centimeter (sq cm). Provisions shall be provided for remoting the field sensing portion of the indicator so that the control unit meter may be read by the operator in a safe area. The field sensing portion shall be so designed that it can be mounted directly on the control unit for mobile versatility.

3.5.3 The indicator shall be designed to operate as specified herein, at any ambient temperature from -40° to 71° centigrade (C).

3.6 Performance. The indicator shall be capable of meeting the tests specified in section 4.

7 Details of components.

3.7.1 The control unit shall be so designed as to be hand-held and capable of being operated by one individual.

3.7.2 Antenna(s) shall be provided to give continuous frequency coverage from 200-11000 megacycles, utilizing a single control unit.

3.7.3 Remote control cable. The cable utilized to connect the antenna to the control unit shall be flexible and 25 feet in length, with suitable attachments for joining additional lengths of cable. Appropriate data to correct for cable attenuation shall be provided. The cable shall be such that it will not cause indicating errors, other than that due to attenuation, when utilized.

3.7.4 Controls.

3.7.4.1 The control unit shall be provided with a control for obtaining the initial zero setting of the indicator and have a control for selecting the frequency band(s) desired. A switch shall be provided for removing electrical power to the control unit when not in use.

3.7.4.2 Electrical controls. The control(s) for obtaining the initial zero setting on the control unit indicator shall be located near the indicating dial to facilitate operation, and shall be constrained so that the setting cannot be accidentally disturbed.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:47Z
Check the source to verify that this is the current version before use.

3.7.5 Batteries. The unit shall operate on mercury batteries designated in MIL-B-18. The batteries shall be contained within the control unit. Operating life of the batteries shall be in excess of 50 hours.

3.7.6 Battery voltmeter. The control unit shall include a voltmeter for determining, without additional equipment, when the useful life of the batteries has been expended.

3.7.7 Control unit case. The control unit shall be furnished with a field case fitted with a removable top to provide protection to the unit while being carried. The case may be constructed of leather, plastic or any other suitable material. The case shall be so constructed that the controls shall be accessible and the antenna mounted when field case is installed on the control unit.

3.7.8 Carrying case. A carrying case shall be provided for the protection of the indicator while being stored or carried. The indicator case shall be furnished with a hinged top cover, made of the same material as the case. This case may be constructed of metal, plastic, or any other suitable material and shall be properly treated or finished to resist corrosion. The case shall be watertight against rain. A suitable handle(s) shall be provided for carrying the case.

3.7.9 Carrying strap. The control unit field case shall be equipped with a shoulder type carrying strap or other arrangement which will permit the control unit to be hung about the neck or shoulder. The carrying strap shall be adjustable, made of the same or similar material as the field carrying case, and shall be at least one half inch wide.

3.7.10 Antenna(s). The antenna(s) shall be constructed as to be attached to the control unit with a minimum of effort. Each antenna shall be calibrated for use with the particular unit with which it is supplied.

3.8 Interchangeability. Parts having identical manufacturer's part numbers shall be completely interchangeable with respect to installation and performance. Manufacturer's part number changes shall be governed by the drawing number requirements of MIL-D-1000.

3.9 Scale ranges. A direct reading, red-green decibel scale indicating the presence of radiated energy above or below the presently accepted safe level at 10 mw per sq cm, as well as the intensity of the energy with respect to that level shall be provided.

3.10 Calibration. The unit shall be capable of being calibrated with equipment currently within the inventory of the USAF.

3.11 Dimensions.

3.11.1 Carrying case. The complete carrying case shall not have dimensions greater than 13 inches (in.) X 18 in. X 6 in.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:47Z
Check the source to verify that this is the current version before use.

3.11.2 Field case. The field case with control unit installed, less antenna shall not have dimensions greater than 3 in. X 4 in. X 8 in.

3.12 Weight. The overall weight of the carrying case and indicator shall not exceed 20 pounds. The weight of the control unit, field case and installed antenna shall not exceed 5 pounds.

3.13 Threads. Unless otherwise specified, the threads of all machine screws 0.060 inch or larger, in diameter, shall conform to MIL-S-7742.

3.14 Marking.

3.14.1 All markings shall be durable to withstand the usage encountered in service. Numerals and letters shall distinctly indicate the graduation to which each applies.

3.14.2 Visibility of dial. The pointer, numerals, at least 1/16 inch of the shortest graduations, and other specified markings on the dial shall be visible from any point within the frustum of a cone whose side makes an angle of 30 degrees with a perpendicular to the dial and whose small diameter is the aperture of the dial.

3.14.3 Operating instructions. A brief operating instruction shall be permanently and legibly mounted on the control unit case for ready reference.

4.4 Identification of product. Equipment, assemblies, and parts shall be marked for identification in accordance with MIL-STD-130.

3.15 Workmanship.

3.15.1 General. The indicator, including all parts and accessories, shall be fabricated and finished in a thoroughly workmanlike manner. Particular attention shall be given to freedom from blemishes, defects, burrs and sharp edges; accuracy of dimensions, radii of fillets, and marking of parts and assemblies; thoroughness of soldering, painting, and wiring; alignment of parts and tightness of assembly screws and bolts; et cetera.

3.15.2 Cleaning. The indicator shall be thoroughly cleaned, and loose, spattered, or excess solder, metal chips, and other foreign material removed during and after final assembly.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:47Z
Check the source to verify that this is the current version before use.

4.2 Classification of tests. The inspection and testing of indicators shall be classified as follows:

4.2.1 Preproduction tests. Preproduction tests are those tests performed on samples submitted for preproduction approval.

4.2.2 Acceptance tests. Acceptance tests are those tests accomplished on indicators submitted for acceptance under contract.

4.3 Test conditions.

4.3.1 Standard atmospheric conditions. Whenever the pressure and temperature at the time of test are not specified definitely, it is understood that the test is to be made at atmospheric pressure (approximately 29.92 inches of mercury) and at room temperature (approximately 25°C). When tests are made with atmospheric pressure or room temperature differing materially from the above values, proper allowance shall be made for the difference from the specified condition.

4.3.2 Tapping. Unless otherwise specified, the indicator shall be gently tapped or vibrated before a test reading is taken.

4.3.3 Attitude. Unless otherwise specified, the indicator shall be tested in normal operating position.

4.3.4 Vibration. A vibration stand shall be used which will vibrate at any desired frequency between 500 and 5000 cycles per minute (cpm) and shall subject the indicator to vibration such that a point on the case will describe in a plane inclined 45 degrees to the horizontal plane, a circle, the diameter of which is equal to the amplitutde specified herein.

4.4 Preproduction tests.

4.4.1 Preproduction test sample. Preproduction test samples shall consist of indicators representative of the production item. The samples shall be identified with the manufacturer's part number and such other information as required by the procuring activity.

4.4.2 Tests. Preproduction test shall consist of the acceptance tests, sampling tests, and the following tests:

4.4.2.1 At the conclusion of each of the following tests, the indicator shall be subjected to and shall meet the requirements specified in 4.5.2.3.

4.4.2.2 Low temperature. The indicator shall be subjected to a temperature of -54°C for a period of 24 hours. The temperature shall then be raised to -40°C for a period of 24 hours. During the low temperature test, the indicator batteries may be remotely located to maintain such items in a warm environment. Only the indicator unit need be maintained in the climatic test cell. While still at this temperature, the indicator shall be tested for compliance with 4.5.2.3.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:47Z
Check the source to verify that this is the current version before use.

4.4.2.3 High temperature exposure. The high temperature exposure shall be conducted in accordance with Method 501, Procedure I of MIL-STD-810. While still at this temperature, the indicator shall meet the requirements specified for scale error in 4.5.2.3. There shall be no damage which would adversely affect subsequent operation.

4.4.2.4 Endurance. The indicator, equipped with mercury batteries, shall be operated for 50 hours at a scale reading of 15 mw per sq cm. The indicator shall be serviceable and accurate within the limits specified for scale error at the end of the 50 hour period with and without 25 foot remote control cable. The indicator shall not require replacement parts or batteries during this 50 hour period. Intermittent operation is authorized. The period of nonoperation shall not exceed one hour at any single inactive cycle.

4.4.2.5 Rain. The indicator carrying case shall be tested in accordance with Method 506, Procedure I, MIL-STD-810. After the test, the indicator carrying case shall be examined to ascertain that no water has entered the unit.

4.4.2.6 Vibration failure. The indicator shall be subjected to vibration with an amplitude between .018 and .020 inch for a 3-hour period. The frequency shall be varied uniformly from 500 to 3000 cpm and returned once each minute during this test. There shall be no looseness on the mechanism or no damage to any part of the indicator as a result of the vibration. The indicator shall be securely mounted on a vibration table during this test.

4.2.7 Humidity. The indicator shall be mounted in its normal operating position in a chamber. The test shall be performed in accordance with Method 507, Procedure I, of MIL-STD-810. There shall be no evidence of corrosion or discoloration of materials at completion of test.

4.4.2.8 Fungus. The indicator, including applicable accessories, shall be subjected to the action of fungi in accordance with Method 508, Procedure I of MIL-STD-810. After the test, the indicator shall be examined to ascertain that no fungus growth has occurred. There shall be no evidence of corrosion or discoloration of materials.

4.4.2.9 Salt. The indicator shall be subjected to salt spray in accordance with Method 509, Procedure I specified in MIL-STD-810. Any evidence of corrosion or discoloration of any part shall constitute failure of the indicator to pass this test.

4.4.2.10 Acoustical noise. The indicator shall be subjected to acoustical noise in accordance with Method 515, Procedure I of MIL-STD-810. Upon completion of this test, the equipment shall conform to the requirements of 4.5.2.3.

4.5. Acceptance tests.

4.5.1 Unless otherwise specified, contractor's records of all inspection work and tests, giving the results of tests required to determine compliance with the requirements and tests specified herein, shall be kept complete and shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:47Z
Check the source to verify that this is the current version before use.

be available to the Government representative at all times. The record of report of inspection and tests shall be signed or approved by a responsible person specifically assigned by the contractor. Contractors not having laboratory testing facilities satisfactory to the Government shall engage the services of a commercial testing laboratory capable of conducting tests to determine compliance with all the requirements and tests in the specification, and acceptable to the Government.

4.5.2 Individual tests. Each indicator shall be subjected to the following tests:

4.5.2.1 Examination of product. Each indicator shall be inspected to determine compliance with the requirements specified herein with respect to materials, workmanship, and marking.

4.5.2.2 Stability. The indicator shall be operated without radio frequency energy input for 15 minutes, and "balanced" by means of the proper controls. On each range of frequencies, the indicator shall be operated with a radio frequency energy input of 15 mw per sq cm for 3 consecutive periods of 5 minutes each, while being quickly and accurately "rebalanced" on zero energy input before each 5-minute period. The variation in reading shall not deviate more than 0.5 db. For purpose of this test, radio frequency energy may be directly coupled into the indicator rather than operating the indicator in an RF field.

4.5.2.3 Scale error. The indicator shall be tested over the entire frequency range of the equipment in 100 megacycle increments between the lowest usable frequency and 1000 megacycles, and 500 megacycle increments to the maximum usable frequency. The error in indicator reading shall not exceed ± 1 db at 10 mw per sq cm over the range of the equipment. Finally, at the discretion of the Government inspector, he may require the contractor to demonstrate the satisfactory operation of any indicator at any frequency(s).

4.5.3 Sampling tests. Five indicators which have been manufactured under essentially the same conditions shall be selected at random from each lot of 500 or fraction thereof and subjected to the following tests:

4.5.3.1 When sampling tests are specified on a number of indicators that are selected as representative of the lot, and one or more fails to meet the specified tests, acceptance of all indicators in the lot, will be withheld until the extent and cause of failure is determined. For operational reasons, individual tests may be continued pending investigation of a sampling test failure, but final acceptance of the entire lot is contingent upon the inspector's decision regarding the overall conformance of the lot with specification requirements. When corrective action has been accomplished, all necessary tests shall be repeated. If investigation indicates that the defects may exist on lots previously accepted, full particulars concerning the defects found, including recommendations for correction, shall be furnished to the contracting officer.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:47Z
Check the source to verify that this is the current version before use.

4.5.3.2 Vibration error. The indicator shall be securely mounted on the vibration stand so that it is in normal operating position. The indicator shall be operated on its own battery and shall be subjected to vibration with an amplitude between .003 and .005 inch at frequencies of from 500 to 3000 cpm.

4.5.3.2.1 Pointer vibration. The maximum amplitude of the pointer vibration and the pointer variation shall not exceed 1/16 inch.

4.5.3.2.2 Accuracy. The reading shall not differ at any time by more than 5 percent from the reading obtained when the indicator is at rest.

4.6 All parts, specimens, or assemblies, destroyed in making tests required by this specification or drawings, shall be in addition to the quantity specified in the contract or purchase order and shall be furnished without increasing the cost of the contract or order.

4.7 Inspection of the preservation, packaging and marking for shipment and storage. Sample items or packs and the inspection of the preservation, packaging, packing and marking for shipment and storage shall be in accordance with the requirements of section 5, or the documents specified therein.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be Level A or C, as specified (see 6.2).

5.1.1 Level A. The complete indicator, safety level, RF, with field case within the carrying case, shall be individually preserved and packaged in accordance with MIL-P-116, Method II-B, in a unit container conforming to PPP-B-636.

5.1.2 Level C. The complete indicator, safety level, RF, with field case within the carrying case, shall be individually preserved and packaged in accordance with the supplier's standard practice.

5.2 Packing. Packing shall be Level A, B or C, as specified (see 6.2)

5.2.1 Level A. Exterior unit containers for indicators preserved and packaged as specified in 5.1.1 shall be weather resistant conforming to PPP-B-636 when used as individual shipping containers. Quantities of 4 each or over shall be packed in an overseas type container, conforming to PPP-B-601 with plywood conforming to NN-P-530 C-D exterior type or equal. Where practicable, exterior shipping containers shall be of uniform shape and size, and of minimum cube and tare. The gross weight of each shipping container shall not exceed the weight limitations of the specification. Closure and strapping shall be in accordance with the appendix of PPP-B-636 or PPP-B-601, as applicable. Waterproofing shall be in accordance with MIL-STD-1186.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:47Z
Check the source to verify that this is the current version before use.

5.2.2 Level B. Indicators preserved and packaged as specified in 5.1.1 shall not be overboxed for domestic shipments. Quantities of 4 each or more shall be palletized in accordance with MIL-STD-147. For quantities of 3 each or less, the unit container shall be the shipping container. Closure and strapping shall be in accordance with the appendix of the applicable container specification.

5.2.3 Level C. Packages that require overpacking for acceptance by the carrier shall be placed in exterior type shipping containers in a manner that will insure safe transportation at lowest rate to the point of delivery. Containers shall comply with Uniform Freight Classification Rules or regulations of other carriers as applicable to the mode of transportation.

5.3 Physical protection. Cushioning, blocking, bracing and bolting, shall be in accordance with MIL-STD-1186, except that for domestic shipments, waterproofing requirements for cushioning materials and containers shall be waived. Drop tests of MIL-STD-1186 shall be waived when preservation, packaging and packing of the item is for immediate use or when drop tests of MIL-P-116 are applicable.

5.4 Marking. Interior and exterior containers shall be marked in accordance with MIL-STD-129. The nomenclature shall be as follows:

Indicator, Radio Frequency Energy
Specification MIL-I-83751(USAF)
Name of Manufacturer
Manufacturer's Part Number
Name of Contractor (if different from Manufacturer)
Contract or Order No.

6. NOTES

6.1 Intended use. The radio frequency safety level indicator covered by this specification is intended for detecting and measuring the amounts of UHF, VHF and microwave energy radiating from high power transmitters and related equipment.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.

b. Location and conditions for preproduction testing.

c. Applicable levels of preservation, packaging, and packing.

Custodian:
Air Force - 82

Reviewer:
Air Force - 82

Preparing Activity:
Air Force - 82

Proj No. 6665-F001

*U.S. GOVERNMENT PRINTING OFFICE 1967-251-518/5147



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:47Z
Check the source to verify that this is the current version before use.

| SPECIFICATION ANALYSIS SHEET | Form Approved Budget Bureau No. 119-R004 |
|---|---|

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use of the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

| ORGANIZATION | CITY AND STATE |
|---|---|

| CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $ |
|---|---|---|

MATERIAL PROCURED UNDER A
☐ Direct Government Contract ☐ Subcontract

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?
   ☐ YES ☐ NO IF "YES" IN WHAT WAY?

4. REMARKS (Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)

| SUBMITTED BY (Printed or typed name and activity) | DATE |
|---|---|

DD Form 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:47Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:47Z
Check the source to verify that this is the current version before use.