INCH-POUND

MIL-T-83965B USAF
26 Nov 90
SUPERSEDING
MIL-T-83965A USAF
22 SEPTEMBER 1982

MILITARY SPECIFICATION

TRUCK, FIRE-RESCUE, A/S32P-10 FORCIBLE ENTRY

This specification is approved for use within the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a diesel engine-driven, four-wheel drive, forcible entry rescue truck with a minimum gross vehicle weight of 11,000 pounds. This vehicle is assembled from standard commercial components and may be supplied complete with standard commercial tools and equipment.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

GGG-H-86	Hammer, Hand (Forged Steel Head)
GGG-S-121	Screwdriver and Screw Starter, Hand
W-B-131	Battery, Storage (Vehicular, Ignition, Lighting and Starting)
GGG-S-291	Shears, Metal Cutting, Bench and Hand
L-S-300	Sheeting and Tape, Reflective, Nonexposed Lens
GGG-C-313	Chisels, Hand: Cape, Diamond Point, Cold Round Nose, and Side Cutting
GGG-S-326	Shovels, Scoops, Spades, Snow Pushers, and Telegraph Spoons
QQ-P-416	Plating, Cadmium (Electrodeposited)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: WR-ALC/MMDETB, Robins AFB,GA 31098-5609, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 4210

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:48Z
Check the source to verify that this is the current version before use.

GGG-P-471	Pliers; Pliers, Slip Joint
GG-G-531	Goggles, Industrial and Spectacles, Industrial, Plastic
GGG-W-00651	Wrenches: Pipe Wrench and Basin Wrench
GGG-A-926	Ax (Single Bit, Double Bit, Pick Head, and Matlock Head)
VV-F-800	Fuel Oil, Diesel
KKK-A-1822	Ambulance, Emergency Medical Care Surface Vehicle

MILITARY

MIL-P-514	Plates, Identification, Instruction and Marking, Blank
MIL-T-5624	Turbine Fuel, Aviation, Grades JP-4 and JP-5
MIL-A-8625	Anodic Coatings for Aluminum and Aluminum Alloys
MIL-P-23377	Primer, Coating, Epoxy-Polyamide, Chemical and Solvent Resistant
MIL-P-26915	Primer Coating, Zinc Dust Pigmented for Steel
MIL-C-46168	Coating, Aliphatic Polyurethane, Chemical Agent Resistant
MIL-T-83133	Turbine Fuel, Aviation, Kerosene Type, Grade JP-8
MIL-C-83286	Coating, Urethane Aliphatic Isocyanate, for Aerospace Applications
MIL-W-83420	Wire, Rope, Flexible, for Aircraft Control

STANDARDS

FEDERAL

FED-STD-595	Colors

MILITARY

MIL-STD-12	Abbreviations for Use on Drawings and on Specifications, Standards, and Technical Documents
MIL-STD-130	Identification Marking of US Military Property
MIL-STD-461	Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference
MIL-STD-462	Electromagnetic Interference Characteristics, Measurements of
MIL-STD-721	Definitions of Terms for Reliability and Maintainability
MIL-STD-781	Reliability Design Qualification and Production Acceptance Tests: Exponential Distribution
MIL-STD-808	Finishes, Materials, and Processes for Corrosion Prevention and Control in Support Equipment
MIL-STD-810	Environmental Test Methods and Engineering Guidelines
MIL-STD-889	Dissimilar Metals
MIL-STD-970	Standards and Specifications, Order of Precedence for the Selection of
MIL-STD-1223	Nontactical Wheeled Vehicle Treatment, Painting, Identification Marking, and Data Plate Standards
MIL-STD-1472	Human Engineering Design Criteria for Military Systems, Equipment and Facilities
MIL-STD-1568	Materials and Processes for Corrosion Prevention and Control in Aerospace Weapons Systems
MIL-STD-1587	Materials and Process Requirements for Air Force Weapon Systems
MIL-STD-1595	Qualification of Aircraft, Missile, and Aerospace Fusion Welders
MIL-STD-1791	Designing for Internal Aerial Delivery in Fixed Wing Aircraft
MS51335	Pintle Assembly, Towing, 18,000 Pound Capacity, Manual Release

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Ave, Philadelphia, PA 19111-5094.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:48Z
Check the source to verify that this is the current version before use.

AIR FORCE DRAWINGS

8838302

2.1.2 Other Government documents. The following other Government documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date specified in the solicitation.

LAWS AND REGULATIONS

49CFR393	Federal Motor Carrier Safety Regulations (FMCSR)
49CFR571	Federal Motor Vehicle Safety Standards (FMVSS)

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, US Printing Office, Washington DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal Agency responsible for issuance thereof.)

2.2. Non-Government publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation (see 6.2).

AMERICAN NATIONAL STANDARDS INSTITUTE

ANSI/UL 498-81	Attachment Plugs and Receptacles

(Application for copies should be addressed to the American National Standards Institute, 1430 Broadway, New York, NY 10018.)

EUROPEAN TYRE AND RIM TECHNICAL ORGANIZATION

Standards

(Application for copies should be addressed to the European Tyre and Rim Technical Organization, 32 Avenue, Brugmann-B, 1060 Brussels, Belgium.)

NATIONAL FIRE PROTECTION ASSOCIATION

NFPA 1931	Design and Design Verification Tests for Fire Department Ground Ladders
NFPA 1983	Fire Service Life Safety Rope, Harnesses, and Hardware

(Application for copies should be addressed to the National Fire Protection Association, Batterymarch Park, Quincy, MA 02269.)

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

J336a	Sound Level for Truck Cab Interior
J366b	Exterior Sound Level for Heavy Trucks and Buses
J534	Lubrication Fitting
J994	Alarm-Backup-Electric-Performance, Test and Application
J1349	Engine Power Test Code, Spark Ignition and Diesel

(Application for copies should be addressed to Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:48Z
Check the source to verify that this is the current version before use.

TIRE AND RIM ASSOCIATION

Year book

(Application for copies should be addressed to Tire and Rim Association, Incorporated, 3200 West Market Street, Akron, OH 44313.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets, or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.2, 4.4 and 6.4).

3.1.1 Selection of specifications and standards. Specifications and standards, necessary commodities, and services not specified herein shall be selected in accordance with MIL-STD-970.

3.1.2 Materials. Materials shall be as specified herein. Selection of materials and processes shall be in accordance with MIL-STD-1568 and MIL-STD-1587. Materials not specifically covered by this specification or referenced document shall be suitable for the intended environment and application. The contractor shall not use nonstandard or proprietary materials and processes without government approval. The use of wood and/or wood products is prohibited, unless otherwise specified. Similarly, vinyl, polyvinylchloride, polyester, and corrosive type RTV (yields acetic acid upon curing) are prohibited for use in all forms, interior and exterior.

3.1.2.1 Protective treatment. Materials that are subject to deterioration shall be protected in such a manner that shall in no way prevent compliance with the performance requirements of this specification. Protective coatings that will chip, crack, or scale with age or extremes of climatic conditions shall not be used.

3.1.2.2 Dissimilar metals. Unless protected against electrolytic corrosion, dissimilar metals shall not be used in intimate contact with each other. Dissimilar metals are defined in MIL-STD-889.

3.1.3 Design and construction. The vehicle shall be constructed so that parts do not work loose in service and shall withstand the loads, shocks, vibrations, and other conditions incident to operation, shipping, and storage with minimum loss of time for maintenance, repair, and servicing. The design of the vehicle shall ensure safe, efficient, and economical operation. All assemblies, controls, and installed equipment shall be located so that there is no adverse interference with each other, or with the operation, and shall be readily accessible for maintenance, operation, and replacement. Complete drainage shall be provided for both internal and exterior pockets, areas, parts and components.

3.1.3.1 Reliability. The vehicle, including all components, shall have a Mean-Time-Between-Failure (MTBF) of not less than 100 hours, demonstrated in accordance with Test Plan XVIIC of MIL-STD-781. A failure is defined as the event or inoperable state in which any item or part of an item does not, or would not, perform as previously specified. Definitions of reliability terms not included herein shall be as found in MIL-STD-721 and MIL-STD-781. In the event of a conflict between these documents, MIL-STD-781 shall take precedence. The vehicle shall be designed for a life expectancy of at least ten years.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:48Z
Check the source to verify that this is the current version before use.

3.1.3.2 Maintainability. The vehicle shall be designed and constructed to provide the following:

a. A minimum number of parts consistent with the performance required herein.

b. A minimum amount of time for assembling, disassembling, locating trouble sources, and maintaining the vehicle. Where practical, components shall be located for rapid inspection and recognition of potential failure.

c. Ease of adjusting, servicing and replacing parts and components.

d. Use of readily available standard tools and equipment for maintenance.

e. Maintenance with a minimum number of tools.

f. Mean corrective maintenance downtime of no greater than one hour.

g. Maximum corrective maintenance downtime of no greater than four hours.

h. Maximum total downtime to perform all daily scheduled maintenance and servicing tasks of no greater than 35 minutes.

3.1.3.2.1 Maintenance tasks. The vehicle shall be designed so that one mechanic, using common hand tools, can perform the following maintenance operations within the time specified:

a. Remove, replace, and adjust all engine driven belts – one hour.

b. Remove and replace alternator – one hour.

c. Remove and replace engine coolant system hose – 1/2-hour.

d. Drain engine lubricating oil, remove, and replace oil filter element(s) and refill crankcase – one hour.

e. Remove and replace fuel filter element(s) – 1/2-hour.

f. Disconnect battery cables, remove and replace batteries and reconnect battery cables – 1/2-hour.

g. Drain torque converter oil and transmission oil, remove and replace all filter elements and strainers, and refill converter and transmission – one hour.

h. Remove and replace starter – one hour.

3.1.3.3 Foolproofness. Where improper installation of an item could cause a malfunction, an asymmetric mounting system shall be provided, where practical, to ensure proper mounting of the item.

3.1.3.4 Fastening devices. All screws, bolts, nuts, pins, and other fastening devices shall be properly designed, manufactured, and installed with adequate means of preventing loss of torque or adjustment. All fasteners shall follow the quality assurance requirements in Air Force Drawing 8838302. Cotter pins, lock washers, or nylon patches shall not be used for this purpose, except for attachment of trim items or as provided in commercial (see 6.3.5) components. Tapped aluminum threads shall have a minimum thread engagement of at least two times the nominal fastener diameter. Ferrous alloy fasteners shall be cadmium plated per QQ-P-416 Type II, to a minimum thickness of 0.0003 inches, unless threaded tolerances dictate a different thickness and aluminum alloy fasteners shall be anodized per MIL-A-8625.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:48Z
Check the source to verify that this is the current version before use.

3.1.3.5 Servicing provisions. Drains, grease fittings, lines, and check points for all components shall be so located that they are readily accessible and do not require special tools for proper servicing.

3.1.3.6 Lubrication. All parts normally requiring grease for lubrication shall be provided with lubrication fittings in accordance with SAE J534. Where the use of high lubrication pressures may damage grease seals, a pressure relief device shall be provided. Extended fittings shall be provided to lubricate parts or assemblies which are not readily accessible for direct lubrication or which are likely to be overlooked because of inaccessibility.

3.1.3.7 Component protection. All space in which work is performed during operation, service, and maintenance of the vehicle shall be free of hazardous protrusions, sharp edges, or other features which may cause injury to personnel. All rotating and reciprocating parts and all parts subject to high operational temperatures or subject to being electrically energized, that are of such nature or so located as to be hazardous to personnel, shall be guarded or insulated to the extent necessary to eliminate the hazard.

3.1.3.8 Foreign object damage. All loose metal parts, such as pins and valve caps, shall be securely attached so they cannot become separated from the vehicle.

3.1.4 Environmental conditions. The vehicle shall be capable of satisfactory storage and operation under the following environmental conditions:

a. Full time exposure to temperatures ranging from -40°F to +125°F.

b. Full time exposure to relative humidities up to 100 percent.

c. Part-time (five percent of the time) exposure to rain; droplets of size 2.0 to 4.5 mm falling at a rate of 13 cm per hour.

d. Part-time (five percent of the time) exposure to salt fog, five percent solution (five parts by weight of salt in 95 parts by weight of water) with fallout of 3.0 ml/80/cm^2/hour.

e. Part-time (five percent of the time) exposure to blowing dust; velocity 1,750 ft/min, concentration 0.5 g/ft^3.

f. Part-time (five percent of the time) exposure to blowing sand; velocity 5,700 ft/min, concentration 0.0773 g/ft^3.

3.1.5 Weight distribution. The weight distribution of the vehicle in any loading condition shall not be unbalanced or improperly distributed. The difference in load between the left and right wheels of any axle shall not exceed five percent of the total load on the axle.

3.1.6 Vehicle lean. The vehicle shall not lean to either side more than one percent of the maximum width, in either the fully loaded or the unloaded condition. Vehicle lean measurements shall be made at the outermost portion of the vehicle (excluding mirrors, mirror support brackets, lights, or asymmetrical shapes) directly above each axle; the difference in body height at each axle shall not exceed one percent of the maximum width at that location.

3.1.7 Electromagnetic interference. The vehicle shall comply with the requirements of MIL-STD-461, Class C1, Group II for electromagnetic interference (emission and susceptibility), except that the limits for UM03 (Figure 8-1) shall be relaxed by 20dB.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:48Z
Check the source to verify that this is the currentversion before use.

3.1.8 Sound levels.

3.1.8.1 Exterior sound level. The maximum sound level produced by the vehicle shall not exceed 83dBA when measured in accordance with SAE J366b. An additional 2dBA allowance shall be permitted for production units to provide for variation in test site, temperature gradients, test equipment, and inherent differences in nominally identical vehicles.

3.1.8.2 Cab interior sound level. The maximum sound level in the cab interior shall not exceed the SAE recommended design criteria for new vehicles when measured in accordance with SAE J336a.

3.1.9 Air transportability. The vehicle shall be air transportable in accordance with MIL-STD-1791 in types C-130, C-141, and C-5 Aircraft and shall be air transportable in Type C-17 Aircraft. Preliminary design guidelines for the Type C-17 are 142 inches maximum height, 204 inches maximum width, 812 inches maximum length, 9° ramp angle, and floor load capacity equal to that allowed for the Type C-5 Aircraft.

3.1.9.1 Tiedowns. The vehicle shall be equipped with sufficient tiedown points so located that it can be restrained in all directions during air transport. The attachment points shall be designed for use with attachment in the aircraft as described in MIL-STD-1791. Sufficient clearance shall be maintained around all attachment points to allow for restraining chains without interference from any other structure. The tiedown points shall have a minimum clear opening of three inches to allow attachment of a chain with a grabhook.

3.2 Performance.

3.2.1 Mobility. The fully loaded and equipped vehicle shall:

a. Maintain a speed of 70 miles per hour (MPH) on a level paved road.

b. Accelerate from a stop to a speed of 65 MPH within 30 seconds on a level paved road.

c. Ascend and descend a 30 percent grade without spillage of any fluid. The fully loaded vehicle shall be capable of ascending an eight percent grade on a hard dry surface at a constant speed of 60 miles per hour.

d. Negotiate a 20 percent side slope in each direction.

e. Negotiate, in each direction, a ramp with a 30.6° minimum slope connecting two horizontal surfaces. The ramp length shall be at least 1.2 times the wheelbase of the vehicle. The vehicle shall be driven forward or backward from one horizontal surface across the ramp crest, ascend or descend the ramp, cross the ramp crest and proceed on the other horizontal surface without any portion of the vehicle, other than its tires, contacting any of the three surfaces.

f. Traverse graded gravel roads at a speed of 30 MPH.

g. Traverse Belgian Block at a speed of 20 MPH.

h. Traverse cross country terrain at a speed of 20 MPH.

i. Comply with applicable requirements of 49CFR571.105 for stopping distances of service brakes.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:48Z
Check the source to verify that this is the currentversion before use.

j. Parking brakes shall hold the vehicle in any load condition in either direction on a hard smooth surface with a slope of 20 percent, with the transmission in the neutral position.

k. Negotiate six inch high blocks with diagonally opposite wheels of the vehicle.

l. Traverse, in one pass at low speed, terrain consisting of unflooded fine grained dry to moist soils having a minimum cone index rating in the critical layer of no greater than 40.

m. Maneuver and negotiate sharp turns and curves at an average speed of 35 MPH without adverse handling or roadability characteristics.

3.3 Chassis.

3.3.1 Powertrain.

3.3.1.1 Engine. The vehicle shall be equipped with a commercial (see 6.3.5) liquid cooled diesel engine of not less than six cylinders. The total power output required by all items driven by the engine shall not exceed its net power output rating at 2,000 feet elevation, determined in accordance with SAE J1349. The engine shall demonstrate the performance characteristics specified herein when using diesel fuel in accordance with W-F-800 and shall operate satisfactorily on Grades JP-4 and JP-5 turbine fuel in accordance with MIL-T-5624 and Grade JP-8 in accordance with MIL-T-83133. Any engine that is adversely affected by any of the above fuels is not acceptable.

3.3.1.1.1 Engine cooling system. The manufacturer's highest capacity cooling system shall be provided.

3.3.1.1.2 Engine starting system. The engine shall start within 15 seconds in any ambient temperature within the required operating range of the vehicle. Installed glow plugs, fluid starting aids and heat from the winterization system (see 3.8) may be used prior to and during the start period to facilitate engine starting under the following conditions:

TEMPERATURE RANGE (DEGREES F)	STARTING AID PERMITTED
40 through 125	None
1 through 39	Glow plugs and fluid starting aids
-40 through 0	Glow plugs, fluid starting aids, and heat from the winterization system

The starting system shall be equipped with an interlock device to prevent starter engagement when the transmission is in any position other than neutral or park.

3.3.1.1.3 Exhaust system. The exhaust system shall be designed to expel exhaust gases in a manner that is not hazardous to operators or mechanics; the outlet shall not be directed toward the ground. The exhaust system, including all fasteners, shall be constructed of corrosion resistant materials. The system shall be protected from damage which could result from traversing rough terrain. The exhaust system shall be provided with a spark arrestor.

3.3.1.2 Transmission. A commercial (see 6.3.5) automatic transmission shall be provided, complete with a hydraulic torque converter. The normal drive range selector position shall provide not less than four gear ratios without selector movement. The transmission shall have a torque capacity of at least 105 percent of the maximum net engine torque. The transmission shall be complete with an automatic transmission cooler adequate for the vehicle's intended use.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:48Z
Check the source to verify that this is the currentversion before use.

3.3.1.2.1 Transfer case. The truck shall be equipped with a two speed transfer case.

3.3.1.3 Axles. The load rating of each axle shall be not less than the imposed load on the axle, measured at the ground, with the vehicle at gross weight.

3.3.1.4 Drive hubs. Unless a full time four wheel drive system with an interaxle compensating device is provided, the vehicle shall be equipped with automatic drive hubs for disengaging the front wheels from the powertrain.

3.3.2 Steering system. The vehicle shall be equipped with an adjustable tilt-type steering wheel and power assisted steering. In the event of power steering failure, manual steering shall be available.

3.3.3 Brakes.

3.3.3.1 Service brakes. The vehicle shall be equipped with power-assisted brakes. Front brakes shall be of the disc type.

3.3.4 Frame. The truck frame shall be the chassis manufacturer's standard or optional assembly for this type vehicle adequate for the performance requirements specified herein. The contractor shall not weld to the frame assembly or add any holes to the frame rail flanges.

3.3.4.1 Bumpers. Bumpers shall be provided at the front and rear of the vehicle. The rear bumper shall be of the step type, recessed and reinforced for mounting a pintle hook in accordance with MS 51335. The pintle hook shall be furnished and mounted on the vehicle.

3.3.4.2 Towing devices. Not less than two hooks, loops or pins for towing the vehicle shall be mounted at the front and rear of the vehicle.

3.3.4.3 Brush guard. A structural brush guard shall be securely mounted to the front of the vehicle to provide adequate protection against brush and other debris encountered during off road use. The brush guard shall protect, but not limit or obstruct the operation of the winch, headlights and warning lights. The outer corners of the brush guard shall be rounded and shall incorporate other protection as required to minimize the hazard to personnel walking around the front of the vehicle.

3.3.4.4 Winch. A 12 volt, 11,000 pound electric winch assembly shall be mounted at the front of the vehicle. The winch shall be provided with 150 feet of 5/16-inch diameter, 7 X 19 aircraft cable, Type-I, Composition B, in accordance with MIL-W-83420. Winch line pull rating on drum shall not be less than 11,000 pounds. The winch shall have forward and reverse drum drive and a drum clutch to permit free spooling of the cable. The winch shall be equipped with a four way roller guide, weatherproof cover, snatch block assembly and choker chain. A clevis hook shall be installed at the end of the cable for quick attachment or removal of the snatch block assembly.

3.3.5 Suspension system. The truck shall be equipped with the chassis manufacturer's standard or optional suspension adequate for the performance requirements specified herein.

3.3.6 Wheels,tires,and splashguards. The vehicle shall be equipped with wheels and tires which meet all Tire and Rim Association or European Tyre and Rim Technical Organization requirements for this application. Tubeless steel belted radial ply tires with all terrain type tread shall be provided. Rubber splashguards shall be designed to prevent mud, stones, debris, and water from being thrown against areas outside of the wheel-wells.

3.3.6.1 Spare wheel. If specified (see 6.2), a spare wheel shall be furnished. The spare wheel shall be identical to the wheels mounted on the truck.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T04:48Z
Check the source to verify that this is the currentversion before use.

3.3.6.2 Spare wheel and tire assembly. If specified (see 6.2), a spare wheel and tire assembly, inflated to the chassis manufacturer's recommended pressure, shall be furnished. The spare wheel and tire assembly shall be identical to the wheels mounted on the truck.

3.3.6.3 Tire tools. Unless otherwise specified (see 6.2), the vehicle shall be equipped with at least a jack, a jack handle, and a wheel lug-nut wrench for replacement of the mounted tire and wheel assembly with a spare assembly. The jack, at its closed height, shall fit under the chassis manufacturer's approved lift points, and shall be capable, without blocking, of raising any wheel of the loaded vehicle to a height sufficient to allow removal and replacement of the wheel and tire assembly.

3.4 Cab. A four-door full width crew cab shall be furnished. A bucket-type seat shall be provided for the driver and a Self-Contained Breathing Apparatus (SCBA) seat with DOT approved frame with walkaway bracket shall be provided for both the right front and right rear seats. The curbside front and rear SCBA seats shall be fully padded spring seats of the high-back type with headrest. SCBA seats shall be upholstered in heavy gauge vinyl and shall be designed to fit all commercial styles of SCBA's, recessed into the seat back. The seats shall rotate horizontally 90° towards the cab doors to allow for emergency entrance and exits. A hand operated locking device, operable by a fire fighter wearing arctic mittens, shall be provided to securely lock each rotating seat. Seat belts with retractors shall be provided at all seating positions. All seating positions shall allow for easy, unrestricted entering and exiting of the cab. An interior dome light and map light, designed and located for use by personnel in any seating position, shall be provided. A space at least 18 inches long by 12 inches wide by 12 inches high, shall be provided for mounting a radio for base operations. The space furnished shall be conveniently located to both the driver and front crew member. The cab shall have a minimum of five coat hooks located in the rear of the cab for storing protective clothing and helmets. Full length running boards on each side of the cab shall be provided to allow for easy entrance and exit for each crew member. Running boards shall be constructed of 0.080 minimum aluminum with a treadplate or deep ribbed, skid resistant surface. The running boards shall be adequately supported and shall be free from sharp edges with rounded shoulders. The running boards shall support a minimum of 250 pounds.

3.4.1 Book cabinet. A cabinet shall be provided behind the front seat on the left side of the cab for securely storing a minimum of 10 books which are 14 inches high, 12 inches deep, and three inches thick. The cabinet shall provide for convenient access for a person seated in the rear jump seat. Quick release type holders for three each Self-Contained Breathing Apparatus shall be mounted on the left hand side of the cabinet.

3.4.2 Doors. Each door shall be furnished with a door restraint. The restraint shall prevent the door from opening past the 90° mark measured from the closed position. The doors in the open position shall not interfere with an armrest.

3.4.3 Accessories. The cab shall be equipped with all accessories furnished as standard equipment by the chassis manufacturer. The following minimum equipment shall be furnished:

a. Tachometer.

b. Engine oil pressure gauge.

c. Engine water temperature gauge.

d. Ammeter or voltmeter.

e. Dual sun visors.

f. Fuel level gauge.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:48Z
Check the source to verify that this is the currentversion before use.

3.4.4 Air conditioning. The vehicle shall be equipped with the chassis manufacturer's standard or optional air conditioning system.

3.4.5 Windshield and windows. The vehicle shall have a tinted windshield and tinted glass.

3.4.6 Rearview mirrors. Outside rearview mirrors shall be mounted on each side of the cab. The mirrors shall be of the west coast type, having separate flat and convex areas enclosed in a common housing. The flat portion of each mirror shall have not less than 100 square inches of reflective area. The mirrors shall be positioned so that the driver can clearly observe the roadway and vehicles approaching from the rear on either side.

3.5 Body.

3.5.1 Utility body. The vehicle shall be equipped with a utility body for storage of the equipment listed in 3.9. Body construction shall be all aluminum with a minimum thickness of 0.187 inches. The body shall have weather tight compartments with bottoms flush and level with or slightly above the bottoms of the doors. The body shall have three side compartments and two compartments at the rear of the vehicle. The body shall be equipped with wheelwell liners which provide sufficient clearance for installation of tire chains and a removable heavy ribbed aluminum rub rail along each side of the lower body. The entire body shall be equipped with an upper platform (see 3.5.2). A ladder in accordance with MIL-STD-1472 shall be installed on the right rear of the body to provide access to the work platform. Handrails shall be mounted as required to facilitate use of the rear step bumper and ladder. Welds shall have a minimum length of two inches.

3.5.1.1 Compartments. The upper rear compartment shall have a horizontally hinged door and shall be designed to accommodate the folding litter (3.9l) and ladders (see 3.9.2). The lower rear compartment and all side compartments shall have upward acting, counter balance, roll-up type aluminum doors that shall provide an opening substantially the full length of the compartment. Roll-up type doors shall have panel, side, bottom and inter-acting top weather proof seals, provided by the door manufacturer. The upper rear compartment shall have a horizontally hinged aluminum door of double panel construction. The hinged door shall have a full length piano type hinge with stainless steel pin and shall be attached with threaded fasteners. All doors shall be equipped with automatic devices to hold them in the open position, latches that are operable with one hand by a fire fighter wearing arctic mittens, and a handle for opening and closing the doors. All fasteners shall be recessed or flush with the compartment interior panels. The compartments listed shall have the following minimum opening dimensions:

COMPARTMENT	WIDTH (INCHES)	HEIGHT (INCHES)	DEPTH (INCHES)
a. Forward, side	26	46	81.5
b. Center, side	42	28	81.5
c. Rear, side	21	46	19.0
d. Lower rear	40	30	29.5

3.5.1.2 Compartment trays and shelving. A full-width roll out tray with ball bearing commercial (see 6.3.5) rollers shall be installed in the bottom of the front compartment and in the right and left center compartments, both designed for storage of heavy equipment. The trays shall be able to roll out without any disassembly of any component. The front compartment tray shall roll out to either side of the vehicle, and shall be designed to support 150 pounds at a 36-inch extension to either side. The roll out trays in the right and left center compartments shall be interchangeable and designed to support 100 pounds at an 18-inch extension. Roll-out trays shall be provided with an automatic locking device that secures the tray in the open and closed positions. A drain hole shall also be provided in each corner of the tray. A half shelf shall be installed in the top portion on both sides of the front compartment and in the lower rear compartment. The left rear and right rear compartments shall both contain two full width shelves. Shelf construction shall be all aluminum with rolled under edges and minimum shelf thickness of 0.187 inches. Shelves shall be adjustable at two inch increments and shall be designed to support a load of at least 100 pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:48Z
Check the source to verify that this is the current version before use.

3.5.2 Work platform. The entire body shall be equipped with an upper work platform; it shall have an upper surface of expanded aluminum tread plate capable of supporting five crew members weighing 175 pounds each with no noticeable deflection. The work platform shall be immediately above the compartment area.

3.6 Electrical system.

3.6.1 Alternator. The engine shall be equipped with an alternator of sufficient capacity to maintain all vehicle electrical components operating simultaneously. The system shall supply full power requirements for operation of the vehicle and all equipment and accessories at engine idle speed without system degradation. An engine high idle speed control, which automatically increases the engine speed and monitors the system's voltage, shall be provided. The device shall be preset so that when activated, it will operate the engine at the appropriate speed; maximum engine speed shall not exceed the engine manufacturer's recommended speed for this type application. The design shall allow for disengagement when the transmission is engaged or the parking brake released. Minimum capacity of the alternator system shall be 145 amperes.

3.6.2 Battery. Two 12 volt batteries, with a minimum rating of 550 cold cranking amperes, shall be furnished. The batteries shall comply with the maintenance free characteristics of W-B-131. A battery selector switch shall be installed, complete with battery isolator. The battery selector switch shall be easily accessible to the driver inside the cab. The battery selector switch shall comply with KKK-A-1822 paragraph 3.7.7. It shall be provided with an oil and fuel resistant housing with weatherproof "O ring" seals at critical areas. An independent feed terminal to guard against accidental battery rundown shall also be provided. The battery selector switch shall be provided with heavy gauge copper electrical contacts and 3/8 inch diameter copper stud terminals with brass hex nuts for attaching cables.

3.6.3 Communication equipment circuit. A dedicated 12 volt electrical circuit with an individual circuit breaker shall be provided with wiring to the space provided for radio installation (see 3.4). The circuit shall be rated at 15 amperes minimum and shall have adequate noise suppression devices to preclude interference from accessory components.

3.6.4 Back up alarm and lighting. An audible electric alarm shall be provided to caution personnel in the area when the vehicle is in reverse gear. The alarm shall be in accordance with SAE J994. Backup lamps shall be provided to adequately illuminate the area behind the vehicle during backing operations. Lamps shall operate only when the ignition switch is energized and reverse gear engaged. Backup lamps shall be rear mounted on each side of the vehicle in a protected location. The color of light from the lamps shall be white (achromatic).

3.6.5 Siren. An electric siren, with basic siren tones (wail, yelp, hi-lo), TAP II, PA, radio broadcast and built-in air horn sound with siren override shall be provided for operating the light bar speaker (see 3.7.4). The siren system shall include a built-in front microphone with siren override switch for PA use, illuminated non-glare control panel with gain control, fuse for protection against failure, and built-in radio interconnect wires. The siren shall have all necessary wiring and connections so that it is adaptable to two way radios which use either carbon or magnetic type microphones and so that it can be used for a public address system and for broadcasting incoming radio messages through the siren speaker. The electronic siren shall be solid-state, with integrated circuits and silicon output transistors. The siren shall have a 100 watt capacity.

3.7 Lighting.

3.7.1 Interior lighting. The cab and all compartments shall be provided with lighting adequate to enable personnel to readily obtain equipment and perform all functions necessary during night operation. Each compartment light shall illuminate the entire compartment area, above and below the shelving area. Sealed contact switches shall be provided to automatically illuminate the lights in the cab or a compartment when its door is opened.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:48Z
Check the source to verify that this is the current version before use.

3.7.2 Floodlights. Four each 500 watt telescopic quartz floodlights shall be installed, one on each corner of the utility body. Telescopic tubing shall be stainless steel or anodized aluminum. Floodlights shall be readily adjustable and shall lock securely in place. A locking twist type knob with finger grooves shall be provided for adjustment. Adjustment knobs shall be attached so they can not become separated from the vehicle. Telescoping capability shall be a minimum of two feet above the highest point of the truck with a 360° rotation capability. Floodlight vertical adjustment shall allow for movement of at least 35° above and 45° below the horizontal. Each floodlight shall be controlled by a lighted indicator switch located on the vehicle's instrument panel. Each switch shall be easily accessible to both the driver and crew member. A single plug-in receptacle, for each set of floodlights, shall be provided to allow for simultaneous operation of both floodlights. Each receptacle shall be provided with a protective cover and shall be located on the right side of the vehicle in a compartment. The receptacles shall be in a location where they do not interfere with the installation or removal of equipment.

3.7.3 Warning lights. Two red flashing lights shall be installed on the front and rear of the vehicle in a protected location. The warning lights shall be three inches in diameter minimum. Warning lights shall operate when the light bar specified in 3.7.4 is activated. When specified (see 6.2) the warning lights shall have a blue lens.

3.7.4 Light bar. A removable light bar, with dual directional (front and rear) reflecting mirrors and two sealed beam synchronized rotating lamps shall be provided. The lamps shall be of the Halogen type with a total minimum beam candlepower of 60,000. The light bar shall be securely attached to the structural rain gutters of the cab; no holes shall be permitted in the roof of the cab. The light bar shall be controlled by a lighted indicator switch located on an overhead panel provided with the light bar or on the vehicles instrument panel. The light bar shall be equipped with a speaker contained in a stainless steel housing.

3.7.5 Spotlight. A five inch minimum diameter, standard automotive, sealed beam spotlight, shall be installed centered on the top forward portion of the cab roof. The spotlight shall be adjustable from inside the cab and shall not interfere with normal driving operations or entering or exiting of the cab. The light shall be capable of 360° horizontal rotation and a vertical angle movement of at least 60° above and 35° below the horizontal. Spotlight rotation shall not interfere with clearance lights, light bar and speaker specified in 3.7.4. All moving parts of each rooflight assembly shall be lubricated and sealed.

3.7.6 Backup lighting. The vehicle shall be equipped with adequate rear lighting for backing of the vehicle. The lighting shall be activated when the vehicle is placed in reverse.

3.8 Winterization system. The vehicle shall be equipped with a winterization system to permit storage and operation in ambient temperatures as low as -40°F. Heaters shall operate on 110 volt alternating current (AC) and shall be wired through a junction block to a single three pronged (male) weatherproof slave receptacle for receiving external power and grounding the vehicle. A three wire connecting cable, 25 feet long and of adequate line capacity to supply power for all heater units simultaneously, shall be furnished. The connecting cable shall include a matching female connector at the vehicle end and a standard weatherproof three pronged (two power, plus one ground) male connector at the other end. Electrical apparatus shall conform to FMCSR 393.77(c)(7). Electrical insulation of connective cable shall withstand normal operating stresses in low ambient air temperature without cracking or loss of dielectric capacity. All heater lead wires shall be installed without interfering with vehicle component operation and without loose excess wire. Provisions for storage of the cable shall be provided in the vehicle cab. Heaters shall be furnished as follows:

a. A coolant heater, 1,500 watt minimum rating, shall be installed in the engine block or in the lower coolant inlet hose controlled by a thermostat with an operating range of 140°F to 160°F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:48Z
Check the source to verify that this is the current version before use.

b. Immersion type engine oil heater, 300 watt minimum rating, with 170°F to 195°F thermostat, shall be installed in the oil pan through any convenient opening. A dipstick-type heater is not acceptable.

c. A battery heater shall be provided having a capacity adequate to maintain battery electrolyte at a temperature of not less than 10°F during vehicle exposure in ambient air temperatures as low as -40°F and shall embody a thermostat to limit the temperature of the electrolyte to not more than 80°F.

d. A fuel warmer or preheater shall be provided to prevent clogging of fuel filters due to wax crystallization in the fuel. The fuel warmer shall use engine coolant to transfer sufficient heat to the diesel fuel to heat it from an inlet temperature of -40°F to an outlet temperature of 10°F, with a flow rate not less than the maximum fuel demand of the engine fuel system.

3.9 Auxiliary equipment. When specified (see 6.2), the following auxiliary equipment shall be furnished; each vehicle shall be furnished with a portable generator (see item i). The equipment shall be securely stowed with quick release clamps which are operable by a person wearing fireman's gloves. Attaching hardware shall be provided regardless of whether the auxiliary equipment is furnished or not.

a. One fireman axe, with pick point, steel head, in accordance with GGG-A-926, Type II, not less than six pounds, shall be stored on the inside of the left rear side compartment. A chrome plated blade cover, rubberized pick point cover and brackets shall be provided.

b. One each snatch block assembly with choker chain, rated for use with the winch specified in 3.3.4.4.

c. Three each Scott Air-Pak IIA or Mine Safety Appliance Company number 401 Pressure Demand Type Self-Contained Breathing Apparatus, with walk-away SCBA brackets and vinyl protective cover, mounted in the left center side compartment.

d. Two each portable, automatic charging type battery powered electric lanterns with automatic charging unit and carrying strap, mounted on top of the cab book cabinet (see 3.4.1).

e. One each, rescue saw and kit. The rescue saw shall be of the air cooled, two-stroke type with a 12-16 inch carbide tipped disc. As a minimum, the saw shall feature a reversible cutter arm, vibration shaped handle system, electronic ignition, three stage air filter, all position carburetor, semiautomatic belt tensioning, and a minimum disc speed of 6300 RPM. The rescue saw kit shall include the rescue saw, carrying case, dust mask, safety goggles, hearing protectors, tool kit, drive belt, main filter and prefilter gasoline stabilizer, three each abrasive disc (steel cutting and concrete cutting), optional blades, one gallon fuel container and instruction manual.

f. Two each, 500 watt outdoor quartz iodine floodlight, with lens protector, carrying handle, weatherproof switch and fully adjustable base. Connectors shall be twist-lock type, in accordance with ANSI/UL 498-81, L6-15, 15 amp three wire type, with rubber boots.

g. Two each 50 foot length of heavy duty oil-resistant, waterproof 3-wire conductor, size number 12, with 600 volt rating, having twist-lock connectors, in accordance with ANSI/UL 498-81, LS-15, 15 amp three wire type, with rubber boots.

h. One each "Y" connector adequate to connect the conductors specified in (g) to the portable generator specified in (i). Connectors shall be twist-lock type, in accordance with ANSI/UL 498-81, LS-15, 15 amp three wire type, with rubber boots.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T04:48Z
Check the source to verify that this is the currentversion before use.

i. One gasoline engine powered, 120 volt, 60 Hz portable generator with a minimum continuous output of 4000 watts. The generator shall feature built-in overload protection, anti-vibration spring mounts, carrying handles with rubber grips, automatic rewind starter, mechanical type governor, muffler, and voltage regulator. The generator shall be provided with each vehicle, mounted on the roll-out tray in the right center compartment. The generator shall be mounted with quick release type clamps to provide easy removal from the compartment tray.

j. One each pike pole, six feet long, with fiberglass handle.

k. One each short handle shovel in accordance with GGG-S-326, Type IV, Class A.

l. One each full length folding litter, stored in the upper rear compartment.

m. Two each 125 foot lengths of life safety rope designed and constructed in accordance with NFPA 1983.

n. One each tube and hose cutter disarming tool with self-aligning swivel head with punch, die and yoke. Minimum length of the tool shall be 40 inches; minimum length from the toggle assembly to the cutter shall be 18 inches.

o. One each tool kit, equipped with the following tools:

(1) One each 1-1/4 pound ball peen hammer in accordance with GGG-H-86, Type II, Class 1, Style A.

(2) One each pipe wrench in accordance with GGG-W-00651, Type VI, Size 14 inch, except with a 90° angle and an aluminum handle.

(3) One each metal cutting shears in accordance with GGG-S-291, Steel, Type II, Class 3, Style B, 7 Inch Nominal Size.

(4) One each lineman's pliers in accordance with GGG-P-471, Type IX Class 1, Style B, 8 Inch Nominal Size.

(5) One each slip joint pliers in accordance with GGG-P-471, Type II, Class 1, Style A, 10 Inch Nominal Size.

(6) One each screwdriver in accordance with GGG-S-121, Type I, Class 5, Style I, Design A, Shape (a) or (b), 8 Inch Nominal Size.

(7) One each screwdriver in accordance with GGG-S-121, Type I, Class 5, Style I, Design A, Shape (a) or (b), 6 Inch Nominal Size.

(8) One each screwdriver in accordance with GGG-S-121, Type I, Class 5, Style I, Design A, Shape (a) or (b), 4 Inch Nominal Size.

(9) One each forged alloy knife type socket head wrench set.

(10) Two each forged alloy knife type socket head wrench set.

(11) One each straight cross tip screwdriver in accordance with GGG-S-121, Type VI, Class 2, Style 1 or 2, 4 Inch Nominal Size (Read and Prince).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:48Z
Check the source to verify that this is the current version before use.

(12) One each straight cross tip screwdriver in accordance with GGG-S-121, Type VI, Class 1, Style 1 or 2, 3 Inch Nominal Size (Phillips).

(13) One each straight cross tip screwdriver in accordance with GGG-S-121, Type VI, Class 1, Style 1 or 2, 4 Inch Nominal Size (Phillips).

(14) One each cold flat chisel in accordance with GGG-C-313, Type IV, Class 1.

p. One each insulated cutter, 20,000 volt, with a minimum 3/8-inch rated cutting capacity for hard steel (Birnell 400). The tool shall have insulated fiberglass handles with rubber hand grips and a drop forged, hardened center cut jaw. Minimum length of the tool shall be 30 inches.

q. Three each pry-axe multi-purpose forcible entry, cutting tool with pick point and pry prong. A leather sheath and instruction manual shall also be provided. The tool shall be of forged steel with an insulated handle. Minimum tool length shall be 18 inches.

r. Three each leather truckman's belt used to carry tools, heel hose, tie-in to ladders and on to hose lines. The belt shall be fully adjustable.

s. Three each standard industrial goggles in accordance with GG-G-531.

t. Two each 16 inch explosion proof vacuum smoke ejector with a minimum 1/3 HP, 115AC motor. Minimum capacity of the smoke ejector shall be 5200 CFM.

u. Six each conical plug, eight inch length by two inch diameter, made of hardwood.

v. Six each conical plug, eight inch length by two inch diameter, made of hard rubber.

w. Two each harness cutter rescue knife with carbon steel "V" blade, Dzus key and finger fitting contour handle. The knife shall have the cutting capability of 10,000 pounds strength webbing per stroke.

x. One each medical extrication device complete with wrap-around jacket, adjustable neck roll, forehead/chin straps, lifting grip handles and storage case.

3.9.1 Fire extinguishers. When specified (see 6.2), the following fire extinguishers shall be provided with mounting brackets.

a. One each hand portable Potassium bicarbonate dry chemical fire extinguisher with a minimum UL rating of 80B:C.

b. Two each hand portable 17 pound Halon 1211 fire extinguisher with a minimum UL rating of 3A:80B:C.

c. One each hand portable dry chemical fire extinguisher for metal fires with a minimum UL rating for six pounds magnesium chips.

3.9.2 Ladders. When specified (see 6.2), the specified type ladder shall be provided and securely mounted in the upper rear compartment (see 3.5.1.1). The securing devices shall be operable by a person wearing fireman's gloves and shall not interfere with the installation and removal of the ladder. Securing devices shall be provided with each vehicle. Ladders shall be in accordance with NFPA 1931.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:48Z
Check the source to verify that this is the current version before use.

a. Two section, 14 foot, aluminum extension ladder.

b. Two section, 14 foot aluminum attic ladder. Overall rail width shall not exceed 13 inches.

c. Three section, 14 foot, self supporting aluminum A-frame ladder.

3.10 Finish and protective coatings.

3.10.1 Cleaning, painting, plating, anodic films, and chemical treatments. Cleaning, painting, anodic films, and chemical treatments shall be in accordance with MIL-STD-808, except that commercial (see 6.3.5) components may be prepared in accordance with the manufacturer's standard practice, provided it is compatible with the exterior finish paint. MIL-P-23377 and MIL-P-26915 epoxy primers shall be used on aluminum and ferrous alloys respectively.

3.10.2 Finish. All mechanically joined components shall be finished before assembly. Welded structures shall have finishes applied after welding. The exterior paint finish shall show no evidence of uneven application, curtains, runs, sags, orange peel, lack of adhesion, or other defect and shall be capable of passing the test described in paragraph 4.8.10 of MIL-C-83286.

3.10.3 Lime yellow. Unless otherwise specified (see 6.2), the outer surfaces of the vehicle shall be painted with DuPont Imron Polyurethane Paint, or equal, Lime Yellow, color number 13670 of FED-STD-595. Chrome items on the vehicle shall not be painted Lime Yellow. Running boards, telescopic tubing, front and rear bumpers shall have a chromed or polished finish.

NOTE

Equal is defined as having performance identical to or superior to DuPont Imron when subjected to the following tests:

a. Tests in accordance with MIL-C-46168:

(1) Paragraph 4.3.17 Flexibility.

(2) Paragraph 4.3.23 Accelerated weathering.

b. Tests in accordance with MIL-C-83286:

(1) Paragraph 4.8.6 Low temperatures resistance.

(2) Paragraph 4.8.10 Resistance to taping.

(3) Paragraph 4.8.12 Pencil hardness.

3.10.4 Forest Green. When specified (see 6.2) the outer surface of the vehicle and the interior surfaces of compartments (except in the cab) shall be painted with polyurethane paint, Forest Green, Color Number 24052 of FED-STD-595. The paint shall be in accordance with MIL-C-83286, or shall be DuPont Imron or equal. All exterior trim items (such as wheels, wheel covers, metal radiator grilles, drip rails, bumpers, door handles, and light trim rings) shall be painted with the same paint as the exterior of the vehicle.

3.10.5 Desert Sand. When specified (see 6.2), the outer surface of the vehicle and the interior surfaces of compartments (except in the cab) shall be painted with polyurethane paint in accordance with MIL-C-83286, Desert Sand, Color Number 30310 of FED-STD-595. All exterior trim items (such as wheels, wheel covers, metal radiator grilles, drip rails, bumpers, door handles, and light trim rings) shall be painted with the same paint as the exterior of the vehicle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:48Z
Check the source to verify that this is the current version before use.

3.10.6 Rustproofing. Unless otherwise specified (see 6.2), the vehicle shall be rustproofed in accordance with the contractor's standard commercial practice. The first article units shall not be rustproofed until after approval of the first article test report.

3.11 Markings. Unless otherwise specified, markings for vehicles painted Lime Yellow shall be applied with reflectorized tape in accordance with L-S-300, Type I, Class 3, Reflectivity 1, red on a white background. Markings for vehicles painted Forest Green shall be applied with black paint, Color Number 37038 of FED-STD-595, and marking for vehicles painted Desert Sand shall be applied with white paint, Color Number 37875 of FED-STD-595.

3.11.1 Identification markings. Unless otherwise specified (see 6.2), the vehicle shall be marked for the appropriate service in accordance with MIL-STD-1223.

3.12 Identification plates and operating instructions. All identification plates, instruction plates, data plates, etc, shall conform to MIL-P-514 and shall be of a size and shape consistent with the information required thereon. Abbreviations shall be in accordance with MIL-STD-12.

3.12.1 Identification plate. An identification plate, permanently marked in accordance with MIL-STD-130, shall be securely attached to the vehicle in a readily accessible location. The identification shall contain the following information:

NOMENCLATURE

MANUFACTURER'S MODEL NUMBER

MANUFACTURER'S SERIAL NUMBER

MANUFACTURER'S NAME

MANUFACTURER'S ADDRESS

MANUFACTURER'S SERVICE PHONE NUMBER

DATE OF MANUFACTURE

CONTRACT NUMBER

NATIONAL STOCK NUMBER

3.12.2 Control markings. All controls, valves, gauges, and indicators used in the operation of the vehicle shall be identified by nameplates securely installed in clearly visible locations.

3.12.3 Operating instructions. Brief operating and precautionary instructions shall be permanently affixed near the appropriate controls. The instructions shall be clear, concise, and adequate to enable operation of the vehicle without damage to the equipment or injury to personnel and shall refer to the components as identified by nameplates.

3.12.4 Transportation data plate. A transportation data plate shall be provided. The plate shall contain at least the following information:

a. Side and rear silhouette views of the vehicle.

b. Horizontal and vertical location of the center of gravity of the vehicle in transport condition.

c. Shipping weight.

d. Loading cubage.

e. Overall length, width, and height.

f. Tiedown instructions for air transport in C-130, C-141 and C-5 Aircraft.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:48Z
Check the source to verify that this is the current version before use.

3.13 Part numbering of interchangeable parts. All parts having the same manufacturer's part number shall be functionally and dimensionally interchangeable. All parts shall be marked for identification in accordance with MIL-STD-130. (Note that MIL-STD-130 does not require marking of commonly known commercial parts which present no identification problem or parts in assemblies which are not normally subject to disassembly or repair).

3.14 Dimensions. The vehicle, in fully operational condition, including all equipment and accessories, shall not exceed the following dimensions:

a. Width (except for mirrors and their brackets), 96 inches.

b. Height, 102 inches.

3.15 Welders. All welders employed in the fabrication of the vehicle, except for commercial (see 6.3.5) components, shall be certified in accordance with the applicable requirements of MIL-STD-1595, the American Welding Society, or the American Society of Mechanical Engineers.

3.15.1 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface parts to be welded shall be free from rust, scale, paint, grease, and other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the welded parts. Welds shall transmit stress without cracking or permanent distortion when the parts connected by the welds are subjected to test, proof, and service loadings.

3.16 Bolted connections. Bolt holes shall be accurately punched or drilled and shall be deburred. Unless torque is specified, threaded fasteners shall be tight and shall not work loose during testing or service usage.

3.17 Riveted connections. Rivet holes shall be accurately punched or drilled and shall be deburred. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surfaces of the compartment.

3.18 Gear and lever assemblies. Gear and lever assemblies shall be properly aligned and meshed and shall be operable without interference, tight spots, loose spots, or other irregularities. Where required for accurate adjustment, gear assemblies shall be free of backlash.

3.19 Cleaning. The vehicle shall be cleaned. Loose, spattered, or excess solder, welding slag, stray bolts, nuts and washers, rust, metal particles, pipe compound, and other foreign matter shall be removed during and after final assembly.

3.20 Workmanship. The vehicle, including all parts and accessories, shall be constructed and finished in a thoroughly workmanlike manner. Particular attention shall be given to freedom from blemishes, defects, burrs, and sharp corners and edges; accuracy of dimensions, surface finish, and radii of fillets; thoroughness of soldering, welding, brazing, painting, wiring and riveting; marking of parts and assemblies; alignment of parts and tightness of assembly fasteners; etc.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless other wise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:48Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of tests. The inspection and testing of the vehicle shall be classified as follows:

a. First article testing (see 4.4)

b. Acceptance testing (see 4.5)

4.3 Test conditions.

4.3.1 Apparatus. Apparatus used in conjunction with the testing specified herein shall be of laboratory precision type and shall be calibrated at proper intervals to ensure laboratory accuracy.

4.3.2 Data. When first article testing is performed (see 6.2.1), at least the following data, unless not applicable, shall be recorded at intervals not to exceed 30 minutes. Additional data and/or shorter intervals shall be provided as appropriate for any specific test.

a. Date

b. Time started.

c. Time finished.

d. Ambient temperature.

e. Engine speed.

f. Engine oil pressure.

g. Engine coolant temperature.

h. Transmission oil temperature.

i. Vehicle odometer reading at the start and finish of each test.

4.3.3 Preparation for tests. The vehicle, equipped with all specified auxiliary equipment, shall be fully serviced and all equipment shall be prepared for immediate operation.

4.3.4 Test rejection criteria. Throughout all tests specified herein, the vehicle shall be closely observed for the following conditions, which shall be cause for rejection:

a. Failure to conform to design or performance requirements specified herein.

b. Spillage or leakage of any liquid, including fuel, coolant, lubricant, or hydraulic fluid, under any operating condition, except as allowed herein.

c. Structural failure of any component, including permanent deformation, or evidence of impending failure.

d. Evidence of excessive wear.

e. Interference between the vehicle components or between the vehicle, the ground, and all required obstacles, with the exception of normal contact by the tires.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:48Z
Check the source to verify that this is the current version before use.

f. Misalignment of components.

g. Evidence of undesirable roadability characteristics, including instability in handling during cornering, braking, and while traversing rough terrain.

h. Conditions which present a safety hazard to personnel during operation, service, or maintenance.

i. Overheating of the engine, transmission, or any other vehicle component.

4.4 First article testing.

4.4.1 First article test samples. The first article test samples shall be identical to the items procured under the terms of the contract. Approval of the first article test report shall not constitute a waiver by the Government of its rights under the provisions of the contract. Two first article samples shall be produced and tested as follows:

a. Contractor test sample (see 4.4.2.1).

b. User test sample (see 4.4.2.2).

4.4.2 First article tests.

4.4.2.1 Contractor test sample. The contractor test sample shall be subjected to the tests described in 4.6.1 through 4.6.8.

4.4.2.2 User test sample. The user test sample (see 4.6.9) may be subjected to and successfully complete the test described in 4.6.1, 4.6.2.1(a), 4.6.3, 4.6.4.3, 4.6.4.4, 4.6.4.5, and 4.6.5.4.

4.4.3 Notification of tests. The procuring activity shall be notified of the time and location of all first article tests so that representatives of the procuring activity may attend. The notification shall be in writing and shall include the nomenclature and the national stock number.

4.5 Acceptance testing. Acceptance testing shall be classified as follows:

a. Individual testing (see 4.5.1).

b. Random sample testing (see 4.5.2).

All defects identified shall be corrected prior to acceptance.

4.5.1 Individual testing. Each production vehicle shall be subjected to the tests specified in 4.6.1, 4.6.2.1(a), 4.6.4.5 and 4.6.5.4.

4.5.2 Random sample testing. Any production vehicle may be selected by the procuring activity at any time to be subjected to the tests described in 4.6.2, 4.6.3 and 4.6.4.

4.5.2.1 Rejection and retest. When a vehicle fails to meet the requirements of this specification, vehicles to be delivered pursuant to the contract may not be accepted until the cause of the failure is determined, corrective action is taken by the contractor and the component that failed is successfully retested to assure compliance with this specification. Tests not involving the failed component may be continued pending the investigation of a test failure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:48Z
Check the source to verify that this is the current version before use.

4.6 Test methods

4.6.1 Examination of product. The vehicle shall be inspected to determine compliance with the requirements specified herein. Particular attention shall be given to materials, workmanship, dimensions, surface finishes, protective coatings and their application, welding and riveting, and markings. Any painted surface on the exterior of the vehicle may be tested in accordance with paragraph 4.8.10 of MIL-C-83286. For the first article and random sample vehicles, this examination shall be accomplished by use of a checklist which lists each not validated by a test and the results of the examination.

4.6.2 Durability road test.

4.6.2.1 Road test. The vehicle, with all auxiliary equipment installed, shall be operated over the following types of roads for the distances described. The test fluid used for the vehicle's engine shall be Grade JP-8 turbine fuel in accordance with MIL-T-83133 or JET-A1 fuel.

a. The vehicle shall be operated over hard surface highways for a distance of 10 miles at an average speed of 40 MPH. During the test, the following operations shall be performed:

(1) Normal or average stops, ten – times.

(2) Quick stops from a speed of at least 30 MPH by instantaneous application of brakes, five times.

(3) Sharp right turns and sharp left turns, five times each.

b. The vehicle shall operate over graded gravel roads for a distance of 300 miles at an average speed of 30 MPH.

c. The vehicle shall operate over a Belgian Block course for a distance of 300 miles at an average speed of 10 MPH.

d. The vehicle shall be tested to demonstrate compliance with 3.2.1(1).

4.6.3 Mobility tests. The vehicle shall perform the following tests with Grade JP-8 turbine fuel in accordance with MIL-T-83133 or JET-A1 fuel as the engines test fluid.

4.6.3.1 Maximum speed and acceleration. The time-speed-distance relationship of the fully loaded vehicle shall be determined while accelerating from a standing start to maximum speed on a dry level paved surface to demonstrate compliance with 3.2.1a and 3.2.1b. Not less than three runs, each in opposite directions, shall be conducted. Maximum speed and acceleration shall be the average for all runs.

4.6.3.2 Grade operation. The fully loaded vehicle shall be driven up and down a eight percent dry paved grade. The maximum speed than can be maintained while climbing the grade shall be measured and recorded in the test report. Engine oil pressure shall be observed and shall not be less than the manufacturer's recommended minimum pressure at the engine operating speed. Engine starting ability shall be demonstrated in both directions on the grade.

4.6.3.3 Side slope operation. The fully loaded vehicle shall be driven in both directions on a side slope of 20 percent. Engine oil pressure shall be observed and shall not be less than the manufacturer's recommended minimum pressure at the engine operating speed. Engine starting ability shall be demonstrated in both directions on the slope.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:48Z
Check the source to verify that this is the current version before use.

4.6.3.4 Ramp test. The fully loaded vehicle shall be driven forward from a hard flat horizontal surface and ascend a ramp with a minimum length of 1.2 times the vehicle wheelbase and a slope of 30.6°. It shall then proceed across the ramp crest onto an upper surface, down the ramp, and onto the lower horizontal surface. The test shall be repeated in the opposite direction.

4.6.3.5 Suspension articulation. The vehicle shall be tested to demonstrate compliance with 3.2.1k. The sides of the blocks may be sloped; however, the block length shall be such that when one tire of a bogie is at the top of the block, the other tire on that side is on the ground.

4.6.3.6 Brake tests.

4.6.3.6.1 Service brake tests. Service brakes shall be tested to demonstrate compliance with the allowable stopping distances identified in 49CFR 571.105. The fully loaded vehicle shall be capable of stopping from 30 and 60 mph within the specified distances. A minimum of four consecutive stops shall be performed for each 30 and 60 mph speed.

4.6.3.6.2 Parking brake tests. The fully loaded vehicle shall be tested to verify compliance with 3.2.1j. The parking brake shall hold the vehicle stationary for five minutes, in each the forward and reverse direction on a 20 percent grade.

4.6.3.7 Road handling test. The fully loaded vehicle shall be driven on a dry level paved surface to demonstrate compliance with 3.2.1m. The vehicle shall operate through right and left turns and maneuver through a standard slalom type course. A minimum of ten right turns, ten left turns and five slalom passes shall be conducted at an average speed of no less than 35 MPH. Throughout the road handling test, the vehicle shall be observed for its roadability, ease of handling and tendency to sway or yaw.

4.6.4 Design verification.

4.6.4.1 Weight and weight distribution. The weight on each corner of the vehicle shall be measured with the unit standing on a flat level surface, both the empty and fully loaded vehicle shall include ballast to simulate a 250 pound crew member in each seating position.

4.6.4.2 Dimensional verification. The dimensions specified herein shall be measured with the vehicle standing on a flat level surface. Overall height and vehicle lean shall be measured in both the empty and the fully loaded conditions, as defined in 4.6.5.1.

4.6.4.3 Electrical lighting test. Floodlights and spotlights shall be tested to demonstrate conformance to 3.7. Each light shall be tested for its ease of accessibility, adjustment and rotation.

4.6.4.4 Alternator output test. With the vehicle stationary and operating at its normal operational speed, the air conditioner, winch and all electrical lighting equipment (floodlights, spotlights, headlights, warning lights, rooflights and light bar) shall be simultaneously operated at maximum equipment output. Operation, as described, shall be maintained for a minimum of one hour. During the test, any evidence of battery discharge or engine overheating shall be cause for rejection.

4.6.4.5 Equipment storage test. Equipment requiring secure storage or attachment to the vehicle shall be verified for ease of attachment/removal by a mechanic wearing arctic mittens or fireman's gloves.

4.6.4.6 Electromagnetic interference measurement. The vehicle and all electrical components shall be tested in accordance with MIL-STD-462 to demonstrate compliance with 3.1.7.

4.6.4.7 Sound level testing. The vehicle shall be tested in accordance with SAE J336a and J366b to demonstrate compliance with 3.1.8.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:48Z
Check the source to verify that this is the current version before use.

4.6.5 Environmental tests.

4.6.5.1 Low temperature storage and operation. The complete vehicle, including all accessories, shall be tested in accordance with Test Method 502.2, Procedures I and II, of MIL-STD-810 to demonstrate compliance with 3.1.4a. Temperature sensor locations shall be approved by the procuring activity. Operational checkouts shall be performed in accordance with paragraph 4.6.5.4. Engine starting aids may be used (see 3.3.1.1.2). When applicable, a fine mist of water shall be applied to the entire windshield to form a thin film of ice. The defroster shall clear the windshield within 15 minutes and maintain clear vision throughout the remainder of the test. "Standard ambient" and "controlled ambient" shall be defined as the ambient condition of the test site. For Procedure I, the vehicle shall be exposed to the minimum required cold storage temperature of 3.1.4a in a steady state condition for 24 hours. For Procedure II, the vehicle shall be exposed to the minimum required cold operational temperature of 3.1.4a in a steady-state condition for 24 hours.

4.6.5.2 High temperature storage and operation. The complete vehicle including all accessories, shall be tested in accordance with Test Method 501.2, Procedures I and II, of MIL-STD-810 to demonstrate compliance with 3.1.4a. Temperature sensor locations shall be approved by the procuring activity. Operational checkouts shall be performed in accordance with 4.6.5.4. "Standard ambient" and "controlled ambient" shall be defined as the ambient condition of the test site. For Procedure I, the vehicle shall be exposed to the maximum required hot storage temperature of 3.1.4a in a steady state condition for 24 hours. For Procedure II, the vehicle shall be exposed to the maximum required hot operational temperature of 3.1.4a in a steady-state condition for 24 hours.

4.6.5.3 Other environmental tests. The components and materials used in the construction of the vehicle shall be subjected to, or certified as having passed, or being capable of passing, the following test methods of MIL-STD-810 to demonstrate compliance with 3.1.4:

a. Humidity - Method 507.2, Procedure I.

b. Salt Fog - Method 509.2, Procedure I.

c. Sand and Dust - Method 510.2, Procedures I and II. For Procedure I, air velocity shall be 1,750 ft/min and high temperature adjustment shall be 125°F. For Procedure II, air velocity shall be 5,700 ft/min; sand concentration of 0.0623 g/ft, plus or minus 0.015 g/ft; 90 minutes per face duration.

d. Rain - Method 506.2, Procedure II.

4.6.5.4 Operational checkout. All controls, levers, mechanisms, and doors shall be actuated a sufficient number of times to ensure consistency of operation and to determine whether the test exposure produced system degradation.

4.6.6 Reliability/durability testing. Compliance with the quantitative reliability requirements of 3.1.3.1 shall be demonstrated by the tests in 4.6.2.1. The test in 4.6.2.1 shall be continued if necessary to accumulate the required 430 hours of operation. Scheduled maintenance, maintenance events, or adjustments authorized by this specification or the procuring activity shall not be counted as failures. A maintenance event is defined as any malfunction that entails maintenance or adjustment, but does not prevent, delay, or reduce the performance of the vehicle as specified herein.

4.6.7 Maintainability demonstration. Compliance with the maintenance downtime requirements shall be demonstrated by task performance. All scheduled maintenance tasks and all tasks listed in 3.1.3.2.1 shall be performed. In addition, corrective maintenance tasks shall be selected by the procuring activity. Not less than 25 percent or more than 50 percent of the total number of tasks shall be demonstrated to verify an average maintenance downtime within the required limit. As a part of this demonstration, the recommended frequencies of the scheduled maintenance tasks and the times recorded to accomplish the tasks shall be used to develop an expected value of scheduled maintenance downtime per measure of use, such as calendar time, hours of operation, or miles traveled. The capability of performing maintenance tasks by personnel wearing arctic mittens shall be demonstrated.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T04:48Z
Check the source to verify that this is the currentversion before use.

4.6.8 Air transportability analysis. A detailed engineering analysis shall be conducted to demonstrate compliance with 3.1.9. The analysis shall include the tiedowns and all major components and their ability to withstand the accelerations specified in MIL-STD-1791. The evaluation shall also include a dimensional analysis for the vehicle while loaded aboard a Type C-130, C-141, and C-5 Aircraft.

4.6.9 User test. The vehicle shall be delivered (where specified in the contract or purchase order, (see 6.2.1) for 30 days of operational use. The test period shall begin after the vehicle has been inspected and prepared for use and shall be available for up to 240 hours of operation. The vehicle shall be available for any eight hour period specified by the Government each day, seven days a week. Any period of more than two hours of the same day that the vehicle is out of service for maintenance or repair shall not be considered part of the test period. The vehicle shall be operated and scheduled maintenance shall be performed by Government personnel using the operation and maintenance procedures contained in the preliminary technical data to be supplied with the vehicle. Any parts or corrective actions required shall be provided by the contractor. Test operations will simulate normal military usage and will not exceed any operating parameters defined by this specification. The sole criteria for acceptance/rejection of the user test shall be based on the performance requirements of this specification. All systems and subsystems of the vehicle may be tested at the beginning and end of the test period.

4.7 Refurbishment. After successful completion of the all required testing, each vehicle shall be restored to like new condition.

5. PACKAGING

5.1 Preparation for delivery shall be in accordance with the terms of the contract.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The vehicle covered by this specification is intended for prolonged periods of standby operations, forcible entry and rescue of personnel entrapped in damaged aircraft, motor vehicles, and facilities.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.

b. Spare wheel, if required (see 3.3.6.1).

c. Spare wheel and tire assembly (see 3.3.6.2).

d. Tire tools, if required (see 3.3.6.3).

e. Warning lights, blue lenses, if required (see 3.7.3).

f. Auxiliary equipment, if required (see 3.9).

g. Fire extinguishers, if required (see 3.9.1).

h. Ladders, if required (see 3.9.2).

i. Finish color required, if not lime yellow, color number 13670 of FED-STD-595 (see 3.10).

j. Identification markings required (see 3.11.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:48Z
Check the source to verify that this is the current version before use.

k. Rustproofing, if other than the manufacturer's standard commercial practice, is required (see 3.10.6).

6.2.1 Consideration of data requirements. The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Descriptions (DID's) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/ provided and that the DID's are tailored to reflect the requirements of the specific acquisition. To ensure correct contractual application of the data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DOD FAR Supplement 27.475.1 exempts the requirement for a DD Form 1423.

Paragraph no.	Data requirement title	Applicable DID No.
a. 4.3.2, 4.5.2, 4.6	First Article Inspection Report	DI-T-4902
b. 4.3.2, 4.4.2.1	First Article Inspection Procedure	DI-T-4901

(Copies of data item descriptions required by the contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer).

6.3 Definitions.

6.3.1 Belgian Block. A Belgian Block course is paved with unevenly laid granite or basalt block forming an undulating surface. It duplicates a rough cobblestone road such as is found in many parts of the world. A cobblestone course may be used as an alternate.

6.3.2 Improved road. An improved road is a smooth, hard surfaced road such as a concrete or asphalt paved highway.

6.3.3 Unimproved road. An unimproved road is an unpaved, unstabilized road with an undulating surface having occasional chuckholes and exposed rocks.

6.3.4 Cross country terrain. Cross country terrain consists of open fields, broken ground, an uneven terrain in general.

6.3.5 Commercial. A manufacturer's standard (product) having been marketed, in production, and sold in substantial quantities to the general public for a minimum of one year prior to the date of invitation for bid or request for proposal. An item is "sold in substantial quantities" only when the quantities regularly sold are sufficient to constitute a real commercial market. Nominal quantities, such as models, samples, prototypes, or experimental units, do not meet this requirement. The "general public" is a significant number of buyers other than the Government or affiliates of the offerer; the item involved must not be for Government end use. For the purpose of this specification, items acquired for "Government end use" include items acquired for foreign military sales.

6.4 First article. When first article inspection is required, the contracting officer should provide specific guidance to offerors whether the item(s) should be a first article sample, a first production item, or a standard production item from the contractor's current inventory and the number of items to be tested as specified in 4.4. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government and that bidders offering such products, who wish to rely on such

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:48Z
Check the source to verify that this is the current version before use.

production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.5 Subject term (key word) listing.

Compartment vehicle, 11,000 GVW
Firefighting equipment storage vehicle
Off-road compartment vehicle

6.6 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Air Force - 99

Preparing activity:
Air Force - 84

Project 4210-F236

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:48Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:48Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-T-83965B	2. DOCUMENT DATE (YYMMDD)

3. DOCUMENT TITLE

4. NATURE OF CHANGE (*Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.*)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON
c. ADDRESS (Include Zip Code) WR-ALC/LZDTD Robins AFB GA 31098-5365	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-03-26 04:48Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:48Z
Check the source to verify that this is the current version before use.