MILITARY SPECIFICATION

CARTRIDGE, DELAY, MARK 101 MOD 0

This amendment forms a part of Military Specification MIL-C-81567(AS) of 27 October 1967, and has been approved by the Naval Air Systems Command, Department of the Navy.

Page 2

Under "DRAWINGS", title of PL 2518489, delete "Cartridge, Delay, MARK 101 MOD 0" and substitute "Cartridge, Delay Type".

Under "DRAWINGS", delete "Dwg. 2519632" and title, and substitute:

| | |
|---|---|
| "DL 2519632 | Test Set, Crtg., Impulse, MARK 49 MOD 0 and Crtg., Delay, MARK 101 MOD 0" |

Under "PUBLICATIONS", delete "BUSANDA Instruction 4030.17" and title.

Page 3

2.2, under "CODE OF FEDERAL REGULATIONS", delete "49 CFR 71-78" and title, and substitute:

| | |
|---|---|
| "49 CFR 171-178 | Transportation, Explosives and other Dangerous Articles" |

Page 4

After Paragraph 3.8.3, add:

"3.8.3.1 Serial number identification. Cartridges shall be legibly identified by serial numbers in accordance with 4.7.6."

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.

Page 7

4.6.1, delete and substitute:

"4.6.1 Packaging, packing and marking. (M105) The packaging and packing of cartridges and the container markings shall be in accordance with Section 5. Quality conformance inspection shall be conducted in accordance with the inspection criteria on the applicable drawings referenced in Section 5."

Page 8

4.7.3, lines 2 and 3, delete "the applicable portions of paragraphs 1308-1318 and 1322 of OP 5" and substitute "the applicable paragraphs of OP 5".

4.7.6, delete and substitute:

"4.7.6 X-ray examination. Examine all cartridges by X-ray and any observable imperfections in assembly shall be cause for cartridge rejection. The cartridges shall be positioned on their sides for the most revealing exposure. All cartridges shall be identified with serial numbers prior to X-ray examination. The cartridge serial numbers shall be in consecutive order beginning with the number one (1) in each production lot. The cartridges for X-ray shall be arranged on trays or boards in consecutive numerical order and each X-ray plate shall carry a permanent identification of the cartridges displayed thereon. The X-ray plate identification shall include the complete lot number, as stamped on the cartridges, and the span of serial numbers displayed. The serial numbers shall be rubber stamped on the cartridges with approximately 1/8 inch high characters, using the same process as that applying to the other cartridge markings. The serial numbers shall be located apart from the other cartridge markings. X-ray plates of the entire production lot shall accompany the ballistic sample to the activity conducting the production lot acceptance test. See 6.2."

Page 9

4.7.7.1, fourth sentence, delete "shall be performed in a nominal ten-cubic centimeter closed chamber specified on Bureau of Naval Weapons Drawing 2519632", and substitute:

"shall be conducted in a test set manufactured in accordance with the drawings listed on DL 2519632"



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.

Page 10

5.1.3, last line, delete "49 CFR 71-78" and substitute "49 CFR 171-178".

5.2.3, last line, delete "49 CFR 71-78" and substitute "49 CFR 171-178".

5.3.1, last line, delete "49 CFR 71-78" and substitute "49 CFR 171-178".

5.3.2, delete and substitute:

"5.3.2 Normal markings. Unless otherwise specified in the contract or order, the marking information on unit packages and shipping containers shall be as specified on Drawings 2518488 and 2518489, respectively, of PL 2518489. The specified marking information shall be applied to the containers in accordance with the applicable provisions of MIL-STD-129."

Page 11

6.2, under "Procurement documents should specify the following:", add:

"e. direction for shipping X-ray plates of entire production lot along with ballistic sample to the activity conducting production lot acceptance test."

6.3.1, delete and substitute:

"6.3.1 Test report. The contract or order should specify that results of ballistic tests are to be forwarded to the Naval Air Systems Command (AIR-53222A) and the procuring activity."

6.4, delete and substitute:

"6.4 Definitions. For the purposes of this specification, the following definitions apply."

Pages 12, 13, 14, and 15

6.5 and subparagraphs, delete and substitute:

"6.5 Explosives safety precautions. Safety precautions for explosive-loaded items are contained in DOD 4145.26M, "DOD Contractors' Safety Manual for Ammunition, Explosives and Related Dangerous Material"."



Project No. 1377-N521

☆ U.S. GOVERNMENT PRINTING OFFICE: 1973-714-545/5395

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.