MILITARY SPECIFICATION

HOSE ASSEMBLIES, COMBINED ASSEMBLIES, HOSE AND COMMUNICATION CABLE

This specification has been approved by the Naval Air Systems Command, Department of the Navy.

The complete requirements for procuring the hose assembly described herein shall consist of this document, the individual detail specifications for the hoses cables of the combined assembly, and the issue in effect of Specification MIL-H-81581.

1. SCOPE

1.1 Scope - This specification covers the detail requirements for hose assemblies covered by individual detail specifications and fastened together in some manner to make up a combined hose assembly.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATION

Military

MIL-H-81581	Hose Assemblies, Breathing Oxygen and Air; General Specification for

DRAWINGS

Naval Air Systems Command

282AS100	Hose and Communication Cable Index, Combined Assemblies

(When requesting any of the applicable documents, refer to both title and number. All requests should be made via the cognizant Government quality assurance representative. Copies of this specification and other unclassified specifications, standards and drawings required by contractors in connection with specific procurement functions should be obtained upon application to the Commanding Officer,

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:44Z
Check the source to verify that this is the current version before use.

Naval Publications and Forms Center (Code 1051), 5801 Tabor Avenue, Philadelphia, Pennsylvania 19120. All other documents should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements - Requirements shall be in accordance with the applicable detail specifications of the individual hose assemblies used in the combined assembly and with the requirements specified herein.

3.2 Qualification - The hose assembly furnished under this specification shall be a product which is qualified for listing on the applicable qualified products list at the time set for opening for bids. Qualification will be in accordance with groups as listed on NASC Index drawing 282AS100. Qualification approval of any individual hose assembly listed within a group will automatically qualify a manufacturer for all other items listed within the group, provided the conditions set forth in MIL-H-81581, paragraph 6.3.1, are complied with.

3.3 Design and construction - The hose assembly shall be in accordance with the general specification and with the applicable drawing listed on NASC Index drawing 282AS100.

3.4 Performance - The performance of the combined hose assembly shall be in accordance with the performance requirements specified in the detail specifications for the individual assemblies making up the combined assembly along with the requirements specified herein.

3.4.1 Visual examination - When subjected to the visual examination specified in 4.2.1, the combined assembly shall be in accordance with the applicable drawing specified in the NASC Index drawing 282AS100. The hose assemblies and or cable assemblies of the combined assembly shall be assembled as specified in the applicable drawing. There shall be no missing, loose, malformed, fractured or damaged components. There shall be no incorrect assembling or improper positioning of components. There shall not be any functioning part that works with difficulty. There shall not be any faulty workmanship or other irregularities.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection - Sampling and inspection shall be in accordance with the applicable detail specification for the individual hoses of the combined assembly and as specified herein for the combined assembly.

4.1.1 Qualification inspection - The qualification inspection of the combined hose assembly shall consist of those inspections required for qualification of the individual hoses or cables of the combined assembly and with the visual examination specified in 3.4.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:44Z
Check the source to verify that this is the current version before use.

4.1.1.1 Qualification samples - The qualification samples shall consist of four combined assemblies of the part number contracted for.

4.1.2 First article inspection - The first article inspection of the combined assembly shall consist of those inspections required for the first article inspection of the individual hoses and/or cables of the combined assembly and with the visual examination specified in 3.4.1.

4.1.2.1 First article samples - The first article sample shall consist of four combined assemblies of the part number contracted for.

4.1.3 Quality conformance inspection - The quality conformance inspection shall consist of those inspections required for the quality conformance inspection of the individual hoses and/or cables of the combined assembly and with the visual inspection specified in 3.4.1.

4.1.4 Sample size - The sample size shall be every combined assembly and the acceptance criteria shall be to reject all defective units.

4.2 Tests and examinations -

4.2.1 Visual examination - Every combined assembly shall be examined visually and shall conform to the requirements of 3.4.1.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with the general specification.

6. NOTES

6.1 Intended use - The combined assembly covered by this detail specification is intended for use in supplying breathing oxygen or air to aircrewmen in the operation of aircraft.

Preparing Activity:
Navy - AS
Project No. 1660-NO23

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:44Z
Check the source to verify that this is the current version before use.