INCH-POUND

MIL-W-44167B(GL)
21 February 1992
SUPERSEDING
MIL-W-44167A(GL)
22 December 1986

MILITARY SPECIFICATION

WASHING MACHINE, LAUNDRY:

OPEN END TYPE, TRAILER MOUNTED

This specification is approved for use by the Natick Research, Development, and Engineering Center, Department of the Amy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 scope. This document covers a trailer mounted laundry washing machine for field use (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specif ications, standards, and handbooks. The following specifications, standards, and handbooks forma part of this documento the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5017 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3510

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:20Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

HH-I-553	-	Insulation Tape, Electric, (Rubber, Natural and Synthetic)
QQ-S-57 1	-	Solder; Tin Alloy, Tin-Lead Alloy, and Lead Alloy
WW-P-521	-	Pipe Fittings, Flange Fittings, and Flanges: Steel and Malleable Iron (Threaded and Butt-welding) class 150

MILITARY

MIL-T- 152	-	Treatment, Moisture- and Fungus-Resistant, of Communications , Electronic, and Associated Electrical Equipment
MIL-T-704	-	Treatment and Painting of Material.
MIL-B-844	-	Blankets, Bed, Wool, Shrink Resistant and Mothproof ed
MIL-L-3153	-	Laundry and Dry Cleaning Machinery and Equipment, Packaging of
MIL-C-5015	-	Connectors, Electrical, Circular Threaded, AN Type, General Specif ication for
MIL-S-36868	-	Sheet, Bed, Cotton, White, Fitted Style
MIL-T-44047	-	Trousers, Camouflage Pattern; Combat
MIL-L-44142	-	Laundry unit , Trailer Mounted

STANDARDS

MILITARY

MIL-STD- 100	-	Engineering Drawings Practices
MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-130	-	Identif ication Marking of U.S. Military Property
MIL-STD-195	-	Marking of Connections for Electrical Assemblies
MIL-STD-454	-	Standard General Requirements for Electronic Equipment
MIL-STD-1472	-	Human Engineering Design Criteria for Military Systems, Equipment and Facilities

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardi" zation Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111 -5094.)

2.1.2 Other Governmnt documents, drawings, and publications. The f ollowing other Government documents, drawings, and publications f orm a part of this document to the extent specified herein. unless otherwise Specified, the issues are those cited in the solicitation.

Source: https://assist.dla.mil -- Downloaded: 202640-22T00:20Z
Check the source to verify that this is the current version before use.

DRAWINGS

Us. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

6-1-9944 - Washing Machine, Laundry: open End Type, Trailer Mounted Assembly

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: ATRNC-UX, Natick, MA 01760-5017.)

DEPARTMENT OF THE ARMY FIELD MANUALS

FM 10-280 - Department of the Army Field Manuals, Field Laundry clothing Exchange, and Bath operations

(Copies are available from the contracting activity or as directed by the attracting activity.)

2.2 Non-Government publications . The f ollowing documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 120 - Pipe, Steel, Black and Hot-Dipped Zinc Coated (Galvanized) Welded and Seamless, For Ordinary uses

A 165 - Electrodeposited Coatings of Cadmium On Steel

A 240 - Heat Resisting Chromium and Chromium-Nickel Stainless Steel Plate, Sheet and Strip for Fusion-welded Unfired Pressure Vessels

A 276 - Stainless and Heat-Resisting Steel Ears and Shapes

A 582 - Free-Machining Stainless and Heat-Resisting Steel Bars, Hot Rolled or Cold Finished

D 3050 - Soil Removal and Reflectance Retention of Fabrics, Measuring

D 3951 - Standard Practice for Commercial Packaging

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:20Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

NFPA NO. 70 - National Electrical Code

(Application for copies should be addressed to the National Fire Protection Association, 1 Batterymarch Park, Quincy, MA 02269.)

UNDERWRITERS LABORATORIES, INC. (UL)

UL 50- Cabinets and Boxes

UL 83 - Thermoplastic-Insulated Wires and Cables

(Application for copies should be addressed to the Underwriters Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.)

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION (NEMA)

MG 1 - Motors and Generators

(Application for copies should be addressed to the National Electrical Manufacturers Association, 2101 L St. , N. W., Washington, DC 20037.)

AMERICAN WELDING SOCIETY, INC. (AWS)

Standards Qualification Procedure of the American Welding Society

(Application for copies should be addressed to the American welding Society, Inc. , 550 N.W. Le Jeune Road, Miami, FL 33126.)

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Welding Qualifications of the American Society of Mechanical Engineers

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th St. , New York, NY 10017.)

ASSOCIATION OF AMERICAN RAILROADS (AAR)

Rail Impact Procedure

(Application for copies should be addressed to the Association of American Railroads, 50 F Street N.W. , 5th Floor, Washington, DC 20001.

Source: https://assist.dla.mil -- Downloaded: 202610-22T00:20Z
Check the source to verify that this is the current version before use.

FACTORY MUTUAL TESTING LABORATORIES (FMTL)

Class Number 3820 - Electrical Utilization Equipment

Class Number 8100 - Commercial Laundry Equipment

(Application for copies should be addressed to Factory Mutual Testing Laboratories, 1151 Providence Highway, Norwood, MA 02062.)

(Non-Government standards and other publications are normally available from organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services .)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws anmd regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Codes and standards. The trailer mounted washing machine shall comply with the applicable requirements of National Fire Protection Association Standard NFPA 70, Underwriters Laboratories (UL) Standard NOS. 50 and 83, and National Electrical Manufacturers Association Standard MG-1. The washing machine shall also conform to Factory Mutual Testing Laboratories (FMTL) standards class Nos. 3820 and 8100 and have FMTL approval. Satisfactory evidence that these requirements have been met shall be submitted to the contracting officer or his authorized representative prior to the start of production (see 4.5).

3.3 Materials and compo The materials and components shall be as specified herein and in the applicable drawings. Materials and components not specifically defined shall be of the quality and construction required to meet the trailer mounted washing machines intended use provided the completed item complies with all of the previsions of this specification. All washing machines, control units, and related parts furnished under any specific contract shall be physically and mechanically identical. This requirement includes parts, assemblies, components, spare parts, and accessories. No changes or deviations will be acceptable without written approval of the contracting officer. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.3.1 Washer cylinder, shell assembly, tie rods, and base panel. The washer cylinder, shell assembly, tie rods, and base panels shall be 304

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:20Z
Check the source to verify that this is the current version before use.

stainless steel conforming to ASTM A 240 or ASTM A 276, as applicable. The rear wall of the shell shall be fabricated using a minimum of .120 inch thick stainless steel.

3.3.2 Drive shaft. The drive shaft shall be 303 stainless steel conforming to AST\M A 582.

3.3.3 Washer door. The washer door shall be cast nickel plated bronze or stainless steel . The door glass shall be suitable for high thermal and mechanical shock.

3.3.4 Valves and pipe fittings. The air actuated cylinders for the drain valve and all internal components of the drain valves shall be fabricated using stainless steel or steel hadware, cadmium plated conforming to ASTM A 165. The drain valve bodies shall be malleable iron and galvanized. Valves shall be designed to provide maximum drain welter flow. Cross-sectional area through the open drain valve shall be sufficient to pass a 3 inch sphere through the valve without obstruction. All piping shall be threaded zinc coated steel pipe conforming to ASTM A 120. Pipe fittings shall be threaded zinc coated steel conforming to WW-P-521, type II. All plating or galvanizing shall be performed after any machining.

3.3.5 Gaskets. All gaskets shall be neoprene. No fiber gaskets will be allowed .

3.4 Alternate materials and components. Materials and components off ered as equivalents to those specified herein and on the applicable drawings shall be equal in form, fit, and function to the specified materials or components. The incorporation of such materials or components in the design of the specified open end washer shall not require modification or change in location of any other material or component, unless such a modification is specifically approved in writing by the contracting officer. Prior to commencing production the contractor shall submit for the contracting off icer’s approval, a list identifying each alternate material or component, together with proof that each listed material or component complies with the requirements listed herein. The contracting officer, at his option, may require a physical sample of the proposed substitution. Approval of the submitted listing, together with the necessary supporting data does not relieve the contractor of the responsibility that the materials and components shall perform in accordance with specified requirements when incorporated into the trailer mounted laundry washing machine.

3.5 Design and construction. Design and construction of the trailer mounted laundry washing machine shall be as specified herein and on Drawing 6-1-9944 and all subsidiary drawings and parts list pertaining thereto.

3.5.1 Washing machine. The washing machine shall be an open end type, capable of precessing not less than a 60 pound load of any type of fabric

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:20Z
Check the source to verify that this is the current version before use.

(BDUs, sheets, blankets, etc.) in accordance with formulas outlined in FM 10-280. The washing machine shall be designed and fabricated to provide proper performance in all types of military applications and conditions including dust, weather extremes, and temperatures ranging between 32°F to 130%?, and transport as identified in this specification. All components shall be fully accessible including an externally mounted motor, drive train, and Control unit. A water overflow drain shall not be used. All components (i.e., drain valves, card reader, level control system, electrical components, and gear reducer) shall, in addition to meeting all requirements of this specification, be commercially proven components with a history of success ful use in industrial laundry applications. Satisf actory evidence shall be provided to the contracting activity prior to commencing production.

3.5.1.1 Cylinder. The cylinder shall have inside dimensions of 36 inches in diameter by 26 inches in depth. The cylinder shall have 3 to 4 ribs. The ribs shall be integral with or seam welded to the cylinder. The cylinder shall be fully supported from front to back by a cylinder spider and tie rod system. The tie rods shall run the full length of the cylinder. The number of tie rods shall equal the number of ribs. All cylinder welding shall be continuous. There shall be no open seams or spaces that may catch buttons or straps during washing.

3.5.1.2 Drive. The cylinder shall be belt driven from the motor to a helical gear reducer. The washer shaft shall be integral with the helical. gear reducer. Gears shall be shaved and heat treated. Gear box bearings shall be needle type, tapered, or ball. Bushings as bearing surfaces are not allowed.

3.5.1.3 Controls. The washer shall be equipped with a programmable control unit which allows for both automatic and manual control of all electrical, mechanical, and air distribution functions. The control unit shall be equipped with a master switch which controls all power to the washer assembly . A second three position switch shall be provided to select either AUTOMATIC, OFF, or MANUAL operation. When the switch is placed in the AUTOMATIC position, all manual controls shall be overridden and the only control shall be by the control chart or cad. When the switch is placed in the MANUAL position, all automatic input shall be overriden and the only control shall be by the manual *itches. The control unit, switches, lights, labels, and associated parts shall be designed using guidance provided in MIL-STD-1472 . All functions associated with water muse shall be controlled by automatic control only. Control unit features shall include, but are not limited to the control and operation of the following functions:

a. Two independent air actuated drain valves (normal drain and reuse drain - automatic only). When either drain valve is in the open position an override shall be provided to close all intake valves.
b. Three independent air actuated intake valves (hot water intake, cold water intake, and reuse inter intake - automatic only).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:20Z
Check the source to verify that this is the current version before use.

C. Hot, mid, and mixed water temperatures.
d. Preset high water level (11 inches) and preset low water level (8 inches). The level shall be measured from the inside bottom of the tumbling basket. Preset water levels shall be capable of being manually adjusted from 2 to 13 inches in increments of one inch. Level shall be accurate and constant (± inch) under all conditions.
e. The number and length of time of the wash cycles.
f. The number and length of time of the rinse cycles.
9" Reuse of rinse water including control for a remote pump (automatic only).

3.5.1.3.1 Programmer controls. Automatic control stroll be achieved by installation of different non-absorbent plastic f ormula cards (or charts) l Each card shall be capable of carrying laundry formulas f- in the appendix of FM 10-280. The cards shall be easily cut in the field without the use of the special cutter or punch if not available. Each washer produced shall be supplied with pre-punched or cut cards conforming in all laundry formulas in the FM 10-280 appendix ten blank formula cards, and a durable card punch. A special storage container shall be permanently attached to the control unit to safely store and protect up to 30 cards and the card punch during transport and operations. All cards shall be of the same size and shall be capable of accepting 60 minutes of control cut-outs. Cards shall be cut to allow one minute internals between cycles for draining. Cards shall be cut to preclude simultaneous drain and water input. Hot water, for the purposes of cutting the cards, are temperatures of 120°F and over. Mix (hot and cold) shall be temperatures of 90% up to 119°F. The card reader and related control unit shall be capable of accepting and processing cards with a formula duration of up to 75 minutes without any malfunction, binding jamming, or adjustment of card or card reader. Cards and card reader shall be designed to provide a minimum of 8 minutes operation per inch travel of card. The card tracks shall be graduated in one minute intervals and the card and card reader shall have a minimum of 12 tracks. Five minutes of operation per inch travel.

3.5.1.3.2 Timer. The washer shall be quipped with a waterproof zero to 15 minute timer incorporated into the control unit. This timer will activate a signal device and will be used during manual operation.

3.5.1.4 Signal devices. Individual visual signal devices and a common audible signal shall be supplied as part of the control unit to alert the operator that: a) supplies are required (automatic rode), b) Cycle is ccmplete (automatic rode), and c) Manual timing cycle is complete. The signal for additional supplies shall only activate after the correct water level is attained. All indicator lights, power lights, and other lighting equipment shall be easily noticed by the operator, even in direct sunlight. The audible signal shall utilize the piezoelectric principle and shall produce a sound frequency of 4500 Hz with a sound intensity of 65 to 90 dB at two feet. The visual signals shall operate in conjunction with the audible

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:20Z
Check the source to verify that this is the current version before use.

signal. When activated, each signal shall operate for 15 to 20 seconds and then shut off. Depending on the formula selected during automatic operations the supply signal may be activated up to six times during the complete cycle. The audible signal circuit shall include a timed, audible signal cancel circuit with switch so that the operator can temporarily cancel the audible signal should he arrive at the control unit before the 15 to 20 second signal period ends. The tired signal cancel period shall not exceed 60 seconds.

3.5.1.5 Recycle of water carobilities. Constant power (110 V, 1 phase, 20A) shall be supplied to an electrical outlet mounted on the rear of the washer control unit. The electrical outlet shall conform to MS 3102 R16-10S per MIL-C-5015 . The outlet shall have a cover that conform to MS 25043-16DA.

3.5.1.6 **Temperature gage.** The washer shall be equipped with a **20°F** to **220°F ± 20°F** dial temperature gage to show water temperature inside the washer cylinder. The gage shall be mounted on the side of the soap chute as shown on Drawing 6-1-9944. The temperature sensing probe shall be installed into a thermal well. The thermal well shall be located at the bottom of the washer drum so that it is totally submersed in water during any wash cycle or at any water level. The thermal well shall be packed with a heatsink compound prior to installation of the sensing probe. Gage accuracy shall be 2 percent of full range.

3.5.2 Electrical requirements .

3.5.2.1 Motors. All motors shall be constructed, classified, and rated in accordance with NEMA MG-1. They shall be rated for continuous operation at 40°C or higher on 208 V,60 Hz, 3 phase power and shall berated at a minimum of 1.5 horse power suitable for reversing duty with proper starting torque for reversing washer service. The rotor shall have ball bearings and be totally enclosed, fan cooled, and capable of withstanding hose washdown. The rotor shall be protected against overload with resettable type heaters. Reset buttons shall be accessible without opening the enclosure where the heaters are mounted. The rotor shall be approved for such application by the rotor manufacturer.

3.5.2.2 Electrical wiring and marking All wiring shall be done in accordance with NFPA No. 70 and marked in accordance with MIL-STD-195 . All wiring connections shall be soldered, taped, or have staked connections. The solder shall conform to type R of QQ-S-571 and the tape shall conform to HH-I-553. A permanent wiring schematic shall be permanently attached to the inside face of the control unit on a removable panel.

3.5.2 .2.1 Wire and wire marking. All wire shall be multi-stranded copper conductor, flame retardant moisture, heat, and oil resistant (type THWN, gasoline and oil resistant in accordance with ANSI/NFPA 70 and UL 83). The minimum wire size shall be determined in accordance with the safe current

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:20Z
Check the source to verify that this is the current version before use.

carrying capacity. All wire shall be black in color with the following exceptions: all ground wire shall be green, all neutral wire shall be white, and if a low voltage DC control system is used, all corresponding DC wire shall be a distinctly different color. All wire shall be numbered for easy identification in agreement with the electric schematics and wiring diagrams. The marking shall be permanently applied to the wire to withstand heat, cold, moisture, and all specified operating conditions herein throughout the life of the set. Marking shall be within 2 to 3 inches of each wire termination. The wire numbering scheme shall be determined by the contractor. A proposed wiring/connection diagram, schematic diagram, and wiring list prepared in accordance with MIL-STD-100 shall be furnished by the contractor for advance approval prior to start of production of the first production unit. A permanent water resistant copy of the wiring diagram shall be permanently mounted to the inside face of the control panel on a removable panel. The wiring diagram copy shall be completely legible.

3.5.2.2.2 Wiring. All wire shall be secured neatly into harnesses. Wires in all harnesses shall be of the proper length and shall be so run and secured (with insulated claps) as to protect insulation against contact with sharp edges, pinching, sharp bending and twisting, abrasion because of vibration or contact with moving parts, exposure to chemicals, and contact With high temperature parts. Wiring shall not be attached to panels or other components that require removal during maintenance, except for actual electrical connections to components. Multiple wires shall be banded together at 5 inch intervals. Where a cable or wire is run between parts that move relative to each other (as a result of vibration, adjustment, inspection, or as a rotter of normal operation), sufficient slack shall be left in the harness to allow repeated movement to take place without bending *or* twisting to the point of damaging the wire or harness in any manner. Wires shall not be spliced. All wires shall terminate in connectors or crimp terminals at each end. Not more than two terminals shall be attached with any one screw on screw type terminal boards. Terminals on electrical components shall not have more than one wire attached. Terminals shall be ring or fork crimp style with insulated sleeves. All wire terminations shall be mechanically strong. All electrical wiring and components shall conform to requirements 1, 9, 11, and 12 of MIL-STD-454.

3.5.2 .2.3 Electrical parts, comments, controls, and instruments. All electrical parts, components, Controls, and instruments shall be identified by a symbol and a number. The number shall be the same as used on the schematic and wiring diagrams. This identification shall be permanently marked in a visible location adjacent to the item on the mounting surface. Each terminal board position shall be numbered and the number permanently marked adjacent to the applicable terminal.

3.5.2.3 Enclosure. The control enclosure shall be equivalent to an enclosure with a type 4 rating in accordance with UL 50. All external operating mechanisms, switches, and controls, when mounted on or through the enclosure, shall be capable of passing the test or tests for the enclosure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:20Z
Check the source to verify that this is the current version before use.

Both inside and outside surfaces of the enclosure, including mans for fastening, shall be treated and finished as specified in 3.9. All controls, level adjustments, and switches shall be fully accessible from the exterior of the enclosure and access to the interior of the enclosure shall not be required except to perform maintenance.

3.5.2.4 Washer door switch. An electrical door lock shall not be used. A safety interlock shall be provided to instantaneously disconnect power to the drive rotor when the door is opened during operation.

3.5.2.5 Moisture and fungus-resistant treatment. Unless otherwise specified (see 6.2), electrical components shall be moisture and fungus-resistant treated with materials conforming to and applied as required in MIL-T-152.

3.5.3 Belt guard A belt guard suitable for truss country travel shall be provided.

3.5.4 Door glass. The washer door glass shall be replaceable without the use of adhesives.

3.6 Performance.

3.6.1 Signal devices. A visual and audible signal shall activate when supplies are injured, a batch is complete, or the manual timing has ended. The signal devices shall activate when tested as specified in 4.4.5.

3.6.2 Chart or card preparation. The formula card shall be capable of carrying Formula III conforming to FM 10-280. The card shall be easily cut in the field without the use of a special punch or special tools when tested as specified in 4.4.5.

3.6.3 Control enclosure. The control unit enclosure shall meet the requirements of UL 50, type 4 when tested as specified in 4.4.5.

3.6.4 Washer door switch. The washer door switch shall prevent operation of the drive motor when tested as specified in 4.4.5.

3.6.5 Washer belt ward. The belt guard on the washer drive assembly shall prevent. contact with the belts or pulleys when tested as specified in 4.4.5.

3.6.6 Cylinder speed. The washer cylinder shall not rotate at any time during a complete wash cycle at speeds greater than 40 rpm or less than 30 rpm when tested as specified in 4.4.5.

3.6.7 Washing machine cycles. The washing machine when operating through complete manual and automatic cycles shall not fail and show no evidence of

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:20Z
Check the source to verify that this is the current version before use.

the following conditions when tested as specified in 4.4.5. Any item that may require adjustment shall be set prior to any testing:

a. Improper interrelationship of components.
b. Improper fit, tightness, or alignment of components.
c. Improper number of cycles, cycle times, or water levels.
d. Improper operation of controls.
e. Overheated bearings or motors.
f. Leaks during filing, washing, rinsing, or draining cycles.
g. Improper or incomplete operation of pressure controls, air valves, intake valves, or discharge valves.
h. structural failure.
i. Need for readjustment of any control or component.

3.6.8 Cleaning capability. The washer shall be capable of removing not less than 80 percent of the soil where tested as specified in 4.4.5.

3.6.9 Moisture removal. The test clothes shall not retain moisture more than 133 percent of initial dry weight of clothes when tested as specified in 4.4.5.

3.6.10 Door gasket. There shall be no sign of leakage of or around the door when tested as specified in 4.4.5.

3.6.11 Endurance. The washer shall launder wool blankets when tested as specified in 4.4.5 (see 6.3.1). All components shall operate properly and there shall be no damage to any of the components or any misalignment of any part throughout the test. There shall be no signs of damage, structural failures, inconsistencies, or evidence of any conditions identified in 3.6.7.

3.6.12 Road traverse. The washer assembly shall traverse the test course and show no damage or any misalignment of any component. The components shall remain securely fastened to the washer assembly with no evidence of looseness or evidence of any conditions identified in 3.6.7, and the washer shall function correctly in all males when tested as specified in 4.4.5 (see 6.3.1 and 6.3.2).

3.6.13 Rail impact. The washer assembly shall show no damage to any component and shall function correctly when tested as specified in 4.4.5 (see 6.3.1 and 6.3.2).

3.6.14 Leak test. This test shall be performed when all other required tests are complete (including 3.6.11, 3.6.12, and 3.6.13). The washer assembly shall show absolutely no evidence of water leaks through seals, seams, valves, pipe f ittings, or any other component when tested as specif ied in 4.4.5.

3.7 Marking. Marking for identification shall be in accordance with MIL-STD-130.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:20Z
Check the source to verify that this is the current version before use.

3.8 Government furnished loan property. When the washer is not procured as part of a contract to fabricate the Army Trailer Mounted laundry per MIL-L-44142, an M-85 Trailer Mounted Laundry without a washer would be Government loaned property (see 6.2 and 6.3.2).

3.9 Preparation and finish of all exposed surfaces. All exterior surfaces to be painted, with the exception of glass, data plates, hose fittings, screw threads, and switches, shall be prepared and finished per MIL-T-704 types F and G. The color of the finish coat shall be Green 383.

3.10 Workmanship. The units shall be free from fractures, splints, punctures, tears, dents, creases, bows, miscasts, deteriorations, or malfunction. There shall be no sharp edges, -burrs, or slivers. The finish shall be free from smudges, poor touch up, saile, scratches, stain, over-spray, sag, imprint, or embedded foreign material. Fasteners shall not be broken, stipped or loose. The end item shall Conform to the quality of product established by this specification.

3.10.1 Welding. The surfaces of parts to be welded shall be free from oxide, scale, paint, grease, and other foreign matter. Welds shall be continuous, sound, smooth, and free f run porosity, cracks, incomplete fusion, and deformation of material. All scale and flux deposits shall be removed from the finished welds and rough edges and projections shall be dressed smooth.

3.10.2 Electrical work and wiring. All electrical work and wiring shall meet the requirements outlined in 3.5.2.2.

3.10.3 Welders. Before assigning any welder to work, the contractor shall provide the contracting off icer, or-his authorized representative, with the names of welders to be employed in the wink, together with certification that each of these welders has passed a qualification test as prescribed by either of the following listed codes for the type welding operation to be performed, and that such qualification is effective as defined by that particular code as follows :

a. Standard Qualification Procedure of the American Welding society.
b. welding Qualif ication of the American Society of Mechanical Engineers .

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the perfomance of all inspection requiremets (exami" nations and tests) as Specified herein. Except as otherwise specif ied in the contract or purchase order, the contractor may use his own or any other facilities suitable for the perfor-mance of the inspection requiements specif ied herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:20Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specif ication shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling impaction, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimesional requirements. unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all Specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements."

4.1.3 Certificates of compliance. When certificates of compliance are submitted, the Governmentt reserves the right to inspect such items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1), it shall be examined for the defects specified in 4.4.2, 4.4.3, and, unless otherwise specified (see 6.3.1 and 6.3.2), shall be tested as specified in 4.4.4. The presence of any defect or failure to pass any test shall be cause for re jection of the f irst article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modif ied, or qualif ied in this specification or applicable purchase document.

4.4.1.1 Component and material certification. Certificates, certified test reports, or listing marks for codes and standards, as applicable, submitted in accordance with 3.2 and 4.5 shall be examined and validated as proof of compliance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:20Z
Check the source to verify that this is the current version before use.

4.4.2 In-process inspection.

4.4.2.1 Surface inspection. Examination of surface preparation prior to welding shall be made to determine compliance with 3.10.1. Examination of surface preparation, pretreatment and priming prior to each succeeding phase, and top coating shall be made to determine compliance with MIL-T-704 . Whenever nonconformance is noted, correction shall be made to the applicable process and all affected items shall be brought into compliance. Parts which cannot be corrected shall be removed from production.

4.4.2.2 Wiring inspection. Examination of wiring procedures and marking shall be made to determine compliance with 3.5.2.2. Whenever nonconformance is noted, correction shall be made to the applicable process and all affected items shall be brought into compliance. Parts which cannot be corrected shall be removed from production.

4.4.2.3 Moisture and fungus treatment l Examination of treatment procedures shall be made to determine compliance With 3.5.2.5. Whenever nonconformance *is* noted correction shall be made to the applicable process and all affected items shall be brought into compliance. Parts which cannot be corrected shall be removed fron production.

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table 1. The lot size shall be expressed in units of washing machines . The sample unit shall be one washing machine. The inspection level shall be 11 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Finish	Color not as specified		201
	Blistered, peeled, chipped, or area of no film		202
	Poor touch-up, orange peel, color separation, smudge, scale, scratched, stained, overspray, sag, imprint, or foreign matter imbedded		203
Design, construction and workmanship applicable to all components and assemblies	Any component or part missing or not specified type or size	101	
	Any component that does not function, malfunctions, or is misplaced to the degree that it does not serve its intended purpose	102	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:20Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Design, construction and workmanship applicable to all components and assemblies (cont'd)	Not fabricated as specified by the document or drawing	103	
	Not clean (evidence of oil, grease, or dirt)		204
	Sharp edge or burr		205
	Puncture, fracture, or malformed	104	
	Design detail deviating from document or drawing requirements	105	
	Evidence of scale, rust, discoloration, or deposit of any foreign matter		206
	Finish omitted or not as specified:		
	a. On brass or aluminum components		207
	b. On steel components	106	
	Area of partial or no finish		208
Riveting	Mating surfaces of riveted components not drawn up tightly 1/	107	209
	Rivet head not in contact with its mating surface 1/	108	210
	Rivet loose - not properly set 1/	109	211
	Roll of a rivet contains more than one split		212
	Portion of a rivet is set or rolled on itself in lieu of being set or rolled on the mating surface of the component	110	
Welding	Missing, incomplete, cracked, fractured, or not fused	111	
	Undercut, not smooth and uniform, or scale or flux deposits not removed		213
Soldering (when applicable)	Missing, not adherent, or incomplete		214
	Not clean (flux residue not removed, pinholes in solder)		215
Bolts, nuts, screws, studs, and other types of threaded fasteners	Broken, stripped, fractured, or not tight		216

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:20Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Electrical assembly	wiring cut , abraded, or not properly installed or joined	112	
	Adequate slack not provided for wiring to relieve strain		217
Marking	Missing; incorrect; incomplete; illegible; of improper size, location, sequence, or method of application	113	

1/ This defect shall be scored as major when seriously affecting serviceability or appearance and minor when affecting serviceability or appearance but not seriously.

4.4.4 End item dimensional examination. The end items shall be examined for compliance with dimensions as specif ied in this specification and on the drawings . Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension that is not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of washing machines. The sample unit shall be one washing machine. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.5 End item testing. Each production end item shall be tested for the characteristics listed in table II. Failure of any test shall be cause for rejection of the end item.

TABLE II. End item tests

Characteristic	Requirement paragraph	Test method
Signal devices	3.6.1	4.6.1
Chart or card preparation	3.6.2	4.6.2
Control enclosure	3.6.3	4.6.3
Washer door switch	3.6.4	4.6.4 and 4.6.4.1
Washer belt guard	3.6.5	4.6.5
Cylinder speed	3.6.6	4.6.6
Washing machine operation	3.6.7	4.6.7, 4.6.7.1, and 4.6.7.2
Cleaning capability	3.6.8	4.6.8
Moisture removal	3.6.9	4.6.9
Door gasket	3.6.10	4.6.10
Endurance	3.6.11	4.6.7.2 and 4.6.11

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:20Z
Check the source to verify that this is the current version before use.

TABLE II. End item tests (cont'd)

Characteristic	Requirement paragraph	Test method
Road traverse	3.6.12	4.6.12 and 4.6.13
Rail impact	3.6.13	4.6.14
Leaks	3.6.14	4.6.15

4.4.6 Packaging inspection. The sampling and inspection of the preservation, packaging, and container marking shall be in accordance with the requirements of MIL-L-3153.

4.5 Code and standard compliance. Certifications, certified test reports, or listing marks for standards submitted in accordance With 3.2 shall be examined and validated as proof of compliance. Prior to Government approval of first shipment, the contractor shall submit to the contracting officer or his authorized representative for approval, certification that the trailer mounted washing machine he proposes to furnish under this specification meets the applicable requirements of NFPA Standard No. 70, UL Standard Nos. 50 and 83, NEMA Standard MG-1, FMYL Standard class Nos. 3820 and 8100 as follows:

4.5.1 NFPA. Acceptable evidence of meeting the requirements of NFPA shall be a certificate of compliance certifying that the wiring of the trailer mounted washing machine conforms to NFPA Standard No. 70.

4.5.2 UL. Acceptable evidence of meting the applicable requirements of the Underwriters Laboratories shall be a UL listing mark or a certified test report from a recognized independent testing laboratory indicating the control unit enclosure has been tested as specified and conforms to UL Standard Nos. 50 and 83. Such evidence bust be acceptable to the contracting off icer.

4.5.3 NEMA. Acceptable evidence of meting the requirements of NEMA shall be a certificate of compliance certifying that the rotors conform to NEMA Standard MG-1.

4.5.4 FMTL. Acceptable evidence of meting the requirements of the Factory Mutual Testing Laboratories Standards class Nos. 3820 and 8100, as applicable, shall be submitted. Such evidence must be acceptable to the contracting officer.

4.6 Methods of inspection.

4.6.1 Signal devices test. Testing of signal devices shall take place using a pre-cut program card or chart conforming to FM 10-280, Formula 1. Any nonconf ormance with the requirements of 3.6.1 shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:20Z
Check the source to verify that this is the current version before use.

4.6.2 Chart or card preparation test. Prepare one chart or card for Formula III of FM 10-280. Any nonconformance with the requirements of 3.6.2 shall constitute failure of this test.

4.6.3 Control enclosure test. The Control enclosure shall be tested for the dust, automized water, icing, and hosedown requirements of UL 50. **Any** nomonformance with the requirements of 3.6.3 shall constitute failure of this test.

4.6.4 Washer door switch static test. With the washer door open, engage the starting switch. Any nonconformance with 3.6.4 shall constitute failure of this test.

4.6.4.1 Washer door switch Operational test . with the washer door closed and no water in the cylinder engage the starting switch. After 30 seconds of operation open the door. Any nonconformance with the requirements of 3.6.4 shall constitute failure of this test.

4.6.5 Washer belt guard test. without the washer operating, f irmly grasp the belt guard from the rear and attempt to move it laterally. Repeat the procedure and attempt to move the guard forward and rearward. **Any** nonconformance with the requirements of 3.6.5 shall constitute failure of this test.

4.6.6 Cylinder speed test. The speed of the washer cylinder shall be determined by the use of a tachometer. The tachometer used shall be accurate to ± 1 rpm. Any nonconformance with the requirements in 3.6.6 shall constitute failure of this test.

4.6.7 Washing machine operational test. With all utility systems connected, manually operate the washer without clothes. Activate individually each intake and discharge valve. Drain the system between each intake test. Activate the remaining switches and verify that each operates. Any nonconformance with the requirements of 3.6•7 shall constitute failure of this test .

4.6.7.1 Washing machine operational loaded test. Upon completion of 4.6.7 load the washer with 60 pounds (dry weight) of wool blankets (type I or II of MIL-B-844) and launder using the program chart or card for wool. The program shall conform to FM 10-280, Formula II. Verify that each cycle time and water level conforms to Formula II. Repeat the procedure utilizing 60 pounds (dry weight) of cotton sheets (MIL-S-36868) and lauder using the program chart or card for cotton sheets. The program shall conform to FM 10-280, Formula III. verify that each cycle time an water level conforms to Formula III. Repeat the procedure utilizing 60 pounds (dry weight) of the trousers (MIL-T-44047) and launder using the program chart or card for the trousers. The program shall conform to FM 10-280, Formula VIII. Verify that each cycle

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:20Z
Check the source to verify that this is the current version before use.

time and water level conforms to Formula VIII. Upon completion of this, load the washer with 60 pounds (dry weight) of wool blankets (type I or II of MIL-B-844) and launder operating the unit in the manual mode utilizing the cycles, times, and water levels noted in FM 10-280, Formula II. Upon completion of this, visually inspect the control unit, program reading device, interior of the washer cylinder, rotor, gear box, intake valves, discharge valves, door glass, and franc. Any programming errors which result in incorrect formula operation will be remedied and the particular test repeated. Programming errors are defined as incorrectly prepared formula charts or cards . Any nonprogramming nonconformance With 3.6.7 during automatic or manual operation shall constitute failure of this test.

4.6.7.2 Twenty hour test (see 6.3.1). Upon completion of 4.6.7.1, load the washer with 60 pounds (dry weight) of wool blankets (type I or II of MIL-B-844) and launder using the program chart or card for wool. The program shall conform to FM 10-280, Formula II. No detergent is required. The washer shall process the wool blankets for 20 consecutive hours at the rate of two cycles per hour. Upon completion of this, visually respect the control unit , program reading device, interior of the washer cylinder, motor, gear box, intake valves, discharge valves, door glass, and frame. Any nonconformance with 3.6.7 shall constitute failure of this test.

4.6.8 Soil removal test. The washer shall be loaded With 60 pounds of cotton sheets conforming to MIL-S-36868 and 10 standard clay soiled swatches laboratory prepared conforming to ASTM D 3050. Launder the items per FM 10-280, Formula 1. After processing, determine the level of soil removal as detailed in ASTM D 3050. The laundry detergents and supplies shall be as specif ied in FM 10-280, Formula I. Any nonconformance with 3.6.8 shall constitute failure of the test.

4.6.9 Moisture removal test. The washer shall be loaded with 60 pounds of the trousers (MIL-T-44047) and laundered in accordance with FM 10-280, Formula VIII. Upon completion of the final rinse cycle weigh the clothes. Any nonconformance with 3.6.9 shall constitute failure of the test.

4.6.10 Door gasket test. Replace the washer door gasket using a new contractor furnished gasket and operate the washer through a 5 minute wash cycle at an 11 inch water level. Any nonconformance With 3.6.10 shall constitute failure of the test.

4.6.11 Endurance test. The washer shall process wool blankets for 160 hours at the rate of two cycles per hour. This shall be accomplished in 8 consecutive 20 hour days. Loaad the washer with 60 pounds (dry weight) of wool blankets (type I or 11 of MIL-B-844) and launder using the program chart or card for wool. Supplies and detergents are required. Throughout the duration of this test and upon completion, visually inspect the control unit, program reading device, interior of the washer cylinder, rotor, gear box, air controls, discharge valves, door glass, welds, and frame. Any nonconf ormance

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T00:20Z
Check the source to verify that this is the currentversion before use.

with 3.6.11 shall constitute failure of this test, and will require correction of the failure/defect, and the entire test shall be restarted from the beginning.

4.6. 12 Thirty mile road and terrain test (see 6.3.1). The comletely assembled washer mounted on the Government furnished Trailer Mounted Laundry shall be towed over not less than 10 miles of paved roads at speeds up to 50 mph as road and weather conditions permit (see 4.6. 12.1) and over not less than 10 miles of graveled roads at speeds averaging 35 mph (see 4.6.12.1) and over not less than 10 miles of open terrain and cross country at speeds averaging 5 mph (see 4.6.12.2). At the completion of road and terrain test load the washer with 60 pounds (dry weight) of wool blankets (type I or II of MIL-B-844) and launder using the program chart or card for wool. The program shall conform to FM 10-280, Formula II. No detergent is required. The washer shall process the wool blankets for two consecutive loads at the rate of two cycles per hair. Throughout the duration of this test and upon completion, visually inspect the control unit, program reading device, interior of the washer cylinder, rotor, gear box, intake valves, discharge valves, door glass, and frame. Any nonconformance with 3.6.12 shall constitute failure of this test.

4.6.12.1 Paved and graveled roads. The paved and graveled road tests shall each include not less than 20 quick starts and 20 quick stops on grades of not less than 5 degrees or more than 10 degrees. Fifty percent of the starts shall be made on the ascending grades and fifty percent on the descending grades.

4.6.12.2 Open terrain and cross country. The open terrain and cross country course shall have surface irregularities consisting of mounds, racks, brush, and irregularities normally found in cross country or open terrain. The trailer shall be pulled along the course at speeds of not less than 5 mph and not greater than 10 mph. The test drive shall include ten abrupt stop, ten abrupt starts, ten sharp left hand turns, and ten sharp right hand turns. Any nonconformance with 3.6.12 shall constitute failure of this test.

4.6.13 Road and terrain test. The completely assembled washer mounted on the Government furnished mailer Mounted Laundry shall be tested by the Government at a specified location (see 6.2). The test shall be as follows:

a. 125 miles over graveled roads at speeds averaging 35 mph. The graveled road test shall include not less than 20 quick starts and stops on grades of not less than 5 percent or greater than 10 percent. Fifty percent of the starts and stop shall be made on ascending grades and 50 percent on descending grades.

b. 125 miles over Belgian block or similar course averaging 10 mph.

c. 125 miles over hilly cross—country terrain and 125 miles over level cross-country terrain at speeds averaging 10 mph. The open terrain and

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:20Z
Check the source to verify that this is the current version before use.

cross-country course shall have surface irregularities consisting of mounds, rocks, brush, and irregularities normally found in moss-country or open terrain. The test drive shall include 20 abrupt starts, 20 sharp left hand turns, and 20 sharp right hand turns. At the completion of 500 mile road test, load the washer with 60 pounds (dry weight) of wool blankets (type I or II of MIL-B-844) and launder using the program chart or card for wool. The program shall conform to FM 10-280, Formula II. No detergent is required. The washer shall process the wool blankets for two consecutive loads at the rate of two cycles per hair. Upon completion of this, visually inspect the control unit, program reading device, interior of the washer cylinder, rotor, gear box, intake valves, discharge valves, door glass, and frame. Any nonconformance With 3.6.12 shall Constitute failure of this test.

4.6.14 Rail impact test. The assembled washer shall be impact tested by the Government at a specified location (see 6.2). The test shall be in accordance with the Association of American Railroads (AM), Rail Impact Procedure as follows :

a. Forward at 4, 6, and 8 mph.
b. Rearward at 8 mph.

The unit shall not require any special Peking or tiedown for this test. At the comletion of the rail impact test, load the washer with 60 pounds (dry weight) of wool blankets (type I or II of MIL-B-844) and launder using the program chart or carol for wool. The program shall conform to FM 10-280, Formula II. No detergent is required. The washer shall process the wool blankets for four consecutive loads at the rate of two cycles per hour. Upon completion of this, visually inspect the control unit, program reading device, interior of the washer cylinder, motor, gear box, intake valves, discharge valves, door glass, and f ram. Any nonconformance with 3.6.13 shall constitute failure of this test.

4.6.15 Leak test. The high water level control system shall be bypassed to allow the water level to reach 6 inches above the center of the cylinder shaft centerline. sixty pounds of woolens shall be processed using the automatic formula card for FM 10-280, Formula II. During and after processing, a visual inspection shall be performed. Any nonconformance With 3.6.14 shall constitute a failure of this test.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2) in accordance with the applicable requirements of MIL-L-3153.

Packing. Packing shall be level A, B, or Commercial, as specified (see 6. 2), in accordance with the applicable requirements of MIL-L-3153 .

5.3 Marking In addition to any special marking required by the contract or purchase order, unit packs and shipping containers shall *be* marked as specified in MIL-L-3153.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:20Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The trailer mounted washing machine is to provide laundry washing service for troops and hospitals in the field.

6.2 Acquisition requirements. Acquisition documents must specify the following :

a. Title, number, and date of this specif ication.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. When moisture and fungus-resistant treatment is required (see 3.5.2.5).
e. Source and delivery of Government loaned furnished property (see 3.8) Trailer Mounted Laundry Unit, M-85.
f. Required location of road and terrain test and rail impact test (see 4.6.13 and 4.6.14).
g" Levels of preservation and packing (see 5.1 and 5.2).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate previsions of Federal Acquisition Regulation (FAR) 52.209-4. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting off icer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.3.1 Modif ied first article testing for small documents. When the procurement is for less than 25 machines and when authorized by the contracting officer, the first article testing may be modif ied as follows:

a. Substitute the 20 hour washing test specified in 4.6.7.2 for the 160 hour washing test specified in 4.6.11.
b. Substitute the 30 mile road test specified in 4.6.12 for the 500 mile mad test specified in 4.6.13.
c. Omit the rail impact test specified in 4.6.14. The exercise of any or all of these options in no way negates the requirements in 3.6.11, 3.6.12, and 3.6.13.

6.3.2 Modified first article testing when washer is part of Army laundry contract. When the washer is procured as part of a contract for f abrication of the Army Trailer Mounted Laundry per MIL-L-44142, first article testing per 4.6.12, 4.6.13 and 4.6.14 would be accomplished as part of the first article test for the Army Trailer Mounted Laundry.

Source: https://assist.dla.mil -- Downloaded: 202640-22T00:20Z
Check the source to verify that this is the current version before use.

6.4 Subject term (key word) listing .

Field laundering
washing Machine

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:

Army-GL

Review activity:

Army-m

Preparing activity:

Army - GL

(Project 3510-A320)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:20Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-W-44167B(GL)	1992 February 21

3. DOCUMENT TITLE

WASHING MACHINE, LAUNDRY: OPEN END TYPE, TRAILER MOUNTED

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON/DSN
U.S. Army Natick RD&E Center	508-651-4531	256-4531
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: STRNC-UXT Natick, MA 01760-5017	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 Previous editions are obsolete 198/290

Source: https://assist.dla.mil -- Downloaded: 20260-22100:202
Check the source to verify that this is the correct version before use.