INCH-POUND

MIL-W-44167B(GL)
AMENDMENT 1
26 May 1993

MILITARY SPECIFICATION

WASHING MACHINE, LAUNDRY: OPEN END TYPE, TRAILER MOUNTED

This amendment forms a part of MIL-W-44167B(GL), dated 21 February 1992, and is approved for use by the Natick Research, Development, and Engineering Center, Department of the Amy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1, under "SPECIFICATIONS, FEDERAL”:

Add "A-A-54337 - Sheet, Bed (Cotton-Polyester, White, Fitted)”

"QQ-S-571 - ": Delete title and substitute: “Solder, Electronic (96 to 485°C)".

Under "SPECIFICATIONS, MILITARY”:

Delete "MIL-S-36868 - Sheet, Bed, Cotton, White, Fitted Style”.

PAGE 3

2.2, last line: Delete “D 3951 -" and its title.

PAGE 4

2.2, following the ASTM methods and source paragraph, add the following new publication:

"AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

B16.14 - Ferrous Pipe Plugs, Bushings and Locknuts with Pipe Threads

(Application for copies should be addressed to the American National Standards Institute, Inc., 11 West 42nd Street, New York, NY 10036.)”.

PAGE 7

3.5.1, line 7: Delete “drain shall not be used.” and substitute “drain shall be used.”.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:20Z
Check the source to verify that this is the current version before use.

PAGE 8

3.5.1.3, subparagraph “g.”: Delete "including control” and substitute "including power".

3.5.1.3.1, next to last line: Delete “Five minutes of” and substitute “Eight minutes of”.

PAGE 9

3.5.1.5: Add the following to the end of paragraph:

“The washer shall have a reuse water input located in the rear of the unit, no higher than 33 inches and shall be a minimum of 12 inches from the overflow drain. The reuse water input shall be a standard 2 inch nominal pipe size, internal pipe thread, extending out 0.75 to 1.25 inches from the rear wall of the washer. The reuse water input shall be plugged with a 2 inch square pattern plug in accordance with ANSI B16.14.".

PAGE 10

3.5.2.2.2, line 16 and 17: Delete “Terminals on electrical components shall not have more than one wire attached." and substitute “Only one wire shall be used with each terminal wire connector.”.

PAGE 11

3.5.2.4, line 1: Delete “shall not be used” and substitute “shall be used”.

3.5.2.5, line 4: Before "MIL-T-152" add "type II of”.

PAGE 19

4.6.7.1, line 6: Delete "(MIL-S-36868)" and substitute "(A-A-54337)".

PAGE 20

4.6.8, line 2: Delete "MIL-S-36868" and substitute "A-A-54337".

Custodian:

Army - GL

Review activity:

Army - AV

Preparing activity:

Army - GL

(Project 3510-A335)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T00:20Z
Check the source to verify that this is the current version before use.