
MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, CERAMIC DIELECTRIC (TEMPERATURE STABLE AND GENERAL PURPOSE), HIGH RELIABILITY, NONLEADED (HIGH FREQUENCY), STYLE CKS29

This specification is approved for use by all Departments and Agencies of the Department of Defense.


The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-C-123.



Y - DIMENSION MAY GO TO .005 AT EDGES OF TERMINATIONS

Inches	mm
.005	0.13
.011	0.28
.012	0.30
.015	0.38
.016	0.40
.020	0.51
.028	0.70
.110	2.80

Dimensions				
		T		
L ±.020	W ±.020	Min	Max	Y ±.011
.110	.110	.028	.110	.016



CIRCUIT DIAGRAM

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are for general information only.
3. Dimensions are for bare chips; for solder coated terminations add .015 to the length and .012 to the width and thickness envelope.

FIGURE 1. Style CKS29 capacitors.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T05:14Z
Check the source to verify that this is the current version before use.

TABLE I. Style CKS29 characteristics.

Part number 1/	Capacitance (pF)	Capacitance tolerance	Voltage-temperature limits	Rated voltage (V dc)
M123A15B-E0R1B-	0.1	B	BG, BP	500
M123A15B-E0R2B-	0.2	B	"	"
M123A15B-E0R3--	0.3	B, C	"	"
M123A15B-E0R4--	0.4	B, C	"	"
M123A15B-E0R5--	0.5	B, C, D	"	"
M123A15B-E0R6--	0.6	"	"	"
M123A15B-E0R7--	0.7	"	"	"
M123A15B-E0R8--	0.8	"	"	"
M123A15B-E0R9--	0.9	"	"	"
M123A15B-E1R0--	1.0	"	"	"
M123A15B-E1R1--	1.1	"	"	"
M123A15B-E1R2--	1.2	"	"	"
M123A15B-E1R3--	1.3	"	"	"
M123A15B-E1R4--	1.4	"	"	"
M123A15B-E1R5--	1.5	"	"	"
M123A15B-E1R6--	1.6	"	"	"
M123A15B-E1R7--	1.7	"	"	"
M123A15B-E1R8--	1.8	"	"	"
M123A15B-E1R9--	1.9	"	"	"
M123A15B-E2R0--	2.0	"	"	"
M123A15B-E2R1--	2.1	"	"	"
M123A15B-E2R2--	2.2	"	"	"
M123A15B-E2R4--	2.4	"	"	"
M123A15B-E2R7--	2.7	"	"	"
M123A15B-E3R0--	3.0	"	"	"
M123A15B-E3R3--	3.3	"	"	"
M123A15B-E3R6--	3.6	"	"	"
M123A15B-E3R9--	3.9	"	"	"
M123A15B-E4R3--	4.3	"	"	"
M123A15B-E4R7--	4.7	"	"	"
M123A15B-E5R1--	5.1	"	"	"
M123A15B-E5R6--	5.6	"	"	"
M123A15B-E6R2--	6.2	"	"	"
M123A15B-E6R8--	6.8	B, C, J, K	"	"
M123A15B-E7R5--	7.5	"	"	"
M123A15B-E8R2--	8.2	"	"	"
M123A15B-E9R1--	9.1	"	"	"
M123A15B-E100--	10	F, G, J, K	"	"
M123A15B-E110--	11	"	"	"
M123A15B-E120--	12	"	"	"
M123A15B-E130--	13	"	"	"
M123A15B-E150--	15	"	"	"
M123A15B-E160--	16	"	"	"
M123A15B-E180--	18	"	"	"
M123A15B-E200--	20	"	"	"
M123A15B-E220--	22	"	"	"
M123A15B-E240--	24	"	"	"
M123A15B-E270--	27	"	"	"
M123A15B-E300--	30	"	"	"
M123A15B-E330--	33	"	"	"
M123A15B-E360--	36	"	"	"
M123A15B-E390--	39	"	"	"
M123A15B-E430--	43	"	"	"

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T05:14Z
Check the source to verify that this is the current version before use.

TABLE I. Style CKS29 characteristics - Continued.

Part number 1/	Capacitance (pF)	Capacitance tolerance	Voltage-temperature limits	Rated voltage (V dc)
M123A15B-E470--	47	F, G, J, K, M	BG, BP	500
M123A15B-E510--	51	"	"	"
M123A15B-E560--	56	"	"	"
M123A15B-E620--	62	"	"	"
M123A15B-E680--	68	"	"	"
M123A15B-E750--	75	"	"	"
M123A15B-E820--	82	"	"	"
M123A15B-E910--	91	"	"	"
M123A15B-E101--	100	"	"	"
M123A15B-M111--	110	"	"	400
M123A15B-M121--	120	"	"	"
M123A15B-M131--	130	"	"	"
M123A15B-M151--	150	"	"	"
M123A15B-M161--	160	"	"	"
M123A15B-M181--	180	"	"	"
M123A15B-M201--	200	"	"	"
M123A15B-L221--	220	"	"	300
M123A15B-L241--	240	"	"	"
M123A15B-L271--	270	"	"	"
M123A15B-L301--	300	"	"	"
M123A15B-L331--	330	"	"	"
M123A15B-L361--	360	"	"	"
M123A15B-L391--	390	"	"	"
M123A15B-L431--	430	"	"	"
M123A15B-L471--	470	"	"	"
M123A15B-K511--	510	"	"	150
M123A15B-K561--	560	"	"	"
M123A15B-K621--	620	"	"	"
M123A15B-K681--	680	"	"	"
M123A15B-K751--	750	"	"	"
M123A15B-K821--	820	"	"	"
M123A15B-K911--	910	"	"	"
M123A15B-K102--	1000	"	"	"

1/ The complete part number shall include additional symbols to indicate characteristic, capacitance tolerance, and termination, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T05:14Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Case type: Multi-layer, unencapsulated, monolithic.

Material: Ceramic.

Characteristics: BG or BP.

Terminations: In accordance with MIL-C-123; symbols G, S, and T only.

Inspection conditions: All visual examinations shall be performed at 20X magnification, using a binocular microscope.

Capacitance: See table I.

Capacitance tolerance: See table I.

Rated voltage: See table I.

Operating temperature: -55°C to +125°C.

Dissipation factor: 0.025 percent maximum at 1 MHz.

Insulation resistance:

At +25°C ±5°C: 10^6 megohms, minimum.

At +125°C ±5°C: 10^5 megohms, minimum.

Equivalent series resistance: In accordance with MIL-C-123.

Resonance frequency: In accordance with MIL-C-123.

Application note: These capacitors are intended for use in RF solid-state circuitry up to and including 25 GHz and cannot be replaced in the field.

CONCLUDING MATERIAL

Custodians:
Air Force - 19
NASA - NA

Review activities:
Army - ER
Navy - EC
Air Force - 85
DLA - ES

Preparing activity:
NASA - NA

Agent:
DLA - ES

(Project 5910-1613)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T05:14Z
Check the source to verify that this is the current version before use.