INCH-POUND

MIL-PRF-123/18A
18 June 2001
SUPERSEDING
MIL-PRF-123/18
21 November 1989

PERFORMANCE SPECIFICATION SHEET

CAPACITORS, FIXED, CERAMIC DIELECTRIC, (GENERAL PURPOSE), HIGH RELIABILITY, LEADED, STYLE CKS24

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-123.



FIGURE 1. Style CKS24 capacitors.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T05:15Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm
.004	0.10	.019	0.48	.092	2.34
.006	0.15	.020	0.51	.148	3.76
.007	0.18	.028	0.71	.260	6.60
.010	0.25	.035	0.89	.283	7.19
.012	0.30	.058	1.47	.320	8.13
.015	0.38	.090	2.29	.325	8.26

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information.
3. Leads shall be centered within ± .005 (0.13 mm).
4. The angle shall be 95° +10°, -5°.
5. The distance between the centers of the mounting holes will be .300 ± .010 inch (7.62 ± 0.25 mm).
6. Nonconductive material shall not extend beyond .030 inch (0.76 mm) from the edge of the capacitor body.

FIGURE 1. Style CKS24 capacitors - Continued.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Case type: Molded plastic, encapsulated.

Lead wire: Type C of MIL-PRF-123.

Capacitance value: See table I.

Capacitance tolerance: See table I.

Operating temperature: -55°C to +125°C.

Voltage-temperature limits: BR characteristic.

Voltage rating: See table I.

Pre-encapsulation terminal strength: In accordance with MIL-PRF-123.

Marking: In accordance with MIL-PRF-123, example 6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T05:15Z
Check the source to verify that this is the current version before use.

TABLE I. Style CKS24 characteristics.

Part or Identifying Number (PIN) 1/	Capacitance (pF)	Voltage-temperature limits	Capacitance tolerance	Rated voltage (V dc)
M123A18BRC124KC	120,000	BR	K	100
M123A18BRC154-C	150,000	BR	K, M	100
M123A18BRB184KC	180,000	BR	K	50
M123A18BRB224-C	220,000	BR	K, M	50
M123A18BRB274KC	270,000	BR	K	50
M123A18BRB334-C	330,000	BR	K, M	50
M123A18BRB394KC	390,000	BR	K	50
M123A18BRB474-C	470,000	BR	K, M	50

1/ The complete PIN will include additional letter(s) to indicate capacitance tolerance and termination, as applicable.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Navy - EC
Air Force - 19
DLA - CC
NASA - NA

Review activities:
Air Force - 11

Preparing activity:
DLA - CC

(Project 5910-2127-07)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T05:15Z
Check the source to verify that this is the current version before use.