MIL-C-28754/21E
29 November 1991
SUPERSEDING
MIL-C-28754/21D
23 MARCH 1981

MILITARY SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, MODULAR, FRAME, CASTING, TYPE IV, DOUBLE SPAN

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the frame described herein shall consist of this specification and the latest issue of MIL-C-28754.

AMSC N/A FSC 5935

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:37Z
Check the source to verify that this is the current version before use.




FIGURE 1. Dimensions and configurations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:37Z
Check the source to verify that this is the current version before use.





FIGURE 1. Dimensions and configurations - Continued. *

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:37Z
Check the source to verify that this is the current version before use.



DETAIL A

INCHES	MM	INCHES	MM	INCHES	MM	INCHES	MM
.0010	.025	.03	.8	.128	3.25	1.281	32.54
.002	.05	.04	1.0	.130	3.30	1.680	42.67
.003	.08	.050	1.27	.148	3.76	2.030	51.56
.004	.10	.05	1.3	.150	3.81	2.070	52.58
.005	.13	.06	1.5	.155	3.94	3.130	79.50
.006	.15	.085	2.16	.170	4.32	4.800	121.92
.007	.18	.087	2.21	.185	4.70	4.890	124.21
.010	.25	.088	2.24	.195	4.95	5.030	127.76
.01	.3	.090	2.29	.225	5.72	5.200	132.08
.015	.38	.09	2.3	.284	7.21	5.320	135.13
.02	.5	.094	2.39	.288	7.32	5.440	138.18
.020	.51	.0985	2.502	.330	8.38	5.620	142.75
.022	.56	.110	2.79	1.202	30.53		

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:37Z
Check the source to verify that this is the current version before use.

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based on 1.0 inch = 25.4 mm.
3. Unless otherwise specified, tolerance is ±.005 on three place decimals, ±.01 on two place decimals and ±2° on angles.
4. Mark on this area with white characters or raised cast characters .06 inch high, raised .01 maximum. No marking but identifying part number.
5. All surfaces to have 125 microinch finish unless otherwise specified.
6. Fillets and edges will have .02 radius maximum unless otherwise specified.
7. A line passing through the centers of the two .0985 ±.0010 diameter holes establishes -B- .
8. Contact numbers 1 and 20 shall be marked on the pin shield in white characters .06 inch high; on opposite side mark 21 and 40.
9. Casting shall not show evidence of flashing or ejector pin marks that extend above the surface.
10. These 4 holes accommodate insert M28754/41-01 and screw M28754/40-01.
11. Center two H holes shall have a .170 ±.03 diameter area on both sides coated with a chemical film.
12. Draft allowances shall remain within specified part tolerances. *
13. All dimensional measurements shall be made with the part in a restrained position. *

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:37Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Material: Aluminum alloy, casting, 360 or 380 in accordance with QQ-A-591.

Chemical film: MIL-C-5541, class 3 (see note 11).

Anodic coating: MIL-A-8625, type II, class 2, black on all other surfaces except surfaces indicated (see note 11). *

Marking: In accordance with MIL-C-28754 and figure 1.

Military part number: M28754/21-(dash number from table I). *

TABLE I
Dash numbers and characteristics

Dash no	Surface treatment
01	With anodize and chemical film
02	Without anodize, without chemical film, without any marking
03	With anodize, with chemical film, without any marking

Supersession data: This specification includes the requirements of drawing number 2874493-3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:37Z
Check the source to verify that this is the current version before use.

QUALIFICATIONS:

Qualifications testing: Perform the applicable tests as specified in MIL-C-28754 and the appendix thereto. *

Extended qualifications: Qualification of M28754/21-01, /21-02, or /21-03 extends qualifications to other products as specified in the appendix to MIL-C-28754. *

The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notation and relationship to the last previous issue.

Custodians:
Army - CR
Navy - SH
Air Force - 85

Preparing activity: *
Navy - SH

(Project 5935-3813-01)

Review activities:
Navy - MC
Air Force - 11, 99 *
DLA - ES

User activities:
Army - AR, MI
Navy - AS *

Agent:
NW *

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:37Z
Check the source to verify that this is the current version before use.