INCH-POUND
MIL-PRF-94E
AMENDMENT 3
24 OCTOBER 1997
SUPERSEDING
AMENDMENT 2
15 MARCH 1996

PERFORMANCE SPECIFICATION

RESISTOR, VARIABLE, COMPOSITION
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-PRF-94E, dated 10 September 1992, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Bottom of page, delete and substitute :

"

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Supply Center, Columbus, Post Office Box 3990, Columbus, OH 43216-5000, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

"

PAGE 2

TABLE IV, delete and substitute:

"TABLE IV. Style of operating shaft

Symbol	Shaft
F	Flatted
S	Slotted

"

PAGE 3

2.1.1, SPECIFICATION, FEDERAL, delete "QQ-S-571" and its corresponding title.

2.1.1, SPECIFICATION, MILITARY, delete "MIL-R-39032" and its corresponding title.

2.1.1, STANDARD, MILITARY, delete "MIL-STD-45662" and its corresponding title.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:53Z
Check the source to verify that this is the current version before use.

Following 2.1.1, add:

"2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DoDISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS are the issues of the documents cited in the solicitation (see 6.2)

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI/NCSL Z540-1	-	Calibration Laboratory and Measuring and Test Equipment, General Requirements for.
J-STD-006	-	Requirements for Electronic Grade Solder Alloys and Fluxed and Non-Fluxed Solid Solder for Electronic Soldering Applications.

(Applications for copies should be addressed to the American National Standards Institute, 11 West 42nd Street New York, NY 10036.)

INTERNATIONAL ORGANIZATION for STANDARDS (ISO)

ISO 10012-1	-	Quality Assurance Requirements for Measuring Equipment, Part 1: Meteorological Confirmation System for Measuring Equipment.

(Applications for copies should be addressed to the American National Standards Institute, 11 West 42nd Street New York, NY 10036.)"

PAGE 7

3.4.5, delete "QQ-S-571" and substitute "J-STD-006".

After 3.4.5, add the following:

"3.4.5.1 Tin plated finished. Use of tin plating is prohibited as a finish and as an undercoat (see 6.15.1). Use of tin-lead (Sn-Pb) finishes as acceptable provided that the minimum lead content is 3 percent."

PAGE 11

* 4.4.4, delete and substitute:

"4.4.4 Retention of qualification. Every 6 months, the manufacturer shall compile a summary of the results of quality conformance inspections in the form of a retention of qualification report, and forward it to the qualifying activity within 30 days from the end of the reporting period as the basis of continued qualification approval. In addition, the manufacturer shall immediately notify the qualified activity whenever the group B inspection data indicates failure of the qualified product to meet the requirements of the specification. Continuation shall be based on the evidence that over a 6-month period, the following has been met:

a. The manufacturer has not modified the design of the item.

b. The specification requirements for the item have not been amended to affect the character of the item.

c. Lot rejection for group A inspection does not exceed the group A sampling plan.

d. The requirements for group B inspections are met.

When group B requirements are not met and the manufacturer has taken corrective action satisfactory to the government, group B retesting shall be instituted. A summary of the retesting shall be forwarded to the qualifying activity within 30 days after completion of the retest. All reports are to be certified by a responsible company official and government inspector."

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:53Z
Check the source to verify that this is the current version before use.

PAGE 13

4.5.1.1, delete and substitute:

"4.5.1.1 Inspection and production lot.

"4.5.1.1.1 Inspection lot. An Inspection lot, as far as practicable, shall consist of all resistors of the same style (regardless of resistance value), produced in a period not to exceed 30 days, produced under essentially the same conditions, and offered for inspection at one time.

"4.5.1.1.2 Production lot. A production lot shall consist of all resistors of the same style, nominal resistance value, and resistance tolerance. Manufacture of all parts in the lot shall have been started, processed, assembled, and tested as a group. Lot identity shall be maintained throughout the manufacturing process."

PAGE 14

4.5.1.2.1.3.2a., after first sentence add:

"Five samples shall be selected from each production lot that formed the failed inspection lot."

PAGE 15

4.5.1.2.1.3.2b., last sentence, delete and substitute:

"If the lot fails this solderability test, the lot may be reworked and retested. If the lot fails a second rework, the lot shall be rejected and shall not be furnished against the requirements of this specification."

PAGE 16

* Table XV, delete.

* 4.5.2, delete.

* 4.5.3, delete.

PAGE 17

4.6.2a, delete and substitute:

"a. Measuring apparatus: Different types of measuring test equipment (multimeter, bridges, or equivalent) are permitted to be used on the initial and final readings of this test, provided the equipment is the same style and model, or it can be shown that the performance of the equipment is equivalent. The supplier shall establish and maintain a calibration system in accordance with ANSI/NCSL Z540-1, ISO 10012-1, or equivalent system as approved by the qualifying activity."

PAGE 23

5.1, delete and substitute:

"5.1 Packaging. For acquisition purpose, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of material is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity."

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:53Z
Check the source to verify that this is the current version before use.

* 6.3, delete and substitute:

"6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Products List whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from Defense Supply Center, Columbus, ATTN: DSCC-VQP, Post Office Box 3990, Columbus, Ohio 43216-5000."

6.13, end of last sentence, add:

"and table XVII-1 herein."

Before table XVIII, add the following:

" TABLE XVI-1. Performance requirements.

Style	RV2	RV4	RV5	RV6	RV7		RV8
Maximum ambient temperature at rated wattage (see figure 6)	70°C	70°C	70°C	70°C	70°C		70°C
Maximum ambient temperature at zero rated wattage derating (see figure 6)	120°C	120°C	120°C	120°C	120°C		120°C
Power rating in watts Taper A (see 3.5.3.1) Tapers C and F (see 3.5.3.2)	 1.0 0.5	 2.0 1.0	 0.5 0.25	 0.5 0.25	panel 0-2.0	rear 1.6-0	 0.5 0.25
Maximum percent change in resistance							
Rotation life (see 3.10)	10	10	10	10	10		10
Load life (see 3.12)	10	10	10	10	10		10
Moisture resistance (see 3.13)	10 max	10 max	10 max	10 max	10 max		10 max
Low temperature storage (see 3.14)	2	2	2	2	2		2
Low temperature operation (see 3.15)	3	3	3	3	3		3
Thermal shock (see 3.16)	6	4	6	4	4		4
Shock (specified pulse) (see 3.18)	2	2	2	2	2		2
Vibration, high frequency (see 3.19)	2	2	2	2	2		2
Insulation resistance (after moisture resistance) (see 3.130	100 megohms	100 megohms	100 megohms	100 megohms	100 megohms		100 megohms
Resistance tolerance ± percent (see table V)	10 and 20	10 and 20	10 and 20	10 and 20	10 and 20		10 and 20

"

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:53Z
Check the source to verify that this is the current version before use.

After 6.15, add the following:

"6.15.1 Tin plated finishes. Tin plating is prohibited (see 3.4.5.1) since it may result in tin whisker growth. Tin whisker growth could adversely affect the operation of electronic equipment systems. For additional information on this matter, refer to ASTM B545 (Standard Specification for Electrodeposited Coating of Tin)."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - CR
Navy - EC
Air Force - 85

Preparing activity:
DLA - CC

(Project 5905-1500)

Review Activities:
Army - AR, AT, AV, CR4, MI
Navy - AS, MC, OS
Air Force - 17, 19, 99

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:53Z
Check the source to verify that this is the current version before use.