NOTE: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND

MIL-PRF-94/4J
AMENDMENT 1
12 October 1989

PERFORMANCE SPECIFICATION

RESISTORS, VARIABLE, COMPOSITION, STYLE RV2

This amendment forms a part of MIL-R-94/4J, dated 11 September 1985, and is approved for use by all Department and Agencies of the Department of Defense.

PAGE 3

TABLE I, delete and substitute:

"TABLE I. Length of operating shaft. 1/

Symbol	Length of operating shaft from mounting surface at resistors. (nominal)		
	Flatted	Slotted	
	Bushings N and S (inches ±1/32)	Bushings N and S (inches, ±1/32)	Bushings L and T (inches, ±1/32)
A	7/8		5/8
B		1/2	
D		7/8	7/8
E			
G		1 1/4	
J		2	
K		2 1/2	

1/ For resistors with panel seals, the mounting surface shall be considered the metal face of the panel seal when the seal is firmly seated against the resistor body."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:55Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, MI
Navy - AS, OS
Air Force - 17, 99
DLA - ES

User activities:
Army - AT, AV, ME
Navy - CG, MC
Air Force - 19

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5905-1157-3)

Source: https://assist.dla.mil -- Downloaded: 202610-16T04:55Z
Check the source to verify that this is the current version before use.