MIL-R-93/17B
22 November 1968
SUPERSEDING
MIL-R-93/17A
28 December 1965

MILITARY SPECIFICATION

RESISTORS, FIXED, WIRE-WOUND (ACCURATE), STYLE RB58

INACTIVE FOR DESIGN AFTER DATE OF THIS SPECIFICATION (SEE 6.3).

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the detail requirements for style RB58, accurate, wire-wound, fixed resistors.

2. APPLICABLE DOCUMENTS

2.1 The following document, of the issue in effect on date of invitation for bids or request for proposal, forms a part of this specification to the extent specified herein.

SPECIFICATION

MILITARY

MIL-R-93 - Resistors, Fixed, Wire-wound (Accurate), General Specification for.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-R-93, and as specified herein.

3.2 Design and construction. The resistor shall be of the design, construction, and physical dimensions specified on figure 1.


3.3 Minimum resistance value. The minimum resistance value available with each applicable tolerance shall be as follows:

Tolerance (± percent)	Symbol	Minimum resistance (ohms)
0.05	A	100
0.10	B	10
0.50	D	0.1
1.00	F	0.1

3.4 Maximum resistance value (based on use of 0.001-inch nominal diameter wire with a nominal resistivity of 800 ohms per circular mil foot). Maximum resistance value shall be 3.01 megohms.

3.5 Power rating. Power rating shall be 1.0 watt.

Source: https://assist.dla.mil -- Downloaded: 202610-16T04:51Z
Check the source to verify that this is the currentversion before use.



Dim	Inches	Millimeters
A	1.500 ±.062	38.10 ±1.57
B	2.000 ±.125	50.80 ±3.18
C	.032 ±.002	.81 ± .05
D	.500 ±.031	12.70 ± .79

NOTE:
Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.

FIGURE 1. Style RB58 resistor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:51Z
Check the source to verify that this is the current version before use.

3.6 Maximum voltage. Maximum voltage shall be 900 volts direct current or peak.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection shall be in accordance with MIL-R-93.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with MIL-R-93.

6. NOTES

6.1 Notes. In addition to the notes specified herein, the notes specified in MIL-R-93 are applicable to this specification.

6.2 Supplementary insulation. Where potential to ground is over 250 volts, supplementary insulation should be provided.

* 6.3 Authorized use. The resistors specified herein are not for use in design after date of this specification. They are authorized for use in design contracts effective prior to on the date of this specification, and to support existing military equipment.

* 6.4 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - EL
Navy - EC
Air Force - 11

Review activities:
Army - EL, MU, MI
Navy - EC, AS, OS
Air Force - 11, 17, 85
DSA - ES

User activities:
Army - ME, AV
Navy - MC
Air Force - 19

Preparing activity:
Army - EL

(Project 5905-0660-12)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:51Z
Check the source to verify that this is the current version before use.