MIL-C-11504C (MU)
1 October 1964
SUPERSEDING
MIL-C-11504B (MU)
12 April 1963

MILITARY SPECIFICATION

CHARGE, DEMOLITION, BLOCK, INERT, 1 POUND PARTS AND LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the quality assurance provisions, and requirements not covered by the drawings, for the parts and loading, assembling and packing for one type of practice item designated as Charge, Demolition, Block, Inert, 1 Pound.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on the date of invitations for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons; General Specification for.
MIL-P-10025 - Packaging, Packing and Marking for Interplant Shipment of Inert Ammunition Components, General Specification for.
MIL-I-45208 - Inspection Requirements; General Specification for.
MIL-I-45607 - Inspection Equipment; Supply and Maintenance of.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105).

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:16Z
Check the source to verify that this is the current version before use.

MIL-STD-109 - Quality Assurance Terms and Definitions.
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes.

DRAWINGS

ORDNANCE CORPS

8886602 - Charge, Demolition, Block, 1 lb., Inert

PUBLICATIONS

ORDNANCE CORPS

IEL-8886602 - Index of Inspection Equipment Lists.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material.-Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Inert charge assemblies.-The inert charge assemblies shall comply with all requirements specified on Drawing (dwg.) 8886602 and with all requirements specified in applicable specifications.

3.3 Crimping.-During the crimping operation, the edge of neither end shall penetrate the outer layer of paper.

3.4 Workmanship.-All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Surface coatings shall be continuous except for a few light scratches not exposing base material. All required marking shall be neat and sharply defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:16Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Contractor quality assurance system.-The contractor shall provide and maintain an effective quality assurance system in compliance with the requirements of Specification MIL-I-45208. The contractor's quality assurance system shall contain a procedure for the reporting of critical defectives found during the course of his inspection and during inspection by the Government. Any critical defect encountered, unless annotated by an asterisk (*) to the right of the characteristic code number (see 6.2), will be reported within 48 hours. A monthly summary report covering those critical defects annotated by an asterisk will be furnished. The agencies to whom the reports will be furnished are identified in paragraph 6.5. The reports shall contain, as a minimum, the following information:

a. Contractor and contract number.
b. Number and revision date of specification.
c. Characteristic code number.
d. Lot or serial number.
e. Number of defectives found.
f. Assignable cause or analysis of occurrence.
g. Corrective action taken or recommended. When the corrective action is beyond the control of the contractor or the scope of the contract, the report shall contain the contractor's recommendation to the Government.

4.1.2 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:16Z
Check the source to verify that this is the current version before use.

a. A statement that the lot complies with all quality assurance provisions of the approved current written description of the system.
b. Number of units of product inspected.
c. Results obtained for all inspection performed.
d. Drawing, specification number and date, together with an identification and date of changes.
e. Certificates of compliance on all material purchased by the contractor when such material is controlled by Government specifications referenced in any of the contractual documents.
f. Number of items in the lot.
g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.3 Government verification.-Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be in accordance with Specification MIL-I-45208 and will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual chara teristics will be directly related to the seri usness of the classif cation assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records.

4.2 Inspection provisions.

4.2.1 Lot formation.-A lot shall consist of inert charge assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification, and same specification revision. Drawing, specification, and process changes not affecting safety, performance or fit, as determined by the Government shall not necessitate changing the lot interfix number.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:16Z
Check the source to verify that this is the current version before use.

4.2.2 Examination.-Sampling plans and procedures for the following classifications of defects shall be in accordance with Standard MIL-STD-105 (ABC-STD-105) except that inspection for critical defects, when listed, shall be 100 percent. Continuous sampling plans in accordance with Standard MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to the individual characteristics listed using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

4.2.2.1 Adapter end (see dwg. 8885256 covering a detail of dwg. 8886602).

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Profile of helix angle	Gage	01001
Minor:	AQL 1.00 percent		
201.	Paint missing or color incorrect	Visual	01002
202.	Evidence of poor workmanship (see 3.4)	Visual	01003

4.2.2.2 Block (see dwg. 8886604 covering a detail of dwg. 8886602).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 percent		
101.	Depth of small cavity, minimum (min.)	Gage	02001
102.	Depth of counterbore, min	Gage	02002

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:16Z
Check the source to verify that this is the current version before use.

	103. Diameter of cavity and counterbore, min	Gage	02003
Minor:	AQL 0.65 percent		
	201. Evidence of poor workmanship (see 3.4)	Visual	02004

4.2.2.3 Assembly, prior to assembling adapter end (see dwg. 8886602).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
	101. Crimp penetrating outer layer (see 3.3)	Visual	03001
	102. Top block inverted	Visual	03002
Minor:	AQL 1.00 percent		
	201. Interior coating missing	Visual-Manual	03003
	202. Evidence of poor workmanship (see 3.4)	Visual	03004

4.2.2.4 Assembly (see dwg. 8886602).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 percent		
	101. Adapter end crimp penetrates outer layer (see 3.3)	Visual	04001
	102. Crimp inadequate	Visual	04002
	103. Contents loose	Manual	04003
Minor:	AQL 0.65 percent		
	201. Total length, maximum	Gage	04004
	202. Tape not covering perforated disc	Visual	04005
	203. Exterior wrapper missing	Visual	04006
	204. Marking missing, misleading or unidentifiable	Visual	04007

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:16Z
Check the source to verify that this is the current version before use.

4.2.3 Testing

4.2.3.1 Crimp strength of ends (flat crimp) (see dwg. 8886602) Major defect - Code No. 04008.-A sample of 25 inert charge assemblies shall be selected from each lot for this test. Testing shall be as specified in 4.3.1 using the applicable test equipment of 4.2.4. If two or more ends fail to meet the requirement, a second sample of 50 assemblies shall be submitted to the test. Acceptance testing shall be stopped and the lot rejected when one end fails to meet the requirement during the testing of the second sample.

4.2.4 Inspection Equipment.-Index of Inspection Equipment Number IEL-8886602 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.2.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the IEL may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.2.4.2 Supply and maintenance.-Supply and maintenance of the equipment listed on the IEL shall be in accordance with Specification MIL-I-45607.

4.2.4.3 Government use of contractor's inspection and test equipment.-The contractor shall make available to the Government all inspection and test equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment, and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

4.3 Test methods and procedures.

4.3.1 Crimp strength of ends.-The assembly shall be assembled to the applicable test equipment and the required force applied parallel to the centerline of the assembly. In the event either end separates or shows evidence of separation, the assembly shall be classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:16Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking.

5.1.1 Level C.-The inert charge assemblies shall be packed and marked in accordance with Specification MIL-P-10025.

5.2 Data cards.-Data card information shall be prepared for each lot in accordance with the procedures specified in Specification MIL-A-2550.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify title, number and date of this specification.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the referenced Inspection Equipment Lists (IEL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.7.

6.3.1 Inspection equipment lists.-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (OO Form 1242-3) the numbers of drawings of existing equipment designs or codes as indicated in paragraph 6.3.2. Design action required of the contractor with respect to the different types of drawings that may be listed is described in paragraphs 6.3.3 and 6.3.4. Action required by the contractor with respect to commercial inspection equipment is described in 6.3.5. The contractor will be required to prepare detailed drawings in accordance with 6.3.6 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:16Z
Check the source to verify that this is the current version before use.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3, 6.3.4, 6.3.5 and 6.3.6 will be designed in the IEL by the following codes:

CDAF - Contractor's design responsibility on Army format in accordance with MIL-D-45608.
CDCF - Contractor's design responsibility on contractor format.
AD - Army design.
ADMU - Army design, mandatory for use.
CE - Commercial equipment.
SCD - Specification control drawing.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications, mandatory and non-mandatory. When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.4 Specification control drawing.-Specification control drawings depict the minimum equipment requirements in outline, descriptive, diagramatic or pictorial form only and specify the required performance or other characteristics. Contractors must prepare detailed drawings (see 6.3.6) of their designs in support of specification control drawings. These contractor prepared designs must be approved by the Government prior to the fabrication or procuring of the equipment. Commercial equipment meeting the requirements of specification control drawings may be approved if described in sufficient detail to permit identification and evaluation by the Government. Designs shall be submitted for approval as specified in 6.3.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:16Z
Check the source to verify that this is the current version before use.

6.3.5 Commercial equipment.-Commercial equipment is inspection equipment that has universal application for a specific function. It is comprised of items commonly used by industry and Government. Contractors are not required to furnish drawings of commercial inspection equipment, but a list of such equipment must be approved by the Government. Lists shall be submitted for approval to the inspection element of the agency administering the contract.

6.3.6 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Contractor designs identified as CDCF may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above. Contractor designs identified as CDAF shall comply with the format and requirements of MIL-D-45608, and in addition, contain the detail and information specified above.

6.3.7 Submission of contractor designs.-Designs shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND. Design review will normally be accomplished within one month after receipt by Picatinny Arsenal. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs.

6.4 Submission of Initial Production, Pre-Production or Qualification Samples.-Instructions, as to the location for the evaluation of Initial Production, Pre-production, or product qualification shall be obtained from the contracting officer. Upon receipt of such request, the contracting officer shall advise Picatinny Arsenal and instructions will be issued accordingly. All inquiries should be forwarded to: Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-NI.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:16Z
Check the source to verify that this is the current version before use.

6.5 Submission of critical defect reports.-For U. S. Army Munitions Command procurements, one copy of each critical defect report will be furnished the cognizant Government inspection agency; the Army Ammunition Procurement and Supply Agency, ATTN: SMUAP-RO; Picatinny Arsenal, ATTN: SMUPA-ND.

6.5.1 Reporting to other services.-For other than U. S. Army Munitions Command procurements, critical defect reporting shall be as prescribed by the Contracting Officer.

Custodian:
Army-MU

Preparing activity:
Army-MU

Project No. 1375-A782

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:16Z
Check the source to verify that this is the current version before use.