NOT MEASUREMENT SENSITIVE


MIL-DTL-11484/440
25 May 2021

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, SURVIVOR RECOGNITION, U.S. CUSTOMS AND BORDER PROTECTION

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-11484.



MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: Epoxy resin, 24K Gold Plated, Matte Finish, Polished Highlights and shall match The Institute of Heraldry Metal Finish Chip Number 8.

DIMENSION:
DIAMETER: 3/4 inch (REF)
THICKNESS: 0.075 inch ± 0.010 inch

ATTACHING DEVICE:
1. The attaching device shall be prong with pick and wing type clutch.

2. The prong shall be centered on the vertical center line on the reverse side, 1/4 inch from the top and fused or soldered to the lapel button.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:14Z
Check the source to verify that this is the current version before use.

EPOXY: Epoxy resin shall be applied to the lapel button as indicated below, and shall match TIOH Hard Enamel Color Chip Numbers listed below. All epoxy shall be floating epoxy.

TIOH HARD ENAMEL COLOR CHIPS	
COLOR CHIP	**LOCATION**
Blue #20	Background
Black #26	Diagonal stripe

NOTE:
The term (REF) refers to the measurements taken from the obverse Government furnished hub or die.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2021-534)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:14Z
Check the source to verify that this is the current version before use.