NOT MEASUREMENT SENSITIVE


MIL-DTL-11484/442
14 October 2021

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, OUTSTANDING UNIT AWARD, DEPARTMENT OF HOMELAND SECURITY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-11484.



MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: 24K Gold Plated, Mirror-like Polished and shall match The Institute of Heraldry Metal Finish Chip Number 6.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:14Z
Check the source to verify that this is the current version before use.

DIMENSIONS:
HEIGHT: 9/16 inch (REF)
WIDTH: 21/32 inch (REF)
THICKNESS: 0.065 ± 0.010 inch

ATTACHING DEVICE:
1. The attaching device shall be prong with pick and wing type clutch.

2. One prongs shall be located on the horizontal center line, 1/4 inch from the top.

EPOXY: Epoxy resin (Stoning epoxy) shall be applied to the Lapel Button as indicated below, and shall match TIOH Hard Enamel Color Chip Numbers listed below.

TIOH HARD ENAMEL COLOR CHIPS	
COLOR AND NUMBER	**LOCATION**
Red #1	1st and 13th stripe
Blue #20	3rd, 11th, 6thand 8th stripe
White #28	2nd, 12th, 5th, and 9th stripe
Blue #33	4th and 10th stripe
Green #12	7th stripe

NOTES:
The term (REF) refers to the measurements taken from the Government furnished hub or die.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2022-010)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:14Z
Check the source to verify that this is the current version before use.