NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/445
07 March 2022

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, INSPECTOR GENERAL BADGE, U.S. ARMY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-11484.

ALL LIGHT SHADED AREAS
TO BE CHIP 18



ALL DARK SHADED AREAS
TO BE CHIP 20

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: 24K Gold Plated, Matte Finish Polished Highlights and shall match The Institute of Heraldry Metal Finish Chip Number 8.

DIMENSIONS:
DIAMETER: 3/4 inch (REF)
THICKNESS: 0.090 ± 0.010 inch

ATTACHING DEVICE:
1. The attaching device shall be prong with pick and wing type clutch.

2. One prong shall be placed on the vertical centerline, 1/4 inch from the top edge.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:14Z
Check the source to verify that this is the current version before use.

EPOXY: Floating epoxy resin shall be applied to the lapel button as indicated above and shall match TIOH Hard Enamel Chip Numbers listed below. If hard enamel is used, then the material will be Gilding Metal 95/5 (UNS Alloy C-210).

TIOH HARD ENAMEL COLOR CHIPS	
COLOR AND NUMBER	**LOCATION**
Blue #18	Letters of the wreath
Blue #20	Background

NOTE:
The term (REF) refers to the measurements taken from the Government furnished hub or die.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2022-068)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:14Z
Check the source to verify that this is the current version before use.