NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/446
28 July 2023

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, CIVILIAN RETIREE, U.S. SPACE FORCE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-11484.



MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: Nickel Plated, Mirror-Like Polished and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 16.

DIMENSIONS:
DIAMETER: 5/8 inch (REF)
THICKNESS (At thickest point): 0.075 inch ± 0.010 inch

ATTACHING DEVICE:
1. Attaching device shall be prong with pick and wing type clutch.

2. The prong shall be on the vertical center line 1/4 inch from the top of the lapel button on the reverse side and fused or soldered to the lapel button.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:14Z
Check the source to verify that this is the current version before use.

EPOXY: Epoxy resin shall be applied to the lapel button as indicated above and shall match TIOH Hard Enamel Color Chip Numbers listed below. Hard cloisonné enamel may be used in lieu of epoxy. If hard cloisonné enamel is used, the required base material shall be Gilding Metal 95/5 (UNS Alloy C-210):

COLOR:	LOCATION:
Blue Epoxy #20	Designation band (Outer Ring)
Black Epoxy #26	Delta

NOTE:
1. The term (REF) refers to measurements taken from the Government furnished hub or die.

Custodians:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review Activity:
DLA - CT

(Project No. 8455-2023-190)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:14Z
Check the source to verify that this is the current version before use.