NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/459(IH)
27 May 2026

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, U.S. FOOD AND DRUG ADMINISTRATION

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-11484.

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: 24K Gold-Plated, Matte Finish, Polished Highlights and shall match The Institute of Heraldry Metal Finish Chip Number 8.

DIMENSIONS:
(Overall): 11/16 inch (REF)
THICKNESS (At thickest point): 0.084 inch ± 0.005 inch

ATTACHING DEVICE:
1. Attaching device shall be prong with pick and wing type clutch

2. The prong shall be located on the vertical center line 1/4 inch from the top of the lapel button on the reverse side and fused or soldered to the lapel button.

EPOXY: Stoned Epoxy resin shall be applied to the lapel button as indicated above and shall match TIOH epoxy Color Chip Numbers listed below.

COLOR	LOCATION
Blue Epoxy #20	Outer Band Around Letters, Numbers and Triangles

NOTE:
The term (REF) refers to the measurements taken from the obverse Government furnished hub or die.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:15Z
Check the source to verify that this is the current version before use.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2026-329)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:15Z
Check the source to verify that this is the current version before use.