DATA ITEM DESCRIPTION

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 110 hours per response, including the time for reviewing information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of reducing this burden, to Washington Headquaters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA. 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC. 20503.

1. TITLE	2. IDENTIFICATION NUMBER
LSA-056, FAILURE MODES, EFFECTS, AND CRITICALITY ANALYSIS (FMECA) REPORT	DI-ILSS-81163A

3. DESCRIPTION/PURPOSE

3.1 This report contains failure mode and effect analysis, criticality analysis, maintainability information, damage mode and effect analysis, and minimum equipment listing information. This report should be used to identify candidates for RCM analysis or design reviews, identify failure modes which impact item criticality number and SHSC assignment.

4. APPROVAL DATE (YYMMDD)	5. OFFICE OF PRIMARY RESPONSIBILITY (OPR)	6a. DTIC APPLICABLE	6b. GIDEP APLLICABLE
920923	TM		

7. APPLICATION/INTERRELATIONSHIP

7.1 This Data Item Description (DID) contains the format and content preparation instructions for the Logistic Support Analysis Record (LSAR) report required by Appendix B, Paragraph 30.31 of MIL-STD-1388-2B.

7.2 This DID is applicable to the acquisition of military systems and equipment.

7.3 This DID supersedes DI-ILSS-81163.

8. APPROVAL LIMITATION	9a. APPLICABLE FORMS	9b. AMSC NUMBER
		A6821

10. PREPARATION INSTRUCTIONS

10.1 Reference documents. The applicable issue of the documents cited herein, including their approval dates and the dates of any applicable amendments, notices, and revision, shall be specified in the contract.

10.2 Format. The report shall be prepared in the format of MIL-STD-1388-2B, Appendix B, Figure 45, using one or more of the report selections specified below.

10.3 Content. The source of data appearing on the LSA-056 summary is contained in Appendix B, Figure 14, LSAR Data Tables to Report Matrix. Data displayed on the report is not required if the data is not specified on DD Form 1949-3, LSAR Data Requirements Form, contained in the statement of work.

10.3.1 Calculations of Item Criticality Number, Failure Mode Criticality Number, and Total Failure Mode Ratio shall be performed in accordance with the formula contained in Appendix B, Paragraph 30.31.2.

10.3.2 The FMECA Report consists of the following:

a. Part I, FMECA Worksheet Summary.
b. Part II, Criticality Analysis Summary.
c. Part III, Failure Mode Analysis Summary

(continued on page 2)

11. DISTRIBUTION STATEMENT

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:44Z
Check the source to verify that this is the current version before use.

Block 10. Preparation Instructions (continued)

10.3.3 Mandatory and optional report selections. The LSA-056 report consists of the following mandatory selections:

a. End Item Acronym Code
b. Start LCN
c. LCN Type (Functional or Physical)
d. Usable On Codes
e. Service Designators

The following are optional selections for the LSA-056 report:

a. Alternate LCN (default is all ALCs)
b. Stop LCN (default is all LCNs subordinate to, and including, the Start LCN)
c. Report Parts 1, 2, 3 (default is no Part is selected)

1. Report Part 1 is further selectable as follows

(a) Safety Hazard Severity Codes (default is SHSCs of 1 and 2 only)

2. Report Part 2 is further selectable as follows

(a) Safety Hazard Severity Codes (default is SHSCs of 1 and 2 only)
(b) Failure Mode Criticality Number value
(c) Failure Probability Level value (a selection must be made against Failure Mode Criticality Number or Failure Probability Level; if Failure Mode Criticality Number and Failure Probability Level are both selected default to Failure Mode Criticality Number)

3. Report Part 3 is further selectable as follows

(a) Safety Hazard Severity Codes (default is SHSCs of 1 and 2 only)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:44Z
Check the source to verify that this is the current version before use.