DATA ITEM DESCRIPTION

Form Approved
OMB No. 0704-0188

public reporting burden for this collection of information is estimated to average 110 hours per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1 TITLE	2 IDENTIFICATION NUMBER
PLANNED MAINTENANCE SYSTEM (PMS) MAINTENANCE INDEX PAGE (MIP)	DI-MNTY-80992

3 DESCRIPTION/PURPOSE

3.1 The Planned Maintenance System (PMS) Maintenance Index Page (MIP) provides an index and cross reference to all maintenance requirements within a card set and/or describes changes to available approved MIPs.

4 APPROVAL DATE (YYMMDD)	5. OFFICE OF PRIMARY RESPONSIBILITY (OPR)	6a DTIC APPLICABLE	6b GIDEP APPLICABLE
900517	N/CEL-TD		

7 APPLICATION/INTERRELATIONSHIP

7.1 This Data Item Description (DID) contains the format and content preparation instructions for the PMS Maintenance Index Page (MIP) resulting from the work described by 3.12 of MIL-P-24534 (Navy).

7.2 This DID is related to DI-MNTY-80994, Planned Maintenance System Functional Block Diagram; DI-MNTY-80979, Planned Maintenance System

(Continued on Page 2)

8 APPROVAL LIMITATION	9a APPLICABLE FORMS	9b AMSC NUMBER
		N4946

10 PREPARATION INSTRUCTIONS

10.1 Format. The Planned Maintenance System (PMS) Maintenance Index Page (MIP) shall be documented using contractor format.

10.2 Content. The MIP shall contain the following:

10.2.1 Ship system, system, subsystem, or equipment. Enter the identifying number of the publication providing the most comprehensive maintenance information for the system or equipment for which the PMS documentation is being prepared; for example, Operational Procedures (OPs), NAVSEA instruction books, manufacturers' pamphlets, NAVSEA technical manuals, and so forth. If additional space is required, enter the phrase: "See Note." A note will be entered in the Maintenance Requirements (MR) description area to provide the additional referenced publications.

10.2.2 Date. This date shall be left blank unless provided by the PMS coordinating activity.

(Continued on Page 2)

DISTRIBUTION STATEMENT

Distribution Statement A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.

7. Application/Interrelationship (continued)

Master System and Subsystem Index; DI-MNTY-80980, Planned Maintenance System Failure Modes and Effects Analysis; DI-MNTY-80981, Planned Maintenance System Functional Failure Analysis; DI-MNTY-80982, Planned Maintenance System Functionally Significant Items Index; DI-MNTY-80983, Planned Maintenance System Additional Functionally Significant Item Index Selection Report; DI-MNTY-80984, Planned Maintenance System Logic Tree Analysis With Supporting Rationale and Justification; DI-MNTY-80985, Planned Maintenance System Servicing and Lubrication Analysis; DI-MNTY-80986, Planned Maintenance System Requirement Index; DI-MNTY-80987, Planned Maintenance System Procedure Evaluation Sheet; DI-MNTY-80988, Planned Maintenance System Task Definition; DI-MNTY-80989, Planned Maintenance System Inactive Equipment Maintenance Requirement Analysis; DI-MNTY-80990, Planned Maintenance System Reliability Centered Maintenance Documentation Control Sheet; DI-MNTY-80991, Planned Maintenance System Maintenance Requirement Card; DI-MNTY-80993, Planned Maintenance System Quality Assurance Check Sheet.

10. Preparation Instructions (Continued)

10.2.3 Configuration. Maintenance index pages that index MRs for group Expanded Ship Work Break-Down Structure (ESWBS) levels 1, 2, or 3 or those that combine more than one ESWBS level 4 grouping, shall contain the level 4 ESWBS numbers and nomenclatures. The level 5 item numbers and nomenclature shall be included. When directed by the PMS coordinating activity, enter the change configuration of system or equipment for which documentation is intended. Each FIELD CHANGE, SHIPALT, ORDALT, or other officially authorized hardware change considered in the development shall be included. Each change that affects maintenance procedures shall be preceded by an asterisk; for example, ORDALTS: *7176, 7380, *7662. When individual elements which make up the system or equipment being documented are not readily identifiable as part of the system or equipment, these elements and their individual change configurations shall be listed in this area. When other information regarding the composition of the system or equipment being documented will facilitate maintenance or management, it will be included in this area. Use brief statements such as Level of Repair Analysis (LORA) configuration or serial numbers 7-30 only. If additional space is required, the configuration data shall be continued in the MR description area by use of a note. When the configuration data is so voluminous as to be impractical to include on the MIP, enter the identification of the publication from which configuration data can be obtained. In those cases where configuration data is not required, this area will not be included on the MIP.

10.2.4 Test column. Each Maintenance Requirement Card (MRC) that contains a test requirement shall be assigned one of the following codes that shall be entered in the test column on the MIP.

B - test is at the intermediate (I) level only.

K - test is performed at the organizational (O) and I levels and results are monitored by the Submersible Ship Ballistic Nuclear (SSBN) Submarine Maintenance Monitoring Support Office (SMMSO).

A - test is performed by shore activity only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.

Preparation Instructions (Continued)

1 - test is scheduled at the O level only and was developed for ESWBS level 1 testing.

2 - test is scheduled at the O level only and was developed for ESWBS level 2 testing.

3 - test is scheduled at the O level only and was developed for ESWBS level 3 testing.

4 - test is scheduled at the O level only and was developed for ESWBS level 4 testing.

5 - test is scheduled at the O level only and was developed for ESWBS level 5 testing.

6 - test may be scheduled at both O and depot (D) levels and developed for level 1 (ship system) testing; for example, OCSOT MIP CS-3/4 is being used under the Combat System Test and Certification Program.

7 - test may be scheduled at both O and D levels and was developed for level 3 testing.

8 - test may be scheduled at both O and D levels and was developed for level 4 testing.

9 - test may be scheduled at both O and D levels and was developed for level 5 (equipment or component) testing.

10.2.5 Other column. Enter the specialized management code, as applicable, listed below. If the MRC is also classified, a two-character code will be entered. The second character space shall identify the MRCs security classification. If there is no applicable specialized management code but the MRC is classified, the classification code shall be in this column.

R - denotes a MR on Deep Submergence Recovery Vehicles (DSRV) systems and equipment that is within the scope of certification.

RC - denotes a MR on DSRV systems and equipment that is within the scope of certification and is also a confidential MRC.

K - denotes a MR (no test) developed under the cognizance of SMMSO.

C - confidential

S - secret

10.2.6 SYSCOM MRC control number column. In the SYSCOM MRC control number column, enter the control number of any reapplied MRCs as recorded on the MRC. In the case of newly developed MRs, make no entries. The control number will be applied by the PMS coordinating activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.

10. Preparation Instructions (Continued)

10.2.6.1 Inactive Equipment Maintenance Requirements. In the Inactive Equipment Maintenance (IEM) section of the MIP, enter SYSCOM control numbers for only those MRCs which are assigned an IEM periodicity code. The IEM requirements shall be listed on the MIP following the operational maintenance requirements. The requirements will be separated from the operational requirements by double horizontal lines and use of boldface print. The IEM section shall be titled Inactive Equipment Maintenance. The first entry following the title shall be: "The following requirements will be scheduled when equipment is inactive for periods of prolonged idleness". When no IEM requirements are justified during IEM analysis, enter the words, "None required." The IEM requirements shall be entered as follows:

10.2.6.1.1 The IEM requirements shall be grouped under the following subheads: Lay Up Maintenance, Periodic Maintenance, Start-Up Maintenance, Operational Test. The subheads shall be initial caps, underlined or boldface print.

NOTE: When Lay Up Maintenance (LU) MRCs are prepared to support system or equipment periods of prolonged idleness, Start-Up (SU) MRCs shall be required suitable for system or equipment operation or activation.

10.2.6.1.2 Within each subheading, the first card entered will be the scheduling card, if applicable. Each MR description shall be numbered. Applicable MRCs listed in the operational maintenance section of the MIP shall be reapplied by relisting the MR followed by a note; for example, "NOTE: Use MRC M-5". If the periodicity of accomplishment for IEM periodic maintenance differs from the operational requirement, the note shall specify the frequency; for example, "NOTE: Accomplish MRC W-1 monthly". When IEM analysis requires use of only a specific section of the operational MRC, that section shall be identified by use of parentheses following the MRC; for example, "NOTE: Accomplish MRC Q-3 (MR-1)".

10.2.6.1.3 The word "None" shall be entered for any subhead where IEM does not apply.

10.2.7 Maintenance requirement description column. When the MRCs aggregated on a MIP are applicable to a number of systems or equipment or units lower than the one shown in the MIP heading, the specific system or equipment unit shall be entered in boldface type (or underlined) on the line preceding the actual MR. Both item name and nomenclature designation shall be provided. The MR description shall be written exactly as it appears on the applicable MRC. The first line of the first maintenance description shall be two spaces below the scheduling aid or column boarder if no scheduling aids apply.

10.2.7.1 Notes. Notes shall be used to define R requirements in the operational maintenance section of the MIP and to continue entries too numerous for the space provided in the reference publication and configuration areas. In addition, notes shall be used to provide management information applicable to a specific MRC; for example, NOTE This MRC applicable to Mod 1 only". The note(s) shall be placed immediately after the last MR description for that MRC and shall be unnumbered. If more than one note is required for the same MRC, the note defining the R requirement shall be listed first.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.

10. Preparation Instructions (Continued)

10.2.7.2 Scheduling aids. All notations affecting the scheduling of MRs shall be located in the MR column preceding the first MR description. When scheduling aids include more than one topic, they shall be typed in boldface and numbered under a scheduling aid heading; for example:

a. Scheduling aids:

(1) Schedule MRC Q-3 for accomplishment only when dockside.
(2) Review MRCs A-9 and A-11. Omit requirement if not applicable; no feedback report required.

b. Asterisks and the symbol # shall be used to call attention to specific scheduling information as follows:

1. * Safety of ship items
2. ** For scheduling purposes only; no MRC is provided.
3. # Mandatory scheduling required.

10.2.7.2.1 Scheduling notations. The first scheduling notation shall be located at least two spaces below the top line which borders the MR column. Two spaces shall be allowed between each scheduling notation entry.

10.2.8 Periodicity column. Enter the periodicity code as shown on the MRCs. The MRCs shall be listed in the following sequence of decreasing frequency: D, 2D, 3D, W, 2W, M, 2M, Q, S, A, 18M, 24M, 30M, 36M, 48M, 54M, 60M, R, and U. Within each periodicity group, list the MRCs in numerical sequence: D-1, D-2, D-3, W-1, W-2, M-1, M-2, Q1R, Q-2, A-1, 18M-1, R-1, R-2, U-1, U-2. When reapplying previously developed MRCs, the condition may occur where the existing MRC is applicable but the number associated with the periodicity falls out of consecutive order. Skipping of sequential code numbers is acceptable; for example: Q-1, Q-3, Q-4, Q-7. Asterisks are used in the periodicity column to call attention to scheduling information applicable to a specific MR. the standard use of the asterisk is:

10.2.8.1 A single asterisk (*) to indicate safety of ship items. The use of the term "safety of ship" is restricted to submarines. The designation of safety of ship items will be recommended by Maintenance Requirement Development Activity (MRDA) by annotation on the verification copy of MIP; for example, Q-1*. The safety of ship notation shall be entered on the verification copy.

10.2.8.2 The double asterisk (**) to indicate that the requirement is listed for scheduling purposes only and there is no MRC. The double asterisk shall be placed beneath the applicable periodicity code in this column, and the notation shall be entered in the MR column.

10.2.8.3 Inactive equipment maintenance-periodicity column. For new MRCs developed exclusively to satisfy IEM requirements, enter the periodicity code as shown on the IEM MRC. Maintenance requirements referring to an operational equipment MRC or IEM scheduling MRC will not have an entry in the periodicity column. The MRCs shall be listed in the following sequence: LU, PM, SU and OT.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.

10. Preparation Instructions (Continued)

10.2.9 Rates column. Enter the rates required as shown on the MRCs.

10.2.9.1 Inactive equipment maintenance rates column. Inactive equipment MRs making reference to equipment operational MRCs and IEM scheduling cards do not require an entry in the rates column.

10.2.10 Man-hours column. Enter the man-hours for each rate as shown on the MRCs.

10.2.10.1 Man-hours inactive equipment maintenance. Inactive equipment MRs making reference to equipment operational MRCs and IEM scheduling cards do not require any entry in the man-hours column.

10.2.11 Related maintenance column. Enter the periodicity codes for MRCs which are identified as related during the procedure evaluation process. Entries in the related maintenance column shall be listed only with the MRC of the longest periodicity; for example, if a weekly and a monthly MRC are related, only the monthly MRC would indicate the related maintenance. If two MRCs of the same frequency are related, the related MRCs shall be entered with both MRCs. When the related MRC is from the same MIP, list only the periodicity code, for example, M-3. When it is of another MIP, list the MIP series of the code also; for example, "EL-10 M-3". When the accomplishment of the related MRC is mandatory, a # shall be placed after the periodicity code; for example "M-3#". when the related MRC is merely a convenience, the # shall be omitted. When there is no related maintenance, the word "None" shall be entered.

10.2.12 Page number. All pages of a MIP shall be identified by completing the entry "Page ___ of ___" on the bottom of the sheet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.