DATA ITEM DESCRIPTION
Title: PLANNED MAINTENANCE SYSTEM (PMS) QUALITY ASSURANCE CHECK SHEET

Number: DI-PSSS-80993A
AMSC Number: N9703
DTIC Applicable: N/A
Preparing Activity: SH
Applicable Forms: N/A

Approval Date: 20160815
Limitation: N/A
GIDEP Applicable: N/A
Project Number: PSSS-2016-019

Use/Relationship:
The Planned Maintenance System (PMS) Quality Assurance (QA) Check Sheet provides the minimum record-keeping requirements for the developing activity to administer a quality assurance program, thereby ensuring the quality, technical accuracy, composition and graphic quality are consistent with applicable technical instructions.

This Data Item Description (DID) contains the format, content, preparation instructions and intended use information for the data product resulting from the work task described in Appendix C of MIL-STD-3034A.

This DID is related to DI-PSSS-80986B, Reliability-Centered Maintenance (RCM) Maintenance Requirement Index (MRI); DI-PSSS-80991B, Planned Maintenance System (PMS) Maintenance Requirement Card (MRC); DI-PSSS-80992B, Planned Maintenance System (PMS) Maintenance Index Page (MIP).

This DID supersedes DI-MNTY-80993.

Requirements:

1. Reference Documents. The applicable issue of the documents cited herein, including their approval dates and dates of any applicable amendments, notices, and revisions, shall be as specified in the contract.

2. Format. The PMS QA Check Sheet shall be in a format similar to that of the sample form of Figure 1 of this DID.

3. Content. The PMS QA Check Sheet shall contain all of the information specified in the sample form of Figure 1 of this DID and as specified in MIL-STD-3034A, Appendix C.

3.1. System/Equipment. Enter the nomenclature of the system, subsystem, equipment, as applicable.

3.2. MIP Series. Enter the Maintenance Index Page (MIP) series identification.

3.3. MRC Number. Enter the identification number of the applicable MRC.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.

3.4. Checked By Column. Enter the initials of the personnel performing the quality assurance check for each item of documentation that was inspected in 4 below.

3.5. Date Column. Enter the date each item of documentation which was inspected by the personnel performing the quality assurance check in 4 below. .

4. Quality Assurance Checks. The following quality assurance checks, as specified in the sample form of Figure 1 of this DID concern MIL-STD-3034A procedure areas:

4.1. Correct nomenclatures are in Ship system, system, subsystem and equipment area as specified in MIL-STD-3034A, paragraph C.6.

4.2. ESWBS levels are in Ship system, system, subsystem, and equipment area as specified in MIL-STD-3034A, paragraph C.6.

4.3. Correct MIP series is in MRC Code area as specified in MIL-STD-3034A, paragraph 5.1.10.2.n.

4.4. Correct periodicity code is in the MRC code area as specified in MIL-STD-3034A, paragraph 5.1.10.2.n.

4.5. Rates area is filled as specified in MIL-STD-3034A, paragraph 5.1.10.2.o.

4.6. M/H area is properly filled in as specified in MIL-STD-3034A, paragraph 5.1.10.2.o.

4.7. Preliminary time is included in M/H area as specified in MIL-STD-3034A, paragraph 5.1.10.2.o.

4.8. Total M/H and Elapsed Time areas are correctly computed and filled in as specified in MIL-STD-3034A, paragraphs 5.1.10.2.p and 5.1.10.2.q, respectively.

4.9. MR Description area is properly filled in (complete sentence, second person imperative, and beginning with an action verb) as specified in MIL-STD-3034A, paragraph 5.1.10.2.l and C.8.

4.10. Safety Precautions area is properly filled in (first precaution refers to a manual or instruction) as specified in MIL-STD-3034A, paragraph 5.1.10.2.m.

4.11. All other specified warnings in Safety Precautions area are in the same order in which they appear in the procedure block as specified in MIL-STD-3034A, paragraph 5.1.10.2.m.(1).

4.12. Cautions do not appear in Safety Precautions area as specified in MIL-STD-3034A, paragraph C.3.11.b.

4.13. For submarine applications, Safety Precautions area contains re-entry control statement as required as specified in MIL-STD-3034A, paragraph 5.1.10.2.m.(4) and 5.1.10.2.r.(7). 4.14.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.

Safety Precautions area contains cleaning solvent statement when required as specified in MIL-STD-3034A, paragraph 5.1.10.2.m.(5).

4.15. Safety Precautions area contains the “DO NOT WORK ALONE” statement, and Rates/MH areas contain the suitable number of personnel, when required as specified in MIL-STD-3034A, paragraph 5.1.10.2.m.(2), 5.1.10.2.o, and 5.1.10.2.p.

4.16. Tools, Parts, Materials, and Test Equipment area is properly filled in in the following order: test equipment materials, parts, tools, and miscellaneous as specified in MIL-STD-3034A, paragraph 5.1.10.2.r.

4.17. Sub-Category (SCAT) codes and nomenclature for test equipment are listed as specified in MIL-STD-3034A, paragraph 5.1.10.2.r.(12).(a).

4.18. Tools are listed by proper nomenclature as specified in MIL-STD-3034A, paragraph 5.1.10.2.r.(8).

4.19. Materials and lubricants are identified by government specification number, item name, and nomenclature as specified in MIL-STD-3034A, paragraph 5.1.10.2.r.(13).(b).

4.20. Page number area is properly filled in as specified MIL-STD-3034A, paragraph C.21.

4.21. Repair parts are properly listed as specified MIL-STD-3034A, paragraph 5.1.10.2.r.(12).(c).

4.22. Equipage and special materials are properly listed as specified in MIL-STD-3034A, paragraph 5.1.10.2.r.(12).(e).

4.23. Classification markings, if applicable, are properly filled in as specified in MIL-STD-3034A, paragraph C.5.

4.24. Language, sentence structure, steps, and terminology meet standard criteria as specified in MIL-STD-3034A, paragraphs C.3.1 through C.3.10.

4.25. Notes are not used for action steps as specified in the MIL-STD-3034A, paragraph C.10 and C.3.11.c.

4.26. Notes are numbered if MRC contains more than one as specified in MIL-STD-3034A, paragraph C.10.

4.27. Warnings and cautions precede applicable step in which hazard is encountered as specified in MIL-STD-3034A, paragraph C.3.11 and C.11.

4.28. Repeat steps are used properly as specified in MIL-STD-3034A, paragraph C.12.a.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.

4.29. References to other publications are restricted as specified in MIL-STD-3034A, paragraph C.4.7.

4.30. Scheduled MRC references are properly made as specified in MIL-STD-3034A, paragraph C.4.8 and C.12.

4.31. Unscheduled MRC references are properly made as specified in MIL-STD-3034A, paragraph C.7.3.

4.32. Fill-in blanks are used properly as specified in MIL-STD-3034A, paragraph C.13.a.2.

4.33. All initial “make ready” steps, such as energizing equipment warmup, positioning switches, opening door, and establishing communications, are included in Preliminary as specified in MIL-STD-3034A, paragraph C.14.

4.34. MR description is exactly as in MR Description area with initial capitals and underlined, or in boldface as specified in MIL-STD-3034A, paragraph C.15.

4.35. Procedural steps directing removal of voltage, pressure, etc. specify the system and equipment nomenclature and refer to the applicable tag-out procedures as specified in MIL-STD-3034A, paragraphs 5.1.10.2.s.(8) and C.9.

4.36. All steps within each MR are in continuous alpha-numerical sequence as specified in MIL-STD-3034A, paragraph C.22.3.

4.37. Tables are numbered and referenced in text as specified in MIL-STD-3034A, paragraph C.17 and C.22.5.

4.38. Close-out statement is included at completion of procedure, if applicable, as specified in MIL-STD-3034A, paragraph C.15.c.

4.39. Procedural steps are factual and concise, and are not susceptible to misinterpretation as specified in MIL-STD-3034A, paragraphs 5.1.10.2.s and C.3.1.

4.40. Optimum value is stated, followed by a range, when a measure or adjustment is identified as specified in MIL-STD-3034A, paragraph C.3.1.

4.41. No words are misspelled as specified in MIL-STD-3034A, paragraph C.3.8.

4.42. Abbreviations used are approved as specified in MIL-STD-3034A, paragraph C.3.9.

4.43. Signs and symbols are standard as specified in MIL-STD-3034A, paragraph C.3.10.

4.44. Figures are numbered and referenced in text as specified in MIL-STD-3034A, paragraph C.22.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.

4.45. Spacing and format meet standard criteria as specified in MIL-STD-3034A, paragraph C.22.2.

4.46. Preferred words and expressions are used as specified in MIL-STD-3034A, Appendix E.

4.47. Capitalization meets standard criteria as specified in MIL-STD-3034A, paragraph C.3.7 and Appendix E.

4.48. Line art meets standard criteria as specified in MIL-STD-3034A, paragraph C.16.

End of DI-PSSS-80993A

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.

SYSTEM/EQUIPMENT				MIP Series		MRC No.
PRELIMINARY		FINAL		No.	DESIRED STANDARD CONDITION	Reference
Checked By	Date	Checked By	Date			
				1	Correct nomenclature is in Ship System, System, Subsystem, and Equipment blocks.	MIL-STD-3034A (C.6)
				2	ESWBS level is in Ship System, System, Subsystem, and Equipment blocks.	MIL-STD-3034A (C.6)
				3	Correct MIP series listed.	MIL-STD-3034A (5.1.10.2.n)
				4	Correct periodicity code listed.	MIL-STD-3034A (5.1.10.2.n)
				5	Rate block(s) is/are properly filled in.	MIL-STD-3034A (5.1.10.2.o)
				6	M/H block is properly filled in.	MIL-STD-3034A (5.1.10.2.o)
				7	Preliminary time is included in M/H block.	MIL-STD-3034A (5.1.10.2.o)
				8	Total Man-hours block is correctly computed and properly filled in.	MIL-STD-3034A (5.1.10.2.p)
				9	Elapsed Time block is correctly computed and properly filled in.	MIL-STD-3034A (5.1.10.2.q)
				10	MR Description block is properly filled in (complete sentence, second person imperative and beginning with an action verb).	MIL-STD-3034A (5.1.10.2.l, C.8)
				11	Safety Precautions block is properly filled in (first precaution refers to a manual or instruction).	MIL-STD-3034A (5.1.10.2.m)
				12	All other specific warnings in Safety Precautions block are in the same order in which they appear in the procedure block.	MIL-STD-3034A (5.1.10.2.m.(1))
				13	Cautions do not appear in Safety Precautions block.	MIL-STD-3034A (C.3.11.b)
				14	For submarine applications, Safety Precautions block contains re-entry control statement as required.	MIL-STD-3034A (5.1.10.2.m.(4))
				15	When scope of certification items are impacted, ensure compliance with DSS-SOC re-entry Control Procedures of SS800 AG MAN-010/P-9290 (with the appropriate DSS-SOC Notebook).	MIL-STD-3034A (5.1.10.2.r.(7))
				16	Safety Precautions block contains cleaning solvent statement when required.	MIL-STD-3034A (5.1.10.2.m.(5))
				17	Safety Precautions block contains the "Do Not Work Alone" statement, and Rates/MH blocks contain the suitable number of personnel, when required.	MIL-STD-3034A (5.1.10.2.m.(2), 5.1.10.2.o, 5.1.10.2.p)

SAMPLE FORM - FIGURE 1 - PMS QUALITY ASSURANCE CHECK SHEET (PAGE 1 OF 4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.

PRELIMINARY		FINAL		No.	DESIRED STANDARD CONDITION	Reference
Checked By	Date	Checked By	Date			
				18	Tools, Parts, Materials, Test Equipment (TPME) block is properly filled in, in the following order: test equipment, materials, parts, tools, and miscellaneous.	MIL-STD-3034A (5.1.10.2.r)
				19	Tools, Parts, Materials, Test Equipment (TPME) is numbered and identified by the applicable Standard PMS Materials Identification Guide (SPMIG) number when available.	MIL-STD-3034A (5.1.10.2.r)
				20	SCAT codes and nomenclature for test equipment are listed.	MIL-STD-3034A (5.1.10.2.r.(12).(a))
				21	Tools called out in procedure match nomenclature of tools listed in TPMTE.	MIL-STD-3034A (5.1.10.2.r.(8))
				22	Materials and lubricants are identified by government or manufacturer specification number, item name, and nomenclature.	MIL-STD-3034A (5.1.10.2.r.(13).(b))
				23	Page number block is properly filled in.	MIL-STD-3034A (C.21)
				24	Repair parts are properly listed.	MIL-STD-3034A (5.1.10.2.r.(12).(b))
				25	Equipage and special materials are properly listed.	MIL-STD-3034A (5.1.10.2. r.(12).(e))
THE FOLLOWING CHECKS CONCERN PROCEDURE BLOCK						
				26	All Personal Protective Equipment (PPE) identified in the 'tools, parts, materials, test equipment' block will have procedure steps pertaining to their use (includes harnesses, rubber aprons, respirators, gloves, etc.) included in the step that the PPE is required.	MIL-STD-3034A (C.9.1)
				27	When SUBSAFE boundaries are to be violated, ensure compliance with SUBSAFE Re-entry Control Procedures of 0924-062-0010 or COMFLTFORCOMINST 4790.3, Volume V, as applicable. When scope of certification items are impacted, ensure compliance with DSS-SOC Re-entry Control Procedures of SS800 AG MAN-010/P-9290 (with the appropriate DSS-SOC Notebook).	MIL-STD-3034A (5.1.10.2.r.(7))
				28	Classification markings, if applicable, are properly filled in.	MIL-STD-3034A (C.5)
				29	Language, sentence structure, steps, and terminology meet standard criteria.	MIL-STD-3034A (C.3.1-C.3.10)
				30	Notes are not used for action steps.	MIL-STD-3034A (C.10, C.3.11.c)
				31	Notes are numbered if MRC contains more than one.	MIL-STD-3034A (C.10)

SAMPLE FORM - FIGURE 1 - PMS QUALITY ASSURANCE CHECK SHEET (PAGE 2 OF 4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.

PRELIMINARY		FINAL		No.	DESIRED STANDARD CONDITION	Reference
Checked By	Date	Checked By	Date			
				32	Situation Requirements are in accordance with current approved list.	MIL-STD-3034A (C.7.2)
				33	WARNINGs address personnel safety; CAUTIONs address equipment damage.	MIL-STD-3034A (C.3.11.a, C.3.11.b)
				34	Warnings and cautions preceded applicable step in which hazard is encountered.	MIL-STD-3034A (C.3.11, C.11)
				35	Repeat steps are used properly.	MIL-STD-3034A (C.12.a)
				36	References to other publications are restricted.	MIL-STD-3034A (C.4.7)
				37	Scheduled MRC references are properly made.	MIL-STD-3034A (C.4.8, C.12)
				38	Unscheduled MRC references are properly made.	MIL-STD-3034A (C.7.3)
				39	Fill-in blanks are used properly.	MIL-STD-3034A (C.13.a.2)
				40	Related Maintenance identified.	MIL-STD-3034A (C.12.b.1)
				41	All initial "make ready" steps, such as energizing equipment, warming-up equipment, positioning switches, opening doors, performing electrical isolation, tag-out of equipment, preparing cleaning solutions, establishing communication, preparing setup of test equipment, and ensuring safe conditions are included in Preliminary.	MIL-STD-3034A (C.14)
				42	If applicable, identify any special plant or equipment conditions that must be in place and ensure they are included in Preliminary Section.	MIL-STD-3034A (C.14)
				43	MR description is exactly as in MR Description block with initial capitals and underlines, or in boldface.	MIL-STD-3034A (C.15)
				44	Procedural steps directing removal of voltage or pressure specify the system and equipment nomenclature and refer to the tag and untag procedures for equipment or system in accordance with Tag-Out User's Manual, NAVSEA S0404-AD-URM-010/TUM, or local tag-out instruction(s).	MIL-STD-3034A (C.9)
				45	All steps within each MR are in continuous alpha-numerical sequence.	MIL-STD-3034A (C.22.3)
				46	Inspection and measurement steps clearly specify limits so that a condition can be easily determined to be acceptable or unacceptable.	MIL-STD-3034A (5.1.10.2.s.(6))
				47	Tables are numbered and referenced in text.	MIL-STD-3034A (C.17, C.22.5)

SAMPLE FORM - FIGURE 1 - PMS QUALITY ASSURANCE CHECK SHEET (PAGE 3 OF 4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.

PRELIMINARY		FINAL		No.	DESIRED STANDARD CONDITION	Reference
Checked By	Date	Checked By	Date			
				48	Electrical panels, circuit breakers, and valves identified by name or number identified for tag-out procedures.	MIL-STD-3034A (5.1.10.2.s.(8))
				49	Close-out statement is included at completion of procedure if applicable.	MIL-STD-3034A (C.15.c)
				50	Procedural steps are factual and concise, and are not susceptible to misinterpretation.	MIL-STD-3034A (5.1.10.2.s, C.3.1)
				51	Optimum value is stated, followed by a range, when a measure or adjustment is specified.	MIL-STD-3034A (C.3.1)
				52	No words are misspelled.	MIL-STD-3034A (C.3.8)
				53	Abbreviations used are those in common usage and not subject to misinterpretation, and abbreviations that are not in common use and are to be used frequently in an MRC should be clarified when first used by spelling out the word or complete phrase, followed by the abbreviation in parentheses.	MIL-STD-3034A (C.3.9)
				54	Signs and symbols are standards.	MIL-STD-3034A (C.3.10)
				55	Figures are numbered and referenced in text.	MIL-STD-3034A (C.22.4)
				56	Spacing and format meet standard criteria.	MIL-STD-3034A (C.22.2)
				57	Preferred words and expressions are used.	MIL-STD-3034A (Appendix E)
				58	Capitalization meets standard criteria.	MIL-STD-3034A (C.3.7, Appendix E)
				59	Line art meets standards.	MIL-STD-3034A (C.16)
				60	General Electrical Safety requirements noted in WARNINGS throughout the procedure where applicable.	NSTM Chapter 300 (2.3.1.2)
				61	Safety precautions and procedures for working on energized equipment are incorporated.	NSTM Chapter 300 (2.4)
				62	HAZMAT requirements noted in WARNINGS throughout the procedure where applicable.	NSTM Chapter 670 (Volume 2)

SAMPLE FORM - FIGURE 1 - PMS QUALITY ASSURANCE CHECK SHEET (PAGE 4 OF 4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:42Z
Check the source to verify that this is the current version before use.