W-F-421b
SEPTEMBER 24, 1956
SUPERSEDING
Int. Fed. Spec. W-F-00421b(GSA-FSS)
Revision-3
June 19, 1956, and
Fed. Spec. W-F-421a
March 7, 1940

FEDERAL SPECIFICATION

FLASHLIGHTS, ELECTRIC, HAND

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 **Scope.**—This specification covers flashlights of tubular construction for general use and for rough service. It does not cover explosion-proof flashlights.

1.2 **Classification.**

1.2.1 *Classes and sizes.*—Flashlights furnished under this specification shall be of the following classes and sizes.

Class 1.—Rough service.
  Size 1.—Two cell.
  Size 2.—Three cell.
Class 2.—General service.
  Size 1.—Two cell.
  Size 2.—Three cell.
  Size 3.—Five cell, searchlight.

2. APPLICABLE SPECIFICATIONS AND STANDARDS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification:

Federal Specifications:

UU-T-111 — Tape; Paper, Gummed (Sealing and Securing).
LLL-F-291 — Fiberboard; Corrugated, Single Face, (Flexible).
PPP-B-566 — Boxes, Folding, Paperboard.
PPP-B-621 — Boxes, Wood, Nailed and Lock-Corner.
PPP-P-31 — Preservation, Packaging, Packing: and Marking of Material; and Shipping Instructions; (Domestic Shipment and Storage).

Military Specifications:

JAN-P-108 — Boxes, Fiberboard, Corrugated and Solid (Military Type).
MIL-P-116—Preservation, Methods of.
JAN-P-117 — Packaging and Packing for Overseas Shipment — Bags, Interior Packaging.
JAN-P-127 — Packaging and Packing for Overseas Shipment — Tape, Adhesive, Pressure-Sensitive, Water-Resistant.

Military Standards:

MIL-STD-105 — Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129—Marking for Shipment and Storage.

(Activities outside the Federal Government may obtain copies of Federal Specifications and Standards as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Ad-

FCS Class 6230

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:27Z
Check the source to verify that this is the current version before use.

ministration Regional Offices in Boston, New York, Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, Seattle, and Washington, D. C.

(Federal Government activities may obtain copies of Federal Specifications and Standards and the Index of Federal Specifications and Standards from established distribution points in their agencies.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 **Qualification.** — Flashlights furnished under this specification shall be a product which has been tested in accordance with the qualification tests described in section 4. (See 4.2 and 6.4.)

3.2 **Materials.** — The materials used throughout shall be suitable in every respect for their intended purpose and such that the finished components shall evidence no indication of damage or protective coating penetrating corrosion when the flashlights are subjected to the tests specified in section 4. Springs and switch contacts shall be of commercial grade or better, spring brass, phosphor bronze or beryllium copper. End or base-cap springs may be of suitable material such as copper coated steel provided the material used has suitable electrical conductivity characteristics and meets all other requirements of this specification.

3.3 **Design.**

3.3.1 *General.*— The flashlights shall be of tubular construction and shall project their beam longitudinally. They shall be furnished complete with lamps but without dry cells.

3.3.2 *Lamp and lampholders.*—Lamps shall be miniature flanged base single contact and shall be solidly retained in place in the lamp receptacle solely by the flange. Means shall be provided to prevent the dry cells from damaging the base of the lamp when tested in accordance with 4.4.7. Dry cells shall be held in place against the lampholder by a helical spring or other acceptable means. Lamps supplied with the flashlights shall be as given in table I for the respective size.

3.3.3 *Switch.*—The switch shall be mounted on the side of the case and shall be a slide type which provides a locked "off" and a positive "on". When specified, a "flashing" position shall be provided. Switches shall resist accidental movement to the "on" position. The switch slide or button, shall be designed so as to permit easy manipulation with one hand. Class 1 flashlights shall meet this requirement when tested under the conditions stated in 4.4.10. The design and construction of the switch mechanism shall be such that it will operate in a satisfactory manner for 50,000 cycles at a rate not to exceed 20 cycles per minute. (See 4.4.2.) The construction shall be such that with the flashlight completely assembled, fresh dry cells in place and the switch in the "off" position, it shall be impossible to energize the lamp by bridging any two points on the exposed surface with an electrical conductor.

3.3.4 *Caps.* — Means shall be provided through the use of a threaded cap or caps for the replacement of lamps and dry cells. All threads shall be of design and fit that may be screwed up using a torque not exceeding 10 inch pounds and the threads shall not strip or ride over those of the mating part when a torque of 25 inch pounds is applied (see 4.4.11).

3.3.5 *Dimensions.*—The overall dimensions of flashlights shall not exceed the values shown in table I. The effective inside diameter of the battery compartment shall be not less than 1⅜ inches nor the maximum diameter more than 1½ inches, and its length and the design of the rear contact spring shall be such that it will accommodate the required number of cells of any length between 2$^{5}/_{16}$ inches and 2$^{13}/_{32}$ inches. The spring shall shorten a minimum of ⅜ inches and exert a force of not less than two pounds when tested in accordance with 4.4.8.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:27Z
Check the source to verify that this is the current version before use.

TABLE I.

Size	Number of cells	Industry lamp number	Maximum over-all dimension		Illumination (candle power)			
			Length	Diameter	Center & 4" Cir. (5 points)		8" Cir. (4 points)	
			Inches	*Inches*	Aver.	Min.	Aver.	Min.
1	2	PR-2	9	2¾	450	300	200	125
2	3	PR-3	12	2¾	700	500	350	200
3	5	PR-12	16	3¾	3000	1900	1000	450

3.3.6 *Light protection.* — When tested in accordance with 4.4.1, flashlight shall give illumination equal to or higher than the values indicated in table I.

3.3.7 *Finish and workmanship.*—The finishes of all components and of the assembled flashlights shall be equal to or better than those recognized as good commercial practice for the material in the same or similar applications, and shall evidence no indication of deterioration when the flashlights are subjected to the tests specified in section 4. The workmanship shall be first class throughout.

3.3.8 *Additional requirements for class 1 flashlights.*—Class 1 flashlights shall be so constructed that there are no exposed exterior electrically conducting parts except the switch handle. A suspension loop shall be positioned near the rear of the flashlight on the opposite side of the case from the switch or in the rear cap. Flashlights shall be provided with suitable gaskets of oil resistant elastomer material at all points through which moisture might pass into the interior of the flashlight including the compartment containing the switch contacts, which shall make the flashlights watertight when tested in accordance with 4.4.3. Class 1 flashlights shall be provided with a spare lamp mounted securely inside the bottom cap in such a manner that it will be readily accessible but will not become displaced or broken when tested in accordance with 4.4.7. The suspension loop shall be constructed and arranged so that when not in use, it may be firmly seated against the flashlight. The opening in the loop shall be sufficient to pass over a rod of rectangular cross-section ¼ inches by 1⅛ inches and the loop shall be capable of supporting in tension a weight of 25 pounds. The flashlights shall be so constructed that when placed in a horizontal position on a stationary flat surface inclined at an angle of 15 degrees to the horizontal, they will not roll or change position. The material of the incline shall be such that the flashlight does not slide during the test (see 4.4.9).

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Sampling.

4.1.1 *Inspection lot.*—All flashlights of the same class and size presented at one time shall be considered a lot for purposes of inspection and tests.

4.1.2 *Sampling for inspection.*—A representative random sample shall be taken from the lot in accordance with table II. Acceptance or rejection of the lot shall be based on the number of defective units found in the sample selected and inspected, as being equal to or less than the specified acceptance number; or equal to or greater than the specified rejection number of table II:

4.1.3 *Sampling for tests.*—A representative random sample shall be taken from the lot in accordance with table III. Acceptance or rejection of the lot shall be based on the number of defective units found in the sample selected and tested as being equal to or less

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:27Z
Check the source to verify that this is the current version before use.

TABLE II.—*Sampling for visual and dimensional inspection based on acceptance quality level (AQL of 2.5 percent)*

Lot size	Sample size	Acceptance number	Rejection number
15 and under	3	0	1
16 to 40	7	0	1
41 to 110	15	1	2
111 to 300	35	2	3
301 to 500	50	3	4
501 and over	75	4	5

NOTE.—The Government Inspector may institute tightened or reduced inspection in accordance with Military Standard MIL–STD–105.

than the specified acceptable number; or equal to or greater than the specified rejection number of table III:

TABLE III.—*Samples for tests*

Lot size	Sample size		Acceptance Number	Rejection Number
	(Flashlight)	(Lamps)*		
500 and under	4	40	0	1
501 to 1301	8	80	0	1
1301 to 3200	10	100	0	1
3201 to 8000	14	140	0	1
8001 and over	20	200	0	1

*A random sample of 10 lamps shall accompany each flashlight and the sample shall include the lamp or lamps furnished with the flashlight and shall be taken from the manufacturer's supply of the same make and type lamp as that with which the flashlight is equipped.

4.1.4 *Sampling for qualification tests.*—The manufacturer shall submit for qualification testing a random sample of three production flashlights of each class and size to be tested and a random sample of ten lamps for each flashlight. The lamp or lamps with which the flashlights are equipped, shall be included in the lamp sample.

4.2 **Qualification tests.**—Qualification tests shall consist of those tests described in 4.4.1 thru 4.4.11. Qualification tests shall be conducted at a Government laboratory, at manufacturer's laboratory under Government supervision, or at a commercial testing laboratory as approved by the Standardization Division, Federal Supply Service, General Services Administration. Approval of the commercial testing laboratory for qualification testing shall be obtained from the Standardization Division prior to the tests. Application for approval shall include the following information:

Name and location of laboratory.

Extent of laboratory's experience in testing flashlights.

Statement that laboratory is equipped to make all tests listed above.

At the conclusion of the qualification tests, three certified copies of the test report shall be submitted to the General Services Administration, FSS, Standardization Division for review and approval.

4.3 **Inspection.**—Each of the sample flashlights selected in accordance with table II shall be visually and dimensionally inspected by the Government inspector to verify compliance with this specification. Any flashlight in the sample having one or more defects shall be rejected, and if the number of defective flashlights in any sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

4.4 **Lot acceptance test by Government inspector.** — Each of the sample flashlights selected in accordance with table III, shall be subjected to the following tests sequenced in the same order as listed below. Any sample flashlight which does not meet the requirements of all required tests, shall cause rejection of the lot represented by the sample.

4.4.1 *Performance test—general.* — Tests shall be conducted in a darkened room. The test shall be performed with each sample flashlight equipped with the lamp selected in accordance with 4.4.1.1. The arrangement shall be such that the amount of reflected light falling on the test plane shall not materially affect the test results.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:27Z
Check the source to verify that this is the current version before use.

4.4.1.1 *Lamp selection.*—The lamp to be used in each of the flashlights to be tested shall be selected from the ten lamps submitted with each flashlight. The lamp shall be the one, based on the judgment of the testing facility, which when burned in the flashlight produces the most symmetrically distributed pattern of light concentrated within the 8-inch circle of the test screen (see 4.4.1.4) when projected from a distance of 10 feet.

4.4.1.2 *Lamp current drain determination.*—The lamp shall be removed from the flashlight and burned at rated voltage for thirty (30) minutes. At the end of this period, the current drain of the lamp at rated voltage shall be determined. The current drain at rated voltage shall be within ten percent (10 percent) of design amperes, i.e., between 0.45 and 0.55 ampere. The lamp shall then be placed in the flashlight.

4.4.1.3 *Test cell selection.*—The flashlight shall be loaded with the required number of selected size D mercury cells (Mallory No. RM42R or equal). (Care shall be taken that the positive terminal of the mercury cell makes contact with the lampholder base. If required, insert small round head brass machine screw into lampholder to complete the circuit). This selection shall be made on the basis of a measurement of the initial open-circuit voltage of the cells and the initial closed-circuit voltage of the cells, taken 15 seconds after closing and while still closed across a 4 ohm (4 ± 0.02 ohm) resistor. These voltages shall be measured with a voltmeter having a resistance of not less than 100 ohms per volt and a scale having at least ten divisions per volt. The initial open-circuit voltage of each cell shall be not less than 1.34 volts. The initial closed-circuit voltage shall be not more than 0.15 volt lower than the measured initial open-circuit voltage.

NOTE.—It has been determined that mercury type cells provide a more stable current supply than regular zinc type dry cells for determining the light producing performance of flashlights. The illumination values given in table I reflect the lower open circuit voltage of mercury cells and are the minimum acceptable values of light produced by flashlights powered by mercury cells.

4.4.1.4 *Illumination readings.*—The flashlight shall be arranged so that its beam is projected on a screen, the plane of which is perpendicular to the optical axis of the flashlight with ten (10) feet between the lens and the screen as described below. For test purposes, the geometric center of the projected beam of light may be considered the point at which the optical axis of the flashlight pierces the test plane. Concentric circles one of 8-inch diameter and one of 4-inch diameter shall be drawn on the screen.

The intersection of these circles with their vertical and horizontal diameters shall be indicated. The intensity of the light falling on the screen at the 8 points of intersection and at the center of the circles shall be read using a light sensitive element having a diameter of 1.5 ± 0.05 inches, centered on the points. The flashlight shall be turned on for 15-second intervals, and the reading for a point shall be taken at the end of the time interval. The flashlight will be turned off for 30 seconds between readings. The center point will be read first, followed by the points on the inner circle and the points on the outer circle.

Conversion formula: Candle power = 100 × meter reading in foot candles. The light measuring equipment shall have a known accuracy of ± 5 percent or better. (See 4.3.6.)

4.4.1.5 *Lamp longevity determination.*—At the completion of the readings at the 9 points, the lamp will be connected to rated voltage for ten hours. Should more than twenty-five percent (25) of the lamps tested fail before reaching ten hours, the flashlight will be considered as having failed to pass the test.

4.4.2 *Switch life test.*—The flashlight switch shall be operated for 50,000 cycles under normal electrical load conditions. A cycle shall be from full "off" to full "on" to full "off" and the cycling rate shall not

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:27Z
Check the source to verify that this is the current version before use.

exceed 20 cycles per minute. The switch shall not fail mechanically or electrically or show excessive wear as a result of this test. A suitable mechanical switch operating device may be used for this test.

4.4.3 *Watertightness (class 1 only).*—The flashlights shall be charged with batteries and submerged for one hour to a depth of one foot below the surface of a 10 percent solution of sodium chloride at room temperature (25° ± 5°C.) The exterior of the flashlights shall be wiped dry and their interiors checked for compliance with 3.3.8.

4.4.4 *Corrosion test (class 1 only).*—The flashlights, completely assembled but without batteries and in a horizontal position, with switch down, shall be partly submerged (approximately 50 percent of exterior surface covered) in a 10 percent solution of sodium chloride at room temperature (25° ± 5°C.) for a period of 24 hours. The flashlight shall be disassembled. the parts wiped dry, rubbed briskly with clean cheese cloth, and checked for compliance with 3.2 and 3.3.7.

4.4.5 *Dimensional and material composition stability test—(not required of metal case flashlights).*—One half of the flashlights in a sample completely assembled, including batteries, shall be subjected to a temperature of 70° ± 2°C. dry heat for 16 hours, followed by a temperature of 45° ± 2°C. at 90 to 100 percent relative humidity for six hours. The flashlights shall then be compared with untested flashlights for dimensional stability, crazing of surface, changes in appearance of materials and other defects. The parts of tested samples shall be interchangeable with corresponding parts of untested samples and after new batteries have been installed, the test samples shall be operable.

4.4.6 *Impact test.—(Not required of metal case flashlights).*—With the flashlights at room temperature (25° ± 5°C.) the case, lens ring, bottom cap, and switch shall be subjected to an impact test, using a 1-pound steel ball. The impact shall be 12-inch pounds for class 2 flashlights and 20-inch pounds for class 1 flashlights (see 3.2).

4.4.7 *Drop test.*—The assembled flashlight, complete with dry cells and lamp or lamps, shall be dropped in free fall through a distance as specified below on to the center of a bed of loose dry sand. The sand shall be at least two feet by two feet by six inches deep and the exposed surface shall be smoothed to a horizontal plane prior to each drop. Each flashlight shall be dropped so that it strikes ten times in an approximate horizontal position, ten times in a vertical position upon the head of the flashlight, and ten times in a vertical position upon the base of the flashlight. Class 2 flashlights shall be dropped 6 feet and class 1 flashlights shall be dropped 12 feet (see 3.2, 3.3.2, 3.3.7, and 3.3.8).

4.4.8 *Battery spring and suspension loop tests.*—With the lens ring, lens, reflector, and lampholder removed, the flashlight resting on its base, and the required number of dry cells in place, a force shall be applied to the top of the upper dry cell as necessary to depress the spring and move dry cells relative to the case to the position which they will occupy when the flashlight is completely assembled. For flashlights that cannot be so tested because of their design, comparable tests shall be made that will indicate that these flashlights meet spring extension and strength requirements of 3.3.5. The suspension loop (class 1 only) shall be tested by suspending a weight of 25 pounds from the loop for a period of one minute with the flashlight in a vertical position, base down, to determine compliance with 3.3.8.

4.4.9 *Anti-roll test (class 1 flashlights only).*—The flashlights, with batteries in place, shall be tested for compliance with anti-roll requirements of 3.3.8.

4.4.10 *Switch manipulation test (class 1 flashlights only).*—The switch slide or button shall be coated with petroleum jelly. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:27Z
Check the source to verify that this is the current version before use.

switch shall then be tested for ease of operation as required under 3.3.3.

4.4.11 *Body thread test.*—Starting with the case of the flashlight, disassembled, it shall be assembled, applying a measured torque of ten-inch pounds ± ½-inch pound, to "screw-up" the caps and other threaded parts. The flashlight shall be examined to determine compliance with the first stated requirements of 3.3.4. A measured torque of 25-inch pounds ± ½-inch pound shall be applied to each of the threaded parts of the case and the flashlight shall then be examined for compliance with the second stated requirement of 3.3.4.

5. PREPARATION FOR DELIVERY

(For definitions and levels, see 6.1)

5.1 Preservation and packaging.

5.1.1 *Level A.*—Flashlights, Electric Hand, shall be preserved and packaged in accordance with the procedures specified for the designated methods as described in Military Specification MIL–P–116 and described in the following paragraphs:

5.1.1.1 *Flashlights, Electric, Hand.*—Flashlights shall be packaged individually method IC–3 as follows: Cushion each flashlight by wrapping in type I, single faced flexible corrugated fiberboard conforming to Federal Specification LLL–F–291. Seal all laps, folds and seams by means of class 1 gummed paper tape conforming to Federal Specification UU–T–111. Inclose each cushioned flashlight within a close-fitting type II, grade A, class b bag conforming to Military Specification JAN–P–117. Exhaust excess air from the barrier bag. Heat seal, to effect closure. Inclose each bagged flashlight within a close-fitting style II, type A, class a folding-carton, conforming to Federal Specification PPP–B–566. Carton closure shall be in conformance with the referenced carton specification. Packages prepared as above shall be required to pass the waterproofness test prescribed in Military Specification MIL–P–116.

5.1.1.2 *Intermediate package.*—Place a suitable quantity of flashlights of like size together within a close-fitting regular slotted style, grade 5, corrugated fiberboard box conforming to Military Specification JAN–P–108. The gross weight of the intermediate package shall not exceed that which is prescribed in the referenced box specification. Box closures shall be in conformance with the referenced box specification, further reinforced at all closures, corners and joints, with type I, grade A, olive drab tape conforming to Military Specification JAN–P–127.

5.1.2 *Level B.*—Flashlights, Electric, Hand shall be preserved and packaged in accordance with the procedures specified for the designated methods as prescribed in Military Specification MIL–P–116 and described in the following paragraphs.

5.1.2.1 *Flashlights, Electric, Hand.*—Flashlights shall be packaged individually method III as follows: Cushion each flashlight as specified in 5.1.1.1. Place each cushioned flashlight within a close-fitting folding carton as specified in 5.1.1.1. No barrier bag required.

5.1.2.2 *Intermediate package.*—Intermediate packages shall be implemented as specified in 5.1.1.2.

5.1.3 *Level C.*—Flashlights, Electric, Hand shall be packaged in accordance with commercial practice, and in a manner that will guarantee adequate protection against corrosion, deterioration and physical damage during direct shipment to the first receiving activity.

5.2 Packing.

5.2.1 *Level A.*—Place a quantity of intermediate packages containing like size flashlights specified in 5.1.1.2 within a close-fitting style 4 nailed wood box conforming to Federal Specification PPP–B–621. Gross weight of the box shall not exceed approximately 150 pounds. Box closure shall be in conformance with the appendix of the referenced box specification.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:27Z
Check the source to verify that this is the currentversion before use.

5.2.1.1 *Metal strapping.* — Shipping containers shall be strapped in conformance with the requirements of the appendix of the applicable container specification only for direct shipment to ports.

5.2.2 *Level B.*—Flashlights, Electric, Hand shall be packed for shipment as specified in 5.2.1 except the style 4 box shall conform to Federal Specification PPP–B–621, and the gross weight shall not exceed approximately 200 pounds. No strapping required.

5.2.3 *Level C.*—Flashlights, Electric, Hand shall be packed for shipment in a manner conforming to the requirements of Uniform Freight Classification Rules for rail shipment, National Motor Freight Classification Rules for truck shipment, Parcel Post Regulations and the regulations of other carriers as applicable to the mode of transportation employed, at lowest transportation rate.

5.3 Marking.—Interior packages and exterior shipping containers shall be marked in accordance with the applicable provisions of Federal Specification PPP–P–31 except Military orders which shall be marked in accordance with the applicable provisions of Military Standard MIL–STD–129.

6. NOTES

6.1 Federal Standard 102 should be referred to for definitions and applications of the various levels of packaging protection for supplies and equipment.

6.2 Ordering data.—Purchasers should exercise any desired options offered herein and should specify the following:

(*a*) Class and size flashlight required (see 1.2)

(*b*) Flashing position on switch, if required (see 3.3.3)

(*c*) Level of packaging and packing required (see 5.)

6.3 Transportation description.—Transportation description applicable to these items is:

Flashlights, Electric Hand

Carload weight 20,000 pounds, subject to Rule 84 Uniform Freight Classification

Truckload weight 24,000 pounds.

6.4 In the procurement of products requiring qualifications, the right is reserved to reject bids for products that have not been subjected to the required tests and found satisfactory for inclusion on the Federal Qualified Products List. The attention of the suppliers is called to this requirement, and manufacturers are urged to communicate with the Standardization Division, Federal Supply Service, General Services Administration, Washington 25, D. C., and arrange to have the products that they propose to offer to the Government tested for qualification, in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products covered by this specification may be obtained from Standardization Division, Federal Supply Service, General Services Administration, Washington 25, D. C. (see 3.1).

Patent notice.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

MILITARY INTERESTS:

Army—E M

Air Force.

Copies of this specification may be purchased for 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:27Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity (as indicated on reverse hereof).

SPECIFICATION

ORGANIZATION (Of submitter)	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS (Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)

SUBMITTED BY (Printed or typed name and activity)	DATE

DD FORM 1 APR 61 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE S-0870

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:27Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

COMMANDING GENERAL
U.S. ARMY ELECTRONICS COMMAND
ATTN: AMSEL-PP-E-SED
FORT MONMOUTH, N.J. 07703

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:27Z
Check the source to verify that this is the current version before use.