AMENDMENT

TO

INTERIM FEDERAL SPECIFICATION

FLASHLIGHT, ELECTRIC, HAND

This amendment was developed by the General Services Administration, Federal Supply Service, Washington, DC 20406, based upon currently available technical information. The General Services Administration has authorized this amendment as a part of Interim Federal Specification W-F-00421C, dated June 5, 1972.

PAGE 3

Paragraph 3.3.3, line 11 - delete "magenta, number 17142" and substitute "black and the lens cap, end cap, and any exposed plastic switch parts shall be yellow obtained without the use of paint, enamel, or any post molding application."

PAGE 4

Paragraph 3.5.4, second line - delete the the wording "5° for the type I and".

Paragraph 3.5.5, fifth sentence - after "type I" add the words "and type II".

PAGE 5

Paragraph 3.5.8, second sentence - delete sentence in its entirety and replace with the following: "The storage compartment shall be provided in the end caps or other accessible area of the flashlight."

Paragraph 3.5.12, delete in its entirety and replace with the following:

"3.5.12 Threads. Matching threads on the caps, rings, and case shall be of a design and fit that can be screwed tight using a torque not to exceed 30 pound inches. Threads shall not strip or ride over those of mating parts when a torque of 50 pound inches ± 2 pound inches is applied. Refer to 4.3.12 for testing of type I and II flashlights and to 4.3.13 for testing of types III and IV flashlights."

PAGE 6

Paragraph 3.5.14, last sentence - delete in its entirety.

PAGE 8

Paragraph 4.3.5, second sentence - delete the wording "5° for the type I and".

PAGE 9

Paragraph 4.3.12 - delete the second sentence in its entirety and replace with the following: "Using the manufacturer's recommended torque for tightening the caps and lens ring, a torque not to exceed 30 pound inches, tighten the caps and lens ring (see 3.5.12) and then remove. This shall be designated as one cycle. In each cycle, the flashlight shall remain in a tightened condition for at least 2 minutes."

Paragraph 4.3.12 - also delete the fourth sentence and replace with the following: "At the end of the test period, the flashlights shall be reassembled using a torque of 50 pound inches ± 2 pound inches (see 3.5.12)."



Source: https://assist.dla.mil -- Downloaded: 2015-09-04T13:24Z
Check the source to verify that this is the current version before use.
Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:27Z
Check the source to verify that this is the current version before use.

Paragraph 4.3.13 - delete in its entirety and replace with the following:

"4.3.13 Gasket and thread. This test is applicable to types III and IV flashlights only. Threaded lens rings and caps of a fully assembled flashlight, including batteries, shall be removed and reassembled to a watertight condition, using the pound-inch torque established by the manufacturer, not to exceed 30 pound inches. This shall be designated as one test cycle. The test shall consist of 100 test cycles. The applied torque in each cycle shall be within ½ pound inches of the manufacturer's established torque, not to exceed 30 pound inches. In each cycle, the flashlight shall remain in a tightened condition for a minimum of 2 minutes. At the completion of the above test, the flashlight shall be assembled and a torque of 50 pound inches ± 2 pound inches shall be applied to each of the threaded parts, whereupon compliance with 3.5.12 shall be determined. The flashlight shall then be disassembled and reassembled using the pound-inches of torque conforming to a watertight condition as established by the manufacturer, not to exceed 30 pound inches of torque. Flashlight shall then be tested as specified in 4.3.14."

Paragraph 4.3.14, part B, second sentence - delete the wording "15 inch pounds" and replace with "30 pound inches".

Paragraph 4.3.16 - delete in its entirety and substitute the following:

"4.3.16 Rough service durability. Tests 4.3.13 and 4.3.14 for types III and IV, and test 4.3.12 for the type II shall precede the following test. The flashlight, complete with dry cells, lamps, and lenses, shall be dropped 12 feet on the center of a bed of loose, dry sand to constitute a free fall. The sand shall be at least 2 feet by 2 feet by 6 inches deep, and the exposed surface of the sand shall be smoothed to a horizontal plane prior to each drop. The flashlight shall be dropped so that it strikes 10 times in an approximate horizontal position, 10 times in a vertical position upon the head of the flashlight, and 10 times in a vertical position upon the base of the flashlight. Parts shall not be tightened once the test has begun. There shall be no damage to the base of the lamp, reflector, or any internal part which could render the flashlight unserviceable. The lamp, and spare lamp when provided, shall not become loose, displaced, or broken. Nonconformance to the above shall constitute failure of the test."



Source: https://assist.dla.mil -- Downloaded: 2015-09-04T13:24Z
Check the source to verify that this is the current version before use.
Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:27Z
Check the source to verify that this is the current version before use.