INCH-POUND


MIL-PRF-39012/19H
w/AMENDMENT 2
18 March 2019
SUPERSEDING
MIL-PRF-39012/19H
w/AMENDMENT 1
20 April 2009

PERFORMANCE SPECIFICATION SHEET

CONNECTORS, RECEPTACLE, ELECTRICAL, COAXIAL, RADIO FREQUENCY, (SERIES BNC (CABLED), SOCKET CONTACT, JAM NUT MOUNTED, CLASS 2)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-39012.



Inches	mm	Inches	mm
.022	0.56	.493	12.52
.065	1.14	.500	12.70
.104	2.64	.505	12.83
.114	2.90	.510	12.95
.215	5.46	.620	15.75
.218	5.54	.630	16.00
.221	5.61	.196	20.22
.240	6.10	.500	20.32
		.843	21.41





FIGURE 1. General configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:45Z
Check the source to verify that this is the current version before use.

NOTES:
1. Dimensions are in inches. Metric equivalents are given for information only.
2. For dimension A, see tables I and III.
3. Dimension .800 inch (20.32 mm) is the largest overall diameter of the connector.
4. Wrench flats are to accommodate standard wrench opening in accordance with FED-STD-H28, appendix 10.
5. Orientation of the body hex flats, mounting flats and bayonet studs shall be ±3° of that orientation shown.
6. All undimensioned pictorial representations are for reference purposes only.
7. Dimension A defines the maximum length of the connector when assembled to the appropriate cable.
8. Series BNC, socket contact interface in accordance with MIL-STD-348.

FIGURE 1. General configuration – Continued.



Inches	mm
.002	0.05
.006	0.15
.010	0.25
.036	0.91
.077	1.96
.234	5.94

CATEGORY "D"

NOTES:
1. Dimensions are in inches. Metric equivalents are given for information only.
2. Chamfer is optional.
3. Concave depression .100 inch (2.54 mm) x .005 inch (0.13 mm) deep between studs permissible.

FIGURE 2. Category D captivation details.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:45Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers, cross-reference, and dimensions.

Part or Identifying Number (PIN) 1/ M39012/19-	Applicable cable 2/ M17/	Dimensions	Inches (millimeters) maximum #
Category A – Field serviceable (no special tools required) 3/			
X101 (Superseding –0111 4/)	Cable group VI 60-RG142 5/ 128-RG400 6/	A	1.250 (31.75)
X102 (Superseding –0118 4/)	Cable group VII 110-RG302 5/ 6/ 7/		
X110	Cable group IV 54-RG122 6/		
X220	Cable group II 113-RG316 5/ 6/		
X225	Cable group X 127-RG393 5/ 6/		

See notes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:45Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers, cross-reference, and dimensions – Continued.

PIN 1/ M39012/19-	Applicable cable 2/ M17/	Dimensions	Inches (millimeters) maximum #
Category C – Field replaceable (SAE-AS22520 crimp tool) See note next to applicable cable group for crimp die 3/ 8/			
X013	Cable group VIA 9/ 111-RG303 5/ 6/	A	1.625 (41.28)
X014	Cable group VIB 9/ 60-RG142 5/ 128-RG400 6/		
X015 (Superseding –0020 4/)	Cable group VIIA 10/ 110-RG302 5/ 6/ 7/		
X016	Cable group IV 11/ 54-RG122 6/ 15/		
X017	Cable group VIIB 10/ 90-RG71 6/ 7/		
X221	Cable group IIA 12/ 113-RG316 5/ 6/		

See notes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:45Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers, Cross-reference, and dimensions – Continued.

PIN 1/ M39012/19-	Applicable cable 2/ M17/	Dimensions	Inches (millimeters) maximum #
Category D – Field replaceable – Defined piece part 3/ 8/ 13/ 14/			
X501	Cable group IV 54-RG122 6/ 15/	A	1.468 (37.31)
X502	Cable group V 95-RG180 5/ 6/ 7/		
X503	Cable group VIB 60-RG142 5/ 128-RG400 6/		
X504	Cable group VIA 111-RG303 5/ 6/		

1/ For cross-reference of PIN to superseded PIN or designation, see table IV.

2/ The latest version of each cable shall be applicable.

3/ These connectors have captivated center contacts.

4/ The superseded PIN is **NOT** acceptable for Government use.

5/ Cable to be used for the +200°C temperature cycling tests. This cable may be used for tests with the approval of the Qualifying Activity.

6/ Cable to be used when performing test requiring cable except as in 5/ and 7/.

7/ These are not 50-ohm cables; therefore, when attached to the specified connectors, VSWR, RF leakage and insertion loss are not applicable.

8/ These connectors are assembled using the applicable crimp tool, to the specified cables stripped as shown on figure 4.

9/ M22520/5-19 cavity B or AS22520/5-05 closure A.
M22520/5-11 cavity A.
M22520/5-57 cavity A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:45Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers, Cross-reference, and dimensions – Continued.

10/ M22520/5-19 cavity A or AS22520/5-07 cavity A.
M22520/5-13 cavity A.
M22520/5-59 cavity A.

11/ AS22520/5-41 cavity B or AS22520/5-05 cavity B.
AS22520/5-09 cavity A.

12/ AS22520/5-35 cavity B or AS22520/5-03 cavity A.

13/ Complete connector assembly shall consist of a body, center contact, ferrule and assembly instructions.


14/ Not to be used in Army equipment.

15/ Inactive for new design, see 187-00001.

Dimensions are in inches. Metric equivalents are given for information only.

X Denotes connector body plating material option. The only plating options allowable are Silver or Nickel over brass in accordance with MIL-PRF-39012. Only connectors of the same materials shall be mated to avoid dissimilar metal problems. **CAUTION: A NICKEL PLATED BODY IS NOT FOR USE IN APPLICATIONS WHERE PASSIVE INTERMODULATION GENERATION (PIM) MAY BE A CONCERN.** Silver is the preferred plating option.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:45Z
Check the source to verify that this is the current version before use.




CRIMP FERRULE

Dash number	Ferrule number 1/	A ±0.003	B ±0.003	Basic crimp tool 2/	Crimp die or positioner AS22520/5
X501 X502	19-50	0.212	0.175	AS22520/5-01	05, 41 Closure B or 9 Closure A
X503	19-51	0.250	0.220		05, 11, 57 Closure A or 19 Closure B
X504	19-52	0.245	0.206		

1/ Contact numbers and ferrule numbers are for identification only.
2/ Class 2 tool may be used by OEM (see SAE-AS22520).

FIGURE 3. Contact and ferrule dimensions for category D only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:45Z
Check the source to verify that this is the current version before use.



CENTER CONTACT

Inches	mm	Inches	mm	Inches	mm	Inches	mm
.001	0.03	.033	0.84	.145	3.68	.220	5.59
.002	0.05	.035	0.89	.175	4.45	.230	5.84
.003	0.08	.040	1.02	.183	4.65	.235	5.97
.005	0.13	.043	1.09	.206	5.23	.250	6.35
.015	0.38	.067	1.70	.210	5.33	.478	12.14
.017	0.43	.083	2.11	.212	5.38	.500	12.70


Dash number	Contact number 1/	A +0.001 -0.002	Basic crimp tool 2/	Crimp die or positioner	Crimp tensile, pounds min. (N)	Color band □	Color band o
X501	19-12	0.033	M22520/1-01	M22520/1-12	10 lbs (44.48)	Orn	Blue
X502	19-11	0.017			6 lbs (26.69)	Blue	
X503 X504	19-10	0.043	M22520/1-01	M22520/1-12	20 lbs (88.96)	Red	

1/ Contact numbers and ferrule numbers are for identification only.
2/ Class 2 tool may be used by OEM (see SAE-AS22520).

NOTES:
1. Dimensions are in inches. Metric equivalents are given for information only.
2. Contact material shall be copper beryllium. Connectors supplied with phosphor bronze contacts are not acceptable for Government use until.
3. Crimp tensile lest shall be in accordance with SAE-AS39029.
4. Copyright notice: All information disclosed in these specification sheets which is or may be copyright is reproduced herein with the express permission of the copyright owner.
5. .003 inch maximum break.
6. Color bands shall be positioned so that no coloring material enters the inspection hole.

FIGURE 3. Contact and ferrule dimensions for category D only - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:45Z
Check the source to verify that this is the current version before use.



Inches	mm
.146	3.71
.166	4.22
.333	8.46
.353	8.97
.427	10.85
.447	11.35
.593	15.06

NOTES
1. Dimensions ore in inches. Metric equivalents are given for information only.

FIGURE 4. Cable stripping dimensions for field replaceable connectors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:45Z
Check the source to verify that this is the current version before use.

ENGINEERING DATA

Nominal impedance: 50 ohms.

Frequency range: 0 to 4 GHz.

Voltage rating:

500 volts rms, maximum working voltage at sea level.

125 volts rms, maximum at 70,000 feet (4.437 kPa).

Temperature rating: -65°C to +165°C.

REQUIREMENTS

Dimensions and configuration: See figures 1 and 3.

Force to engage and disengage:

Longitudinal force: 3 pounds (13.34 N), maximum.

Torque: 2.5 Inch-pounds (.28Nm), maximum.

Coupling proof torque: Not applicable.

Inspection conditions: Coupling torque not applicable.

Mating characteristics:

In accordance with MIL-STD-348 and figure 2 for dimensions.

Center contact (socket):

Oversize test pin: .057 inch (1.45 mm) diameter, minimum (nonclosed entry contacts only).

Insertion depth: .125 inch (3.17 mm), minimum.

Number of insertions: 1.

Insertion force test: Steel test pin diameter .054 inch (1.37 mm), minimum.

Test pin finish: 16 microinches (0.406 µm).

Insertion force: 2 pounds, (8.90 N), maximum.

Withdrawal force test: Steel test pin diameter .052 inch (1.32 mm), maximum.

Withdrawal force: 2 ounces (.56 N), minimum.

Test pin finish: 16 microinches (0.406 µm).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:45Z
Check the source to verify that this is the current version before use.

Hermetic seat: Not applicable.

Leakage: Connector shall be mounted in mounting hole shown on figure 1 with mating end capped.

Test applicable to mounting seal only.

Air pressure - 30 Lbf/in^2.

Duration - 30 seconds, minimum.

Insulation resistance: MIL-STD-202-302, test condition B, 5,000 megohms, minimum.

Center contact retention: 6 pounds (26.69 N), minimum axial force. Applicable to captivated center contact connectors only.

Corrosion (salt spray): MIL-STD-202-101, test condition B.

Voltage standing wave ratio (VSWR): From 500 to 4 GHz, or approximately 80 percent of upper cutoff frequency of the cable, whichever is lower; 1.30, maximum.

Swept frequency VSWR test setup:

Item 6: VSWR shall be less than 1.015+ .005 F (F in GHz). -

Item 16: VSWR shall be less than 1.015 + .005 F (F in GHz).

Second step of VSWR checkout procedure: VSWR shall be less than 1.045+.019 F (F in GHz).

Group B inspection: VSWR shall be less than 1.1+ .01 F (F in GHz).

Qualification and group C inspection: VSWR shall not exceed 1.15.

VSWR procedure.

The VSWR shall be measured in accordance with the following procedure or a method acceptable to the Government.

Part should be tested using a Network Analyzer with the Time Domain (TDR) option installed. This is essential to allow the effect of the adapters to be “gated” out. The recommended network analyzer systems include suitable equipment with NIST traceability or equivalent. All gating will be completed in accordance with the procedures stated by the network analyzer manufacturer with the following time domain settings:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:45Z
Check the source to verify that this is the current version before use.

TABLE II. Suggested Time Domain Settings.

Transform Mode 1/	Gate Type	Gate Shape 2/	Start Gate Time (ps)	Stop Gate Time (ps)
Low-pass	Bandpass	Minimum, Normal, Wide	End of Adapter 3/ – Rise Time of Gate 4/	End of Device Under Test + Rise Time of Gate

1/ The low-pass mode will have a higher resolution than the band-pass mode.
2/ Each shape specified will not be smaller than the minimum gate span to ensure the response has the correct start and stop times.
3/ "Port Extension" is also used for detection to move the measurement plane after calibration is complete.
4/ The minimum window is used for best resolution.
5/ The maximum window is used for best dynamic range.

The printer/plotter and the computer should be any unit compatible to the system. The test adapters will utilize the following frequency bands:

Frequency	VSWR
500 MHz	1.055
1 GHz	1.055
5 GHz	1.075
10 GHz	1.100
15 GHz	1.125
18 GHz	1.140
26 GHz	1.180
40 GHz	1.25
50 GHz	1.30
65 GHz	1.375

50-ohm precision air lines may also be used on both sides of the device under test.

Calibration of the system should be performed using the manufacturer's calibration kits and the recommended calibration procedures. The frequency range shall be DC to 65 GHz. The VSWR calibration test setup shall be verified using the manufacturers verification kits. The calibrated system VSWR shall be less than 1.02 + .001F (F in GHZ).

The VSWR of the DUT shall be measured using the procedures described in the manufacturer's operating instructions. The time domain shall then be used to remove the effects of the test adapter with the recommended settings as mentioned above.

The output shall be generated using the appropriate printer/plotter.

Connector durability: 500 cycles minimum at 12 cycles/minute maximum. The connector shall meet the mating characteristics and force to engage end disengage requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:45Z
Check the source to verify that this is the current version before use.

Contact resistance: In milliohms maximum:

	Initial	After environment
Center contact	1.5	2.0
Outer contact (silver)	.2	Not applicable
Outer contact (nickel)	.4	Not applicable
Braid to body	.1	Not applicable

Dielectric withstanding voltage: MIL-STD-202-301. 1,500 volts rms minimum at sea Level.

Vibration, high frequency: MIL-STD-202-204, test condition B. No discontinuity permitted.

Shock: MIL-STD-202-213, test condition G. No discontinuity permitted.

Thermal shock: MIL-STD-202-107, test condition B, except test high temperature shall be +85°C. High temperature shall be +200°C for connectors using +200° cables (see tables I and III).

Moisture resistance: MIL-STD-202-106. No measurements at high humidity. Insulation resistance shall be at least 200 megohms within 5 minutes after removal from humidity.

Corona Level:

Voltage: 375 volts rms, minimum.

Altitude: 70,000 feet (4.437 kPa).

RF high potential withstanding voltage:

Voltage and frequency: 1,000 volts rms at a frequency from 5 to 7.5 MHz.

Leakage current: Not applicable.

Cable retention force:

Noncrimp assemblies: 40 pounds (177.92 N), minimum.

Crimp assemblies:

10 pounds (44.48 N), minimum for cables .155 - .189 inch (3.96 mm – 4.80 mm) OD.

20 pounds (88.96 N), minimum for cables .190 - .229 inch (4.83 mm – 5.82 mm) OD.

30 pounds (133.45 N), minimum for cables .230 - .249 inch (5.84 mm – 6.32 mm) OD.

40 pounds (177.93 N), minimum for cables .250 inch (6.35 mm) OD - and larger.

Coupling mechanism retention force: Not applicable.

RF leakage: -55 dB minimum, tested at a frequency between 2 and 3 GHz.

Insertion loss: .2 dB maximum tested at 3 GHz.

PIN: M39012/19 (dash number from table I or “B” number from table III).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:45Z
Check the source to verify that this is the current version before use.

Group qualification: See table III.

TABLE III. Group qualification. 1/

Group	Submission and qualification of 2/ any of the following connectors M39012/	Qualifies the following connectors M39012/
I	17-X101 17-X103 17-X111 17-X118 18-X102 18-X103 18-X111 18-X118 19-X101 19-X110 19-X111 19-X118 19-X220	17-X101 17-X102 17-X103 17-X111 17-X118 18-X101 18-X102 18-X103 18-X111 18-X118 19-X101 19-X102 19-X110 19-X111 19-X118 19-X220
II	17-X102 18-X101 19-X102	17-X102 18-X101 19-X102
III	17B0004 17B0005 17B0006 17B0007 17B0009 17B0019 18B0004 18B0005 18B0006 18B0007 18B0009 18B0019 19B0003 19B0004 19B0005 19B0006 19B0008 19B0019	17B0004 17B0005 17B0006 17B0007 17B0008 17B0009 17B0012 17B0019 18B0004 18B0005 18B0006 18B0007 18B0008 18B0009 18B0012 18B0019 19B0003 19B0004 19B0005 19B0006 19B0007

See notes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:45Z
Check the source to verify that this is the current version before use.

TABLE III. Group qualification - Continued. 1/

Group	Submission and qualification of 2/ any of the following connectors M39012/	Qualifies the following connectors M39012/
III		19B0008 19B0012 19B0019
IV	17B0008 17B0012 18B0008 18B0012 19B0007 19B0012	17B0008 17B0012 18B0008 18B0012 19B0007 19B0012
V	17-X013 17-X014 17-X016 17-X020 18-X013 18-X014 18-X016 18-X020 19-X013 19-X014 19-X016 19-X020 19-X221	17-X013 17-X014 17-X015 17-X016 17-X017 17-X020 18-X013 18-X014 18-X015 18-X016 18-X017 18-X020 19-X013 19-X014 19-X015 19-X016 19-X017 19-X020 19-X221
VI	17-X015 17-X017 18-X015 18-X017 19-X015 19-X017	17-X015 17-X017 18-X015 18-X017 19-X015 19-X017
VII	19-X501 19-X503 19-X504	19-X501 19-X502 19-X503 19-X504
VIII	19-X502	19-X502

See notes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:45Z
Check the source to verify that this is the current version before use.

1/ If a connector manufacturer produces a connector which meets all the requirements for two or more connector PIN's (within the same series), the manufacturer may receive qualification approval for two or more connector plus qualifying the one connector. It is not necessary that such connectors be in the same group. Each connector, however, must be marked with its own appropriate PIN. For group qualification, the connectors must be of similar design and be of the same materials and plating.

2/ For qualification retention, where more than one part is listed in a group in this column, data may be supplied on any of those parts in order to retain qualification for those parts in the corresponding right hand column. The part does not necessarily have to be the part initially qualified.

3/ Qualification by similarity may be given for the like styles of currently qualified TNC series connectors with the approval of the qualifying and preparing activity. Similarity will include, cable accommodation, materials and plating, assembly procedures and crimp tools/dies, as a minimum.

TABLE IV. Category B – Non-field replaceable (special tools may be required).

Not for Air Force, Army or Navy use. For OEM use only.

Dash number 1/ 2/ 3/	Applicable cable M17/ 4/	Dimensions	Inches (millimeters) maximum #
M39012/19B0003	028-RG058* 5/	A	1.625 (41.28)
M39012/19B0004	084-RG223*		
M39012/19B0005	111-RG303*		
M39012/19B0006	060-RG142*@ 29-RG59*Δ 6/ 030-RG062Δ 7/		
M39012/19B0007	97-RG210 Δ		
M39012/19B0008	054-RG122 8/		
M39012/19B0012	90-RG71*Δ		
M39012/19B0019	110-RG302*@Δ		

1/ For cross-reference of PIN to superseded PIN or type designation, see table IV.
2/ For maintenance replacements for category B, see table V.
3/ Inactive for new design.
4/ The latest version of each cable shall be applicable.
5/ Inactive for new design; see 183-00001.
6/ Inactive for new design; see 184-00001.
7/ Inactive for new design; see 185-00001.
8/ Inactive for new design; see 187-00001.
Dimensions are in inches. Metric equivalents are given for information only.
* Cable to be used when performing tests requiring cable except as in notes @ and Δ.
@ Cable to be used for the +200°C temperature cycling tests. This cable may be used for tests with the approval of the Qualifying Activity.
Δ These are not 50 ohm cables; therefore, when attached to the specified connectors, VSWR, RF leakage, and insertion loss are not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:45Z
Check the source to verify that this is the current version before use.

TABLE V. Cross-reference of PIN's.

Preferred PIN M39012/19	Substitute for PIN or type designation 1/ 2/
-0101	UG-909/U, M39012/19-0001
-0102	UG-910/U, M39012/19-0002
B0003	M23329/3-15, M39012/19-0003
B0004	M23329/3-16, M39012/19-0004
B0005	M23329/3-17, M39012/19-0005
B0006	M23329/3-18, M39012/19-0006
B0007	M23329-3-19, M39012/19-0007
B0008	M23329/3-20, M39012/19-0008
-0110	M39012/19-0010
-0111	M39012/19-0011
B0012	M39012/19-0012
-0013	
-0014	
-0015	
-0016	
-0117	
-0018	M39012/19-0018
B0019	M39012/19-0019
-0020	
-0501	
-0502	
-0503	
-0504	

1/ The superseded PIN or the type designation is for cross-reference only. Where a superseded PIN or type designation is not given, none was assigned or will be assigned. The PIN M39012/19-XXXX shall be used in all cases for marking and identifying the connector.

2/ The basic type designation includes all letter versions of the specified number, e.g. UG-18/U includes UG-18 A/U, UG-18 B/U, etc.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:45Z
Check the source to verify that this is the current version before use.

TABLE VI. Maintenance replacements for category D.

Category B* number Inactive for new design	Category C dash number	Category A dash number	Category D dash number
B0003	0013	0101	0504
B0004	0014	0101	---
B0005	0013	0101	---
B0006	0014	0101	0503
B0007	0015	0102	---
B0008	0016	0110	0501
B0012	0017	0102	---
B0019	0020	0118	---

*Category B connectors are for original installation only. They will not be stocked or acquired by the Government.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-PRF-39012, this document references the following:

FED-STD-H28
MIL-STD-202-101
MIL-STD-202-106
MIL-STD-202-107
MIL-STD-202-204
MIL-STD-202-213
MIL-STD-202-301
MIL-STD-202-302
MIL-STD-348
SAE-AS22520
SAE-AS39029

CONCLUDING MATERIAL

Custodians:
Army-CR
Navy - EC
Air Force – 85
NASA - NA
DLA – CC

Preparing activity:
DLA-CC

(Project 5935-2019-039)

Review activities:
Army - AT, AV, EA, MI
Navy - AS, MC, OS, SH
Air Force -19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:45Z
Check the source to verify that this is the current version before use.