
MILITARY SPECIFICATION SHEET

CONNECTORS, PLUG, ELECTRICAL, COAXIAL, RADIO FREQUENCY,

(SERIES BNC (CABLED), PIN CONTACT, RIGHT ANGLE, CLASS 2)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the connectors described herein shall consist of this specification and the latest issue of MIL-C-39012.



Inches	mm
.44	11.18
.510	12.95
.593	15.06
.800	20.32
.963	24.46
1.218	30.94

MARKING IMPLEMENTATION DATE, CATEGORY B, SEE TABLE IV

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. For dimensions A and B see table I and III.
4. Dimension A, 1.218 and .593 are the largest overall dimension of the connector.
5. Wrench flats to accommodate standard wrench in accordance with FED-STD-H28, appendix 10.
6. All undimensioned pictorial representations are for reference purposes only.
7. Dimension A defines the maximum length of the connector when assembled to the appropriate cable.
8. Series BNC, pin contact interface in accordance with MIL-STD-348.

FIGURE 1. General configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:46Z
Check the source to verify that this is the current version before use.

AMSC N/A FSC 5935

DISTRIBUTION STATMENT A. Approved for public release; distribution is unlimited.

TABLE I. Dash numbers, cross reference, and dimensions.

Dash number 1/	Applicable cable M17/ #	Dimensions	Inches (millimeters) maximum
Category A - Field serviceable (no special tools required)			
0101 4/	028-RG058 084-RG223* 060-RG142@ 128-RG400		
0102 4/	29-RG59*Δ 030-RG62Δ 90-RG71Δ 97-RG210Δ	A	1.750 (44.45)
0108 4/	110-RG302*@Δ		
Category C - Field replaceable (MIL-C-22520 crimp tool) 3/ See footnote symbol next to applicable cable for crimp die			
0006 4/	028-RG058*~ 111-RG303~		
0007 4/	084-RG223*~ 060-RG142@~ 128-RG400~		
0010 4/	110-RG302*@Δ>	A	2.000 (30.80)
0011 4/	97-RG210Δ> 29-RG59*Δ> 030-RG062Δ> 90-RG71Δ>		
Category D - Field replaceable - Defined piece parts 3/5/2/			
0501 4/	054-RG122*		
0502 4/	095-RG180*Δ		
0503 4/	060-RG142*	A	1.828 (46.43)
	128-RG400	B	1.578 (40.08)
0504 4/	028-RG058*		

See footnotes on following page.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:46Z
Check the source to verify that this is the current version before use.

1/ For cross reference of dash number to superseded part number or type designation, see table IV.

2/ Not to be used in Army equipment.

3/ These connectors are assembled, using the applicable crimp tool, to the specified cables stripped as shown on figure 3.

4/ These connectors have captivated center contacts.

5/ Complete connector assembly shall consist of a body, center contact, ferrule, and assembly instructions.

The latest version of each cable shall be applicable.

* Cable to be used when performing tests requiring cable except as in notes @ and ∆.


@ Cable to be used for the +200°C temperature cycling tests.

∆ These are not 50 ohm cables; therefore, when attached to the specified connectors, VSWR, RF leakage, and insertion loss are not applicable.

~ M22520/5-19 Closure B or M22520/5-05 Closure A
M22520/5-11 Closure A
M22520/5-57 Closure A

> M22520/5-19 Closure A or M22520/5-07 Closure A
M22520/5-13 Closure A
M22520/5-59 Closure A

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:46Z
Check the source to verify that this is the current version before use.




Dash No.	Ferrule No. 2/	A ±.001	B ±.001	Basic crimp tool 1/	Crimp die or positioner M22520/5-
0501 0502	20-50	.212	.175	M22520/5-01	05, 41 Closure B or 9 Closure A
0503	20-51	.250	.220		05, 11, 57 Closure A or 19 Closure B
0504	20-52	.245	.206		

1/ Class 2 tool may be used by OEM (see MIL-C-22520).
2/ Contact numbers and ferrule numbers are for identification only.

FIGURE 2. Contact and ferrule dimensions for category D only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:46Z
Check the source to verify that this is the current version before use.



CENTER CONTACT

Inches	mm
.001	.03
.002	.05
.005	.13
.015	.38
.017	.43
.033	.84
.035	.89
.040	1.02
.043	1.09
.067	1.70
.083	2.11
.145	3.68
.175	4.45
.183	4.65
.206	5.23
.212	5.38
.220	5.59
.235	5.97
.245	6.22
.250	6.35
.500	12.70
.611	15.52


Dash No.	Contact No. 2/	A +.001 -.002	Basic crimp tool 1/	Crimp die or positioner	Crimp tensile min	Color band □	Color band ○
0501	20-12	.033	M22520/1-01	M22520/1-12	10 lbs	Orn	Violet
0502	20-11	.017			6 lbs	Blue	
0503 0504	20-10	.043	M22520/1-01	M22520/1-12	20 lbs	Red	

1/ Class 2 tool may be used by OEM (see MIL-C-22520).
2/ Contact numbers and ferrule numbers are for identification only.

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Crimp tensile test shall be in accordance with MIL-C-39029.
4. Contact numbers and ferrule numbers are for identification only.
5. .003 maximum break.

FIGURE 2. Contact and ferrule dimensions for category D only - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:46Z
Check the source to verify that this is the current version before use.



Inches	mm
.146	3.71
.166	4.22
.333	8.46
.353	8.97
.427	10.85
.447	11.35
.593	15.06

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.

FIGURE 3. Cable stripping dimensions for field replaceable connectors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:46Z
Check the source to verify that this is the current version before use.

ENGINEERING DATA:

Nominal impedance: 50 ohms.

Frequency range: 0 to 4,000 MHz.

Voltage rating:

500 volts rms, maximum working voltage at sea level.

125 volts rms, maximum at 70,000 feet.

Temperature rating: -65°C to +165°C.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Force to engage and disengage:

Longitudinal force: 3 pounds, maximum.

Torque: 2-1/2 inch-pounds, maximum.

Coupling proof torque: Not applicable.

Inspection conditions: Coupling torque not applicable.

Mating characteristics:

Reference MIL-STD-348.

Outer contact:

Test ring ID: .319 maximum, 16 microinch finish.

Insertion force: 5 pounds, maximum when inserted a minimum of .093.

Contacts with slotted members: Shall contact a .324, minimum diameter ring with .031 of their tip ends.

Hermetic seal: Not applicable.

Leakage (pressurized connectors): Not applicable.

Insulation resistance: Method 302 of MIL-STD-202, test condition B, 5,000 megohms, minimum.

Center contact retention: 6 pounds, minimum axial force. Applicable to captivated-center-contact connectors only.

Corrosion (salt spray): Method 101 of MIL-STD-202, test condition B.

Voltage standing wave ratio (VSWR): From 500 to 4,000 MHz, or approximately 80 percent of upper cutoff frequency of the cable, whichever is lower; 1.35, maximum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:46Z
Check the source to verify that this is the current version before use.

Swept frequency VSWR test setup:

Item 6: VSWR shall be less than 1.015+.005 F (F in GHz).

Item 16: VSWR shall be less than 1.015+.005 F (F in GHz).

Second step of VSWR checkout procedure: VSWR shall be less than 1.045+.019 F (F in GHz).

Group B inspection: VSWR shall be less than 1.1+.01 F (F in GHz).

Qualification and group C inspection: VSWR shall not exceed 1.15.

Connector durability: 500 cycles, minimum at 12 cycles per minute, maximum. The connector shall meet the mating characteristics and force to engage and disengage requirements.

Initial: 5 pounds, maximum.

Final: 5 pounds, maximum; 1 pound, minimum.

Contact resistance: In milliohms, maximum:

	Initial	After environment
Center contact	2.0	2.5
Outer contact	.2	Not applicable
Braid to body	.1	Not applicable

Dielectric withstanding voltage: Method 301 of MIL-STD-202, 1,500 volts rms, minimum at sea level.

Vibration, high frequency: Method 204 of MIL-STD-202, test condition B. No discontinuity permitted.

Shock: Method 213 of MIL-STD-202, test condition G. No discontinuity permitted.

Thermal shock: Method 107 of MIL-STD-202, test condition B, except test high temperature shall be +85°C. High temperature shall be +200°C for connectors using +200°C cables (see tables I and III).

Moisture resistance: Method 106 of MIL-STD-202. No measurements at high humidity. Insulation resistance shall be at least 200 megohms within 5 minutes after removal from humidity.

Corona level:

Voltage: 375 volts rms, minimum.

Altitude: 70,000 feet.

RF high potential withstanding voltage:

Voltage and frequency: 1,000 volts rms at a frequency from 5 to 7.5 MHz.

Leakage current: Not applicable.

Cable retention force:

Noncrimp assemblies: 40 pounds, minimum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:46Z
Check the source to verify that this is the current version before use.

Crimp assemblies:

50 pounds, minimum for cables .155 - .189 OD.

60 pounds, minimum for cables .190 - .229 OD.

75 pounds, minimum for cables .230 - .249 OD.

90 pounds, minimum for cables .250 OD and larger.

Coupling mechanism retention force: 100 pounds, minimum.

RF leakage: -55 dB minimum, tested at a frequency between 2 and 3 GHz. This requirement may be met by meeting the RF leakage requirement on the MIL-C-39012/16 connector which has the same mating end design and which is intended for the same cable.

Insertion loss: .3 dB, maximum tested at 3 GHz.

Part number: M39012/20 (dash number from table I or "B" number from table III).

TABLE II. Group Qualification.

Group	Submission and qualification of any of the following connectors	Qualifies the following connectors
	M39012/20	M39012/20
I	-0101 -0108	-0101 -0108 0102
II	B0002 B0003	B0002 B0003
III	-0006 -0007 -0010	-0006 -0007 -0010
IV	-0501 -0503 -0504	-0501 -0502 -0503 -0504
V	-0502	-0502

NOTE: If a connector manufacturer produces a connector which meets all the requirements for two or more connector part numbers (within the same series), the manufacturer may receive qualification approval for two or more connector part numbers qualifying the one connector. It is not necessary that such connectors be in the same group. Each connector, however, must be marked with its own appropriate part number. For group qualification, the connectors must be of similar design.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:46Z
Check the source to verify that this is the current version before use.

TABLE III. Category B - Nonfield replaceable (special tools may be required).

Not for Air Force or Navy use. For OEM use only

Dash number 1/ 2/ 3/	Applicable cable M17/#	Dimensions	Inches (millimeters) maximum
M39012/20B0002	028-RG058*	A	2.000 (50.80)
M39012/20B0003	084-RG223*		

1/ For cross reference of dash number to superseded part number or type designation, see table IV.

2/ For maintenance replacements for category B, see table V.

3/ Inactive for new design.

The latest version of each cable shall be applicable.

* Cable to be used when performing tests requiring cable except as in notes @ and ∆.

@ Cable to be used for the +200°C temperature cycling tests.

∆ These are not 50 ohm cables; therefore, when attached to the specified connectors, VSWR, RF leakage, and insertion loss are not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:46Z
Check the source to verify that this is the current version before use.

TABLE IV. Cross reference of part numbers.

Preferred part number M39012/20	Substitute for part number or type designation 1/2/
-0101	UG-913/U, M39012/20-0001
B0002 3/	UG-1812/U, M39012/20-0002
B0003 3/	UG1813/U, M39012/20-0003
-0006	M39012/20-0004
-0007	
-0108	M39012/20-0008
-0010	M39012/20-0009
-0501	
-0502	
-0503	M39012/20-0005
-0504	

1/ The superseded part number or the type designation is for cross reference only. Where a superseded part number or type designation is not given, none was assigned or will be assigned. The part number M39012/20-XXXX shall be used in all cases for marking and identifying the connector.

2/ The basic type designation includes all letter versions of the specified number, e.g. UG-18/U includes UG-18 A/U, UG-18B/U, etc.

3/ The new "B" part numbers will be required marking 6 months after the date of this specifications. The previous part number may be used in the interim.

TABLE V. Maintenance replacements for category B.

Category B number* Inactive for new design	Category C dash number	Category A dash number	Category D dash number
B0002	0006	0101	0504
B0003	0007	0101	---

*Category B connectors are for original installation only. They will not be stocked or acquired by the Government.

Revisions letters are not used to denote changes due to the extensiveness of the changes.

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - CR, EA, MI
Air Force - 11, 17, 99
OLA - ES

User activities:
Army - AT, AV
Navy - AS, MC, OS, SH
Air Force - 19

Preparing activity:
Army - CR

Agent:
DLA - ES

(Project 5935-3518-12)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:46Z
Check the source to verify that this is the current version before use.