MILITARY SPECIFICATION

IGNITER, MARK 188 MOD 0

This amendment forms a part of Military Specification MIL-I-23453 (Wep), dated 7 November 1962, and is approved for use by the Naval Air Systems Command, Department of the Navy and is available for use by al 1 Departments and Agencies of the Department of Defense.

Throughout the specification, reference (except drawing references) to Bureau of Naval Weapons or Bureau of Naval Ordnance shall be changed to Naval Air Systems Command.

PAGE 3

Delete parenthetical statement at top of page and substitute:

" (Copies of specifiactions i cations, standards, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)"

2.2, Delete in its entirety and substitute:

"2.2 Other publications. The following document forms a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

CODE OF FEDERAL REGULATIONS

49 CFR 100-199 Transportation

(Application for copies should be addressed to Superintendent of Documents, Government Printing Office, Washington, D. C. 20402.)"

PAGE 4

Delete 3.4.1, 3.4.2, and 3.4.3 and substitute:

"3.4.1 Ignition delay. Ignition delay shall be 0.040 second maximum (see 6.4.1).

Source: https://assist.dla.mil -- Downloaded: 202640-19T16:56Z
Check the source to verify that this is the currenversion before use.

3.4.2 Ignition rise time. Ignition rise time shall be 0.050 ± 0.030 second (see 6.4,2).

3.4.3 Maximum chamber pressure. Maximum chamber pressure shall be 575 ± 175 psig (see 6.4.3).

PAGE 5

* 4.4.3: Delete "-85" and "175" and substitute "-40" and "150".

PAGE 6

* 4.4.4.1.1, line 2: Delete "-85" in two places and substitute "-40".

* 4.4.4.1.1, line 5: Delete "175" in two places and substitute "150".

* 4.4.4.1.2, line 2: Delete "-85" and "175" and substitute "-40" and "150".

* 4,4.4.1.3, line 2: Delete "-85" and substitute "-40".

* 4.4.2.1, line 2: Delete "175" in two places and substitute "150".

* 4.4.2.1, line 5: Delete "-85" in two places and substitute "-40".

* 4.4.4.2.2, line 2: Delete "175" and "-85" and substitute "150" and "-40",

PAGE 7

* 4.4.4.2.3, line 2: Delete "175" and substitute "150".

* 4.4.5, line 4: Delete "175" in two places and substitute "150".

* 4.4.5, line 5: Delete "-85" in two places and substitute "-40".

PAGE 8

4.5.2, line 2: Delete "-85" and "175" and substitute "-40" and "150".

5.1.1, line 2: Delete "49 CFR 71-78" and substitute "49 CFR 171-178".

PAGE 9

5.2.1, line 2: Delete "49 CFR 71-78" and substitute "49 CFR 171-178".

5.3.1, line 2: Delete "49 CFR 71-78" and substitute "49 CFR 171-178".

Source: https://assist.dla.mil -- Downloaded: 202610-19T16:56Z
Check the source to verify that this is the current version before use.

Delete 6.3 *through* 6.3.6.8 *inclusive* (pages 10, 11, 12) and NOTICE on page 12.

Add new 6.3 as follows:

"6.3 Safety precautions. The safety precaution requirements of the "Contractors' Safety Manual for Ammunition, Explosives, and Related Dangerous Material," DOD 4145.26M, are applicable. NOTE: When this specification is used as part of the description of work to be accomplished by a Government activity, the safety precaution requirements of "Ammunition and Explosives Ashore," OP 5, are applicable."

Add "6.4 Definitions.

6.4.1 Ignition delay. Ignition delay is defined as the time from application of current to the attainment of 10% of maximum chamber pressure during a ballistic performance test in accordance with 4.5.2.

6.4.2 Ignition rise time. Ignition rise time is defined as the time for the chamber pressure to rise from 10% to 75% of maximum chamber pressure during a ballistic performance test.

6.4.3 Maximum chamber pressure. Maximum chamber pressure is defined as the maximum pressure needed in the test chamber during a ballistic performance test."

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:

Navy-AS
(Project 1340-N682)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:56Z
Check the source to verify that this is the current version before use.